




PERMUTATION-INVARIANT CODES: A NUMERICAL STUDY AND QUDIT CONSTRUCTIONS

LIAM J. BOND[1,2], JIŘÍ MINÁŘ[1,2], MARIS OZOLS[1,3,4], ARGHAVAN SAFAVI-NAINI[1,2], AND VLADYSLAV VISNEVSKYI[1,2,5]

Abstract. We investigate Permutation-Invariant (PI) quantum error-correcting codes encoding a logical qudit of dimension $\mathrm{d_L}$ in PI states using physical qudits of dimension $\mathrm{d_P}$. We extend the Knill–Laflamme (KL) conditions for $d-1$ deletion errors from qubits to qudits and investigate numerically both qubit ($\mathrm{d_L}=\mathrm{d_P}=2$) and qudit ($\mathrm{d_L}>2$ or $\mathrm{d_P}>2$) PI codes. We analyze the scaling of the block length n in terms of the code distance d, and compare to existing families of PI codes due to Ouyang, Aydin–Alekseyev–Barg (AAB) and Pollatsek–Ruskai (PR). Our three main findings are: (i) We conjecture that qubit PI codes correcting up to $d-1$ deletion errors have block length $n(d)\geq(3d^2+1)/4$, which implies an upper bound $d\leq\sqrt{12n-3}/3$ on their code distance, and that PR codes can saturate this bound. (ii) For qudit PI codes encoding a single qudit we numerically observe that increasing $\mathrm{d_P}$ results in n monotonically decreasing and approaching the quantum Singleton bound $n(d)\geq 2d-1$. (iii) We propose a semi-analytic extension of the qubit AAB construction to qudits that finds explicit solutions by solving a linear program. Our results therefore provide key insights into lower bounds on the block length scaling of both qubit and qudit PI codes, and demonstrate the benefit of increased physical local dimension in the context of PI codes.

arXiv:2603.10981v1 [quant-ph] 11 Mar 2026

Contents

1. Introduction 1
2. Preliminaries 3
3. Numerical study of qubit PI codes 5
4. Knill–Laflamme conditions for qudit PI codes 9
5. Study of qudit PI Codes 13
6. Discussion 16
7. Acknowledgments 17
References 18
Appendix A. Minor proofs 21
Appendix B. Numerical results for coefficient fixing in qubit codes with $t=2$ and $t=3$ 21
Appendix C. Qudit PI codes on discrete simplices 22

1. Introduction

1.1. **Background.** Quantum computers promise to solve certain problems faster than classical ones. For example, the problem of factoring can be solved in exponentially faster runtime [Sho97], and the problem of unstructured search in quadratically faster runtime [Gro96]. However, quantum computers are vulnerable to decoherence and quantum noise which limits their scalability, both in terms of the number of qubits and the number of gate operations. Solving this challenge will require the use of quantum error correction (QEC) to protect quantum information from noise-induced errors.

At the heart of QEC is the quantum error-correcting code (QECC), whereby a logical qubit is encoded across many physical qubits in such a way that errors can be detected and corrected. Experimental realizations of quantum error correction beyond break-even, i.e. the regime in which the coherence time of an actively error-corrected logical qubit exceeds that of any qubit without active error correction, has been experimentally

(1) QuSoft, Amsterdam
(2) Institute of Physics, University of Amsterdam
(3) Institute for Logic, Language and Computation, University of Amsterdam
(4) Korteweg-de Vries Institute for Mathematics, University of Amsterdam
(5) Centre for the Mathematics of Quantum Theory, University of Copenhagen
E-mail addresses: l.j.bond@uva.nl, j.minar@uva.nl, marozols@gmail.com, safavinaini@gmail.com, vladislav.visnevskyy@gmail.com.

