

Optimal physical approximations of pure-state cloning and transposition are complementary channels

Vanessa Brzić,[1] Dmitry Grinko,[2,3] Michał Studziński,[4] and Marco Túlio Quintino[1]

[1] *Sorbonne Université, CNRS, LIP6, F-75005 Paris, France*
[2] *QuSoft, Amsterdam, The Netherlands*
[3] *Institute for Logic, Language and Computation, and Korteweg-de Vries Institute for Mathematics, University of Amsterdam, The Netherlands*
[4] *International Centre for Theory of Quantum Technologies, University of Gdańsk, Prof. Marii Janion 4, 80-309 Gdańsk, Poland*

State cloning and state transposition are fundamental transformations that, despite being desirable, cannot be perfectly realised as a consequence of two distinct requirements of quantum theory: cloning is forbidden by linearity, while transposition is ruled out by complete positivity. In this work, we show that, in spite of these disparate conceptual restrictions, the best physically allowed realisation of both transformations arises from a single physical process described by an isometry, which simultaneously implements their best possible approximations. This complementary relation allows us to determine the exact quantum and private classical capacities of the universal symmetric $N \to N + K$ cloning channel in the fully general multicopy qudit setting, thereby closing the remaining gap in the quantum capacity problem for universal cloning. We provide an explicit circuit that simultaneously implements optimal pure-state $N \to K$ transposition and optimal $N \to N + K$ symmetric cloning, both attaining the same fidelity. Additionally, we prove that the optimal $N \to K$ pure state transposition channel is unique and realised by an estimation strategy. We also obtain the optimal mixed-state $N \to 1$ transposition, and discuss its differences from its pure-state analogue.

arXiv:2603.23628v3 [quant-ph] 26 Sep 2026

The fundamental principles of quantum theory, such as linearity and complete positivity, give rise to a number of no-go theorems that challenge the expectations inherited from classical information processing. While copying information is a basic primitive of classical computation, the perfect cloning of an unknown quantum state is forbidden by the no-cloning theorem, as a direct consequence of the linear structure of quantum mechanics [1, 2]. These limitations, however, constitute defining features of quantum information processing. The no-cloning theorem forms a cornerstone of security proofs in quantum cryptography, ensuring that information encoded in quantum systems cannot be copied without introducing detectable disturbances [3]. Likewise, the transposition map plays an important role in entanglement theory, through the positive partial transpose (PPT) criterion for entanglement detection [4, 5], is known to allow better performance in estimation tasks [6–9] and it allows 2-copy incompatible measurements to become compatible [10]. However, transposition of a quantum state is a paradigmatic example of a positive but not completely positive map, and therefore cannot be physically realised as a quantum channel [4, 11].

The problem of circumventing such no-go theorems by identifying the best physically admissible approximations to unphysical transformations has been extensively studied in quantum information theory [12–24], with a general semidefinite-programming framework [25, 26]. In the case of pure-state inputs, optimal universal $N \to N + K$ quantum cloning machines have been characterised for arbitrary finite dimension [14, 15]. By contrast, previous results on optimal pure-state transposition were restricted to the qubit $N \to 1$ scenario, through its unitary equivalence with the universal NOT [21], and to the $1 \to 1$ setting in arbitrary finite dimension [27]. When considering mixed states, the quantum cloning problem is often referred to as quantum broadcasting [28], and most existing results are restricted to qubits [29–31]. In particular, Ref. [31] analysed the optimal qubit $N \to K$ broadcast NOT, which is unitarily equivalent to mixed-state $N \to K$ transposition for qubits, while qudit $N \to 1$ mixed-state transposition was studied in Ref. [17].

Moreover, in certain cases, a relation between cloning and transposition has been identified. The ancillary output of an isometry implementing the optimal universal $1 \to 2$ cloner was noticed to realise the optimal $1 \to 1$ transposition channel [32, 33], equivalent to the so-called *anticlone*. This is an instance of channel complementarity [34], in which two channels arise from different outputs of a single global isometry. However, since these results are not fully general in dimension and number of copies, it remains unclear whether the observed relationship between transposition and cloning is merely an artefact of these specific cases or reflects a fundamental connection between the two transformations. Identifying such complementarity relations reveals how different quantum-information tasks can emerge from the same underlying process, which is of direct importance, for example, in quantum Shannon theory, where the information available to the environment is closely tied to the communication capabilities of the original channel [34–37]

In this work, we prove that the connection between cloning and transposition persists in full generality for universal symmetric cloning of pure-state inputs. This shows that optimal physical realisations of forbidden quantum transformations can be related despite the disparate nature of the no-go theorems that prohibit th
More precisely, we consider quantum channels that
proximate the transformation of N copies of an arbitr