



Arts & crafts: Strong random unitaries and geometric locality

Marten Folkertsma,[1] Lorenzo Grevink,[2] Jonas Helsen,[2] and Alicja Dutkiewicz[2]

[1] *QuSoft and UvA, Amsterdam, the Netherlands*
[2] *QuSoft and CWI, Amsterdam, the Netherlands*

We study the problem of constructing strong approximate unitary k-designs on D-dimensional grids (and more generally on Cartesian products of graphs), building on the work of Schuster et al. [SML+25] which establishes strong unitary designs in 1D and in all-to-all connectivity. We provide two constructions. The first construction leverages the existing all-to-all connectivity result with general routing theory to provide flexible (but slightly suboptimal) strong k-designs in arbitrary connectivities. The second construction is more direct, requires no auxiliaries and has provably optimal depth (in the number of qubits n) for D-dimensional grids with constant dimension. Combining these techniques also allows us to construct strong pseudorandom unitaries on D-dimensional grids with provably optimal depth.

arXiv:2605.03023v1 [quant-ph] 4 May 2026

I. INTRODUCTION

Random quantum processes have been a growing field of study in quantum computing and quantum information theory, having significant applications in numerous fields of study including quantum machine learning [LTW+25], many-body physics [FKNV23], and quantum gravity [HP07, BGL+23]. Moreover, they are widely used in practical applications such as device benchmarking [EAŻ05, EFH+23], state tomography [HKP20, HW23] and quantum cryptography [JLS18, Kre21]. A natural theoretical model for randomness in quantum systems is given by Haar-random unitaries, which correspond to the uniform distribution over the unitary group. However, simple counting arguments show that implementing a Haar-random unitary requires resources exponential in the system size [Kni95], making them computationally intractable and physically unrealistic.

Consequently, a substantial line of work [HL09, NHKW16, HJ19, Haf22, HMMH+23, HM23, MPSY24, SHH25, CHH+25, MH25, SML+25, HLT25] is devoted to finding ensembles of unitaries that are efficient to construct, but appear to be Haar random in certain contexts. For example, an ensemble that appears to be random to any computationally-bounded adversary is called a *pseudorandom unitary* (PRU), and an ensemble that appears to be random to any adversary that samples a unitary at most k times is called a *unitary k-design*. More recently, *strong* variants of these notions have been introduced, in which the adversary is allowed access not only to a unitary U, but also to its inverse $U^\dagger$ [SML+25]. These provide a more faithful approximation to Haar randomness, as many quantum algorithms and physical processes naturally involve both forward and inverse evolutions, whereas the standard (weak) design condition provides no guarantee in this setting. Therefore, in this work we focus on strong designs and PRUs.

Recent works have provided efficient constructions of such random unitary ensembles via random quantum circuits – sequences of local random gates, typically acting on pairs of qubits. A crucial aspect of these constructions determining the scaling of resources with the number of qubits n is the underlying connectivity, which specifies which pairs of qubits can interact. In the most powerful setting of *all-to-all* connectivity, strong designs can be constructed in depth $\mathcal{O}(\log(n))$ [SML+25], and weak designs can be achieved in a surprisingly low depth of $\mathcal{O}(\log\log(n))$ [CSBH25]. At the other extreme, when qubits are arranged in a one-dimensional chain and can only interact with their nearest neighbors, a lightcone argument shows that strong designs require depth $\Omega(n)$, and this bound is achieved by [SML+25], while weak designs can be achieved in depth $\mathcal{O}(\log n)$ [SHH25, LL26], representing an exponential slowdown in both cases compared to all-to-all. These modern, optimal constructions rely on *gluing lemmas*, which allow combining small designs into larger ones. More general D-dimensional connectivities were studied prior to the introduction of strong designs and gluing lemmas, achieving the depth $d = \mathcal{O}\left(n^{1/D}\right)$ [HM23] for weak designs, which turned out to be not at all tight. The optimal depth for strong designs in intermediate connectivities remains an open question.

This question is not merely theoretical – intermediate connectivity structures are highly relevant in practice. While some emerging platforms based on neutral atoms [BGL+26] or ion traps [RAA+25] are expected to achieve (nearly) all-to-all connectivity, many others are designed to respect local geometries. For example, superconducting qubits [ACC+26, BM21, goo25] and silicon quantum dots [LPF+18] are typically laid out in regular two-dimensional grids. Higher dimensional geometries also arise: for instance, irregular three-dimensional geometries naturally appear in NV centers platforms, and three-dimensional lattices error-correcting codes have been studied due to the possibility of transversal magic gates [Bom15]. Moreover, beyond hardware considerations, regular lattices in arbitrary dimensions have been subject of theoretical studies of quantum chaos [LG22]. Together, these considerations motivate the main question of this paper:



Question. *At what depth do random circuits form strong unitary designs and PRUs in general connectivities?*