

2021–2025



arXiv:2606.25037v2 [quant-ph] 1 Oct 2026

Arbitrarily Loss-Tolerant Quantum Position Verification in a Single Execution

Llorenç Escolà-Farràs[1], Boris Škorić[1], and Florian Speelman[2,3]

[1] *Technische Universiteit Eindhoven, Eindhoven, The Netherlands*
[2] *QuSoft, CWI Amsterdam, The Netherlands*
[3] *University of Amsterdam, Amsterdam, The Netherlands*

October 2, 2026

Abstract

Quantum position verification (QPV) aims to certify the location of an untrusted prover, but faces two major obstacles: fundamentally, entanglement-based attacks and, experimentally, photon loss. A commitment-based modification introduced in *Phys. Rev. Lett.* **135**, 260801 addresses both in sequentially repeated protocols. Its security analysis, however, relies on the sequential structure and does not extend to parallel repetition. We use a different proof approach to establish security of the commitment modification for a parallel BB84-based QPV protocol. Against bounded-entanglement adversaries, the acceptance probability decays exponentially in the minimum number k of successfully committed qubits. The protocol tolerates arbitrary transmission loss and noise rates up to 3.7%, while allowing arbitrarily slow quantum communication. This yields a fully loss-tolerant, single-execution QPV protocol secure against bounded-entanglement attacks, removing transmission loss as a fundamental limitation on verification distance. We also revisit sequential repetition, correcting the treatment of conditioning on commitment and replacing the earlier conditional guarantee with an unconditional security bound, without the finite-size correction to the correctness gap. The resulting bound provides improved quantitative security parameters for experimental implementations.

1 Introduction

Quantum position verification (QPV) combines relativistic signalling constraints with quantum information to certify the spatial location of an untrusted prover P at a claimed position *pos*. In a one-dimensional setting, two verifiers V_0 and V_1 send information toward the claimed location and accept only if the prover returns correct answers within the time window consistent with being located at *pos*. Quantum information is essential for this task: even under computational assumptions, protocols relying solely on classical information can be broken in this setting by adversaries who copy and redistribute the transmitted information [CGMO09], whereas the no-cloning theorem prevents such a strategy for arbitrary quantum states.

Despite this no-cloning advantage, unconditional security of QPV is impossible. Adversaries sharing arbitrarily large amounts of entanglement can simulate an honest prover and break any QPV protocol [BCF+14, BK11]. Consequently, much of the literature has focused on restricted—but still powerful—adversarial models, most commonly by bounding the amount of pre-shared entanglement [KMSB06, KMS11, LL11, RG15, CL15, Spe16a, Dol19, DC22, GC19, CM22, BCS22, GLW16, EFPS24, Unr14, LLQ22, ACC+24, GGG+26, BHM+26, CM26, ACCM24, ACM25, EFS25]. When the number of pre-shared entangled qubits is bounded (bounded entanglement) by q, this setting is referred to as the BE(q) model. Moreover, QPV has recently progressed beyond a purely theoretical primitive, with the first experimental demonstrations reported in laboratory settings [KPB+25, KZG+26, FYSZ+26].

Among the most studied protocols is the BB84-based scheme $\mathrm{QPV}_{\mathrm{BB84}}$ [KMSB06, KMS11]. In this protocol, one verifier sends a BB84 state while the other sends the corresponding basis information, timed to arrive simultaneously at the claimed location. The prover measures the received