



# SpiderCSS: Scalable Fault-Tolerant CSS State Preparation

Boldizsár Poór,[1] Andrey Boris Khesin,[1] Sarah Meng Li,[2,3]
Benjamin Rodatz,[1] John van de Wetering,[2,3] and Richie Yeung[1]

[1] *University of Oxford, Oxford, United Kingdom*
[2] *University of Amsterdam, Amsterdam, Netherlands*
[3] *QuSoft, Amsterdam, Netherlands*

Fault-tolerant preparation of logical states is a critical primitive for the realization of large-scale fault-tolerant quantum computing. This paper introduces SpiderCSS, a scalable compilation pipeline that generates highly optimized, fault-tolerant state preparation circuits for arbitrary Calderbank-Shor-Steane (CSS) codes. Starting from an idealized specification of a CSS state, we use the ZX-calculus and fault-equivalent rewrites to construct a diagram that prepares the given state while preserving the fault tolerance of the initial ideal ZX-diagram. From this diagram, SpiderCSS constructs a fault-tolerant CSS-state preparation circuit using a modular construction that is CNOT-minimal both within each component and also in the way these components are connected together. By only using fault-equivalent rewrites, the final circuit is provably fault-tolerant without needing expensive verification. Monte Carlo simulations across a variety of CSS codes up to distance 15 show that SpiderCSS scales efficiently and constructs circuits with substantially reduced depth and qubit footprint compared to existing scalable and heuristic methods, while simultaneously achieving an average decrease of 33.7% in logical error rate and an increase 9.5% in acceptance rate.

arXiv:2610.03714v1 [quant-ph] 2 Oct 2026

## I. INTRODUCTION

Fault-tolerant quantum computation requires reliable preparation of encoded states [1]. To ensure fault tolerance we require controlling fault propagation, since a single circuit fault can affect several output qubits. The challenge is to achieve fault tolerance with low quantum resource overhead while keeping circuit construction tractable as code size and distance increase. In this paper, we will focus on preparing states in CSS codes.

*Calderbank–Shor–Steane (CSS) codes* [2, 3] are stabilizer codes with purely $X$- and $Z$-type generators, whose logical states $|\bar{0}\rangle$ and $|\bar{+}\rangle$ are examples of *CSS states*. These states are used as logical inputs to a computation and as ancillas for syndrome extraction in Steane-style error correction [4–8].

The current best methods for CSS state preparation either use hand-optimized circuits, SAT solvers, or heuristic modular constructions. Hand-optimized circuits can achieve low overhead but rely on code-specific human insight that is difficult to scale systematically [9–11]. Automated synthesis using satisfiability (SAT) solvers or Integer Linear Programming (ILP) can produce highly-optimized circuits for small codes, but the search becomes expensive as the code size and required level of fault tolerance increase [12–14].

The current best modular construction, Flag at Origin (FaO) [15], improves the scalability of circuit construction through reusable flag gadgets and its resource overhead depends on how these components are assembled and scheduled. FaO works by first constructing a library of fault-tolerant flagged gadgets which makes it possible to fault-tolerantly apply a sequence of control (or target) operations of a CNOT gate on a single qubit. Utilizing the fact that any CSS state can be constructed in a way that only control or target operations are applied to each qubit, FaO composes these flagged gadgets to obtain a fully fault-tolerant CSS-state preparation circuit. While this method scales much better than methods relying on SAT solvers or ILP, it is still computationally limited by the (offline) generation of the flagged gadgets and the resulting circuits can have a large depth due to the depth of the flagged gadgets.

In this paper, we present *SpiderCSS*, a new modular construction that significantly improves upon the state-of-the-art FaO in terms of scalability, resource usage, depth, acceptance rate, and logical error rate. First, each component of our pipeline runs in polynomial time so that our method is scalable beyond what was possible before. Second, our method requires fewer entangling gates and achieves lower depth. This is achieved by using a better approach to construct fault-tolerant CAT states based on the SpiderCat [16] and Fault Tolerance by Construction [17] frameworks, then finding novel ways to route the qubit lines to minimize the cost of connecting the states together to form the target CSS state. Third, our method has an improved acceptance rate (meaning the average number of shots needed to get one that passes all the checks is lower) and a lower logical error probability (meaning the chance we accept a run that actually contains a non-trivial logical error is lower). We achieve this by minimizing the number of flags in the CAT states in our construction and by letting our qubit routing algorithm try to minimize qubit lifetime and maximize qubit reuse.

In total, we benchmarked our pipeline on codes ranging from 7 to 144 qubits and from distance 3 to distance 15. The results are shown in Figure 1. In all directly comparable cases, we match or improve on the CNOT count, with reductions of up to 53.8%. When prioritizing depth, our circuits are consistently shallower than those of FaO, with nearly 10× reduction in circuit depth in the best case. Estimated logical error rates are lower for most codes with reported results, with the largest reduction being approximately 90%, while acceptance rates are higher across all benchmarks.