
2016–
2022


2015–
2019



arXiv:1804.05058v1 [quant-ph] 13 Apr 2018

Improvements in Quantum SDP-Solving with Applications

Joran van Apeldoorn* András Gilyén†

Abstract

Following the first paper on quantum algorithms for SDP-solving by Brandão and Svore [BS17] in 2016, rapid developments has been made on quantum optimization algorithms. In 2017 van Apeldoorn et al. [AGGW17] improved the quantum algorithm introduced by [BS17] and gave stronger lower bounds as well. Recently Brandão et al. [BKL+18] improved the quantum SDP-solver in the so-called quantum state input model, where the input matrices of the SDP are given as purified mixed states. They also gave the first non-trivial application of quantum SDP-solving by obtaining a more efficient algorithm for the problem of shadow tomography [Aar17].

In this paper we improve on all previous quantum SDP-solvers. Mainly we construct better Gibbs-samplers for both input models, which directly gives better bounds for SDP-solving. We also combine the Fast Quantum OR lemma of Brandão et al. [BKL+18] and the Gentle Quantum Search Lemma of Aaronson [Aar17], and use the techniques from van Apeldoorn et al. [AGGW17] to give an improved general quantum SDP-solving framework. For an SDP with m constraints involving $n \times n$ matrices, our improvements yield an $\widetilde{\mathcal{O}}\big((\sqrt{m}+\sqrt{n}\gamma)s\gamma^4\big)$ upper bound on SDP-solving in the sparse matrix input model and an $\widetilde{\mathcal{O}}\big(\big(\sqrt{m}+B^{2.5}\gamma^{3.5}\big)B\gamma^4\big)$ upper bound in the quantum state input model. Here $\gamma = Rr/\varepsilon$ is the additive error ε scaled down with bounds R and r on the size of optimal solutions, s is the row-sparsity of the input matrices in the sparse matrix input model and B is a normalization factor for the input states in the quantum state model. We also introduce the quantum operator input model, which generalizes both other input models. In this more general model we give an $\widetilde{\mathcal{O}}\big((\sqrt{m}+\sqrt{n}\gamma)\alpha\gamma^4\big)$-query algorithm, where α is a normalization factor of the input operators.

We then apply these results to the problem of shadow tomography to simultaneously improve the best known upper bounds on sample complexity [Aar17] and complexity [BKL+18]. Furthermore, we apply our quantum SDP-solvers to the problems of quantum state discrimination and E-optimal design. In both cases we beat the classical lower bound in terms of some parameters, at the expense of heavy dependence on some other parameters.

Finally we prove two lowers bounds for solving SDPs using quantum algorithms: (1) $\tilde{\Omega}(\sqrt{m}B/\varepsilon)$ in the quantum state input model, and (2) $\tilde{\Omega}(\sqrt{m}\alpha/\varepsilon)$ in the quantum operator input model. These lower bounds show that the $\sqrt{m}$ factor and the polynomial dependence on the parameters B, α, and $1/\varepsilon$ are necessary.

*QuSoft, CWI, the Netherlands. Supported by the Netherlands Organization for Scientific Research, grant number 617.001.351. apeldoor@cwi.nl

†QuSoft, CWI, the Netherlands. Supported by ERC Consolidator Grant 615307-QPROGRESS. gilyen@cwi.nl