



2016–
2021

arXiv:1809.01261v3 [quant-ph] 2 Jul 2019

Dynamical fidelity susceptibility of decoherence-free subspaces

Joris Kattemölle, Jasper van Wezel
Institute for Theoretical Physics, University of Amsterdam, Science Park 904, Amsterdam, The Netherlands and
QuSoft, CWI, Science Park 123, Amsterdam, The Netherlands

In idealized models of a quantum register and its environment, quantum information can be stored indefinitely by encoding it into a decoherence-free subspace (DFS). Nevertheless, perturbations to the idealized register-environment coupling will cause decoherence in any realistic setting. Expanding a measure for state preservation, the dynamical fidelity, in powers of the strength of the perturbations, we prove stability to linear order is a generic property of quantum state evolution. The effect of noise perturbation is quantified by a concise expression for the strength of the quadratic, leading order, which we define as the dynamical fidelity susceptibility of DFSs. Under the physical restriction that noise acts on the register k-locally, this susceptibility is bounded from above by a polynomial in the system size. These general results are illustrated by two physically relevant examples. Knowledge of the susceptibility can be used to increase coherence times of future quantum computers.

I. INTRODUCTION

Quantum computers may be used to simulate general quantum mechanical systems [1, 2]. Already they drive an enormous effort in the control of quantum systems [3] and spur interest in quantum information theory, with connections to high-energy physics [4–6] and the quantum-to-classical transition [7].

The biggest roadblock on the way to scalable quantum computation is that of noise and decoherence [8–10]. Quantum error correction offers solutions to this problem [11, 12]. In active quantum error correction, errors have to be detected and corrected, whereas in passive error correction, the strategy is to avoid the errors by encoding. The two forms of error correction can be used in conjunction [13, 14], and can be described in the same mathematical framework [15].

An important player in the passive category is the decoherence-free subspace (DFS) [10, 14, 16–21]. Although DFSs have been superseded theoretically by more general notions of passive error correction [22], they remain of interest both in theory and in practice [23–25]. In this technique, symmetries of the register-environment coupling are exploited to store quantum information in a register subspace whose reduced time evolution is purely unitary. In contrast to states outside of a DFS, those in it do not suffer from decoherence. Only register-environment models with enough symmetry allow for DFSs.

In real systems, there are small deviations from the idealized model of the interaction between the quantum register (the 'system') and the environment (the 'bath'). In particular, these may lead to 'super-decoherence' [26], where the decoherence time scales adversely with the system size, even for states in a DFS. Quantifying the sensitivity of DFSs to perturbations has lead to the definition of the 'dynamical fidelity' [20, 27].

The dynamical fidelity is a measure for the closeness of two states: (*i*) a state, possibly in a DFS, evolving in time under the original model, and (*ii*) the *same* initial state, evolving under the presence of an additional system-bath interaction whose strength is proportional to ε. At the initial time, the dynamical fidelity equals unity, but as time evolves the two states will start to diverge, decreasing the fidelity. The dynamical fidelity can be seen as a generalization of the Loschmidt echo [28] to open quantum systems, and is related to a different fidelity in the context of phase transitions [29–31]. Here the fidelity measures the closeness between the ground states of Hamiltonians with different parameter values.

In an initial qualitative study [27], it was shown the dynamical fidelity can *only* depend linearly on ε whenever the unperturbed system evolves unitarily on its own in a nontrivial way. This is so for nondegenerate logical states, or whenever the quantum register is used in a quantum computation. Conversely, there is no term linear in ε whenever the quantum register does not evolve on its own. This led to the conclusion that DFSs are 'robust' or 'stable' against perturbations when used as quantum memory, but not when used during a quantum computation [20, 21, 27, 28, 32–35].

Here we prove there never is a linear dependence on ε. In the parlance of the previous work this means DFSs are also stable when used during a quantum computation. However, we show the result even holds for initial states outside of a DFS. In retrospect, the absence of a linear term in the expansion of the dynamical fidelity is a consequence of its definition. This can be considered positive for DFSs, because it shows states in a DFS do not react more strongly to perturbations than regular states. For the fidelity in the context of phase transitions the absence of a linear term is already known [29–31].

We go on to introduce the dynamical fidelity susceptibility of DFSs (χ), 'susceptibility' for short, defined as the strength of the term in the dynamical fidelity proportional to $\varepsilon^2 t^2$ [36]. As the first nontrivial term, the susceptibility quantifies the leading order sensitivity to perturbations of states in a DFS. Surprisingly, it does not depend on the unperturbed Hamiltonian, so the leading order behavior of DFSs is as if there were no unperturbed