
2014–
2018


2018–
2020



Quantum hardness of learning shallow classical circuits

Srinivasan Arunachalam* Alex B. Grilo † Aarthi Sundaram ‡

arXiv:1903.02840v2 [quant-ph] 19 Sep 2019

Abstract

In this paper, we study the quantum learnability of constant-depth classical circuits under the uniform distribution and in the distribution-independent framework of PAC learning. In order to attain our results, we establish connections between quantum learning and quantum-secure cryptosystems. We then achieve the following results.

1. **Hardness of learning AC^0 and TC^0 under the uniform distribution.** Our first result concerns the concept class TC^0 (resp. AC^0), the class of constant-depth and polynomial-sized circuits with unbounded fan-in majority gates (resp. AND, OR, NOT gates). We show the following:

   - if there exists no quantum (quasi-)polynomial-time algorithm to solve the Ring-Learning with Errors (RLWE) problem, then there exists no (quasi-)polynomial-time quantum learning algorithm for TC^0; and
   - if there exists no $2^{O(d^{1/\eta})}$-time quantum algorithm to solve RLWE with dimension $d = O(\text{polylog}\, n)$ (for every constant $\eta > 2$), then there exists no $O(n^{\log^{\nu} n})$-time quantum learning algorithm for $\text{poly}(n)$-sized AC^0 circuits (for a constant $\nu > 0$), matching the *classical* upper bound of Linial et al. [LMN93]

   where the learning algorithms are under the uniform distribution (even with access to quantum membership queries). The main technique in these results uses an explicit family of pseudo-random functions that are believed to be quantum-secure to construct concept classes that are hard to learn quantumly under the uniform distribution.

2. **Hardness of learning TC^0_2 in the PAC setting.** Our second result shows that if there exists no quantum polynomial-time algorithm for the LWE problem, then there exists no polynomial-time quantum-PAC learning algorithm for the class TC^0_2, i.e., depth-2 TC^0 circuits. The main technique in this result is to establish a connection between the quantum security of public-key cryptosystems and the learnability of a concept class that consists of decryption functions of the cryptosystem.

Our results show that quantum resources do not give an *exponential* improvement to learning constant-depth polynomial-sized neural networks. This also gives a strong (conditional) negative answer to one of the "Ten Semi-Grand Challenges for Quantum Computing Theory" raised by Aaronson [Aar05].

*Center for Theoretical Physics, MIT. Funded by the MIT-IBM Watson AI Lab under the project *Machine Learning in Hilbert space*. arunacha@mit.edu

†CWI and QuSoft, Amsterdam, The Netherlands. Supported by ERC Consolidator Grant 615307-QPROGRESS. alexg@cwi.nl

‡Joint Center for Quantum Information and Computer Science, University of Maryland, USA. Supported by the Department of Defense. aarthims@umd.edu