

2015–
2019



Quadratic speedup for finding marked vertices by quantum walks

Andris Ambainis* András Gilyén† Stacey Jeffery‡ Martins Kokainis§

March 19, 2019

arXiv:1903.07493v1 [quant-ph] 18 Mar 2019

Abstract

A quantum walk algorithm can detect the presence of a marked vertex on a graph quadratically faster than the corresponding random walk algorithm (Szegedy, FOCS 2004). However, quantum algorithms that actually find a marked element quadratically faster than a classical random walk were only known for the special case when the marked set consists of just a single vertex, or in the case of some specific graphs. We present a new quantum algorithm for finding a marked vertex in any graph, with any set of marked vertices, that is (up to a log factor) quadratically faster than the corresponding classical random walk.

1 Introduction

As shown by Szegedy [Szeg04], quantum walks provide a quadratic speedup over classical random walks for search tasks. If a classical random walk hits a marked element in an expected number of HT steps, called the *hitting time*, then the quantum walk runs in time $\mathcal{O}\big(\sqrt{HT}\big)$. However, this speedup comes with a caveat: the quantum walk does not necessarily *find* a marked element, but it can *detect* a deviation from the starting state caused by marked elements. This issue has been well known since Szegedy's work in 2004, yet it has eluded all attempts to solve it.

Several generalizations of Szegedy's framework have been proposed but they only solve this issue in restricted cases. Tulsi [Tul08] showed how to solve it for the random walk on an $N \times N$ grid with exactly one marked element. Here, the classical hitting time is $HT = \mathcal{O}\big(N^2 \log N\big)$. Szegedy's algorithm detects the presence of a marked element in $\mathcal{O}\big(\sqrt{HT}\big) = \mathcal{O}\big(N\sqrt{\log N}\big)$ steps. Measuring the final state of Szegedy's algorithm, however, only gives the marked element with probability $\Theta(1/\log N)$. Tulsi showed how to improve this to $\Theta(1)$, with the running time remaining $\mathcal{O}\big(N\sqrt{\log N}\big)$. Magniez, Nayak, Richter and Santha [MNRS12] then extended this to the random walk on any vertex transitive graph with exactly one marked element. Meanwhile Magniez, Nayak, Roland and Santha [MNRS11] presented an alternative extension of Szegedy's work, giving a quantum algorithm for finding a marked vertex that runs in a number of steps $\mathcal{O}\big(\sqrt{1/(\delta\varepsilon)}\big)$, where δ is the eigenvalue gap of (the Markov chain corresponding to) the walk and ε is the probability that a vertex is initially marked. This can be as small as $\mathcal{O}\big(\sqrt{HT}\big)$ in certain cases, but significantly larger in others.

Later, Krovi, Magniez, Ozols and Roland [KMOR16] proposed a new algorithm (based on a new notion of interpolated quantum walk) that achieves a quadratic advantage for finding a marked element for a random walk on any graph G with exactly one marked element. The same result was achieved by Dohotaru and Høyer [DH17], using a different method.

*Faculty of Computing, University of Latvia. Supported by Latvian Council of Science grant lzp-2018/1-0173 and QuantERA project QuantAlgo 680-91-034.

†QuSoft, CWI and University of Amsterdam, the Netherlands. Supported by ERC Consolidator Grant QPROGRESS and partially supported by QuantERA project QuantAlgo 680-91-034.

‡QuSoft and CWI, the Netherlands. Supported by an NWO Veni Innovational Research Grant under project number 639.021.752 and an NWO WISE Grant.

§Faculty of Computing, University of Latvia. Supported by QuantERA project QuantAlgo 680-91-034.