
2018–
2019


2015–
2019



arXiv:1912.04233v1 [quant-ph] 9 Dec 2019

A Unified Framework of Quantum Walk Search

Simon Apers* András Gilyén†,‡ Stacey Jeffery§

December 10, 2019

Abstract

The main results on quantum walk search are scattered over different, incomparable frameworks, most notably the *hitting time framework*, originally by Szegedy, the *electric network framework* by Belovs, and the *MNRS framework* by Magniez, Nayak, Roland and Santha. As a result, a number of pieces are currently missing. For instance, the electric network framework allows quantum walks to start from an arbitrary initial state, but it only detects marked elements. In recent work by Ambainis et al., this problem was resolved for the more restricted hitting time framework, in which quantum walks must start from the stationary distribution.

We present a new quantum walk search framework that unifies and strengthens these frameworks. This leads to a number of new results. For instance, the new framework not only detects, but finds marked elements in the electric network setting. The new framework also allows one to interpolate between the hitting time framework, which minimizes the number of walk steps, and the MNRS framework, which minimizes the number of times elements are checked for being marked. This allows for a more natural tradeoff between resources. Whereas the original frameworks only rely on quantum walks and phase estimation, our new algorithm makes use of a technique called *quantum fast-forwarding*, similar to the recent results by Ambainis et al. As a final result we show how in certain cases we can simplify this more involved algorithm to merely applying the quantum walk operator some number of times. This answers an open question of Ambainis et al.

1 Introduction

Quantum walk search refers to the use of quantum walks to solve a search problem on a graph. In the last two decades, this topic has received a great deal of attention, with a rich literature attesting to the progress on understanding quantum walk algorithmic techniques [AKR05, Sze04, MNRS11, KMOR16, Bel13, AGJK19, DH17] and developing applications [BŠ06, MSS07, JKM12, BCJ+13, BJLM13, Mon18, KT17, HM18, Kir18]. Despite this long line of progress, the main results on quantum walk search lie somewhat scattered in different frameworks, and a number of pieces are currently missing.

The quantum walk search frameworks that we consider are the *hitting time framework* originally due to Szegedy [Sze04], the *MNRS framework* due to Magniez, Nayak, Roland and Santha [MNRS11], the *electric network framework* due to Belovs [Bel13], and the *controlled quantum amplification framework* by Dohotaru and Høyer [DH17]. We summarize these frameworks, as well as the corresponding complexities, in Table 1. In this work we unify these different

*Inria, France and CWI, the Netherlands. Supported by the CWI-Inria International Lab. simon.apers@inria.fr

†QuSoft, CWI and University of Amsterdam, the Netherlands. Supported by ERC Consolidator Grant QPROGRESS and partially supported by QuantERA project QuantAlgo 680-91-034.

‡Caltech, USA. Supported by the Institute for Quantum Information and Matter, an NSF Physics Frontiers Center (NSF Grant PHY-1733907). agilyen@caltech.edu

§QuSoft and CWI, the Netherlands. Supported by an NWO Veni Innovational Research Grant under project number 639.021.752, an NWO WISE Grant, and QuantERA project QuantAlgo 680-91-03. SJ is a CIFAR Fellow in the Quantum Information Science Program. jeffery@cwi.nl