

2017–
2021



Quantum Algorithm for Path-Edge Sampling

Stacey Jeffery[1], Shelby Kimmel[2], and Alvaro Piedrafita[1]

[1]CWI & QuSoft
[2]Middlebury College, skimmel@middlebury.edu

arXiv:2303.03319v1 [quant-ph] 6 Mar 2023

Abstract

We present a quantum algorithm for sampling an edge on a path between two nodes s and t in an undirected graph given as an adjacency matrix, and show that this can be done in query complexity that is asymptotically the same, up to log factors, as the query complexity of detecting a path between s and t. We use this path sampling algorithm as a subroutine for st-path finding and st-cut-set finding algorithms in some specific cases. Our main technical contribution is an algorithm for generating a quantum state that is proportional to the positive witness vector of a span program.

1 Introduction

Finding and detecting paths between two vertices in a graph are important related problems, both in and of themselves, and as subroutines in other applications, but there is still much to understand in this area. While classically these problems seem to be equivalent, an intriguing question is whether the same holds for quantum algorithms: there are cases where a quantum algorithm can *detect* a path between s and t in significantly less time than any known quantum algorithm takes to *find* such a path. In particular, path finding on a glued trees graph is one of Aaronson's top ten open problems in query complexity [CCD+03, Aar21], as the best known quantum algorithms that find an st-path in such graphs have exponentially worse running time than the best quantum algorithms for detecting one, and understanding how these problems are related could improve our understanding of why quantum computers achieve dramatic speedups for certain problems. As an example of more immediate practical interest: path finding in supersingular isogeny graphs is one approach to attacking cryptosystems based on supersingular isogenies [CLG07, DJP14], but currently the best known attack of this form still takes exponential time [Tan09] (see also [GV18]).

In this paper, we consider the quantum query complexity of a somewhat intermediate problem: finding an edge on an st-path in an undirected graph.[1] In the classical case, it seems hard to imagine how one could find an edge on an st-path without first finding an st-path, but we show that in the quantum case, one can sample an st-path edge with similar resources to what is needed to detect the existence of an st-path. In some cases, this can be done with significantly fewer queries than the best previously known path-finding algorithms. We show this ability to sample an edge on a path has some useful applications, including to sabotaging networks (finding st-cut sets) and to finding paths in certain graphs faster than existing path finding algorithms.

Previously, Dürr, Heiligman, Høyer and Mhalla [DHHM06] described an algorithm for connectivity in the adjacency matrix model that uses $O(n^{3/2})$ queries for an n-vertex graph. Their algorithm works by keeping track of known connected components, and then uses a quantum search to look for any edge that connects any two components previously not known to be connected. While the authors use this algorithm to decide connectivity, we note that after $O(n^{3/2})$

[1]In this paper, we use *path* to refer to a self-avoiding path, meaning a path with no repeated vertices.