
2021–
2025


2022–
2025



A quantum cloning game with applications to quantum position verification

Llorenç Escolà-Farràs, [1,2] Léo Colisson Palais [1,3] and Florian Speelman, [1,2]

[1] QuSoft & CWI Amsterdam, The Netherlands
[2] QuSoft & Informatics Institute, University of Amsterdam, The Netherlands
[3] Laboratoire Jean Kuntzmann, Université Grenoble Alpes, France

We introduce a quantum cloning game in which k separate collaborative parties receive a classical input, determining which of them has to share a maximally entangled state with an additional party (referee). We provide the optimal winning probability of such a game for every number of parties k, and show that it decays exponentially when the game is played n times in parallel. These results have applications to quantum cryptography, in particular in the topic of quantum position verification, where we show security of the routing protocol (played in parallel), and a variant of it, in the random oracle model.

arXiv:2410.22157v1 [quant-ph] 29 Oct 2024

Introduction.— Non-local correlations have extensively been studied in the field of quantum information theory, see e.g. [1]. Bell [2] originally showed that distant parties sharing quantum resources can reproduce correlations that could never be attained by any classical theory. Often, non-local correlations are studied as *non-local games*, which provide an operational framework for understanding them. These games are interesting per se from a fundamental point of view, since they give rise to understanding the underlying essence of nature, but they additionally lead to applications such as secure key distribution [3], certified randomness [4], reduced communication complexity [5], self-testing [6, 7], and computation [8].

A vast literature in non-local games covers the scenario where a classical referee sends questions to non-communicating collaborative parties, and their task is to produce answers according to a certain publicly-known predicate, where the questions and answers are all *classical*. The best-known non-local game is the CHSH game [9]. Non-locality has also been investigated in terms of supersets of non-local games, called *monogamy-of-entanglement (MoE) games* [10], where a quantum referee sends the same classical question to the players and the parties have to guess the (classical) outcome of a referee's quantum measurement (depending on the question). MoE games have been used to provide security proofs for the quantum cryptographic primitives device-independent quantum key distribution [11] and quantum position verification [12]. Such games were later generalized under the name of *extended non-local games* [13].

Here, we introduce the concept of the *quantum cloning game*, played by k distant parties and a quantum referee. The referee publically announces a party, i.e., sends the same classical question to all the players, and the chosen party has to end up with the maximally entangled (EPR) state with the referee. At the beginning of the game, the players are allowed to share any quantum state with the referee. In this work, we show that the optimal winning probability for players using any quantum resources is given by $\frac{1}{2} + \frac{1}{2k}$, converging to $\frac{1}{2}$ for a large number of players. We analyze the game when it is played n times in parallel, showing an exponential decay in n of the optimal winning probability. Additionally, the quantum cloning game can be generalized to any arbitrary quantum state instead of an EPR state, and we provide its optimal winning probability.

We show that these results have applications in quantum position verification (QPV), which is a cryptographic primitive consisting of verifying the location of an untrusted party. Securely implementing this primitive is unachievable using only classical information, because a general attack exists even when using computational assumptions [14]. Due to the no-cloning theorem [15] the general classical attack does not apply if quantum information is used instead [12, 16], however, a general quantum attack exists which requires exponential entanglement [17, 18]. This means that hope for protocols secure against reasonable amounts of entanglement is alive, and indeed there has been much analysis on attacks on specific protocols [12, 19–27], and security analysis under extra assumptions [28, 29], such as the random oracle model [30]. A generic 1-dimensional (the main ideas generalize to higher dimensions) QPV protocol is described in the following way: two verifiers V_0 and V_1, placed on the left and right of an untrusted prover P, supposedly at the position *pos*, send quantum and classical messages to P at the speed of light, and he has to pass a challenge and reply correctly to them at the speed of light as well, if so, the verifiers *accept*, and if any of them receives a wrong answer or the timing does not correspond with the time it would have taken for light to travel back from the honest prover, the verifiers *reject*. The time consumed by the prover to perform the challenge is assumed to be negligible, and the verifiers are assumed to have perfectly-synchronized clocks.

In this work, we consider the *routing* QPV protocol [12], which has an appealing simple form: the prover has to return a received qubit to one of the verifiers, where the choice of verifier is a function of the classical information sent by the verifiers [12]. Besides the theoretical interest of this protocol, it is also an appealing candidate for free-space quantum position verification, when the quantum messages can travel with the vacuum speed of light, since the hardware of the prover could hypothetically be as simple as a mirror or an optical switch. Despite theoretical work on this protocol [27, 31–34], there were gaps left