


2021–
2026

QuSoft is named on page 13 of the paper.

arXiv:2204.12303v3 [quant-ph] 20 Dec 2023

ON CONVERSES TO THE POLYNOMIAL METHOD

JOP BRIËT AND FRANCISCO ESCUDERO GUTIÉRREZ

Abstract. A surprising 'converse to the polynomial method' of Aaronson et al. (CCC'16) shows that any bounded quadratic polynomial can be computed exactly in expectation by a 1-query algorithm up to a universal multiplicative factor related to the famous Grothendieck constant. A natural question posed there asks if bounded quartic polynomials can be approximated by 2-query quantum algorithms. Arunachalam, Palazuelos and the first author showed that there is no direct analogue of the result of Aaronson et al. in this case. We improve on this result in the following ways: First, we point out and fix a small error in the construction that has to do with a translation from cubic to quartic polynomials. Second, we give a completely explicit example based on techniques from additive combinatorics. Third, we show that the result still holds when we allow for a small additive error. For this, we apply an SDP characterization of Gribling and Laurent (QIP'19) for the completely-bounded approximate degree.

1. Introduction

A celebrated result of Beals et al. [BBC+01], known as the *polynomial method* in quantum complexity theory, leverages the problem of lower bounding the quantum query complexity of a Boolean function to lower bounding the approximate degree. The method is based on the fact that for every t-query quantum algorithm $\mathcal{A}$ that takes an n-bit input and returns a sign, there is a real n-variable polynomial f of degree at most $2t$ such that $f(x) = \mathbb{E}[\mathcal{A}(x)]$ for every x. Here, the expectation is taken with respect to the randomness in the measurement done by $\mathcal{A}$.[1] In addition to many new lower bounds, this result led to a line of

This research was supported by the European Union's Horizon 2020 research and innovation programme under the Marie Skłodowska-Curie grant agreement no. 945045, and by the NWO Gravitation project NETWORKS under grant no. 024.002.003.

[1] We identify a quantum query algorithm with the (random) function representing its output on a given input string.