


2022–
2023

2021–
2025



QuSoft is named on page 39 of the paper.

arXiv:2302.02870v2 [cs.CC] 19 Dec 2023

NOISY DECODING BY SHALLOW CIRCUITS WITH PARITIES: CLASSICAL AND QUANTUM

JOP BRIËT, HARRY BUHRMAN, DAVI CASTRO-SILVA,
AND NIELS M. P. NEUMANN

Abstract. We consider the problem of decoding corrupted error correcting codes with $\mathrm{NC}^0[\oplus]$ circuits in the classical and quantum settings. We show that any such classical circuit can correctly recover only a vanishingly small fraction of messages, if the codewords are sent over a noisy channel with positive error rate. Previously this was known only for linear codes with large dual distance, whereas our result applies to any code. By contrast, we give a simple quantum circuit that correctly decodes the Hadamard code with probability $\Omega(\varepsilon^2)$ even if a $(1/2-\varepsilon)$-fraction of a codeword is adversarially corrupted.

Our classical hardness result is based on an equidistribution phenomenon for multivariate polynomials over a finite field under biased input-distributions. This is proved using a structure-versus-randomness strategy based on a new notion of rank for high-dimensional polynomial maps that may be of independent interest.

Our quantum circuit is inspired by a non-local version of the Bernstein-Vazirani problem, a technique to generate "poor man's cat states" by Watts et al., and a constant-depth quantum circuit for the OR function by Takahashi and Tani.

1. Introduction

Error correcting codes (ECCs), formally introduced in Shannon's celebrated work [Sha48], protect digital signals from noise. An ECC is a map $E : \Sigma^k \to \Sigma^n$, for a finite alphabet Σ and positive integers $n \geq k$, with the property that any message $x \in \Sigma^k$ can be decoded from the codeword $E(x)$ even if the codeword is partially corrupted. If too many errors occur, however, recovering the original message may become impossible. In such cases one can instead resort to *list decoding*, an influential idea proposed in seminal works of Elias [Eli57] and Wozencraft [Woz58], which aims to give a small list of messages whose

This work was supported by the Dutch Research Council (NWO/OCW), as part of the Quantum Software Consortium programme (project number 024.003.037), the NETWORKS programme (grant no. 024.002.003), and the Quantum Delta NL program.
This is the full version of an extended abstract that appeared in the proceedings of ITCS'24.