

2021–
2026

QuSoft is named on page 19 of the paper.

arXiv:2304.06713v2 [quant-ph] 28 Jun 2023

INFLUENCES OF FOURIER COMPLETELY BOUNDED POLYNOMIALS AND CLASSICAL SIMULATION OF QUANTUM ALGORITHMS

FRANCISCO ESCUDERO GUTIÉRREZ

Abstract. We give a new presentation of the main result of Arunachalam, Briët and Palazuelos (SICOMP'19) and show that quantum query algorithms are characterized by a new class of polynomials which we call Fourier completely bounded polynomials. We conjecture that all such polynomials have an influential variable. This conjecture is weaker than the famous Aaronson–Ambainis (AA) conjecture (Theory of Computing'14), but has the same implications for classical simulation of quantum query algorithms.

We prove a new case of the AA conjecture by showing that it holds for homogeneous Fourier completely bounded polynomials. This implies that if the output of d-query quantum algorithm is a homogeneous polynomial p of degree $2d$, then it has a variable with influence at least $\mathrm{Var}[p]^2$.

In addition, we give an alternative proof of the results of Bansal, Sinha and de Wolf (CCC'22 and QIP'23) showing that block-multilinear completely bounded polynomials have influential variables. Our proof is simpler, obtains better constants and does not use randomness.

1. Introduction

Understanding the quantum query complexity of Boolean functions $f : D \to \{-1, 1\}$, where D is a subset of $\{-1, 1\}^n$, has been a crucial task of quantum information science [Amb18]. Query complexity is a model of computing where rigorous upper and lower bounds can be proven, which allows one to compare the power of quantum computers with classical ones. Many celebrated quantum algorithms show an advantage in terms of query complexity, for example in unstructured search [Gro96], period finding [Sho99], Simon's problem [Sim97], NAND-tree evaluation [FGG07] and element distinctness [Amb07]. However, these advantages are limited to be polynomial in the case of total functions (those with $D = \{-1, 1\}^n$), while they can be exponential for highly structured problems (informally, this means that $|D| = o(2^n)$), such as for Simon's problem [Sim97], period finding [Sho99] or k-fold forrelation [AA15, Tal20, BS21, SSW21]. It is widely believed that a lot of structure is necessary for superpolynomial speedups[1]. The following folklore conjecture, which has circulated since the late 90s, but was first formally posed by Aaronson and Ambainis [AA09], formalizes this idea.

This research was supported by the European Union's Horizon 2020 research and innovation programme under the Marie Skłodowska-Curie grant agreement no. 945045, and by the NWO Gravitation project NETWORKS under grant no. 024.002.003.

[1]Recently, Yamakawa and Zhandry showed that superpolynomial speedups can be attained in unstructured search problems. However, that does not contradict the believe that structure is needed to achieve superpolynomial speedups in decision problems, which are those modeled by Boolean functions [YZ22].