

2023–
2024

QuSoft is named on page 37 of the paper.

arXiv:2412.03182v1 [quant-ph] 4 Dec 2024

QUANTITATIVE CONVERGENCE OF TRAINED QUANTUM NEURAL NETWORKS TO A GAUSSIAN PROCESS

ANDERSON MELCHOR HERNANDEZ, FILIPPO GIRARDI, DAVIDE PASTORELLO, AND GIACOMO DE PALMA

Abstract. We study quantum neural networks where the generated function is the expectation value of the sum of single-qubit observables across all qubits. In [Girardi *et al.*, arXiv:2402.08726], it is proven that the probability distributions of such generated functions converge in distribution to a Gaussian process in the limit of infinite width for both untrained networks with randomly initialized parameters and trained networks. In this paper, we provide a quantitative proof of this convergence in terms of the Wasserstein distance of order 1. First, we establish an upper bound on the distance between the probability distribution of the function generated by any untrained network with finite width and the Gaussian process with the same covariance. This proof utilizes Stein's method to estimate the Wasserstein distance of order 1. Next, we analyze the training dynamics of the network via gradient flow, proving an upper bound on the distance between the probability distribution of the function generated by the trained network and the corresponding Gaussian process. This proof is based on a quantitative upper bound on the maximum variation of a parameter during training. This bound implies that for sufficiently large widths, training occurs in the lazy regime, *i.e.*, each parameter changes only by a small amount. While the convergence result of [Girardi *et al.*, arXiv:2402.08726] holds at a fixed training time, our upper bounds are uniform in time and hold even as $t \to \infty$.

Contents

1. Introduction 2
1.1. Our results 3
2. Preliminaries 4
2.1. Training data 5
2.2. Quantum neural networks 5
2.3. Light cones 6
2.4. Assumptions on architecture and initialization 7
2.5. The neural tangent kernel 9
2.6. The assumptions for the neural tangent kernel 10
2.7. The expected behavior of $N(m)$ in circuits with logarithmic depth 10
2.8. The Wasserstein distance of order 1 11
3. Some relevant facts about Gaussian Processes 12
4. Multidimensional Stein methods 13
4.1. The analytic solution for the linearized model 14
5. Main results 15
6. Convergence at initialization 16
7. Convergence of the trained network 19
7.1. Quantitative lazy training for a finite size circuit 19
7.2. The Wasserstein distance between f and f^{lin} 24
7.3. The closeness between f^{lin} and a Gaussian process 25
8. Conclusions 31
Acknowledgements 32
Appendix A. Regularity of the solutions of the Stein equation 32
Appendix B. Convergence Towards a Gaussian Process 33
References 35

Date: December 5, 2024.
Key words and phrases. Quantum machine learning, quantum neural networks, supervised learning, Wasserstein distance, Stein's method, quantum neural tangent kernel, lazy training, Gaussian processes.