


2022–
2023

QuSoft is named on page 37 of the paper.

arXiv:2505.13134v1 [cs.CC] 19 May 2025

A NEAR-OPTIMAL QUADRATIC GOLDREICH–LEVIN ALGORITHM

JOP BRIËT AND DAVI CASTRO-SILVA

Abstract. In this paper, we give a quadratic Goldreich-Levin algorithm that is close to optimal in the following ways. Given a bounded function f on the Boolean hypercube $\mathbb{F}_2^n$ and any $\varepsilon > 0$, the algorithm returns a quadratic polynomial $q : \mathbb{F}_2^n \to \mathbb{F}_2$ so that the correlation of f with the function $(-1)^q$ is within an additive ε of the maximum possible correlation with a quadratic phase function. The algorithm runs in $O_\varepsilon(n^3)$ time and makes $O_\varepsilon(n^2 \log n)$ queries to f, which matches the information-theoretic lower bound of $\Omega(n^2)$ queries up to a logarithmic factor.

As a result, we obtain a number of corollaries:

- A near-optimal self-corrector of quadratic Reed-Muller codes, which makes $O_\varepsilon(n^2 \log n)$ queries to a Boolean function f and returns a quadratic polynomial q whose relative Hamming distance to f is within ε of the minimum distance.
- An algorithmic polynomial inverse theorem for the order-3 Gowers uniformity norm.
- An algorithm that makes a polynomial number of queries to a bounded function f and decomposes f as a sum of $\mathrm{poly}(1/\varepsilon)$ quadratic phase functions and error terms of order ε.

Our algorithm is obtained using ideas from recent work on quantum learning theory. Its construction deviates from previous approaches based on algorithmic proofs of the inverse theorem for the order-3 uniformity norm (and in particular does not rely on the recent resolution of the polynomial Freĭman-Ruzsa conjecture).

1. Introduction

Fourier analysis plays an indispensable role in theoretical computer science. A celebrated example of its use is in the analysis of the property-testing algorithm of Blum, Luby and Rubinfeld [BLR93], which uses a constant number of queries to a function $f : \mathbb{F}_2^n \to \mathbb{F}_2$ to decide with good probability whether f is close to some linear function or far from all linear functions. In effect, this algorithm tests whether the phase function $(-1)^{f(x)}$ has a Fourier coefficient of large magnitude. The famous Goldreich-Levin algorithm goes a step further and