

Trading inverses for an irrep in the Solovay-Kitaev theorem

Adam Bouland[1] and Māris Ozols[2]

[1]*Department of EECS, UC Berkeley, Berkeley, CA USA*
[2]*QuSoft and University of Amsterdam, Amsterdam, Netherlands*

arXiv:1712.09798v2 [quant-ph] 28 May 2018

Abstract

The Solovay-Kitaev theorem states that universal quantum gate sets can be exchanged with low overhead. More specifically, any gate on a fixed number of qudits can be simulated with error ϵ using merely $\mathrm{polylog}(1/\epsilon)$ gates from any finite universal quantum gate set $\mathcal{G}$. One drawback to the theorem is that it requires the gate set $\mathcal{G}$ to be closed under inversion. Here we show that this restriction can be traded for the assumption that $\mathcal{G}$ contains an irreducible representation of any finite group G. This extends recent work of Sardharwalla *et al.* [SCHL16], and applies also to gates from the special linear group. Our work can be seen as partial progress towards the long-standing open problem of proving an inverse-free Solovay-Kitaev theorem [DN06, Kup15].

1 Introduction

Quantum computing promises to solve certain problems exponentially faster than classical computers. For instance, quantum computers can factor integers [Sho97], simulate quantum mechanics [BCK15], and compute certain knot invariants [AJL09] exponentially faster than the best known classical algorithms. The power of quantum computing is formalized using the notion of quantum circuits, in which polynomial number of quantum gates are applied to a standard input state, and the answer to the computational problem is obtained by measuring the final state. This results in the complexity class BQP (see [NC10, KSV02] for an introduction).

Each gate in the circuit is a unitary transformation drawn from some finite *gate set* $\mathcal{G}$; it represents elementary quantum operations that can be performed in hardware and which may vary between different realizations of quantum computing. Each gate can act on at most some finite number k of quantum systems at a time, where each individual system (or *qudit*) has d levels. A gate set $\mathcal{G}$ is called *universal*[1] if it is capable of approximately generating any quantum transformation on a sufficiently large number of qudits [CLMO11].

In general, the computational power of a quantum device may depend on the gate set $\mathcal{G}$ at its disposal. Clearly, if a gate set is not universal, it may have restricted computational power.[2] But *a priori*, the computational power of different universal gate sets could vary as well. This is because

[1]This is also known as *physical universality*.

[2]But not always! Some gate sets which are not physically universal are nevertheless capable of universal quantum computing via an encoding; this is known as *encoded universality* [NC10].