


2016–
2022

# Convex optimization using quantum oracles

Joran van Apeldoorn[1], András Gilyén[2], Sander Gribling[3], and Ronald de Wolf[4]

[1]QuSoft, CWI, Amsterdam, the Netherlands. apeldoor@cwi.nl
[2]QuSoft, CWI, Amsterdam, the Netherlands. gilyen@cwi.nl
[3]QuSoft, CWI, Amsterdam, the Netherlands. gribling@cwi.nl
[4]QuSoft, CWI and University of Amsterdam, the Netherlands. rdewolf@cwi.nl

arXiv:1809.00643v4 [quant-ph] 20 Dec 2019

We study to what extent quantum algorithms can speed up solving convex optimization problems. Following the classical literature we assume access to a convex set via various oracles, and we examine the efficiency of reductions between the different oracles. In particular, we show how a separation oracle can be implemented using $\widetilde{\mathcal{O}}(1)$ quantum queries to a membership oracle, which is an exponential quantum speed-up over the $\Omega(n)$ membership queries that are needed classically. We show that a quantum computer can very efficiently compute an approximate subgradient of a convex Lipschitz function. Combining this with a simplification of recent classical work of Lee, Sidford, and Vempala gives our efficient separation oracle. This in turn implies, via a known algorithm, that $\widetilde{\mathcal{O}}(n)$ quantum queries to a membership oracle suffice to implement an optimization oracle (the best known classical upper bound on the number of membership queries is quadratic). We also prove several lower bounds: $\Omega(\sqrt{n})$ quantum separation (or membership) queries are needed for optimization if the algorithm knows an interior point of the convex set, and $\Omega(n)$ quantum separation queries are needed if it does not.

## 1 Introduction

Optimization is a fundamental problem in mathematics and computer science, with many real-world applications. As people try to solve larger and larger optimization problems, the efficiency of optimization becomes more and more important, motivating us to find the best possible algorithms. Recent experimental progress on building quantum computers draws attention to new approaches to the problem: can we solve optimization problems more efficiently by exploiting quantum effects such as superposition, interference, and entanglement? For many discrete optimization problems [Gro96, DH96, Szeg04, DHHM06, AŠ06] significant speed-ups have been shown, but less is known about *continuous* optimization problems.

One of the most successful continuous optimization paradigms is *convex* optimization, which optimizes a convex function over a convex set that is given explicitly (by a set of constraints) or implicitly (by an oracle). See Bubeck [Bub15] for a recent survey. Quantum algorithms for convex optimization have been considered before. In 2008, Jordan [Jor08] described a faster quantum algorithm for minimizing quadratic functions. Recently, for an important class of convex optimization problems (semidefinite optimization) quantum speed-ups were achieved using algorithms whose runtime scales polynomially with the desired precision and some geometric parameters [BS17, vAGGdW17, BKL+19, vAG19].