



# Round elimination in exact communication complexity

Jop Briët[*] Harry Buhrman[¶] Debbie Leung[‡] Teresa Piovesan[§]
Florian Speelman[†]

December 24, 2018

arXiv:1812.09290v1 [quant-ph] 21 Dec 2018

**Abstract**

We study two basic graph parameters, the chromatic number and the orthogonal rank, in the context of classical and quantum exact communication complexity. In particular, we consider two types of communication problems that we call *promise equality* and *list* problems. For both of these, it was already known that the one-round classical and one-round quantum complexities are characterized by the chromatic number and orthogonal rank of a certain graph, respectively.

In a promise equality problem, Alice and Bob must decide if their inputs are equal or not. We prove that classical protocols for such problems can always be reduced to one-round protocols with no extra communication. In contrast, we give an explicit instance of a promise equality problem that exhibits an exponential gap between the one- and two-round exact quantum communication complexities. Whereas the chromatic number thus fully captures the complexity of promise equality problems, the hierarchy of "quantum chromatic numbers" (starting with the orthogonal rank) giving the quantum communication complexity for every fixed number of communication rounds turns out to enjoy a much richer structure.

In a list problem, Bob gets a subset of some finite universe, Alice gets an element from Bob's subset, and their goal is for Bob to learn which element Alice was given. The best general lower bound (due to Orlitsky) and upper bound (due to Naor, Orlitsky, and Shor) on the classical communication complexity of such problems differ only by a constant factor. We exhibit an example showing that, somewhat surprisingly, the four-round protocol used in the bound of Naor et al. can in fact be optimal. Finally, we pose a conjecture on the orthogonality rank of a certain graph whose truth would imply an intriguing impossibility of *round elimination* in quantum protocols for list problems, something that works trivially in the classical case.

[*]Centrum Wiskunde & Informatica (CWI), Science Park 123, 1098 XG Amsterdam, The Netherlands. Funded by a Rubicon grant from the Netherlands Organization for Scientific Research (NWO). E-mail: j.briet@cwi.nl.

[¶]QuSoft, University of Amsterdam, and CWI, Science Park 123, 1098 XG Amsterdam, The Netherlands. Supported by NWO Gravitation-grants NETWORKS and QSC as well as EU grant QuantAlgo and CIFAR. E-mail: buhrman@cwi.nl.

[‡]University of Waterloo, Waterloo, Canada. Funded in part by NSERC, CRC, and CIFAR. E-mail: wcleung@math.uwaterloo.ca.

[§]Centrum Wiskunde & Informatica (CWI), Science Park 123, 1098 XG Amsterdam, The Netherlands. Funded in part by the EU project SIQS. E-mail: tere.piovesan@gmail.com.

[†]Qusoft and Centrum Wiskunde & Informatica (CWI), Science Park 123, 1098 XG Amsterdam, The Netherlands. Funded in part by the EU project SIQS. E-mail: speelman@cwi.nl.