




2021–
2025

2020–
2022

Parallel repetition of local simultaneous state discrimination

Llorenç Escolà Farràs[1,2], Jaròn Has[3], Maris Ozols[1,3,4], Christian Schaffner[1,2], and Mehrdad Tahmasbi[5]

[1] QuSoft, Amsterdam, The Netherlands
[2] Informatics Institute, University of Amsterdam, The Netherlands
[3] Korteweg-de Vries Institute (KdVI), University of Amsterdam, The Netherlands
[4] Institute for Logic, Language, and Computation (ILLC), University of Amsterdam, The Netherlands
[5] Tufts University, Medford, MA, USA

arXiv:2211.06456v2 [quant-ph] 9 Apr 2025

Local simultaneous state discrimination (LSSD) is a recently introduced problem in quantum information processing. Its classical version is a non-local game played by non-communicating players against a referee. Based on a known probability distribution, the referee generates one input for each of the players and keeps one secret value. The players have to guess the referee's value and win if they all do so. For this game, we investigate the advantage of no-signalling strategies over classical ones. We show numerically that for three players and binary values, no-signalling strategies cannot provide any improvement over classical ones. For a certain LSSD game based on a binary symmetric channel, we show that no-signalling strategies are strictly better when multiple simultaneous instances of the game are played. Good classical strategies for this game can be defined by codes, and good no-signalling strategies by list-decoding schemes. We expand this example game to a class of games defined by an arbitrary channel, and extend the idea of using codes and list decoding to define strategies for multiple simultaneous instances of these games. Finally, we give an expression for the limit of the exponent of the classical winning probability, and show that no-signalling strategies based on list-decoding schemes achieve this limit.

Contents

1 Introduction **2**
1.1 Our contributions . . . 3
1.2 Open problems . . . 3

2 Preliminaries **4**
2.1 Quantum information . . . 4
2.2 Linear programming . . . 4

3 Local simultaneous state discrimination (LSSD) **5**
3.1 Classical resources . . . 6
3.2 Quantum resources . . . 7
3.3 No-signalling resources . . . 7

4 The binary-symmetric-channel game **8**
4.1 Two-fold parallel repetition of the binary-symmetric-channel game . . . 9
4.2 Three-fold parallel repetition of the BSC game . . . 12
4.3 Arbitrary parallel repetition . . . 13
4.3.1 Classical strategies . . . 13
4.3.2 No-signalling strategies . . . 14