

2021–
2025

arXiv:2211.12841v1 [math.CO] 23 Nov 2022

Perfect state transfer in quantum walks on orientable maps

Krystal Guo* Vincent Schmeits†

November 23, 2022

Abstract

A discrete-time quantum walk is the quantum analogue of a Markov chain on a graph. Zhan [*J. Algebraic Combin.* 53(4):1187–1213, 2020] proposes a model of discrete-time quantum walk whose transition matrix is given by two reflections, using the face and vertex incidence relations of a graph embedded in an orientable surface. We show that the evolution of a general discrete-time quantum walk that consists of two reflections satisfies a Chebyshev recurrence, under a projection. For the vertex-face walk, we prove theorems about perfect state transfer and periodicity and give infinite families of examples where these occur. We bring together tools from algebraic and topological graph theory to analyze the evolution of this walk.

Keywords: quantum walk, graph embeddings, graph eigenvalues
Mathematics Subject Classifications 2020: 05C50, 05C10, 81P45

Contents

1 Introduction **1**

2 Preliminaries **3**

3 Vertex-face quantum walk **8**

4 Perfect state transfer **11**

5 Periodic maps **15**

6 Periodic maps with $U^s = I$ **19**

7 Infinite families of examples **22**
7.1 Dipoles with one or two faces 23
7.2 Toroidal grids 24

8 Computations **28**

9 Further directions and open problems **30**

1 Introduction

Quantum computing gives rise to many interesting applications of combinatorics; in this paper, we bring together ideas from algebraic and topological graph theory to study properties, including state transfer and

*Korteweg-de Vries Institute for Mathematics, University of Amsterdam, Amsterdam, The Netherlands. QuSoft (Research center for Quantum software & technology), Amsterdam, The Netherlands. k.guo@uva.nl
†Korteweg-de Vries Institute for Mathematics, University of Amsterdam, Amsterdam, The Netherlands. v.f.schmeits@uva.nl