


2020–
2024

2021–
2025



PERMUTATION TESTS FOR QUANTUM STATE IDENTITY

HARRY BUHRMAN[1], DMITRY GRINKO[2], PHILIP VERDUYN LUNEL[3], AND JORDI WEGGEMANS[3]

Abstract. The quantum analogue of the equality function, known as the *quantum state identity problem*, is the task of deciding whether n unknown quantum states are equal or unequal, given the promise that all states are either pairwise orthogonal or identical. Under the one-sided error requirement, it is known that the permutation test is optimal for this task, and for two input states this coincides with the well-known Swap test. Until now, the optimal measurement in the general two-sided error regime was unknown. Under more specific promises, the problem can be solved approximately or even optimally with simpler tests, such as the circle test.

This work attempts to capture the underlying structure of (fine-grained formulations of) the quantum state identity problem. Using tools from semi-definite programming and representation theory, we (i) give an optimal test for any input distribution without the one-sided error requirement by writing the problem as an SDP, giving the exact solutions to the primal and dual programs and showing that the two values coincide; (ii) propose a general G-test which uses an arbitrary subgroup G of S_n, giving an analytic expression of the performance of the specific test, and (iii) give an approximation of the permutation test using only a classical permutation and $n-1$ Swap tests.

arXiv:2405.09626v1 [quant-ph] 15 May 2024

Contents

1. Introduction 1
1.1. Our results 2
2. Preliminaries 4
2.1. Notation 4
2.2. Representation theory background 4
2.3. Semidefinite programming 5
3. The permutation test 5
3.1. The SDP formulation of the optimal measurement for Haar-random inputs 5
3.2. Unknown is the same as Haar-random 7
3.3. Warm-up: optimality for $\mu = (n-h, h)$ with $p = 1/2$ 7
3.4. The general setting 8
4. The G-test 9
4.1. The Circle test 9
4.2. The Iterated Cyclic Wreath test 10
5. Approximation of the permutation test by the Iterated Swap Tree 10
5.1. The Iterated Swap Tree protocol 10
5.2. A recursive upper bound 12
6. Discussion and open problems 14
Acknowledgements 15
References 15

1. Introduction

One of the most basic tasks in quantum information is to compare two or more unknown quantum states. In particular, we will be interested in a quantum version of the equality function, known as the *quantum state identity problem* (QSI_n) [KNY08]. Here one is given n *unknown* quantum states $|\psi_1\rangle, |\psi_2\rangle \ldots, |\psi_n\rangle$, each of local dimension d, with the promise that all states are either pairwise orthogonal or identical. Given as an input such a collection of unknown states satisfying the promise, the task is now to decide whether the input states are all equal or not, with high probability.

For two input states, the corresponding problem QSI_2 can be solved by the so-called *Swap Test* [BBD+97, BCWd01]. The Swap test applies, controlled by a qubit in the $|+\rangle$ state in the first register, a controlled Swap operation to the input states, followed by a Hadamard operation and measurement in the computational basis

[1]QuSoft, University of Amsterdam & Quantinuum, Partnership House, Carlisle Place, London
[2]QuSoft, University of Amsterdam, Amsterdam, The Netherlands
[3]QuSoft, CWI, Amsterdam, The Netherlands
E-mail addresses: h.m.buhrman@uva.nl, dmitry.grinko@cwi.nl, philip.verduyn.lunel@cwi.nl, jrw@cwi.nl.
Date: May 17, 2024.