



Catalytic entanglement transformations with noisy hardware

Hemant Sharma[1,2], Aleksandr Mokeev[4], Jonas Helsen[2], and Johannes Borregaard[3]

[1]QuTech, Delft University of Technology, 2628 CJ, Delft, The Netherlands
[2]QuSoft and CWI, Science Park 123, 1098 XG Amsterdam, The Netherlands
[3]Department of Physics, Harvard University, Cambridge, Massachusetts 02138, USA
[4]Department of Electrical Engineering, Eindhoven University of Technology, 5600 MB, Eindhoven, The Netherlands

arXiv:2505.05964v1 [quant-ph] 9 May 2025

The availability of certain entangled resource states (catalyst states) can enhance the rate of converting several less entangled states into fewer highly entangled states in a process known as catalytic entanglement concentration (EC). Here, we extend catalytic EC from pure states to mixed states and numerically benchmark it against non-catalytic EC and distillation in the presence of state-preparation errors and operational errors. Furthermore, we analyse the re-usability of catalysts in the presence of such errors. To do this, we introduce a novel recipe for determining the positive-operator valued measurements (POVM) required for EC transformations, which allows for making tradeoffs between the number of communication rounds and the number of auxiliary qubits required. We find that in the presence of low operational errors and depolarising noise, catalytic EC can provide better rates than distillation and non-catalytic EC.

1 Introduction

Entanglement is a crucial resource for building quantum networks for secure communication [1, 2], distributed quantum computing [3], and networked quantum sensing [4]. However, the distribution of entanglement in a network is challenging because of errors and loss, which deteriorate the quality of shared entanglement. Several protocols have been developed to convert low-quality entanglement into high-quality entanglement, including distillation [5, 6] and entanglement concentration (EC) [7, 8].

Hemant Sharma: h.sharma-1@tudelft.nl

Bilocal Clifford distillation protocols (or simply distillation) have been the canonical approach for creating high-quality entanglement from mixed entangled states due to their relatively simple execution. They have been studied intensely [9, 10], and have been demonstrated in experiments [11, 12, 13]. EC, on the other hand, has not been demonstrated experimentally. In particular, previous theoretical studies have considered only pure states, which makes them incompatible with realistic, noisy hardware. Moreover, they have been studied only in the absence of operational errors [14]. This includes entanglement catalysis protocols that we treat as an extension of EC. Entanglement catalysis uses pre-shared entanglement that remains unchanged after the protocol to increase the rate of EC [15, 16]. It can also be used for catalytic quantum teleportation [17].

In this paper, we extend the analysis of EC protocols to the more practically relevant regime of noisy hardware. We do this by considering both mixed state inputs and operational errors. As part of our analysis, we introduce a novel recipe for determining the local operations and classical communication needed for performing the EC protocols. In particular, we allow for a practical trade-off between the number of communication rounds and the number of auxiliary qubits in the implementation based on hardware constraints.

We numerically simulate EC both with and without entanglement catalysis and compare the performances to a canonical protocol of distillation in the presence of both state-preparation errors and operational errors. We find that the distillation protocol is more resistant against incoherent, depolarising-type errors, whereas the EC protocols are more resilient against coherent, unitary-type errors. For operational errors, we find that they affect both catalytic EC and non-catalytic