



Minimizing the number of edges in LC-equivalent graph states

Hemant Sharma,[1,2,*] Kenneth Goodenough,[3] Johannes Borregaard,[4] Filip Rozpędek,[3] and Jonas Helsen[2]

[1] *QuTech, Delft University of Technology, 2628 CJ, Delft, The Netherlands*

[2] *QuSoft and CWI, Science Park 123, 1098 XG Amsterdam, The Netherlands*

[3] *College of Information and Computer Sciences, University of Massachusetts Amherst, Amherst, Massachusetts 01003, USA*

[4] *Department of Physics, Harvard University, Cambridge, Massachusetts 02138, USA*

(Dated: June 13, 2025)

Graph states are a powerful class of entangled states with numerous applications in quantum communication and quantum computation. Local Clifford (LC) operations that map one graph state to another can alter the structure of the corresponding graphs, including changing the number of edges. Here, we tackle the associated edge-minimization problem: finding graphs with the minimum number of edges in the LC-equivalence class of a given graph. Such graphs are called minimum edge representatives (MER), and are crucial for minimizing the resources required to create a graph state. We leverage Bouchet's algebraic formulation of LC-equivalence to encode the edge-minimization problem as an integer linear program (`ILP`). We further propose a simulated annealing (`SA`) approach guided by the local clustering coefficient for edge minimization. We identify new MERs for graph states with up to 16 qubits by combining `SA` and `ILP`. We extend the ILP to weighted-edge minimization, where each edge has an associated weight, and prove that this problem is NP-complete. Finally, we employ our tools to minimize resources required to create all-photonic generalized repeater graph states using fusion operations.

arXiv:2506.00292v1 [quant-ph] 30 May 2025

I. INTRODUCTION

Graph states are a powerful yet tractable class of multipartite entangled states that have been extensively studied in quantum science. Beyond their theoretical significance [1, 2], they support a wide range of applications, including measurement-based quantum computation [3–5], all-photonic quantum repeaters [6–11], loss-tolerant error-correcting codes [12–14], and quantum metrology [15]. Significant efforts have been directed toward both their experimental realization [16–25] and theoretical optimization, encompassing photonic graph state generation [26–30], general graph state construction [31], and state distribution [32].

A graph state $|G\rangle$ is represented by a graph G with vertices that correspond to qubits initialized in the $|+\rangle$ state, and edges that correspond to controlled-Z (CZ) gates applied to pairs of qubits. Graph states can also be defined by Pauli stabilizers, and thus constitute a subset of the stabilizer states. By applying local Clifford (LC) gates, i.e. single-qubit Clifford unitaries, one can transform a graph state $|G\rangle$ into a different *local Clifford equivalent* (or LC-equivalent) graph state $|H\rangle$ with possibly fewer edges in its graph. It was shown in Ref. [33] that two graph states are LC-equivalent if and only if their graphs are related by a sequence of graph operations called *local complementations*.

A natural goal is to identify LC-equivalent graph states with the fewest edges—referred to as *minimum edge representatives* (MERs). These serve as canonical representatives of *LC-orbits*, the equivalence classes under local complementation [34]. MERs have been studied as a means to reduce the physical resources needed for graph state preparation [31]. However, identifying MERs is challenging due to the convoluted structure of LC-orbits, as shown in Ref [34]. Existing methods typically rely on brute-force enumeration of the entire orbit via local complementations, which quickly becomes intractable since the number of orbit elements can grow exponentially with the number of qubits. As a result, prior work on MERs has been limited to graphs with up to 12 qubits [31, 34].

In this work, we introduce three algorithms to address the edge-minimization problem: given a graph G, find an LC-equivalent graph H with the minimum number of edges. Our first algorithm, `SA`, uses simulated annealing [35] to obtain approximate solutions for graphs with up to 100 qubits. The second algorithm, `ILP`, is an integer linear program based on Bouchet's algebraic characterization of LC-equivalence [36]. While `ILP` guarantees globally optimal solutions, its runtime scales exponentially in the worst case. Combining both approaches, our third method, `SA+ILP`, uses `SA` to precondition the input to `ILP`, yielding a significant constant-factor speedup. This hybrid approach enables us to compute exact MERs for graphs with up to 16 qubits. Moreover, we extend `ILP` to tackle the weighted-edge minimization problem: finding LC-equivalent graphs that minimize the total edge weight. We prove this problem is NP-complete via a reduction from the vertex-minor problem [37].

To demonstrate the practical utility of our approach, we use `SA` to optimize the resources required for the creation of all-photonic *generalized* repeater graph states (gRGS) [11]. These states can be utilized for sharing multiple units of entanglement in a quantum network. Moreover, they can be constructed using single-photon sources and fusion operations [38]. However, the probabilistic nature of fusion and photon loss leads to a high number of required single photons

* h.sharma-1@tudelft.nl