



QKD Oracles for Authenticated Key Exchange

Kathrin Hövelmanns[1], Daan Planken[2,3], Christian Schaffner[2,3], and Sebastian R. Verschoor[2,3]

[1] Eindhoven University of Technology, The Netherlands
[2] University of Amsterdam, The Netherlands
[3] QuSoft, Amsterdam, The Netherlands
qkdOraclesForAKE@hoevelmanns.net

arXiv:2509.12478v1 [cs.CR] 15 Sep 2025

Abstract. Authenticated Key Exchange (AKE) establishes shared ('symmetric') cryptographic keys which are essential for secure online communication. AKE protocols can be constructed from public-key cryptography like Key Encapsulation Mechanisms (KEMs). Another approach is to use Quantum Key Distribution (QKD) to establish a symmetric key, which uses quantum communication. *Combining* post-quantum AKE and QKD *appropriately* may provide security against quantum attacks even if only one of the two approaches turns out to be secure.
We provide an extensive review of existing security analyses for combined AKE and their formal security models, and identify some gaps in their treatment of QKD key IDs. In particular, improper handling of QKD key IDs leads to Dependent-Key attacks on AKE.
As our main conceptual contribution, we model QKD as an oracle that closely resembles the standard ETSI 014 QKD interface. We demonstrate the usability of our QKD oracle for cryptographic security analyses by integrating it into a prominent security model for AKE, called CK$^+$ model, thereby obtaining a security model for combined AKE that catches Dependent-Key attacks. In this model, we formally prove security of a new protocol that combines QKD with a triple-KEM handshake. This is the first provably secure hybrid protocol that maintains information-theoretic security of QKD.

Keywords: Post-Quantum Cryptography · PQC · Quantum Key Distribution · QKD · Authenticated Key Exchange · AKE · Provable Security · Hybrid Protocols · Combined Security · Dependent-Key attacks

1 Introduction

Today's secure online communication heavily relies on symmetric cryptography. One way to establish shared symmetric *session keys* is to use Authenticated Key Exchange (AKE) protocols, which are often based on public-key cryptography. AKE guarantees that session keys remain unknown to anyone but the two intended parties. By this guarantee, unauthorized parties cannot obtain these session keys, and thus the honest parties' communication is protected by symmetric cryptography. It is, however, not completely straightforward how these AKE security guarantees should be formalized – over the past three decades, different security definitions [BR94, CK01, Kra05, LLM07] have been given, all coming with subtle differences and advantages/disadvantages.

Post-quantum AKE. Quantum computers threaten the security of many widely deployed AKE protocols, as Shor's quantum algorithm [Sho94] breaks the assumptions underlying the current

KH was supported by an NWO VENI grant (Project No. VI.Veni.222.397). DP and SV were supported by the Dutch National Growth Fund (NGF), as part of the Quantum Delta NL programme. CS is (partially) supported by gravitation project Challenges in Cyber Security (CiCS) with file number 024.006.037 which is financed by the Dutch Research Council (NWO). Date: September 15, 2025