



A Quantum Time-Space Tradeoff for Directed *st*-Connectivity

Stacey Jeffery[1,2] and Galina Pass[2]

[1]CWI, Amsterdam
[2]QuSoft & University of Amsterdam

arXiv:2510.08403v1 [quant-ph] 9 Oct 2025

Abstract

Directed *st*-connectivity (DSTCON) is the problem of deciding if there exists a directed path between a pair of distinguished vertices s and t in an input directed graph. This problem appears in many algorithmic applications, and is also a fundamental problem in complexity theory, due to its NL-completeness. We show that for any $S \geq \log^2(n)$, there is a quantum algorithm for DSTCON using space S and time $T \leq 2^{\frac{1}{2}\log(n)\log(n/S)+o(\log^2(n))}$, which is an (up to quadratic) improvement over the best classical algorithm for any $S = o(\sqrt{n})$. Of the S total space used by our algorithm, only $O(\log^2(n))$ is quantum space – the rest is classical. This effectively means that we can trade off classical space for quantum time.

1 Introduction

In the directed *st*-connectivity problem (DSTCON), the input is a directed graph on n vertices with two distinguished vertices s and t, and the goal is to decide if there is a directed path from s to t. This fundamental problem underlies a wide range of applications in (e.g.) logistics, databases [AHV95, Ull89], compilers [ALSU06, NNH99], and model checking [CGP99, BK08].

In addition to its practical applications, DSTCON plays a central role in space-bounded complexity theory. It is NL-complete (under NC^1 reductions), where NL is the class of problems decidable by non-deterministic logspace machines. Consequently, understanding its complexity has broad implications for space-bounded computation. For example, a classical (or quantum) algorithm for DSTCON using $O(\log(n))$ space would show that L, the class of problems solvable in $O(\log(n))$ space (or its quantum analogue) contains NL – a major breakthrough in either case.

Currently, the smallest space complexity of any classical or quantum algorithm for DSTCON is $S = O(\log^2(n))$, achieved by Savitch's (classical) algorithm. However, Savitch's algorithm achieves this low space complexity at the expense of a large *quasipolynomial* time complexity, using

$$T \leq 2^{\log^2(n)+O(\log(n))}$$

steps of computation. In contrast, a simple breadth-first search (BFS) algorithm solves this problem in just $T = O(n^3)$ steps (in the adjacency-matrix model), but at the expense of a much larger $S = \widetilde{O}(n)$ space requirement. The fundamental nature of this problem, as well as its many applications, motivates understanding the best possible *tradeoff* between the time and space needed to solve it. Progress was made by Barnes, Buss, Ruzzo and Schieber [BBRS98], who gave a classical algorithm that runs in time

$$T \leq 2^{\log^2(\frac{n}{S})+O(\log n \log\log n)} \tag{1}$$

given any space $S \geq \log^2(n)$. Their approach combines a breadth-first search with a clever recursive algorithm.

For quantum algorithms, the study of space-bounded complexity is even more well motivated, as quantum memories are expected to be limited in size for the foreseeable future. It is an important question in which memory regimes we can still achieve speedups over classical algorithms, and time-space tradeoffs are a key part of this picture. We can make such a tradeoff even more useful by