

# A Simpler Exponential-Time Approximation Algorithm for MAX-$k$-SAT

Harry Buhrman* Sevag Gharibian† Zeph Landau‡ François Le Gall§
Norbert Schuch¶ Suguru Tamaki||

arXiv:2510.18164v1 [cs.DS] 20 Oct 2025

**Abstract**

We present an extremely simple polynomial-space exponential-time $(1-\varepsilon)$-approximation algorithm for MAX-$k$-SAT that is (slightly) faster than the previous known polynomial-space $(1-\varepsilon)$-approximation algorithms by Hirsch (Discrete Applied Mathematics, 2003) and Escoffier, Paschos and Tourniaire (Theoretical Computer Science, 2014). Our algorithm repeatedly samples an assignment uniformly at random until finding an assignment that satisfies a large enough fraction of clauses. Surprisingly, we can show the efficiency of this simpler approach by proving that in any instance of MAX-$k$-SAT (or more generally any instance of MAXCSP), an exponential number of assignments satisfy a fraction of clauses close to the optimal value.

## 1 Introduction

**Background.** In 1997, Paturi, Pudlák and Zane [7] gave a simple randomized algorithm for $k$-SAT running in time "moderately" exponential in the number of variables $n$, i.e., in time

$$O(2^{(1-c/k)n}) \text{ for some universal constant } c > 0. \tag{1}$$

While the constant $c$ has been improved over the years (e.g., by Paturi, Pudlák, Saks and Zane [6] and Schöning [8]), no similar running time is known for MAX-$k$-SAT with $k \geq 3$.[1] There nevertheless exist nontrivial moderately-exponential-time *approximation* algorithms for MAX-$k$-SAT. In this work, we focus on approximation algorithms with complexity depending on the number of variables, i.e., algorithms with complexity similar to Eq. (1). There are three main prior works [1, 4, 5], which we review below.

**Previous approximation algorithms.** Let $f$ be any instance of $k$-SAT with $n$ variables and $m$ clauses. For an assignment $z \in \{0,1\}^n$, we denote by $\mathcal{C}(f,z)$ the number of clauses in $f$ satisfied by $z$, and write

$$m^* = \max_{z\in\{0,1\}^n} \mathcal{C}(f,z).$$

*Quantinuum and QuSoft.
†Department of Computer Science and Institute for Photonic Quantum Systems, Paderborn University.
‡Department of Computer Science, University of California, Berkeley.
§Graduate School of Mathematics, Nagoya University.
¶Faculty of Mathematics and Faculty of Physics, University of Vienna.
||Graduate School of Information Science, University of Hyogo.

[1] For $k = 2$, Williams [9] showed how to obtain running time $O^*(2^{\omega n/3})$, where $\omega$ is the exponent of matrix multiplication. Here, the notation $O^*(\cdot)$ removes $\text{poly}(n)$ factors. Similarly, for lower bounds the notation $\Omega^*(\cdot)$ will remove $\text{poly}(n)$ factors.