

Logic (PHIL 2080, COMP 2620, COMP 6262)

Chapter: Introduction to Logic

Pascal Bercher

Planning & Optimization

Yoshihiro Maruyama

Logic
Intelligent Agents

College of Engineering and Computer Science
the Australian National University (ANU)

23 & 25 February 2021



Organizational Matters

Team: The Lecturers, 1/3


Prof. Dr. John Slaney

(2011 – 2020, now retired)

<http://users.cecs.anu.edu.au/~jks/>

We inherited his course; he produced:

- Course structure and content
- Most exercises (also for exams)
- The *Logic for Fun (L4F)* platform
- The online course notes
- The plagiarism scanner



Team: The Lecturers, 2/3


Dr. Pascal Bercher

since 2021

<https://cecs.anu.edu.au/people/pascal-bercher>

- *Studies*: Computer Science (with minor Cognitive Science)
- *PhD*: Computer Science: Hierarchical Planning
- *Research*:
 - Hierarchical Task Network (HTN) Planning
 - Heuristic Search
 - Complexity Theory

→ Pascal will teach the first 50% of the course



Team: The Lecturers, 3/3


Dr. Yoshihiro Maruyama

since 2021

<https://cs.anu.edu.au/people/yoshihiro-maruyama>

- *Studies*: Mathematics, Philosophy, Computer Science
- *PhD*: Computer Science: Category-theoretical Logic
- *Research*: Mathematical and Philosophical Logic:
 - category-theoretical logic
 - categorical foundations of mathematics, CS, AI, physics
 - philosophy of logic, mathematics, AI, science in general

→ Yoshi will teach the second 50% of the course



Australian
National
University

Pascal Bercher and Yoshihiro Maruyama

4.34

Team: The Tutors

- See Wattle for the complete list and contact info.
- What do they do?
 - Give the tutorials/workshops
 - Answer your questions (via Wattle forum)
 - (Co-)Mark the homework, assignments, and exam



Australian
National
University

Pascal Bercher and Yoshihiro Maruyama

5.34

Various: Appointments/Dates

- Lectures:
 - Online live, recordings available via Wattle/Echo360
 - 2 per week, (approx.) 50 minutes each, see Wattle for dates
- Workshops/tutorials:
 - Only online via Zoom: please activate video and bring a headset
 - Once per week, 120 minutes each, see Wattle for dates
 - We'll do both tutorial-like "standard" exercises as well as workshop-like modeling tasks
- Appointments:
 - Only in exceptional cases. If required ask for appointment via mail
 - Otherwise ask all questions via the forum or your tutor



Australian
National
University

Pascal Bercher and Yoshihiro Maruyama

6.34

Various: Exercises and Exam

- Homework every two weeks:
 - Standard exercises (do proofs) or modeling tasks
 - Get corrected by tutors, marks are just FYI, they do *not* count towards the exam/course mark
 - Collaboration (up to 3 people) is strongly encouraged, but please don't hand in the same results several times
- Three Assignments:
 - 1 related to formal proofs, 1 via Logic for Fun (L4F) and 1 essay
 - Each assignment counts 15% of the final mark
 - Any form of cheating will be escalated and has serious consequences
 - Deadlines: Are strict, no exceptions (unless you have a *serious* reason, backed up by medical certificates, for example)
- Exam
 - Will be online, 3 hours
 - Counts 55% of final mark



Australian
National
University

Pascal Bercher and Yoshihiro Maruyama

7.34

Organizational Matters

Introduction to Logic


Sequents

Propositional Calculus

Summary

Various: Course Material

- Slides (see Wattle)
- Online book “Logic Notes” (<http://users.cecs.anu.edu.au/~jks/LogicNotes/index.html>)
- Our modeling tool “Logic for Fun (L4F)” (<https://l4f.cecs.anu.edu.au/>)
- Online forum! (Set Wattle reminders accordingly!)
- For further reading, see books:
 - G. Restall. *Logic: An Introduction*. Ed. by J. Shand. Routledge, 2005 (Well-suited for Philosophy students)
 - D. van Dalen. *Logic and Structure*. Springer, 2012 (Well-suited for Computer Science and Mathematics students)

 Australian National University

Pascal Bercher and Yoshihiro Maruyama

8.34

Organizational Matters

Introduction to Logic

Sequents


Propositional Calculus

Summary

Various: Feedback/Corrections

- Nobody is perfect!
- Did you find an error in the slides? (Even just a typo!)
- Do you have an idea on how to improve the slides?
 - More content? Less content?
 - Adding a specific example?
 - Adding a specific explanation?
 - Explaining a specific error many make?

→ Let us know! Drop us/the respective lecturer an email!

 Australian National University

Pascal Bercher and Yoshihiro Maruyama

9.34

Organizational Matters


Introduction to Logic

Sequents

Propositional Calculus

Summary

Introduction to Logic

 Australian National University

Pascal Bercher and Yoshihiro Maruyama

10.34

Organizational Matters

Introduction to Logic


Sequents

Propositional Calculus

Summary

Motivation: Motivations

See presentation by Yoshi!

 Australian National University

Pascal Bercher and Yoshihiro Maruyama

11.34

Introduction: What is Logic?

- Logic is a mathematical discipline, and the basis of many related fields, most notably computer science.
 - Logic is the Science of Reasoning:
 - Good/correct reasoning vs. bad/wrong reasoning
 - Making (and reasoning about) valid arguments
- ⇒ See Monty Python sketch “argument clinic”
(e.g., <https://www.dailymotion.com/video/x2hwqn9>)



Introduction: What's an argument?

Example:

- | | | |
|------------------------------|---|------------|
| • All footballers are bipeds | } | premises |
| • Socrates is a footballer | | |
| • Thus, Socrates is a biped | } | conclusion |

→ This is a valid argument

Arguments consist of premises and a conclusion.



Introduction: What's an Argument?

Another Example:

- | | | |
|-----------------------------|---|------------|
| • All cats are insects | } | premises |
| • Snoopy is a cat | | |
| • Thus, Snoopy is an insect | } | conclusion |

→ This is also a valid argument!

- Although everything was wrong!
- All premises and the conclusion!

→ But we don't care, since it has a valid *form*. We exploit this form, and abstract from the content to reason about the conclusions.



Introduction: What's an Argument?

Our final Example:

- | | | |
|------------------------------------|---|------------|
| • All logicians are rational | } | premises |
| • Restall ¹ is rational | | |
| • Thus, Restall is a logician | } | conclusion |

→ Interestingly, this is an invalid (wrong!) argument!

- Although everything was right!
- All premises and the conclusion!

→ *Wrong form*: The conclusion did not *follow* from the premises.

¹Greg Restall, professor of logic at the University of Melbourne, author of the best-known book on substructural logic and editor in chief of the Australasian Journal of Logic, is presumably a logician if anyone is.



Introduction: Forms of Arguments

Valid arguments have, e.g., the following form:

- All A s are B s;
- x is an A ;
- Therefore, x is a B .

The example with Restall did not work because it used a wrong form:

- All A s are B s;
- x is an B ;
- Therefore, x is an A .



Introduction: Valid Arguments

- An argument is considered valid, when ever the conclusion logically follows from the premises.
- “Logically follows” abstracts away from the number of “intermediate steps” that are required so that the conclusion becomes “obvious”.
- For example, if we take all axioms of some mathematical system as the premises and one of it’s (valid) theorems/propositions as its conclusion, this forms a valid argument – no matter how ingenious the theorem is!
- Thus, showing that an argument is actually valid is hard!
- We will break down arguments into a sequence of arguments, so that every conclusion “follows in one step” from its premises.
- This will be done via *natural deduction* (next chapter and couple of weeks!), based on *sequents*, which represent arguments.



Sequents



Introduction to Sequents

Our convention:

- Letters from the *end* of the alphabet: set
- ... *beginning* ... : single object of the kind that’s in the set

This represents sequent: $X : A$

- X is a set of formulae
- A is a single formula

This represents a “good” sequent: $X \vdash A$

- Read it: A follows (logically) from X
- For example, “the query A follows from the data X ”



Organizational Matters

Introduction to Logic

Sequents

Propositional Calculus

Summary


Definition of Sequents

- \vdash is a relation, so how is it defined?
- When are we allowed to write $X \vdash A$ (instead of just $X : A$)?

When the following the properties hold:

- If A is in X , then $X \vdash A$ (reflexivity)
- If $X \vdash A$, then $X \cup Y \vdash A$ for all Y (monotonicity)
- If $X \vdash A$ and $Y, A \vdash B$, then $X, Y \vdash B$ (transitivity)
 - $X, A \vdash B$ is short for $X \cup \{A\} \vdash B$ and (also called cut)
 - $X, Y \vdash A$ is short for $X \cup Y \vdash A$

When these criteria hold, we also say it's a *consequence relation*.

 Australian National University

Pascal Bercher and Yoshihiro Maruyama

20.34

Organizational Matters

Introduction to Logic


Sequents

Propositional Calculus

Summary

The Purpose of Sequents

- Sequents are used to express *valid* arguments! (This will be formally covered in week 4.)
- Recall that an argument (in the sense of logic) is valid even if the “step” from the premises to the conclusion is far from obvious.
- To “prove” that a sequent is valid we will derive a sequence of sequents, by only “slightly” manipulating the involved formulae.
- More details will be given later when we study *natural deduction*.

 Australian National University

Pascal Bercher and Yoshihiro Maruyama

21.34

Organizational Matters


Introduction to Logic

Sequents

Propositional Calculus

Summary

Propositional Calculus

 Australian National University

Pascal Bercher and Yoshihiro Maruyama

22.34

Organizational Matters

Introduction to Logic

Sequents

Propositional Calculus

Summary

Introduction

Logic is about making statements:


(natural language) sentence

Socrates is a goat

constant predicate

What's a predicate?

- It will formally be defined later, when we deal with *predicate logics*
- A predicate relates various objects (constants) to each other, e.g.:
 - isGoat(Socrates) or isGoat(Goat)
 - isFootballer(Socrates)
 - Kicks(Socrates,Goat) or Kicks(Socrates,Ball)
- Actually, predicates do not exist in *propositional logics*, where we have *propositions* instead, e.g.,
 - SocratesIsGoat or GoatIsGoat
 - SocratesIsFootballer
 - SocratesKicksGoat or SocratesKicksBall \rightarrow Since this is way too long, we usually just write p, q, r , etc.

 Australian National University

Pascal Bercher and Yoshihiro Maruyama

23.34

Basic Definitions: Terminology

Atoms refer to any “atomic” truth statement:

- true (denoted by \top , T , or 1)
- false (denoted by \perp , F , or 0)
- any propositional symbol (denoted by p, q, r, \dots)

What’s missing for *non-atomic* statements? Connectives!

- Socrates is a goat, ...
 - because ...
 - although ...
 - until ...
 - and ...
 - or ...
- It is not true that ...
 - Socrates is a goat
 - ...

Basic Definitions: Syntax of Connectives

Which connectors do exist in propositional logic?

- ... and ...: \wedge e.g., $(p \wedge \top)$ or $(p \wedge (q \wedge r))$
- ... or ...: \vee e.g., $(\perp \vee \top)$ or $(p \vee (q \wedge r))$
- if ..., then ...: \rightarrow e.g., $(p \rightarrow q)$ or $((p \wedge q) \rightarrow (p \vee q))$
also: ... implies ...
- ... if and only if ...: \leftrightarrow e.g., $(p \leftrightarrow q)$ or $((p \wedge q) \leftrightarrow (q \wedge p))$
- not ...: \neg e.g., $((\neg p) \rightarrow q)$ or $\neg(p \rightarrow q)$

Basic Definitions: Semantics of Connectives

What do these connectives *mean*?

- The semantics will be covered *formally* in a later section, so this is just a “teaser” for *some* of the connectives.
- Our connectives act like functions, assigning any input pattern a new output (just like logical gates in “technical computer science” / “computer architecture”).
- Examples:
 - $(\neg p)$ inverts p ’s truth value: \top is switched to \perp , and vice versa.
 - $(p \wedge q)$ is true if and only if both p and q are true.
 - $(p \vee q)$ is true if and only if at least one of p and q are true.

Basic Definitions: Semantics of Connectives

What do these connectives *mean*?

- The semantics will be covered *formally* in a later section, so this is just a “teaser” for *some* of the connectives.
- Our connectives act like functions, assigning any input pattern a new output (just like logical gates in “technical computer science” / “computer architecture”).
- Examples: (expressed as *truth tables*)

| p | \neg | p | q | \wedge | p | q | \vee |
|---------|---------|---------|---------|----------|---------|---------|---------|
| \perp | \top | \perp | \perp | \perp | \perp | \perp | \perp |
| \perp | \top | \perp | \top | \perp | \perp | \top | \top |
| \top | \perp | \top | \perp | \perp | \top | \perp | \top |
| | | \top | \top | \top | \top | \top | \top |

Basic Definitions: Semantics of Connectives

What do these connectives *mean*?

- The semantics will be covered *formally* in a later section, so this is just a “teaser” for *some* of the connectives.
- Our connectives act like functions, assigning any input pattern a new output (just like logical gates in “technical computer science” / “computer architecture”).
- Examples: (expressed as *truth tables*)

| p | \neg | p | q | \wedge | p | q | \vee |
|-----|--------|-----|-----|----------|-----|-----|--------|
| 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0 | 1 | 0 | 1 | 0 | 0 | 1 | 1 |
| 1 | 0 | 1 | 0 | 0 | 1 | 0 | 1 |
| | | 1 | 1 | 1 | 1 | 1 | 1 |



Basic Definitions: Semantics of Connectives in Natural Language

Note that natural language does not always translate 1-to-1 to logics:

- “Jane and Jill went up the hill”:
says more than just $\text{WentUpHill}(\text{Jane}) \wedge \text{WentUpHill}(\text{Jill})$,
because it means that they went there *together*.
- “One false move and I will shoot!”
Does not mean $\text{Move}(\text{You}) \wedge \text{Shoot}(I)$, but
 $\text{Move}(\text{You}) \rightarrow \text{Shoot}(I)$
- Funnily, “Don’t move or I shoot”:
Is not meant to mean $\neg \text{Move}(\text{You}) \vee \text{Shoot}(I)$, but also means
 $\text{Move}(\text{You}) \rightarrow \text{Shoot}(I)$, but both are equivalent.

Modeling “the real world” (based on natural language) is not easy,
and partially covered in some exercises of Logic For Fun.



Basic Definitions: Precedence of Connectives (Syntax Simplification)

Our connectives use some precedence, which we exploit to eliminate parentheses! Connectives, ordered by precedence:

- Highest: \neg e.g., $\neg p \rightarrow q \equiv (\neg p) \rightarrow q$
- Second-highest: \wedge e.g., $p \wedge q \vee r \equiv (p \wedge q) \vee r$
- Mid: \vee e.g., $p \rightarrow q \vee r \equiv p \rightarrow (q \vee r)$
- Second-Lowest: \rightarrow e.g., $p \rightarrow \neg q \leftrightarrow r \equiv (p \rightarrow (\neg q)) \leftrightarrow r$
- Lowest: \leftrightarrow e.g., $\neg p \vee q \leftrightarrow q \wedge r \equiv ((\neg p) \vee q) \leftrightarrow (q \wedge r)$

We reduce parenthesis to simplify and avoid confusion by exploiting:

- *precedence*, e.g., we write $(p \wedge \neg q \wedge r) \rightarrow (p \vee \neg q \vee r)$ instead of $((p \wedge (\neg q)) \wedge r) \rightarrow (p \vee ((\neg q) \vee r))$, and
- *associativity*, e.g., we write $p \wedge q \wedge r$ instead of $(p \wedge (q \wedge r))$



Connective Scopes and Main Connective: Connective Scopes

- Every connective has a *scope*.
- “[The scope of a connective] is defined to be the shortest formula or subformula in which that occurrence lies.” (Logic Notes)
- Examples: In the formula $\neg(p \wedge q) \rightarrow ((p \vee r) \rightarrow \neg s)$
 - ... the scope of its first \neg is $(p \wedge q)$
 - ... the scope of its second \neg is s



Connective Scopes and Main Connective: Main Connective

- Every formula has a *main connective*:
- “[T]he main connective of any formula [...] is the one which is not inside the scope of any other. [...] The scope of the main connective is the whole formula.” (Logic Notes)
- Examples: The main connective of . . .
 - $\neg(p \wedge q) \rightarrow ((p \vee r) \rightarrow \neg s)$ is: the first \rightarrow
 - $(p \wedge q) \vee r$ is: \vee
 - What’s the main connective of $(p \wedge q) \vee r \vee (q \rightarrow r)$?
Recall that “ $(p \wedge q) \vee r \vee (q \rightarrow r)$ ” is only syntactic sugar!
 - ▶ It was either $((p \wedge q) \vee r) \vee (q \rightarrow r)$ [then, it’s the right \vee],
 - ▶ or it was $(p \wedge q) \vee (r \vee (q \rightarrow r))$ [then, it’s the left \vee]
- Why is it important to identify the main connective?
Because we will manipulate sequents based on their main connective!

Connective Scopes and Main Connective: Type of Formula

The main connective dictates the type of a formula:

- if main connective is \neg , formula is a *negation*
- ... \wedge , ... *conjunction*
- ... \vee , ... *disjunction*
- ... \rightarrow , ... *implication*
- ... \leftrightarrow , ... *double-implication*

Substitution: Substitutions of Formulae

What is a substitution?

- “Formula A is a substitution instance of formula B if and only if A results from B by substitution of formulas for sentence letters.” (Logic Notes) – (Definitions is specific to *propositional* logic.)

Non-Example:

- “Original” formula: $q \vee q$
- The formula $(p \wedge q) \vee \neg r$ is *not* a substitution instance of it (because the left part had to be the same as the right)

Substitution: Substitutions of Formulae

What is a substitution?

- “Formula A is a substitution instance of formula B if and only if A results from B by substitution of formulas for sentence letters.” (Logic Notes) – (Definitions is specific to *propositional* logic.)

Organizational Matters

○○○○○○○○○

Introduction to Logic

○○○○○○○○○

Sequents

○○○○

Propositional Calculus

○○○○○○○○○○○

Summary

●○

Summary

 Australian National University

Pascal Bercher and Yoshihiro Maruyama

33.34

Organizational Matters

○○○○○○○○○

Introduction to Logic

○○○○○○○○○

Sequents

○○○○

Propositional Calculus

○○○○○○○○○○○

Summary

○●

Content of this Lecture

- Organizational Matters
- *Sequents*, as a way to express valid arguments
- Introduction to *Propositional Logic*
 - Its syntax and (a preview to) its semantics
 - What connectives exist (and which don't)
 - How to identify the type of a formula (e.g., negation, conjunction, disjunction, implication, double-implication)
 - What's a substitution

→ The entire Logic Notes section "Introduction"

 Australian National University

Pascal Bercher and Yoshihiro Maruyama

34.34