

Histogram Equalisation 14 Jan 2026

Anubhav Rathore Input: Image Output: Image (Histogram Equalised)

Contents

- [Defaults](#)
- [Wikipedia Example - Hardcoded Histogram Equalisation](#)
- [Self-Built Histogram Equalisation Operation](#)
- [In-built operator](#)

Defaults

```
clc;
clear all;
close all;
```

Wikipedia Example - Hardcoded Histogram Equalisation


```
myImage = [52 55 61 59 79 61 76 61
            62 59 55 104 94 85 59 71
            63 65 66 113 144 104 63 72
            64 70 70 126 154 109 71 69
            67 73 68 106 122 88 68 68
            68 79 60 70 77 66 58 75
            69 85 64 58 55 61 65 83
            70 87 69 68 65 73 78 90];

myImage = cast(myImage, "uint8");
subplot(3,2,1);
imshow(myImage);
title("Original-Image");


eq_img_1 = [0 12 53 32 190 53 174 53
            57 32 12 227 219 202 32 154
            65 85 93 239 251 227 65 158
            73 146 146 247 255 235 154 130
            97 166 117 231 243 210 117 117
            117 190 36 146 178 93 20 170
            130 202 73 20 12 53 85 194
            146 206 130 117 85 166 182 215];

eq_img_1 = cast(eq_img_1, "uint8");
subplot(3,2,2), imshow(eq_img_1), title("Hard-Coded h(v) from WikiPedia");
subplot(3,2,5), imhist(myImage), title("Original Histogram");
```


Original-Image



Hard-Coded $h(v)$ from WikiPedia



Original Histogram




Self-Built Histogram Equalisation Operation


```
[R,C] = size(myImage);
counts = imhist(myImage);
cdf_counts = cumsum(counts);
cdf_min = cdf_counts(find(cdf_counts > 0, 1));
L = 256; % 8 bit image
eq_img_2 = zeros(R,C, "uint8");

for row = 1:R
    for col = 1:C
        curr_pixel = myImage(row,col);
        h_v = round(((cdf_counts(curr_pixel + 1) - cdf_min)/((R*C)-cdf_min))*(L-1));
        eq_img_2(row,col) = h_v;
    end
end
subplot(3,2,3), imshow(eq_img_2), title("Self-Built Operator");
subplot(3,2,6), imhist(eq_img_2), title("Equalised Histogram");
```


Original-Image




Hard-Coded $h(v)$ from Wikipedia




Self-Built Operator



Original Histogram




Equalised Histogram




In-built operator

```
eq_img_3 = histeq(myImage);  
subplot(3,2,4);  
imshow(eq_img_3);  
title("In-Built Operator");
```


Original-Image




Hard-Coded $h(v)$ from Wikipedia




Self-Built Operator



In-Built Operator



Original Histogram



Equalised Histogram

