University of the Philippines - Baguio

Archie Junio's Reference Notebook

29/04/2026

Contents

1. Data Structures 1
1.1. Segment Tree 1
1.2. Union Find 1
1.3. 2D Sparse Table 1
2. Dynamic Programming 1
2.1. Lichao Tree 1
2.2. Divide And Conquer 2
3. Geometry 2
3.1. Angles And Rotations 2
3.2. Distances 2
3.3. Intersections 2
3.3.1. Circle Line Intersection 2
3.3.2. Circle Circle Intersection 2
3.3.3. Line Intersect 2
3.4. Closest Pair 2
3.5. Convex Hull 2
3.5.1. Convex Hull 2
3.5.2. Convex Hull 3D 2
3.6. Areas 3
3.6.1. Triangle Area 3
3.6.2. Polygon Area 3
3.7. Dot Cross 3
3.8. Line Sweep Closest Pair 3
4. Graphs 3
4.1. Max Flow 3
4.1.1. Dinic 3
4.1.2. Edmonds Karp 3
4.1.3. Bipartite Matching 3
4.2. Shortest Path 4
4.2.1. Dijkstra 4
4.2.2. Bellman Ford 4
4.3. Minimum Spanning Tree 4
4.3.1. Kruskal Min Spanning Tree 4
4.3.2. Prim Min Spanning Tree 4
4.4. Least Common Ancestor 4
4.4.1. Binary Lifting Lca 4
4.4.2. Euler Lca 5
4.4.3. Tarjan Lca 5
4.5. Minimum Mean Weight Cycle 5
4.6. Strongly Connected Components 5
4.7. Heavy Light Decomposition 5
4.8. Euler Path/Cycle 6
4.8.1. Directed Euler 6
4.8.2. Undirected Euler 6
4.9. Tree Isomorphism 7
4.10. Centroid Decomposition 7
5. Math I Algebra 7
6. Math II Combinatorics 7
6.0.1. Lucas Theorem 7
6.0.2. Catalan Numbers 8
6.0.3. Kth Permutation 8
6.0.4. Factoradics 8
7. Math III Number Theory 8
7.0.1. Gcd Subset Counter 8
7.0.2. Linear Diophantine 8
7.0.3. Chinese Remainder Theorem 8
8. Math IV Numerical Methods 8
8.0.1. Fast Square Testing 8
8.0.2. Simpson Integration 8
9. Strings 8
9.0.1. Longest Common Prefix 8
9.0.2. Hasher 9
9.0.3. Z Algorithm 9
9.0.4. Aho Corasick Trie 9
9.0.5. Knuth Morris Pratt 9
9.0.6. Trie 9
9.0.7. Suffix Array 9
9.0.8. Booth Min String Rotation 10
10. Other Algorithms 10
10.0.1. Longest Increasing Subsequence 10
10.0.2. Cycle Find 10
10.0.3. 2Sat 10
10.0.4. Dpll 11
10.0.5. Stable Marriage 11
10.0.6. Dates 11

1. Data Structures

1.1. Segment Tree.

```
class SegmentTree:
    def __init__(self, data):
        self.n = len(data)
        self.tree = [0] * (2 * self.n)
        for i in range(self.n):
            self.tree[self.n + i] = data[i]
        for i in range(self.n - 1, 0, -1):
            self.tree[i] = self.tree[i << 1] + self.tree[i << 1 | 1]

    def update(self, p, value):
        p += self.n
        self.tree[p] = value
        while p > 1:
            self.tree[p >> 1] = self.tree[p] + self.tree[p ^ 1]
            p >>= 1

    def query(self, l, r):
        res = 0
        l += self.n
        r += self.n
        while l < r:
            if l & 1:
                res += self.tree[l]
                l += 1
            if r & 1:
                r -= 1
                res += self.tree[r]
            l >>= 1
            r >>= 1
        return res
```

1.2. Union Find.

```
class DSU:
    def __init__(self, n):
        self.parent = list(range(n))
        self.size = [1] * n

    def find(self, i):
        if self.parent[i] == i:
            return i
        self.parent[i] = self.find(self.parent[i])
        return self.parent[i]

    def union(self, i, j):
        root_i = self.find(i)
        root_j = self.find(j)

        if root_i != root_j:
            if self.size[root_i] < self.size[root_j]:
                root_i, root_j = root_j, root_i
            self.parent[root_j] = root_i
            self.size[root_i] += self.size[root_j]
            return True
        return False

    def get_size(self, i):
        return self.size[self.find(i)]
```

1.3. 2D Sparse Table.

```
import math

class SparseTable2D:
    def __init__(self, A):
        self.A = A
        self.n = len(A)
        self.m = len(A[0])

        self.LOGN = int(math.log2(self.n)) + 1
        self.LOGM = int(math.log2(self.m)) + 1

        self.lg = [0] * (max(self.n, self.m) + 1)
        for i in range(2, len(self.lg)):
            self.lg[i] = self.lg[i // 2] + 1

        self.st = [[[[0] * self.m for _ in range(self.n)]
                    for _ in range(self.LOGM)]
                   for _ in range(self.LOGN)]

        self.build()

    def build(self):
```

```
for i in range(self.n):
    for j in range(self.m):
        self.st[0][0][i][j] = self.A[i][j]

for bj in range(1, self.LOGM):
    for i in range(self.n):
        for j in range(self.m - (1 << bj) + 1):
            self.st[0][bj][i][j] = max(
                self.st[0][bj - 1][i][j],
                self.st[0][bj - 1][i][j + (1 << (bj - 1))]
            )

for bi in range(1, self.LOGN):
    for i in range(self.n - (1 << bi) + 1):
        for j in range(self.m):
            self.st[bi][0][i][j] = max(
                self.st[bi - 1][0][i][j],
                self.st[bi - 1][0][i + (1 << (bi - 1))][j]
            )

for bi in range(1, self.LOGN):
    for bj in range(1, self.LOGM):
        for i in range(self.n - (1 << bi) + 1):
            for j in range(self.m - (1 << bj) + 1):
                self.st[bi][bj][i][j] = max(
                    self.st[bi - 1][bj - 1][i][j],
                    self.st[bi - 1][bj - 1][i + (1 << (bi - 1))][j],
                    self.st[bi - 1][bj - 1][i][j + (1 << (bj - 1))],
                    self.st[bi - 1][bj - 1][i + (1 << (bi - 1))][j + (1 << (bj - 1))]
                )

def query(self, x1, y1, x2, y2):
    kx = self.lg[x2 - x1 + 1]
    ky = self.lg[y2 - y1 + 1]

    return max(
        self.st[kx][ky][x1][y1],
        self.st[kx][ky][x2 - (1 << kx) + 1][y1],
        self.st[kx][ky][x1][y2 - (1 << ky) + 1],
        self.st[kx][ky][x2 - (1 << kx) + 1][y2 - (1 << ky) + 1]
    )
# Input Format: st = SparseTable2D(grid)
#               print(st.query(1, 1, 2, 2))
```

2. Dynamic Programming

2.1. Lichao Tree.

```
class Line:
    __slots__ = ['m', 'c']
    def __init__(self, m=0, c=float('-inf')):
        self.m = m
        self.c = c

    def eval(self, x):
        return self.m * x + self.c

class Node:
    __slots__ = ['line', 'left', 'right']
    def __init__(self):
        self.line = Line()
        self.left = None
        self.right = None

class LiChaoTree:
    def __init__(self, min_x=-10**12, max_x=10**12):
        self.root = Node()
        self.min_x = min_x
        self.max_x = max_x

    def add_line(self, m, c):
        self._insert(self.root, self.min_x, self.max_x, Line(m, c))

    def _insert(self, node, l, r, new_line):
        mid = (l + r) // 2

        left_better = new_line.eval(l) > node.line.eval(l)
        mid_better = new_line.eval(mid) > node.line.eval(mid)

        if mid_better:
            node.line, new_line = new_line, node.line
        if r - l <= 1:
            return

        if left_better != mid_better:
            if not node.left:
                node.left = Node()
            self._insert(node.left, l, mid, new_line)
        else:
            if not node.right:
                node.right = Node()
            self._insert(node.right, mid, r, new_line)

    def query(self, x):
        return self._query(self.root, self.min_x, self.max_x, x)

    def _query(self, node, l, r, x):
        if not node:
            return float('-inf')
        if r - l <= 1:
            return node.line.eval(x)

        mid = (l + r) // 2
        res = node.line.eval(x)

        if x < mid:
            res = max(res, self._query(node.left, l, mid, x))
        else:
            res = max(res, self._query(node.right, mid, r, x))

        return res
```

2.2. Divide And Conquer.

```
INF = float('inf')

def solve_dp(g, k_L, k_R, n_L, n_R, dp, cost_func):
    if n_L > n_R:
        return

    n_M = (n_L + n_R) // 2
    best_k = -1
    dp[g][n_M] = INF

    for k in range(k_L, min(n_M, k_R) + 1):
        current_val = dp[g - 1][k] + cost_func(k + 1, n_M)
        if current_val < dp[g][n_M]:
            dp[g][n_M] = current_val
            best_k = k

    solve_dp(g, k_L, best_k, n_L, n_M - 1, dp, cost_func)
    solve_dp(g, best_k, k_R, n_M + 1, n_R, dp, cost_func)
```

3. Geometry

3.1. Angles And Rotations.

```
def angle(a, b, c): # angle formed by abc in radians: PI < x <= PI
    return abs((arg(a-b) - arg(c-b)) % (2 * math.pi))
def rotate(p, a, d): # rotate point a about pivot p CCW at d radians
    return p + (a - p) * complex(math.cos(d), math.sin(d))
```

3.2. Distances.

```
# Distance: Point to 2D Line (ax + by + c = 0)
def dist_pt_line_eq(p, a, b, c):
    return abs(a*p.real + b*p.imag + c) / math.hypot(a, b)

# Distance: Point to 2D Line through points a and b
def dist_pt_line(p, a, b):
    cp = (p - a).conjugate() * (b - a)
    return abs(cp.imag) / abs(b - a)

# Distance: Point to 3D Plane (ax + by + cz + d = 0)
def dist_pt_plane(p, a, b, c, d):
    # math.hypot supports 3+ arguments in Python 3.8+
    return abs(a*p.x + b*p.y + c*p.z + d) / math.hypot(a,b,c)

# Distance: Shortest distance between 3D lines AB and CD
def dist_line_3d(A, B, C, D):
    u, v, w = B - A, D - C, A - C
    a, b = u.dot(u), u.dot(v)
    c, d, e = v.dot(v), u.dot(w), v.dot(w)
    det = a * c - b * b
    if det < 1e-9: # Parallel lines
        s, t = 0.0, d / b if b > c else e / c
    else: # Skew lines
        s = (b * e - c * d) / det
        t = (a * e - b * d) / det
    p1 = P3(A.x + u.x*s, A.y + u.y*s, A.z + u.z*s)
    p2 = P3(C.x + v.x*t, C.y + v.y*t, C.z + v.z*t)
    vec = p1 - p2
    return math.sqrt(vec.dot(vec))
```

3.3. Intersections.

3.3.1. *Circle Line Intersection.*

```
EPS = 1e-9
def projLine(p, a, b): # Project point p onto line segment ab
    v = b - a
    scalar = ((p - a) * v.conjugate()).real / abs(v)**2
    return a + v * scalar

def rotate(c, p, t): # Rotate point p around center c by t radians
    return c + (p - c) * cmath.rect(1, t)

def CL_inter(c, r, a, b):
    p = projLine(c, a, b)
    d = abs(c - p)
    ans = []

    if d > r + EPS: pass # None
    elif d > r - EPS: ans.append(p) # Tangent
    elif d < EPS: # Diameter
        v = r * (b - a) / abs(b - a)
        ans.append(c + v)
        ans.append(c - v)
    else: # Secant
        t = math.acos(d / r)
        p = c + (p - c) * r / d
        ans.append(rotate(c, p, t))
        ans.append(rotate(c, p, -t))
    return ans
```

3.3.2. *Circle Circle Intersection.*

```
EPS = 1e-9
def rotate(c, p, t):
    # Rotate point p around center c by t radians
    return c + (p - c) * cmath.rect(1, t)

def CC_inter(c1, r1, c2, r2):
    d = abs(c1 - c2)
    ans = []
    if d < EPS: # Concentric circles
        if abs(r1 - r2) < EPS:
            pass # Infinite intersections (same circle)
    elif r1 < EPS: # Circle 1 is a point
        if abs(d - r2) < EPS:
            ans.append(c1)
    else: # General case using Law of Cosines
        s = (r1*r1 + d*d - r2*r2) / (2*r1*d)
        s = max(-1.0, min(1.0, s)) # Prevent float domain errors
        t = math.acos(s)
        # Point on C1's radius pointing towards C2
        mid = c1 + (c2 - c1) * r1 / d
        ans.append(rotate(c1, mid, t))
        if abs(math.sin(t)) >= EPS:
            # FIXED: Rotate around c1, not c2!
            ans.append(rotate(c1, mid, -t))
    return ans
```

3.3.3. *Line Intersect.*

```
def line_inter_fast(a, b, c, d):
    A = cross(d - a, b - a)
    B = cross(c - a, b - a)
    return (B * d - A * c) / (B - A) if B - A else None
```

3.4. Closest Pair.

```
def closest_pair(pts):
    if len(pts) <= 1: return float('inf')
    px = sorted(pts) # Automatically sorts by x, then y
    def solve(l, r): # Base case: Brute force for small partitions
        if r - l <= 3:
            d = float('inf')
            for i in range(l, r):
                for j in range(i + 1, r):
                    d = min(d, math.dist(px[i], px[j]))
            return d
        mid = (l + r) // 2
        mid_x = px[mid][0]
        # Recursively find the minimum in both halves
        d = min(solve(l, mid), solve(mid, r))
        # Gather points in the middle strip
        strip = [p for p in px[l:r] if abs(p[0] - mid_x) < d]
        strip.sort(key=lambda p: p[1]) # Sort strip by y
        # Check at most 7 geometric neighbors in the strip
        for i, p1 in enumerate(strip):
            for p2 in strip[i+1 : i+8]:
                d = min(d, math.dist(p1, p2))
        return d
    return solve(0, len(px))
```

3.5. Convex Hull.

3.5.1. *Convex Hull.*

```
def cross(o, a, b): # 2D cross product of OA and OB vectors
    return (a[0]-o[0])*(b[1]-o[1]) - (a[1]-o[1])*(b[0]-o[0])

def convex_hull(pts): # Sorts by x, then by y automatically
    pts = sorted(set(pts))
    if len(pts) <= 1:
        return pts
    def build(iterable):
        h = []
        for p in iterable:
            while len(h) >= 2 and cross(h[-2], h[-1], p) <= 0:
                h.pop()
            h.append(p)
        return h
    lower = build(pts)
    upper = build(reversed(pts))
    return lower[:-1] + upper[:-1]
```

3.5.2. *Convex Hull 3D.*

```
class P3:
    __slots__ = ['x', 'y', 'z']
    def __init__(self, x=0, y=0, z=0):
        self.x, self.y, self.z = x, y, z
    def __sub__(self, o):
        return P3(self.x-o.x, self.y-o.y, self.z-o.z)
    def cross(self, o):
        return P3(self.y*o.z - self.z*o.y,
                  self.z*o.x - self.x*o.z,
                  self.x*o.y - self.y*o.x)
    def dot(self, o):
        return self.x*o.x + self.y*o.y + self.z*o.z
    def __eq__(self, o):
        return (self.x, self.y, self.z) == (o.x, o.y, o.z)
    def __lt__(self, o):
        return (self.x, self.y, self.z) < (o.x, o.y, o.z)

class Face:
    __slots__ = ['p', 'q']
    def __init__(self, p, q):
        self.p = p # Tuple of 3 point indices
        self.q = q # Normal vector (P3 object)

def hull_3D(pts):
    n = len(pts)
    faces = []
    dead = [[True] * n for _ in range(n)]
    def add_face(a, b, c):
        q = (pts[b] - pts[a]).cross(pts[c] - pts[a])
        faces.append(Face((a, b, c), q))
        dead[a][b] = dead[b][c] = dead[c][a] = False
    # Initialize with a degenerate tetrahedron
    add_face(0, 1, 2)
    add_face(0, 2, 1)
    for i in range(3, n):
        f_inv = []
        for f in faces:
            # If face is visible from the point
            if (pts[i] - pts[f.p[0]]).dot(f.q) > 0:
                for j in range(3):
                    dead[f.p[j]][f.p[(j+1)%3]] = True
            else:
                f_inv.append(f)
        faces = []
        for f in f_inv:
            for j in range(3):
                a, b = f.p[j], f.p[(j+1)%3]
                # If reverse edge is dead but forward is alive
                if dead[b][a]:
                    add_face(b, a, i)
        faces.extend(f_inv)
    return faces
```

3.6. Areas.

3.6.1. *Triangle Area.*

```
def area(a, b, c):
    s = (a + b + c) / 2
    return (s*(s-a)*(s-b)*(s-c)) ** 0.5
```

3.6.2. *Polygon Area.*

```
def area(p, n):
    a = 0
    for i in range(n):
        j = (i - 1) % n
        a += cross(p[i], p[j])
    return abs(a) / 2
```

3.7. Dot Cross.

```
def dot(a, b):
    return a.x * b.x + a.y * b.y # + a.z * b.z
def cross(a, b):
    return a.x * b.y - a.y * b.x
def cross(a, b, c):
    return cross(a, b) + cross(b, c) + cross(c, a)
def cross3D(a, b):
    return point3(a.x*b.y - a.y*b.x, a.y*b.z - a.z*b.y, a.z*b.x -
↪   a.x*b.z)
```

3.8. Line Sweep Closest Pair.

```
import math

def dist_sq(p1, p2):
    return (p1[0] - p2[0])**2 + (p1[1] - p2[1])**2

def closest_pair(points):
    points.sort()

    def solve(pts):
        n = len(pts)

        if n <= 3:
            return min(dist_sq(pts[i], pts[j])
                        for i in range(n)
                        for j in range(i + 1, n)) if n > 1 else
↪   float('inf')

        mid = n // 2
        mid_x = pts[mid][0]

        left = pts[:mid]
        right = pts[mid:]

        d = min(solve(left), solve(right))

        strip = [p for p in pts if (p[0] - mid_x) ** 2 < d]
        strip.sort(key=lambda p: p[1])

        for i in range(len(strip)):
            for j in range(i + 1, min(i + 7, len(strip))):
                d = min(d, dist_sq(strip[i], strip[j]))

        return d

    return solve(points)
```

4. Graphs

4.1. Max Flow.

4.1.1. *Dinic.*

```
INF = float('inf')
class Dinic:
    def __init__(self, n, s, t):
        self.n, self.s, self.t = n, s, t
        self.edges = []
        self.adj = [[] for _ in range(n)]

    def add_edge(self, u, v, c, bi=False):
        self.adj[u].append(len(self.edges))
        self.edges.append([v, c, 0])
        self.adj[v].append(len(self.edges))
        self.edges.append([u, c if bi else 0, 0])

    def bfs(self):
        self.dist = [-1] * self.n
        self.dist[self.s] = 0
        q = deque([self.s])
        while q:
            u = q.popleft()
            for i in self.adj[u]:
                v, c, f = self.edges[i]
                if self.dist[v] < 0 and c > f:
                    self.dist[v] = self.dist[u] + 1
                    q.append(v)
        return self.dist[self.t] != -1

    def dfs(self, u, pushed):
        if pushed == 0 or u == self.t: return pushed
        while self.ptr[u] < len(self.adj[u]):
            i = self.adj[u][self.ptr[u]]
            v, c, f = self.edges[i]
            if self.dist[u]+1 == self.dist[v] and c > f:
                tr = self.dfs(v, min(pushed, c - f))
                if tr > 0:
                    self.edges[i][2] += tr
                    self.edges[i^1][2] -= tr
                    return tr
            self.ptr[u] += 1
        return 0

    def calc_max_flow(self):
        flow = 0
        while self.bfs():
            self.ptr = [0] * self.n
            while True:
                pushed = self.dfs(self.s, INF)
                if not pushed:
                    break
                flow += pushed
        return flow
```

4.1.2. *Edmonds Karp.*

```
INF = float('inf')
class EdmondsKarp:
    def __init__(self, n, s, t):
        self.n, self.s, self.t = n, s, t
        self.adj = [[] for _ in range(n)]
        self.res = [[0] * n for _ in range(n)]

    def add_edge(self, u, v, w):
        self.adj[u].append(v)
        self.adj[v].append(u)
        self.res[u][v] += w

    def bfs(self):
        self.par = [-1] * self.n
        self.par[self.s] = self.s
        q = deque([self.s])
        while q:
            u = q.popleft()
            for v in self.adj[u]:
                if self.res[u][v] > 0 and self.par[v] == -1:
                    self.par[v] = u
                    if v == self.t:
                        return True
                    q.append(v)
        return False

    def calc_max_flow(self):
        ans = 0
        while self.bfs():
            flow = INF
            u = self.t
            while u != self.s:
                p = self.par[u]
                flow = min(flow, self.res[p][u])
                u = p
            u = self.t
            while u != self.s:
                p = self.par[u]
                self.res[p][u] -= flow
                self.res[u][p] += flow
                u = p
            ans += flow
        return ans
```

4.1.3. *Bipartite Matching.*

```
from collections import deque

INF = float('inf')
class BipartiteGraph:
    def __init__(self, n, m):
        self.n = n
        self.m = m
        self.adj = [[] for _ in range(n)]
        self.L = [-1] * n
        self.R = [-1] * m
        self.dist = [INF] * (n + 1)

    def add_edge(self, u, v):
        self.adj[u].append(v)

    def bfs(self):
        queue = deque()
        for v in range(self.n):
            if self.L[v] == -1:
                self.dist[v] = 0
                queue.append(v)
            else:
                self.dist[v] = INF
        self.dist[self.n] = INF
        while queue:
            v = queue.popleft()
            if self.dist[v] < self.dist[self.n]:
                for u in self.adj[v]:
                    next_v = self.R[u]
                    dist_next = self.dist[next_v] if next_v != -1 else
↪   self.dist[self.n]
                    if (next_v == -1 and self.dist[self.n] == INF) or \
                        (next_v != -1 and self.dist[next_v] ==
↪   INF):
                        target = next_v if next_v != -1 else self.n
                        self.dist[target] = self.dist[v] + 1
                        if target != self.n:
                            queue.append(target)
        return self.dist[self.n] != INF

    def dfs(self, v):
        if v != -1:
            for u in self.adj[v]:
                next_v = self.R[u]
                dist_next = self.dist[next_v] if next_v != -1 else
↪   self.dist[self.n]
                if dist_next == self.dist[v] + 1:
                    if self.dfs(next_v):
                        self.R[u] = v
                        self.L[v] = u
                        return True
            self.dist[v] = INF
            return False
        return True

    def maximum_matching(self):
        matching = 0
        for u in range(self.n):
            for v in self.adj[u]:
                if self.R[v] == -1:
                    self.L[u] = v
                    self.R[v] = u
                    matching += 1
                    break
        while self.bfs():
            for i in range(self.n):
                if self.L[i] == -1 and self.dfs(i):
                    matching += 1
        return matching
# Input Format: g = BipartiteGraph(2, 2)
#               g.add_edge(0, 0)
#               g.add_edge(0, 1)
#               g.add_edge(1, 0)
#               print(f"Max Matching: {g.maximum_matching()}")
```

4.2. Shortest Path.

4.2.1. *Dijkstra.*

```
import heapq
INF = float('inf')
def dijkstra(n, adj, s):
    dist = [INF] * n
    dist[s] = 0
    pq = [(0, s)]

    while pq:
        d, u = heapq.heappop(pq)
        if dist[u] < d:
            continue
        for v, w in adj[u]:
            if dist[v] > d + w:
                dist[v] = d + w
                heapq.heappush(pq, (dist[v], v))
    return dist
```

4.2.2. *Bellman Ford.*

```
INF = float('inf')
def bellman_ford(n, adj, s):
    dist = [INF] * n
    dist[s] = 0
    for _ in range(n - 1):
        for u in range(n):
            if dist[u] == INF: continue
            for v, w in adj[u]:
                if dist[u] + w < dist[v]:
                    dist[v] = dist[u] + w
    for u in range(n):
```

```
------- if dist[u] == INF: continue ----------------------------------
------- for v, w in adj[u]: ------------------------------------------
----------- if dist[u] + w < dist[v]: ------------------------------
--------------- return dist, True ------------------------------------
--- return dist, False -------------------------------------------------
```

4.3. Minimum Spanning Tree.

4.3.1. *Kruskal Min Spanning Tree.*

```
import heapq -------------------------------------------------------------

class UnionFind: ---------------------------------------------------------
--- def __init__(self, n): ---------------------------------------------
------- self.parent = list(range(n)) -------------------------------------
------- self.rank = [0] * n ----------------------------------------------

--- def find(self, x): -------------------------------------------------
------- while self.parent[x] != x: ---------------------------------------
----------- self.parent[x] = self.parent[self.parent[x]] -------------
----------- x = self.parent[x] -----------------------------------------
------- return x ---------------------------------------------------------

--- def unite(self, a, b): ---------------------------------------------
------- a = self.find(a) -------------------------------------------------
------- b = self.find(b) -------------------------------------------------

------- if a == b: -------------------------------------------------------
----------- return False -----------------------------------------------

------- if self.rank[a] < self.rank[b]: ----------------------------------
----------- self.parent[a] = b -----------------------------------------
------- else: ------------------------------------------------------------
----------- self.parent[b] = a -----------------------------------------
----------- if self.rank[a] == self.rank[b]: ---------------------------
--------------- self.rank[a] += 1 ------------------------------------

------- return True ------------------------------------------------------

def kruskal(n, edges): ---------------------------------------------------
--- edges = edges[:] ---------------------------------------------------
--- heapq.heapify(edges) -----------------------------------------------

--- uf = UnionFind(n) --------------------------------------------------
--- total_weight = 0 ---------------------------------------------------
--- mst = [] -----------------------------------------------------------

--- while edges: -------------------------------------------------------
------- w, u, v = heapq.heappop(edges) -----------------------------------
------- if uf.unite(u, v): -----------------------------------------------
----------- mst.append((u, v, w)) --------------------------------------
----------- total_weight += w ------------------------------------------

----------- if len(mst) == n - 1: --------------------------------------
--------------- break ------------------------------------------------

--- return mst, total_weight -------------------------------------------
```

4.3.2. *Prim Min Spanning Tree.*

```
import heapq -------------------------------------------------------------

def prim(n, adj, start=0): -----------------------------------------------
--- visited = [False] * n ----------------------------------------------
--- pq = [(0, start, -1)] ----------------------------------------------

--- total_weight = 0 ---------------------------------------------------
--- mst = [] -----------------------------------------------------------

--- while pq: ----------------------------------------------------------
------- w, u, parent = heapq.heappop(pq) ---------------------------------

------- if visited[u]: ---------------------------------------------------
----------- continue ---------------------------------------------------

------- visited[u] = True ------------------------------------------------

------- if parent != -1: -------------------------------------------------
----------- mst.append((parent, u, w)) ---------------------------------
----------- total_weight += w ------------------------------------------

------- for v, weight in adj[u]: -----------------------------------------
----------- if not visited[v]: -----------------------------------------
--------------- heapq.heappush(pq, (weight, v, u)) -------------------

--- return mst, total_weight -------------------------------------------
```

4.4. Least Common Ancestor.

4.4.1. *Binary Lifting Lca.*

```
import math ----------------------------------------------------------------

class BinaryLifting: -----------------------------------------------------
--- def __init__(self, adj): -------------------------------------------
------- self.n = len(adj) ------------------------------------------------
------- self.LOG = math.ceil(math.log2(self.n)) + 1 ----------------------
------- self.adj = adj ---------------------------------------------------

------- self.dep = [0] * self.n ------------------------------------------
------- self.par = [[-1] * self.LOG for _ in range(self.n)] --------------

------- self.build(0) ----------------------------------------------------

--- def dfs(self, u, p): -----------------------------------------------
------- self.par[u][0] = p -----------------------------------------------
------- for v in self.adj[u]: --------------------------------------------
----------- if v != p: -------------------------------------------------
--------------- self.dep[v] = self.dep[u] + 1 ------------------------
--------------- self.dfs(v, u) ---------------------------------------

--- def build(self, root): ---------------------------------------------
------- self.dfs(root, root) ---------------------------------------------

------- for k in range(1, self.LOG): -------------------------------------
----------- for u in range(self.n): ------------------------------------
--------------- self.par[u][k] = self.par[self.par[u][k-1]][k-1] -----

--- def lift(self, u, k): ----------------------------------------------
------- for i in range(self.LOG): ----------------------------------------
----------- if k & (1 << i): -------------------------------------------
--------------- u = self.par[u][i] -----------------------------------
------- return u ---------------------------------------------------------

--- def lca(self, u, v): -----------------------------------------------
------- if self.dep[u] < self.dep[v]: ------------------------------------
----------- u, v = v, u ------------------------------------------------

------- u = self.lift(u, self.dep[u] - self.dep[v]) ----------------------

------- if u == v: -------------------------------------------------------
----------- return u ---------------------------------------------------

------- for k in reversed(range(self.LOG)): ------------------------------
----------- if self.par[u][k] != self.par[v][k]: -----------------------
--------------- u = self.par[u][k] -----------------------------------
--------------- v = self.par[v][k] -----------------------------------

------- return self.par[u][0] --------------------------------------------
```

4.4.2. *Euler Lca.*

```
class EulerLCA: ----------------------------------------------------------
--- def __init__(self, adj): -------------------------------------------
------- self.n = len(adj) ------------------------------------------------
------- self.adj = adj ---------------------------------------------------

------- self.euler = [] --------------------------------------------------
------- self.first = [-1] * self.n ---------------------------------------
------- self.depth = [0] * self.n ----------------------------------------

------- self.build(0) ----------------------------------------------------

--- def dfs(self, u, p, d): --------------------------------------------
------- self.first[u] = len(self.euler) ----------------------------------
------- self.depth[u] = d ------------------------------------------------
------- self.euler.append(u) ---------------------------------------------

------- for v in self.adj[u]: --------------------------------------------
----------- if v != p: -------------------------------------------------
--------------- self.dfs(v, u, d + 1) --------------------------------
--------------- self.euler.append(u) ---------------------------------

--- def build(self, root): ---------------------------------------------
------- self.dfs(root, root, 0) ------------------------------------------

------- m = len(self.euler) ----------------------------------------------
------- LOG = m.bit_length() ---------------------------------------------

------- self.st = [[0] * m for _ in range(LOG)] --------------------------
------- self.log = [0] * (m + 1) -----------------------------------------

------- for i in range(2, m + 1): ----------------------------------------
----------- self.log[i] = self.log[i // 2] + 1 -------------------------

------- for i in range(m): -----------------------------------------------
----------- self.st[0][i] = self.euler[i] ------------------------------

------- for k in range(1, LOG): ------------------------------------------
----------- for i in range(m - (1 << k) + 1): --------------------------
--------------- a = self.st[k-1][i] ----------------------------------
--------------- b = self.st[k-1][i + (1 << (k-1))] -------------------
--------------- self.st[k][i] = a if self.depth[a] < self.depth[b] else
↪  b

--- def lca(self, u, v): -----------------------------------------------
------- l, r = self.first[u], self.first[v] ------------------------------
------- if l > r: --------------------------------------------------------
----------- l, r = r, l ------------------------------------------------

------- k = self.log[r - l + 1] ------------------------------------------
------- a = self.st[k][l] ------------------------------------------------
------- b = self.st[k][r - (1 << k) + 1] ---------------------------------

------- return a if self.depth[a] < self.depth[b] else b -----------------
```

4.4.3. *Tarjan Lca.*

```
class DSU: ---------------------------------------------------------------
--- def __init__(self, n): ---------------------------------------------
------- self.p = list(range(n)) ------------------------------------------

--- def find(self, x): -------------------------------------------------
------- if self.p[x] != x: -----------------------------------------------
----------- self.p[x] = self.find(self.p[x]) ---------------------------
------- return self.p[x] -------------------------------------------------

--- def unite(self, a, b): ---------------------------------------------
------- self.p[self.find(b)] = self.find(a) ------------------------------

class Tarjan: ------------------------------------------------------------
--- def __init__(self, adj, queries): ----------------------------------
------- self.adj = adj ---------------------------------------------------
------- self.queries = queries -------------------------------------------
------- self.n = len(adj) ------------------------------------------------
```

```
        self.dsu = DSU(self.n)
        self.vis = [False] * self.n
        self.anc = [0] * self.n
        self.res = {}

    def dfs(self, u, p):
        self.anc[u] = u

        for v in self.adj[u]:
            if v == p:
                continue
            self.dfs(v, u)
            self.dsu.unite(u, v)
            self.anc[self.dsu.find(u)] = u

        self.vis[u] = True

        for v, idx in self.queries[u]:
            if self.vis[v]:
                self.res[idx] = self.anc[self.dsu.find(v)]
```

4.5. Minimum Mean Weight Cycle.

```
def min_mean_cycle(adj):
    n = len(adj)
    INF = float('inf')

    arr = [[INF] * n for _ in range(n + 1)]

    for i in range(n):
        arr[0][i] = 0

    for k in range(1, n + 1):
        for u in range(n):
            if arr[k - 1][u] == INF:
                continue
            for v, w in adj[u]:
                arr[k][v] = min(arr[k][v], arr[k - 1][u] + w)

    result = INF

    for v in range(n):
        if arr[n][v] == INF:
            continue

        max_avg = -INF
        for k in range(n):
            if arr[k][v] == INF:
                continue
            avg = (arr[n][v] - arr[k][v]) / (n - k)
            max_avg = max(max_avg, avg)

        result = min(result, max_avg)

    return result
```

4.6. Strongly Connected Components.

```
class KosarajuGraph:
    def __init__(self, n):
        self.n = n
        self.graph = [[] for _ in range(n)]
        self.rev_graph = [[] for _ in range(n)]
        self.vis = [0] * n
        self.sccs = []

    def add_edge(self, u, v):
        self.graph[u].append(v)
        self.rev_graph[v].append(u)

    def dfs(self, u, adj, container):
        self.vis[u] = 1
        for v in adj[u]:
            if not self.vis[v]:
                self.dfs(v, adj, container)
        container.append(u)

    def kosaraju(self):
        topo = []

        # First pass
        self.vis = [0] * self.n
        for i in range(self.n):
            if not self.vis[i]:
                self.dfs(i, self.graph, topo)

        # Second pass
        self.vis = [0] * self.n
        self.sccs = []

        for u in reversed(topo):
            if not self.vis[u]:
                comp = []
                self.dfs(u, self.rev_graph, comp)
                self.sccs.append(comp)

        return self.sccs
```

4.7. Heavy Light Decomposition.

```
class SegmentTree:
    def __init__(self, n):
        self.n = n
        self.tree = [0] * (4 * n)

    # Example: point update
    def update(self, idx, val, node=1, l=0, r=None):
        if r is None:
            r = self.n - 1
        if l == r:
            self.tree[node] = vala
            return
        mid = (l + r) // 2
        if idx <= mid:
            self.update(idx, val, node * 2, l, mid)
        else:
            self.update(idx, val, node * 2 + 1, mid + 1, r)
        self.tree[node] = self.tree[node * 2] + self.tree[node * 2 + 1]

    # Example: range query
    def query(self, ql, qr, node=1, l=0, r=None):
        if r is None:
            r = self.n - 1
        if qr < l or r < ql:
            return 0
        if ql <= l and r <= qr:
            return self.tree[node]
        mid = (l + r) // 2
        return self.query(ql, qr, node * 2, l, mid) + \
               self.query(ql, qr, node * 2 + 1, mid + 1, r)

class HeavyLightTree:
    def __init__(self, n):
        self.n = n
        self.adj = [[] for _ in range(n)]

        self.par = [-1] * n
        self.heavy = [-1] * n
        self.dep = [0] * n
        self.path_root = [0] * n
        self.pos = [0] * n

        self.segment_tree = SegmentTree(n)
        self.current_pos = 0

    def add_edge(self, u, v):
        self.adj[u].append(v)
        self.adj[v].append(u)

    def dfs(self, u):
        size = 1
        max_subtree_size = 0

        for v in self.adj[u]:
            if v != self.par[u]:
                self.par[v] = u
                self.dep[v] = self.dep[u] + 1
                subtree_size = self.dfs(v)

                if subtree_size > max_subtree_size:
                    max_subtree_size = subtree_size
                    self.heavy[u] = v

                size += subtree_size

        return size

    def decompose(self, u, root):
        self.path_root[u] = root
        self.pos[u] = self.current_pos
        self.current_pos += 1

        if self.heavy[u] != -1:
            self.decompose(self.heavy[u], root)

        for v in self.adj[u]:
            if v != self.par[u] and v != self.heavy[u]:
                self.decompose(v, v)

    def build(self, root=0):
        self.par[root] = root
        self.dep[root] = 0
        self.dfs(root)
        self.decompose(root, root)

    # Query path u -> v
    def query(self, u, v):
        res = 0
        while self.path_root[u] != self.path_root[v]:
            if self.dep[self.path_root[u]] <
↪   self.dep[self.path_root[v]]:
                u, v = v, u
            start = self.path_root[u]
            res += self.segment_tree.query(self.pos[start],
↪   self.pos[u])
            u = self.par[start]

        # Same path
        if self.dep[u] > self.dep[v]:
            u, v = v, u
        res += self.segment_tree.query(self.pos[u], self.pos[v])
        return res

    # Update node value
    def update(self, u, value):
        self.segment_tree.update(self.pos[u], value)
```

4.8. Euler Path/Cycle.

4.8.1. *Directed Euler.*

```
from collections import defaultdict

class DirectedEuler:
    def __init__(self, n):
        self.n = n
        self.adj = defaultdict(list)
        self.indeg = [0]*n
        self.outdeg = [0]*n
        self.edge_count = 0

    def add_edge(self, u, v):
        self.adj[u].append(v)
        self.outdeg[u] += 1
        self.indeg[v] += 1
        self.edge_count += 1

    def find_start_node(self):
        start = -1
        end = -1
        for i in range(self.n):
            if self.outdeg[i] - self.indeg[i] == 1:
                if start != -1:
                    return -1
                start = i
            elif self.indeg[i] - self.outdeg[i] == 1:
                if end != -1:
                    return -1
                end = i
            elif self.indeg[i] != self.outdeg[i]:
                return -1

        if start == -1:
            for i in range(self.n):
                if self.outdeg[i] > 0:
                    return i
        return start

    def get_euler_path(self):
        start = self.find_start_node()
        if start == -1:
            return None

        stack = [start]
        path = []

        local_adj = {u: self.adj[u][:] for u in self.adj}

        while stack:
            u = stack[-1]
            if u in local_adj and local_adj[u]:
                v = local_adj[u].pop()
                stack.append(v)
            else:
                path.append(stack.pop())

        if len(path) != self.edge_count + 1:
            return None

        return path[::-1]


    class UndirectedEuler:
        def __init__(self, n):
            self.n = n
            self.adj = defaultdict(list)
            self.edge_count = 0

        def add_edge(self, u, v):
            self.adj[u].append(v)
            self.adj[v].append(u)
            self.edge_count += 1

        def is_valid(self):
            odd = 0
            for i in range(self.n):
                if len(self.adj[i]) % 2 != 0:
                    odd += 1
            return odd == 0 or odd == 2

        def get_euler_path(self):
            if not self.is_valid():
                return None

            start = 0
            for i in range(self.n):
                if len(self.adj[i]) % 2 == 1:
                    start = i
                    break
                if len(self.adj[i]) > 0:
                    start = i

            stack = [start]
            path = []

            local_adj = {u: self.adj[u][:] for u in self.adj}

            while stack:
                u = stack[-1]
                if u in local_adj and local_adj[u]:
                    v = local_adj[u].pop()
                    local_adj[v].remove(u)
                    stack.append(v)
                else:
                    path.append(stack.pop())

            if len(path) != self.edge_count + 1:
                return None

            return path[::-1]
```

4.8.2. *Undirected Euler.*

```
from collections import defaultdict

class UndirectedEuler:
    def __init__(self, n):
        self.n = n
        self.adj = defaultdict(list)
        self.edge_count = 0

    def add_edge(self, u, v):
        self.adj[u].append(v)
        self.adj[v].append(u)
        self.edge_count += 1

    def is_valid(self):
        odd = 0
        for i in range(self.n):
            if len(self.adj[i]) % 2 != 0:
                odd += 1
        return odd == 0 or odd == 2

    def get_euler_path(self):
        if not self.is_valid():
            return None

        start = 0
        for i in range(self.n):
            if len(self.adj[i]) % 2 == 1:
                start = i
                break
            if len(self.adj[i]) > 0:
                start = i

        stack = [start]
        path = []

        local_adj = {u: self.adj[u][:] for u in self.adj}

        while stack:
            u = stack[-1]
            if u in local_adj and local_adj[u]:
                v = local_adj[u].pop()
                local_adj[v].remove(u)
                stack.append(v)
            else:
                path.append(stack.pop())

        if len(path) != self.edge_count + 1:
            return None

        return path[::-1]
```

4.9. Tree Isomorphism.

```
from collections import deque

def bfs(u, adj, n):
    vis = [False] * n
    pre = [-1] * n
    q = deque()

    q.append(u)
    vis[u] = True

    last = u

    while q:
        u = q.popleft()
        last = u

        for v in adj[u]:
            if not vis[v]:
                vis[v] = True
                pre[v] = u
                q.append(v)

    return last, pre

def tree_centers(r, adj, n):
    u, _ = bfs(r, adj, n)
    v, pre = bfs(u, adj, n)

    path = []
    while v != -1:
        path.append(v)
        v = pre[v]

    size = len(path)

    med = [path[size // 2]]
    if size % 2 == 0:
        med.append(path[size // 2 - 1])

    return med

def rootcode(u, adj, p, d, pr):
    children = []
    for v in adj[u]:
        if v != p:
            children.append(rootcode(v, adj, u, (d + 1) % len(pr), pr))

    children.sort()
```

```
    h = len(children) + 1
    for x in children:
        h = h * pr[d] + x

    return h

def treecode(root, adj, n, pr):
    c = tree_centers(root, adj, n)

    if len(c) == 1:
        return (rootcode(c[0], adj, -1, 0, pr) << 1) | 1
    else:
        return (rootcode(c[0], adj, -1, 0, pr) *
                rootcode(c[1], adj, -1, 0, pr)) << 1

def isomorphic(r1, adj1, r2, adj2, n1, n2, pr, rooted=False):
    if rooted:
        return rootcode(r1, adj1, -1, 0, pr) == rootcode(r2, adj2, -1,
↪  0, pr)
    return treecode(r1, adj1, n1, pr) == treecode(r2, adj2, n2, pr) --
```

4.10. Centroid Decomposition.

```
import sys
sys.setrecursionlimit(10**7)

INF = 10**9

class CentroidDecomposition:
    def __init__(self, n):
        self.n = n
        self.adj = [[] for _ in range(n)]

        self.LG = 20
        self.jmp = [[-1] * self.LG for _ in range(n)]
        self.path = [[INF] * self.LG for _ in range(n)]

        self.sz = [0] * n
        self.seph = [0] * n
        self.shortest = [INF] * n
        self.blocked = [False] * n

    def add_edge(self, a, b):
        self.adj[a].append(b)
        self.adj[b].append(a)

    def dfs(self, u, p):
        self.sz[u] = 1
        for v in self.adj[u]:
            if v != p and not self.blocked[v]:
                self.sz[u] += self.dfs(v, u)
        return self.sz[u]

    def find_centroid(self, u, p, n):
        for v in self.adj[u]:
            if v != p and not self.blocked[v] and self.sz[v] > n // 2:
                return self.find_centroid(v, u, n)
        return u

    def makepaths(self, sep, u, p, depth, h):
        self.jmp[u][h] = sep
        self.path[u][h] = depth

        for v in self.adj[u]:
            if v != p and not self.blocked[v]:
                self.makepaths(sep, v, u, depth + 1, h)

    def separate(self, h=0, u=0):
        self.dfs(u, -1)
        c = self.find_centroid(u, -1, self.sz[u])

        self.seph[c] = h
        self.makepaths(c, c, -1, 0, h)

        self.blocked[c] = True

        for v in self.adj[c]:
            if not self.blocked[v]:
                self.separate(h + 1, v)

    def paint(self, u):
        for h in range(self.seph[u] + 1):
            c = self.jmp[u][h]
            self.shortest[c] = min(self.shortest[c], self.path[u][h])

    def closest(self, u):
        ans = INF
        for h in range(self.seph[u] + 1):
            c = self.jmp[u][h]
            ans = min(ans, self.shortest[c] + self.path[u][h])
        return ans
```

5. Math I Algebra

6. Math II Combinatorics

6.0.1. *Lucas Theorem.*

```
_fact_cache = []
_last_p = -1

def lucas(n, k, p):
    if k < 0 or k > n:
        return 0
    if k == 0 or n == k:
        return 1

    global _fact_cache, _last_p
    if _last_p != p:
        _fact_cache = [1] * p
        for i in range(2, p):
            _fact_cache[i] = (_fact_cache[i - 1] * i) % p
        _last_p = p

    res_num = 1
    res_den = 1

    while n > 0 or k > 0:
        ni, ki = n % p, k % p
        if ki > ni:
            return 0
        res_num = (res_num * _fact_cache[ni]) % p
        res_den = (res_den * _fact_cache[ki] * _fact_cache[ni - ki]) %
↪  p
        n //= p
        k //= p
    return (res_num * pow(res_den, p - 2, p)) % p
# Input Format: print(lucas(n, k, p))
```

6.0.2. *Catalan Numbers.*

```
def catalan(n):
    if (n == 0 or n == 1):
        return 1

    dp = [0] * (n + 1)
    dp[0] = dp[1] = 1

    for i in range(2, n + 1):
        for j in range(i):
            dp[i] += dp[j] * dp[i-j-1]

    return dp[n]

# for i in range(10):
#     print(catalan(i))
```

6.0.3. *Kth Permutation.*

```
#fact = [1, 1, 2, 6, 24, 120, 720, 5040, 40320, 362880]

def findKthPermutation(n, k):
    nums = [str(i) for i in range(1, n + 1)]

    fact = [1] * n
    for i in range(1, n):
        fact[i] = fact[i - 1] * i

    k -= 1
    res = []

    for i in range(n - 1, -1, -1):
        idx = k // fact[i]
        k %= fact[i]

        res.append(nums.pop(idx))

    return ''.join(res)
```

6.0.4. *Factoradics.*

```
def factoradic(arr):
    n = len(arr)
    ft = FenwickTree(n)
    for i in range(1, n + 1):
        ft.add(i, 1)

    res = []
    for val in arr:
        bit_val = val + 1
        s = ft.query(bit_val - 1)
        ft.add(bit_val, -1)
        res.append(s)
    return res

def permute(fact, n):
    ft = FenwickTree(n)
    for i in range(1, n + 1):
        ft.add(i, 1)

    res = []
    for val in fact:
        idx = ft.find_kth(val)
        ft.add(idx, -1)
        res.append(idx - 1)
    return res
```

7. Math III Number Theory

7.0.1. *Gcd Subset Counter.*

```
def gcd_subset_count(arr):
    n = len(arr)
    mx = max(arr)

    f = [0] * (mx + 1)
    for x in arr:
        f[x] += 1

    gcnt = [0] * (mx + 1)

    for i in range(mx, 0, -1):
        add = 0

        for j in range(i, mx + 1, i):
            add += f[j]
```

```
    total = (1 << add) - 1  # 2^add - 1

    sub = 0
    for j in range(2 * i, mx + 1, i):
        sub += gcnt[j]

    gcnt[i] = total - sub

return gcnt
```

7.0.2. *Linear Diophantine.*

```
def gcd(a, b):
    if a == 0:
        return b
    return gcd(b % a, a)

def isPossible(a, b, c):
    g = gcd(a, b)

    return c % g == 0
```

7.0.3. *Chinese Remainder Theorem.*

```
def gcd_extended(a, b):
    if a == 0:
        return b, 0, 1
    gcd, x1, y1 = gcd_extended(b % a, a)
    x = y1 - (b // a) * x1
    y = x1
    return gcd, x, y

def find_min_x(num, rem):
    prod = 1
    for n in num:
        prod *= n

    result = 0
    for i in range(len(num)):
        prod_i = prod // num[i]
        _, inv_i, _ = gcd_extended(prod_i, num[i])
        result += rem[i] * prod_i * inv_i

    return result % prod
```

8. Math IV Numerical Methods

8.0.1. *Fast Square Testing.*

```
import math

class FastSquareTester:
    def __init__(self):
        self.M = 0
        self.init_is_square()

    def init_is_square(self):
        for i in range(64):
            self.M |= (1 << (i * i % 64))

    def is_square(self, x):
        if x < 0: return False
        if x == 0: return True

        if not (self.M & (1 << (x & 63))):
            return False

        c = (x & -x).bit_length() - 1
        if c & 1:
            return False

        temp_x = x >> c
        if (temp_x & 7) != 1:
            return False

        r = int(math.isqrt(temp_x))
        return r * r == temp_x

tester = FastSquareTester()
```

8.0.2. *Simpson Integration.*

```
def f(x):
    return x ** 2
def simpson_integration(a, b, n=1000000):
    if n % 2 != 0:
        n += 1

    h = (b - a) / n
    s = f(a) + f(b)

    for i in range(1, n):
        x = a + h * i
        if i % 2 == 1:
            s += 4 * f(x)
        else:
            s += 2 * f(x)

    return s * (h / 3)
```

9. Strings

9.0.1. *Longest Common Prefix.*

```
def build_lcp(s, sa):
    n = len(s)
    rank = [0] * n
    lcp = [0] * n

    for i in range(n):
        rank[sa[i]] = i

    k = 0
    for i in range(n):
        if rank[i] == 0:
            k = 0
            continue

        j = sa[rank[i] - 1]

        while i + k < n and j + k < n and s[i + k] == s[j + k]:
            k += 1

        lcp[rank[i]] = k

        if k > 0:
            k -= 1

    return lcp
```

9.0.2. *Hasher.*

```
class Hasher:
    def __init__(self, s, bases=[31, 37], mod=10 ** 9 + 7):
        self.bases = bases
        self.mod = mod
        self.n = len(s)
        self.num_hashes = len(bases)
        self.p_pow = [[1] * (self.n + 1) for _ in
↪   range(self.num_hashes)]
        self.h_ans = [[0] * (self.n + 1) for _ in
↪   range(self.num_hashes)]

        for i, b in enumerate(self.bases):
            for j in range(self.n):
                self.p_pow[i][j + 1] = (self.p_pow[i][j] * b) %
↪   self.mod
                self.h_ans[i][j + 1] = (self.h_ans[i][j] + s[j] *
↪   self.p_pow[i][j]) % self.mod

    def get_hash(self, l, r):
        return tuple((self.h_ans[i][r + 1] - self.h_ans[i][l]) %
↪   self.mod
                     for i in range(self.num_hashes))

    def are_equal(self, l1, r1, l2, r2):
        if (r1 - l1) != (r2 - l2): return False

        h1 = self.get_hash(l1, r1)
        h2 = self.get_hash(l2, r2)

        return all((h1[i] * self.p_pow[i][l2]) % self.mod ==
                   (h2[i] * self.p_pow[i][l1]) % self.mod
                   for i in range(self.num_hashes))
```

9.0.3. *Z Algorithm.*

9.0.4. *Aho Corasick Trie.*

```
from collections import deque
import random
import string

class Node:
    def __init__(self):
        self.next = {}
        self.fail = None
        self.count = 0

    def add(self, s):
        node = self
        for c in s:
            if c not in node.next:
                node.next[c] = Node()
            node = node.next[c]
        node.count += 1

    def prepare(self):
        root = self
        q = deque()

        root.fail = root

        for child in root.next.values():
            child.fail = root
            q.append(child)

        while q:
            head = q.popleft()

            for c, nxt in head.next.items():
                f = head.fail

                while f != root and c not in f.next:
                    f = f.fail

                nxt.fail = f.next[c] if c in f.next else root

                nxt.count += nxt.fail.count

                q.append(nxt)

    def search(self, s):
        root = self
```

```
        p = self
        ans = 0

    for c in s:
        while p != root and c not in p.next:
            p = p.fail

        if c in p.next:
            p = p.next[c]
            ans += p.count

    return ans
```

9.0.5. *Knuth Morris Pratt.*

```
def build_kmp(f):
    n = len(f)
    par = [0] * (n + 1)

    par[0] = -1
    if n > 0:
        par[1] = 0

    i, j = 2, 0

    while i <= n:
        if f[i - 1] == f[j]:
            j += 1
            par[i] = j
            i += 1
        elif j > 0:
            j = par[j]
        else:
            par[i] = 0
            i += 1

    return par


def kmp(s, f):
    par = build_kmp(f)

    i = 0
    j = 0
    ans = []

    n, m = len(s), len(f)

    while i + j < n:
        if s[i + j] == f[j]:
            j += 1
            if j == m:
                ans.append(i)
                i += j - par[j]
                if j > 0:
                    j = par[j]
        else:
            i += j - par[j]
            if j > 0:
                j = par[j]

    return ans
```

9.0.6. *Trie.*

```
class Node:
    def __init__(self):
        self.children = {}
        self.prefixes = 0
        self.words = 0

class Trie:
    def __init__(self):
        self.root = Node()

    def insert(self, seq):
        cur = self.root

        for i in range(len(seq) + 1):
            cur.prefixes += 1

            if i == len(seq):
                cur.words += 1
                break

            head = seq[i]

            if head not in cur.children:
                cur.children[head] = Node()

            cur = cur.children[head]

    def countMatches(self, seq):
        cur = self.root

        for c in seq:
            if c not in cur.children:
                return 0
            cur = cur.children[c]

        return cur.words

    def countPrefixes(self, seq):
        cur = self.root

        for c in seq:
            if c not in cur.children:
                return 0
            cur = cur.children[c]

        return cur.prefixes
```

9.0.7. *Suffix Array.*

```
class SuffixArray:
    def __init__(self):
        self.n = 0
        self.suffix = []
        self.equiv = []
        self.equiv_pair = []
        self.s = ""

    def build(self, s):
        if not s.endswith('$'):
            s += '$'

        self.s = s
        self.n = len(s)

        self.suffix = list(range(self.n))
        self.equiv = [0] * self.n
        self.equiv_pair = [(0, 0)] * self.n

        self.suffix.sort(key=lambda i: s[i])

        cls = 0
        for i in range(self.n):
            if i == 0 or s[self.suffix[i]] != s[self.suffix[i - 1]]:
                cls += 1
            self.equiv[self.suffix[i]] = cls

        k = 1
        while k < self.n:
            for i in range(self.n):
                self.equiv_pair[i] = (
                    self.equiv[i],
                    self.equiv[(i + k) % self.n]
                )

            self.suffix.sort(key=lambda i: self.equiv_pair[i])

            cls = 0
            new_equiv = [0] * self.n

            for i in range(self.n):
                if i == 0 or self.equiv_pair[self.suffix[i]] !=
↪  self.equiv_pair[self.suffix[i - 1]]:
                    cls += 1
                new_equiv[self.suffix[i]] = cls

            self.equiv = new_equiv
            k <<= 1

    def _cmp(self, start, pattern):
        s = self.s
        n = len(s)

        i = start
        j = 0

        while i < n and j < len(pattern):
            if s[i] != pattern[j]:
                return ord(s[i]) - ord(pattern[j])
            i += 1
            j += 1

        if j == len(pattern):
            return 0
        return -1

    def lower_bound(self, pattern):
        l, r = 0, self.n - 1
        res = self.n

        while l <= r:
            m = (l + r) // 2
            if self._cmp(self.suffix[m], pattern) >= 0:
                res = m
                r = m - 1
            else:
                l = m + 1

        return res

    def upper_bound(self, pattern):
        l, r = 0, self.n - 1
        res = self.n

        while l <= r:
            m = (l + r) // 2
            if self._cmp(self.suffix[m], pattern) > 0:
                res = m
                r = m - 1
            else:
                l = m + 1

        return res

    def count_occurrences(self, pattern):
        L = self.lower_bound(pattern)
        R = self.upper_bound(pattern)
        return max(0, R - L)
```

9.0.8. *Booth Min String Rotation.*

```
def booth(s: str) -> int:
    s = s + s
    n = len(s)

    f = [-1] * n
    k = 0

    for j in range(1, n):
        i = f[j - k - 1]

        while i != -1 and s[j] != s[k + i + 1]:
            if s[j] < s[k + i + 1]:
                k = j - i - 1
            i = f[i]

        if i == -1 and s[j] != s[k]:
            if s[j] < s[k]:
                k = j
            f[j - k] = -1
        else:
            f[j - k] = i + 1

    return k
```

10. Other Algorithms

10.0.1. *Longest Increasing Subsequence.*

```
def lis(arr):
    if not arr:
        return []

    n = len(arr)
    seq = []
    back = [0] * n

    for i in range(n):
        lo, hi = 0, len(seq)
        while lo < hi:
            mid = (lo + hi) // 2
            if arr[seq[mid]] < arr[i]:
                lo = mid + 1
            else:
                hi = mid

        res = lo
        if res < len(seq):
            seq[res] = i
        else:
            seq.append(i)
        back[i] = -1 if res == 0 else seq[res - 1]

    ans = []
    at = seq[-1]
    while at != -1:
        ans.append(at)
        at = back[at]

    return ans[::-1]
```

10.0.2. *Cycle Find.*

```
def find_cycle(x0, f):
    t = f(x0)
    h = f(f(x0))

    while t != h:
        t = f(t)
        h = f(f(h))

    mu = 0
    h = x0
    while t != h:
        t = f(t)
        h = f(h)
        mu += 1

    lam = 1
    h = f(t)
    while t != h:
        h = f(h)
        lam += 1

    return mu, lam
```

10.0.3. *2Sat.*

```
class TwoSAT:
    def __init__(self, n):
        self.n = n
        self.N = 2 * n
        self.adj = [[] for _ in range(self.N)]

    def var(self, x):
        return x << 1

    def neg(self, x):
        return x ^ 1

    def add_imp(self, x, y):
        self.adj[x].append(y)

    def add_or(self, x, y):
        self.add_imp(self.neg(x), y)
        self.add_imp(self.neg(y), x)

    def sat(self):
        n = self.N
        adj = self.adj

        index = 0
        stack = []
        onstack = [False] * n
        ids = [-1] * n
        low = [0] * n
        comp = [-1] * n
        self.time = 0
        self.comp_id = 0

        def dfs(u):
            nonlocal index

            ids[u] = low[u] = index
            index += 1
            stack.append(u)
            onstack[u] = True

            for v in adj[u]:
                if ids[v] == -1:
                    dfs(v)
                    low[u] = min(low[u], low[v])
                elif onstack[v]:
                    low[u] = min(low[u], ids[v])

            if low[u] == ids[u]:
                while True:
                    v = stack.pop()
                    onstack[v] = False
                    comp[v] = self.comp_id
                    if v == u:
                        break
                self.comp_id += 1

        for i in range(n):
            if ids[i] == -1:
                dfs(i)

        for i in range(0, n, 2):
            if comp[i] == comp[i ^ 1]:
                return False

        return True
```

10.0.4. *Dpll.*

```
class SAT:
    def __init__(self):
        self.clauses = []
        self.n = 0

    def var(self):
        self.n += 1
        return self.n

    def clause(self, c):
        self.clauses.append(c)

    def clause_sat(self, clause, assign):
        unknown = False

        for x in clause:
            v = abs(x)
            val = assign[v]

            if x > 0 and val == 1:
                return True
            if x < 0 and val == 0:
                return True

            if val == -1:
                unknown = True

        return False if not unknown else None

    def propagate(self, assign):
        changed = True

        while changed:
            changed = False

            for clause in self.clauses:
                sat = False
                unassigned = []

                for x in clause:
                    v = abs(x)

                    if x > 0 and assign[v] == 1:
                        sat = True
                        break
                    if x < 0 and assign[v] == 0:
                        sat = True
                        break

                    if assign[v] == -1:
                        unassigned.append(x)

                if sat:
                    continue

                if len(unassigned) == 0:
                    return False  # contradiction

                if len(unassigned) == 1:
                    x = unassigned[0]
```

```
------------------- v = abs(x) ----------------------------------------
------------------- val = 1 if x > 0 else 0 ---------------------------
 ---------------------------------------------------------------------
------------------- if assign[v] != -1 and assign[v] != val: ----------
----------------------- return False ------------------------------------
 ---------------------------------------------------------------------
------------------- if assign[v] == -1: -------------------------------
----------------------- assign[v] = val ---------------------------------
----------------------- changed = True ----------------------------------
 ---------------------------------------------------------------------
------- return True ---------------------------------------------------
 ---------------------------------------------------------------------
--- def solve_dfs(self, assign, idx=1): -------------------------------
------- if idx > self.n: ----------------------------------------------
----------- return True -------------------------------------------------
 ---------------------------------------------------------------------
------- if assign[idx] != -1: -----------------------------------------
----------- return self.solve_dfs(assign, idx + 1) ----------------------
 ---------------------------------------------------------------------
------- for val in [0, 1]: --------------------------------------------
----------- new_assign = assign[:] --------------------------------------
----------- new_assign[idx] = val ---------------------------------------
 ---------------------------------------------------------------------
----------- if self.propagate(new_assign): ------------------------------
--------------- if self.solve_dfs(new_assign, idx + 1): -----------------
------------------- return True -------------------------------------------
 ---------------------------------------------------------------------
------- return False --------------------------------------------------
 ---------------------------------------------------------------------
--- def solve(self): --------------------------------------------------
------- assign = [-1] * (self.n + 1) ----------------------------------
 ---------------------------------------------------------------------
------- if not self.propagate(assign): --------------------------------
----------- return False ------------------------------------------------
 ---------------------------------------------------------------------
------- return self.solve_dfs(assign) ---------------------------------
 ---------------------------------------------------------------------
--- def get_value(self, x): -------------------------------------------
------- return self.assign[x] == 1 ------------------------------------
```

10.0.5. *Stable Marriage.*

```
from collections import deque -------------------------------------------
 ---------------------------------------------------------------------
def stable_marriage(n, m_pref, w_pref): -------------------------------
--- w_rank = [[0] * n for _ in range(n)] ------------------------------
 ---------------------------------------------------------------------
--- for w in range(n): ------------------------------------------------
------- for i, man in enumerate(w_pref[w]): ---------------------------
----------- w_rank[w][man] = i ------------------------------------------
 ---------------------------------------------------------------------
--- q = deque(range(n)) -----------------------------------------------
 ---------------------------------------------------------------------
--- at = [0] * n ------------------------------------------------------
 ---------------------------------------------------------------------
--- eng = [-1] * n ----------------------------------------------------
 ---------------------------------------------------------------------
--- res = [-1] * n ----------------------------------------------------
 ---------------------------------------------------------------------
--- while q: ----------------------------------------------------------
------- m = q.popleft() -----------------------------------------------
 ---------------------------------------------------------------------
------- while at[m] < n: ----------------------------------------------
----------- w = m_pref[m][at[m]] ----------------------------------------
----------- at[m] += 1 --------------------------------------------------
 ---------------------------------------------------------------------
----------- if eng[w] == -1: --------------------------------------------
--------------- eng[w] = m --------------------------------------------
--------------- res[m] = w --------------------------------------------
--------------- break -------------------------------------------------
 ---------------------------------------------------------------------
----------- if w_rank[w][m] < w_rank[w][eng[w]]: ----------------------
--------------- q.append(eng[w]) --------------------------------------
--------------- eng[w] = m --------------------------------------------
--------------- res[m] = w --------------------------------------------
--------------- break -------------------------------------------------
 ---------------------------------------------------------------------
--- return res --------------------------------------------------------
```

10.0.6. *Dates.*

```
def c_div(a, b): --------------------------------------------------------
--- return int(a / b) -------------------------------------------------
 ---------------------------------------------------------------------
def date_to_int(y, m, d): -----------------------------------------------
--- k = c_div(m - 14, 12) ---------------------------------------------
 ---------------------------------------------------------------------
--- return ( ----------------------------------------------------------
------- 1461 * (y + 4800 + k) // 4 ------------------------------------
------- + 367 * (m - 2 - k * 12) // 12 --------------------------------
------- - 3 * ((y + 4900 + k) // 100) // 4 ----------------------------
------- + d - 32075 ---------------------------------------------------
--- ) -----------------------------------------------------------------
 ---------------------------------------------------------------------
 ---------------------------------------------------------------------
def int_to_day(jd): -----------------------------------------------------
--- return jd % 7 -----------------------------------------------------
 ---------------------------------------------------------------------
 ---------------------------------------------------------------------
def int_to_date(jd): ----------------------------------------------------
--- x = jd + 68569 ----------------------------------------------------
--- n = 4 * x // 146097 -----------------------------------------------
--- x -= (146097 * n + 3) // 4 ----------------------------------------
 ---------------------------------------------------------------------
--- i = (4000 * (x + 1)) // 1461001 -----------------------------------
--- x -= 1461 * i // 4 - 31 -------------------------------------------
 ---------------------------------------------------------------------
--- j = 80 * x // 2447 ------------------------------------------------
--- d = x - 2447 * j // 80 --------------------------------------------
 ---------------------------------------------------------------------
--- x = j // 11 -------------------------------------------------------
--- m = j + 2 - 12 * x ------------------------------------------------
--- y = 100 * (n - 49) + i + x ----------------------------------------
 ---------------------------------------------------------------------
--- return y, m, d ----------------------------------------------------
```