University of the Philippines - Baguio

Archie Junio's Reference Notebook

30/04/2026

Contents

1. Data Structures 1
1.1. Fenwick Tree 1
1.2. Segment Tree 1
1.3. Union Find 1
1.4. 2D Sparse Table 1
1.5. Leq Counter 1
1.5.1. Leq Counter Array 1
1.5.2. Leq Counter Map 2
1.6. Misof Tree 2
1.7. Mo Algorithm 2
1.8. Ordered Statistics Tree 2
1.9. Splay Tree 3
1.10. Implicit Treap 4
1.11. Unique Counter 4
2. Dynamic Programming 4
2.1. Lichao Tree 4
2.2. Divide And Conquer 5
3. Geometry 5
3.1. Angles And Rotations 5
3.2. Distances 5
3.3. Intersections 5
3.3.1. Circle Line Intersection 5
3.3.2. Circle Circle Intersection 5
3.3.3. Line Intersect 5
3.4. Closest Pair 5
3.5. Polygon Centroid 6
3.6. Convex Hull 6
3.6.1. Convex Hull 6
3.6.2. Convex Hull 3D 6
3.7. Areas 6
3.7.1. Triangle Area 6
3.7.2. Polygon Area 6
3.8. Dot Cross 6
3.9. Line Sweep Closest Pair 6
3.10. Point Projection 6
3.11. Great Circle Distance 7
3.12. Point In Polygon 7
3.13. Cut Polygon By Line 7
3.14. Triangle Centers 7
3.15. Convex Polygon Intersection 8
3.16. Pick Theorem Lattice 8
3.17. Minimum Enclosing Circle 8
3.18. Shamos Algorithm 8
3.19. Kd Tree 9
4. Graphs 9
4.1. Max Flow 9
4.1.1. Dinic 9
4.1.2. Edmonds Karp 9
4.1.3. Bipartite Matching 9
4.2. Shortest Path 10
4.2.1. Dijkstra 10
4.2.2. Bellman Ford 10
4.3. Minimum Spanning Tree 10
4.3.1. Kruskal Min Spanning Tree 10
4.3.2. Prim Min Spanning Tree 10
4.4. Least Common Ancestor 10
4.4.1. Binary Lifting Lca 10
4.4.2. Euler Lca 11
4.4.3. Tarjan Lca 11
4.5. Minimum Mean Weight Cycle 11
4.6. Strongly Connected Components 11
4.7. Heavy Light Decomposition 11
4.8. Euler Path/Cycle 12
4.8.1. Directed Euler 12
4.8.2. Undirected Euler 12
4.9. Tree Isomorphism 13
4.10. Centroid Decomposition 13
4.11. Minimum Arborescence 13
4.12. Biconnected Components 14
4.13. Blossom 14
5. Math I Algebra 14
5.0.1. Generating Function Manager 14
5.0.2. Fast Fourier Transform 15
5.0.3. Fft Polynomial Multiplication 15
5.0.4. Number Theoretic Transform 15
5.0.5. Polynomial Long Division 16
5.0.6. Matrix Multiplication 16
5.0.7. Matrix Power 17
5.0.8. Gauss Jordan Matrix Determinant 17
6. Math II Combinatorics 17
6.0.1. Lucas Theorem 17
6.0.2. Catalan Numbers 17
6.0.3. Kth Permutation 17
6.0.4. Factoradics 17
7. Math III Number Theory 17
7.0.1. Gcd Subset Counter 17
7.0.2. Linear Diophantine 18
7.0.3. Chinese Remainder Theorem 18
7.0.4. Euler Totient 18
7.0.5. Extended Euclidean Algorithm 18
7.0.6. Modular Exponentiation 18
7.0.7. Mod Inverse 18
7.0.8. Modulo Solver 18
7.0.9. Primitive Root 18
7.0.10. Josephus 18
8. Math IV Numerical Methods 18
8.0.1. Fast Square Testing 18
8.0.2. Simpson Integration 19
9. Strings 19
9.1. Longest Common Prefix 19
9.2. Hasher 19
9.3. Z Algorithm 19
9.4. Aho Corasick Trie 19
9.5. Palindromes 19
9.5.1. Palindromic Tree 19
9.5.2. Eertree 20
9.6. Knuth Morris Pratt 20
9.7. Trie 20
9.8. Suffix Array 21
9.9. Booth Min String Rotation 21
10. Other Algorithms 21
10.1. Longest Increasing Subsequence 21
10.2. Cycle Find 21
10.3. 2Sat 21
10.4. Dpll 22
10.5. Stable Marriage 22
10.6. Dates 22
10.7. Simulated Annealing 23
10.8. Simplex 23
10.9. Fast Input Reading 23
10.10. Bit Hacks 23

1. Data Structures

1.1. Fenwick Tree.

```
class Fenwick: ----------------------------------------------------------
--- def __init__(self, arr): ------------------------------------------
------- self.n = len(arr) -------------------------------------------
------- self.ar = [0] * self.n --------------------------------------
------- for i in range(self.n): -------------------------------------
----------- self.ar[i] += arr[i] ----------------------------------------
----------- j = i | (i + 1) ---------------------------------------------
----------- if j < self.n: ----------------------------------------------
--------------- self.ar[j] += self.ar[i] ------------------------------
 ------------------------------------------------------------------------
--- def sum(self, i): -------------------------------------------------
------- res = 0 -----------------------------------------------------
```

```
        while i >= 0:
            res += self.ar[i]
            i = (i & (i + 1)) - 1
        return res

    def range_sum(self, i, j):
        return self.sum(j) - (self.sum(i - 1) if i > 0 else 0)

    def add(self, i, val):
        while i < self.n:
            self.ar[i] += val
            i |= i + 1

    def get(self, i):
        res = self.ar[i]
        if i > 0:
            lca = (i & (i + 1)) - 1
            i -= 1
            while i != lca:
                res -= self.ar[i]
                i = (i & (i + 1)) - 1
        return res

    def set(self, i, val):
        self.add(i, val - self.get(i))

    def range_add(self, l, r, val):
        self.add(l, val)
        if r + 1 < self.n:
            self.add(r + 1, -val)

    def point_query(self, i):
        return self.sum(i)
```

1.2. Segment Tree.

```
class SegmentTree:
    def __init__(self, data):
        self.n = len(data)
        self.tree = [0] * (2 * self.n)
        for i in range(self.n):
            self.tree[self.n + i] = data[i]
        for i in range(self.n - 1, 0, -1):
            self.tree[i] = self.tree[i << 1] + self.tree[i << 1 | 1]

    def update(self, p, value):
        p += self.n
        self.tree[p] = value
        while p > 1:
            self.tree[p >> 1] = self.tree[p] + self.tree[p ^ 1]
            p >>= 1

    def query(self, l, r):
        res = 0
        l += self.n
        r += self.n
        while l < r:
            if l & 1:
                res += self.tree[l]
                l += 1
            if r & 1:
                r -= 1
                res += self.tree[r]
            l >>= 1
            r >>= 1
        return res
```

1.3. Union Find.

```
class DSU:
    def __init__(self, n):
        self.parent = list(range(n))
        self.size = [1] * n

    def find(self, i):
        if self.parent[i] == i:
            return i
        self.parent[i] = self.find(self.parent[i])
        return self.parent[i]

    def union(self, i, j):
        root_i = self.find(i)
        root_j = self.find(j)

        if root_i != root_j:
            if self.size[root_i] < self.size[root_j]:
                root_i, root_j = root_j, root_i
            self.parent[root_j] = root_i
            self.size[root_i] += self.size[root_j]
            return True
        return False

    def get_size(self, i):
        return self.size[self.find(i)]
```

1.4. 2D Sparse Table.

```
import math

class SparseTable2D:
    def __init__(self, A):
        self.A = A
        self.n = len(A)
        self.m = len(A[0])

        self.LOGN = int(math.log2(self.n)) + 1
        self.LOGM = int(math.log2(self.m)) + 1

        self.lg = [0] * (max(self.n, self.m) + 1)
        for i in range(2, len(self.lg)):
            self.lg[i] = self.lg[i // 2] + 1

        self.st = [[[[0] * self.m for _ in range(self.n)]
                   for _ in range(self.LOGM)]
                  for _ in range(self.LOGN)]

        self.build()

    def build(self):
        for i in range(self.n):
            for j in range(self.m):
                self.st[0][0][i][j] = self.A[i][j]

        for bj in range(1, self.LOGM):
            for i in range(self.n):
                for j in range(self.m - (1 << bj) + 1):
                    self.st[0][bj][i][j] = max(
                        self.st[0][bj - 1][i][j],
                        self.st[0][bj - 1][i][j + (1 << (bj - 1))]
                    )

        for bi in range(1, self.LOGN):
            for i in range(self.n - (1 << bi) + 1):
                for j in range(self.m):
                    self.st[bi][0][i][j] = max(
                        self.st[bi - 1][0][i][j],
                        self.st[bi - 1][0][i + (1 << (bi - 1))][j]
                    )

        for bi in range(1, self.LOGN):
            for bj in range(1, self.LOGM):
                for i in range(self.n - (1 << bi) + 1):
                    for j in range(self.m - (1 << bj) + 1):
                        self.st[bi][bj][i][j] = max(
                            self.st[bi - 1][bj - 1][i][j],
                            self.st[bi - 1][bj - 1][i + (1 << (bi - 1))][j],
                            self.st[bi - 1][bj - 1][i][j + (1 << (bj - 1))],
                            self.st[bi - 1][bj - 1][i + (1 << (bi - 1))][j + (1 << (bj - 1))]
                        )

    def query(self, x1, y1, x2, y2):
        kx = self.lg[x2 - x1 + 1]
        ky = self.lg[y2 - y1 + 1]

        return max(
            self.st[kx][ky][x1][y1],
            self.st[kx][ky][x2 - (1 << kx) + 1][y1],
            self.st[kx][ky][x1][y2 - (1 << ky) + 1],
            self.st[kx][ky][x2 - (1 << kx) + 1][y2 - (1 << ky) + 1]
        )
# Input Format: st = SparseTable2D(grid)
#               print(st.query(1, 1, 2, 2))
```

1.5. Leq Counter.

1.5.1. *Leq Counter Array.*

```
def merge(left, right):
    i = j = 0
    res = []
    while i < len(left) and j < len(right):
        if left[i] <= right[j]:
            res.append(left[i])
            i += 1
        else:
            res.append(right[j])
            j += 1
    res.extend(left[i:])
    res.extend(right[j:])
    return res
def merge_sort(arr):
    if len(arr) <= 1:
        return arr
    mid = len(arr) // 2
    left = merge_sort(arr[:mid])
    right = merge_sort(arr[mid:])
    return merge(left, right)
```

1.5.2. *Leq Counter Map.*

```
import bisect

class MergeSortTree:
    def __init__(self, arr):
        self.n = len(arr)
        self.size = 1
        while self.size < self.n:
            self.size <<= 1

        self.tree = [[] for _ in range(2 * self.size)]

        for i in range(self.n):
            self.tree[self.size + i] = [arr[i]]

        for i in range(self.size - 1, 0, -1):
            self.tree[i] = sorted(self.tree[i << 1] + self.tree[i << 1 | 1])

    def query(self, l, r, x):
        l += self.size
        r += self.size

        ans = 0
```

```
------- while l < r:
----------- if l & 1:
--------------- ans += bisect.bisect_right(self.tree[l], x)
--------------- l += 1
----------- if r & 1:
--------------- r -= 1
--------------- ans += bisect.bisect_right(self.tree[r], x)
----------- l >>= 1
----------- r >>= 1

------- return ans
```

1.6. Misof Tree.

```
BITS = 15
MAXV = 1 << BITS

class MisofTree:
--- def __init__(self):
------- self.cnt = [[0, 0] for _ in range(1 << (BITS + 1))]
------- self.root = 1
------- self.nodes = 2

--- def _new_node(self):
------- idx = self.nodes
------- self.nodes += 1
------- if idx >= len(self.cnt):
----------- self.cnt.append([0, 0])
------- return idx

--- def insert(self, x):
------- node = self.root
------- for i in reversed(range(BITS)):
----------- b = (x >> i) & 1
----------- self.cnt[node][b] += 1

----------- nxt = self.cnt[node].__len__()
----------- if not hasattr(self, "child"):
--------------- self.child = {}

----------- if (node, b) not in self.child:
--------------- self.child[(node, b)] = self._new_node()

----------- node = self.child[(node, b)]

--- def erase(self, x):
------- node = self.root
------- path = []

------- for i in reversed(range(BITS)):
----------- b = (x >> i) & 1
----------- path.append((node, b))
----------- node = self.child[(node, b)]

------- for node, b in path:
----------- self.cnt[node][b] -= 1

--- def kth(self, k):
------- node = self.root
------- res = 0

------- for i in reversed(range(BITS)):
----------- left = self.cnt[node][0]

----------- if k < left:
--------------- node = self.child.get((node, 0), node)
----------- else:
--------------- k -= left
--------------- res |= (1 << i)
--------------- node = self.child.get((node, 1), node)

------- return res
```

1.7. Mo Algorithm.

```
from collections import defaultdict

LOGN = 21

def hilbert_order(x, y, pow, rotate):
--- if pow == 0:
------- return 0
--- hpow = 1 << (pow - 1)
--- if x < hpow:
------- if y < hpow:
----------- seg = 0
------- else:
----------- seg = 3
--- else:
------- if y < hpow:
----------- seg = 1
------- else:
----------- seg = 2
--- seg = (seg + rotate) & 3
--- rotate_delta = [3, 0, 0, 1]
--- nx = x & (x ^ hpow)
--- ny = y & (y ^ hpow)
--- nrot = (rotate + rotate_delta[seg]) & 3
--- sub_sq_size = 1 << (2 * pow - 2)
--- ans = seg * sub_sq_size
--- add = hilbert_order(nx, ny, pow - 1, nrot)
--- if seg == 1 or seg == 2:
------- ans += add
--- else:
------- ans += sub_sq_size - add - 1
--- return ans

class Query:
--- def __init__(self, idx, l, r):
------- self.id = idx
------- self.l = l
------- self.r = r
------- self.ord = hilbert_order(l, r, LOGN, 0)

--- def __lt__(self, other):
------- return self.ord < other.ord

def mo_algorithm(arr, queries):
--- queries.sort()

--- freq = defaultdict(int)
--- distinct = 0

--- def add(i):
------- nonlocal distinct
------- x = arr[i]
------- freq[x] += 1
------- if freq[x] == 1:
----------- distinct += 1

--- def remove(i):
------- nonlocal distinct
------- x = arr[i]
------- freq[x] -= 1
------- if freq[x] == 0:
----------- distinct -= 1
--- ans = [0] * len(queries)
--- l = 0
--- r = -1
--- for q in queries:
------- while r < q.r:
----------- r += 1
----------- add(r)
------- while r > q.r:
----------- remove(r)
----------- r -= 1
------- while l > q.l:
----------- l -= 1
----------- add(l)
------- while l < q.l:
----------- remove(l)
----------- l += 1
------- ans[q.id] = distinct
--- return ans
```

1.8. Ordered Statistics Tree.

```
class OrderedSet:
--- def __init__(self):
------- self.root = None

--- def insert(self, x):
------- if self.contains(x):
----------- return
------- l, r = split(self.root, x)
------- self.root = merge(merge(l, Node(x)), r)

--- def erase(self, x):
------- self.root = self._erase(self.root, x)

--- def _erase(self, t, x):
------- if not t:
----------- return None
------- if t.key == x:
----------- return merge(t.left, t.right)
------- elif x < t.key:
----------- t.left = self._erase(t.left, x)
------- else:
----------- t.right = self._erase(t.right, x)
------- pull(t)
------- return t

--- def contains(self, x):
------- t = self.root
------- while t:
----------- if t.key == x:
--------------- return True
----------- t = t.left if x < t.key else t.right
------- return False

--- def order_of_key(self, x):
------- t = self.root
------- res = 0
------- while t:
----------- if x <= t.key:
--------------- t = t.left
----------- else:
--------------- res += 1 + size(t.left)
--------------- t = t.right
------- return res

--- def find_by_order(self, k):
------- t = self.root
------- while t:
----------- left_sz = size(t.left)
----------- if k < left_sz:
--------------- t = t.left
----------- elif k == left_sz:
--------------- return t.key
----------- else:
--------------- k -= left_sz + 1
--------------- t = t.right
------- return None
```

1.9. Splay Tree.

```
class SplayTree:
    def __init__(self, arr=None):
        self.root = None
        if arr:
            self.root = self.build(arr, 0, len(arr))
    def build(self, arr, l, r):
        if l >= r:
            return None
        m = (l + r) // 2
        node = Node(arr[m])
        node.left = self.build(arr, l, m)
        node.right = self.build(arr, m + 1, r)
        if node.left:
            node.left.parent = node
        if node.right:
            node.right.parent = node
        self.pull(node)
        return node
    def pull(self, x):
        x.size = 1
        if x.left:
            x.size += x.left.size
        if x.right:
            x.size += x.right.size
    def push(self, x):
        if x and x.rev:
            x.left, x.right = x.right, x.left
            if x.left:
                x.left.rev ^= True
            if x.right:
                x.right.rev ^= True
            x.rev = False
    def rotate(self, x):
        p = x.parent
        g = p.parent

        if p.left == x:
            b = x.right
            x.right = p
            p.left = b
        else:
            b = x.left
            x.left = p
            p.right = b
        if b:
            b.parent = p
        x.parent = g
        if g:
            if g.left == p:
                g.left = x
            else:
                g.right = x
        p.parent = x
        self.pull(p)
        self.pull(x)
    def splay(self, x):
        if not x:
            return None

        while x.parent:
            p = x.parent
            g = p.parent

            if g:
                self.push(g)
            self.push(p)
            self.push(x)

            if not g:
                self.rotate(x)
            elif (g.left == p) == (p.left == x):
                self.rotate(p)
                self.rotate(x)
            else:
                self.rotate(x)
                self.rotate(x)

        self.root = x
        return x

    def kth(self, k):
        x = self.root
        while x:
            self.push(x)
            lsize = x.left.size if x.left else 0

            if k < lsize:
                x = x.left
            elif k > lsize:
                k -= lsize + 1
                x = x.right
            else:
                return self.splay(x)
        return None

    def split(self, k):
        if k == 0:
            r = self.root
            self.root = None
            return None, r

        x = self.kth(k - 1)

        right = x.right
        if right:
            right.parent = None

        x.right = None
        self.pull(x)

        return x, right

    def merge(self, left, right):
        if not left:
            return right
        if not right:
            return left

        x = left
        while True:
            self.push(x)
            if not x.right:
                break
            x = x.right

        while x.parent:
            if x.parent.parent:
                if (x.parent.left == x) == (x.parent.parent.left ==
↪   x.parent):
                    self.rotate(x.parent)
                else:
                    self.rotate(x)
            self.rotate(x)

        x.right = right
        right.parent = x
        self.pull(x)

        return x

    def insert(self, k, val):
        left, right = self.split(k)
        node = Node(val)
        merged = self.merge(left, node)
        self.root = self.merge(merged, right)

    def _split_root(self, root, k):
        if not root:
            return None, None
        self.root = root
        return self.split(k)

    def erase(self, k):
        left, temp = self.split(k)
        mid, right = self._split_root(temp, 1)
        self.root = self.merge(left, right)

    def reverse(self, l, r):
        left, temp = self.split(l)
        mid, right = self._split_root(temp, r - l + 1)

        if mid:
            mid.rev ^= True

        merged = self.merge(left, mid)
        self.root = self.merge(merged, right)

    def assign(self, k, val):
        node = self.kth(k)
        node.value = val
        self.pull(node)

    def inorder(self):
        res = []
        stack = []
        x = self.root

        while stack or x:
            while x:
                self.push(x)
                stack.append(x)
                x = x.left

            x = stack.pop()
            res.append(x.value)
            x = x.right

        return res

    def check_no_cycle(self):
        seen = set()

        def dfs(x):
            if not x:
                return
            if id(x) in seen:
                raise Exception("Cycle detected")
            seen.add(id(x))
            dfs(x.left)
            dfs(x.right)

        dfs(self.root)
```

1.10. Implicit Treap.

```
class Node:
    __slots__ = ("val", "sum", "delta", "prio", "size", "l", "r")

    def __init__(self, val):
        self.val = val
        self.sum = val
        self.delta = 0
        self.prio = random.randint(1, 1 << 30)
        self.size = 1
        self.l = None
```

```
------- self.r = None
def sz(v):
--- return v.size if v else 0
def sm(v):
--- return v.sum if v else 0
def apply(v, d):
--- if not v:
------- return
--- v.delta += d
--- v.val += d
--- v.sum += d * sz(v)
def push(v):
--- if not v or v.delta == 0:
------- return
--- apply(v.l, v.delta)
--- apply(v.r, v.delta)
--- v.delta = 0
def pull(v):
--- if not v:
------- return
--- v.size = 1 + sz(v.l) + sz(v.r)
--- v.sum = v.val + sm(v.l) + sm(v.r)
def split(v, k):
--- if not v:
------- return (None, None)
--- push(v)
--- if sz(v.l) >= k:
------- l, v.l = split(v.l, k)
------- pull(v)
------- return (l, v)
--- else:
------- v.r, r = split(v.r, k - sz(v.l) - 1)
------- pull(v)
------- return (v, r)
def merge(l, r):
--- if not l or not r:
------- return l or r
--- if l.prio > r.prio:
------- push(l)
------- l.r = merge(l.r, r)
------- pull(l)
------- return l
--- else:
------- push(r)
------- r.l = merge(l, r.l)
------- pull(r)
------- return r
class Treap:
--- def __init__(self):
------- self.root = None
--- def size(self):
------- return sz(self.root)
--- def insert(self, pos, val):
------- node = Node(val)
------- l, r = split(self.root, pos)
------- self.root = merge(merge(l, node), r)
--- def erase(self, pos):
------- l, r = split(self.root, pos)
------- m, r = split(r, 1)
------- self.root = merge(l, r)
--- def get(self, pos):
------- def _get(v, k):
----------- push(v)
----------- if k < sz(v.l):
--------------- return _get(v.l, k)
----------- elif k > sz(v.l):
--------------- return _get(v.r, k - sz(v.l) - 1)
----------- return v.val
------- return _get(self.root, pos)
--- def range_sum(self, lq, rq):
------- l1, r1 = split(self.root, rq + 1)
------- l2, mid = split(l1, lq)
------- res = sm(mid)
------- self.root = merge(merge(l2, mid), r1)
------- return res
--- def range_add(self, lq, rq, d):
------- l1, r1 = split(self.root, rq + 1)
------- l2, mid = split(l1, lq)
------- apply(mid, d)
------- self.root = merge(merge(l2, mid), r1)
--- def inorder(self):
------- res = []
------- def dfs(v):
----------- if not v:
--------------- return
----------- push(v)
----------- dfs(v.l)
----------- res.append(v.val)
----------- dfs(v.r)
------- dfs(self.root)
------- return res
```

1.11. Unique Counter.

```
import bisect
class LeqCounter:
--- def __init__(self, arr):
------- self.n = len(arr)
------- self.seg = [[] for _ in range(4 * self.n)]
------- self._build(1, 0, self.n - 1, arr)
--- def _build(self, idx, l, r, arr):
------- if l == r:
----------- self.seg[idx] = [arr[l]]
----------- return
------- m = (l + r) // 2
------- self._build(idx * 2, l, m, arr)
------- self._build(idx * 2 + 1, m + 1, r, arr)
------- # merge
------- self.seg[idx] = sorted(self.seg[idx * 2] + self.seg[idx * 2 +
↪  1])
--- def _query(self, idx, l, r, ql, qr, x):
------- if qr < l or r < ql:
----------- return 0
------- if ql <= l and r <= qr:
----------- return bisect.bisect_right(self.seg[idx], x)
------- m = (l + r) // 2
------- return (
----------- self._query(idx * 2, l, m, ql, qr, x) +
----------- self._query(idx * 2 + 1, m + 1, r, ql, qr, x)
------- )
--- def count(self, l, r, x):
------- if l > r:
----------- return 0
------- return self._query(1, 0, self.n - 1, l, r, x)
class UniqueCounter:
--- def __init__(self, A):
------- n = len(A)
------- self.B = [0] * (n + 1)
------- last = {}
------- for i in range(1, n + 1):
----------- val = A[i - 1]
----------- self.B[i] = last.get(val, 0)
----------- last[val] = i
------- self.leq = LeqCounter(self.B)
--- def count(self, l, r):
------- return self.leq.count(l + 1, r + 1, l)
```

2. Dynamic Programming

2.1. Lichao Tree.

```
class Line:
--- __slots__ = ['m', 'c']
--- def __init__(self, m=0, c=float('-inf')):
------- self.m = m
------- self.c = c
--- def eval(self, x):
------- return self.m * x + self.c
class Node:
--- __slots__ = ['line', 'left', 'right']
--- def __init__(self):
------- self.line = Line()
------- self.left = None
------- self.right = None
class LiChaoTree:
--- def __init__(self, min_x=-10**12, max_x=10**12):
------- self.root = Node()
------- self.min_x = min_x
------- self.max_x = max_x
--- def add_line(self, m, c):
------- self._insert(self.root, self.min_x, self.max_x, Line(m, c))
--- def _insert(self, node, l, r, new_line):
------- mid = (l + r) // 2
------- left_better = new_line.eval(l) > node.line.eval(l)
------- mid_better = new_line.eval(mid) > node.line.eval(mid)
------- if mid_better:
----------- node.line, new_line = new_line, node.line
------- if r - l <= 1:
----------- return
------- if left_better != mid_better:
----------- if not node.left:
--------------- node.left = Node()
```

```
---------- self._insert(node.left, l, mid, new_line) ----------------
------- else: ---------------------------------------------------
---------- if not node.right: ---------------------------------------
--------------- node.right = Node() ---------------------------------
---------- self._insert(node.right, mid, r, new_line) ---------------
 ------------------------------------------------------------------
--- def query(self, x): ----------------------------------------------
------- return self._query(self.root, self.min_x, self.max_x, x) -----
 ------------------------------------------------------------------
--- def _query(self, node, l, r, x): ---------------------------------
------- if not node: -----------------------------------------------
---------- return float('-inf') --------------------------------------
------- if r - l <= 1: ---------------------------------------------
---------- return node.line.eval(x) ----------------------------------
----------  ----------------------------------------------------------
------- mid = (l + r) // 2 -----------------------------------------
------- res = node.line.eval(x) ------------------------------------
-------  ---------------------------------------------------------
------- if x < mid: ------------------------------------------------
---------- res = max(res, self._query(node.left, l, mid, x)) --------
------- else: ------------------------------------------------------
---------- res = max(res, self._query(node.right, mid, r, x)) -------
----------  ----------------------------------------------------------
------- return res -------------------------------------------------
```

2.2. Divide And Conquer.

```
INF = float('inf') -----------------------------------------------
 ----------------------------------------------------------------
def solve_dp(g, k_L, k_R, n_L, n_R, dp, cost_func): --------------
--- if n_L > n_R: ------------------------------------------------
------- return -----------------------------------------------------
 ----------------------------------------------------------------
--- n_M = (n_L + n_R) // 2 -------------------------------------
--- best_k = -1 ------------------------------------------------
--- dp[g][n_M] = INF -------------------------------------------
 ----------------------------------------------------------------
--- for k in range(k_L, min(n_M, k_R) + 1): --------------------
------- current_val = dp[g - 1][k] + cost_func(k + 1, n_M) -------
------- if current_val < dp[g][n_M]: -------------------------
---------- dp[g][n_M] = current_val ----------------------------
---------- best_k = k ------------------------------------------
 ----------------------------------------------------------------
--- solve_dp(g, k_L, best_k, n_L, n_M - 1, dp, cost_func) ------
--- solve_dp(g, best_k, k_R, n_M + 1, n_R, dp, cost_func) ------
```

3. Geometry

3.1. Angles And Rotations.

```
def angle(a, b, c): # angle formed by abc in radians: PI < x <= PI ---
--- return abs((arg(a-b) - arg(c-b)) % (2 * math.pi)) ----------
def rotate(p, a, d): # rotate point a about pivot p CCW at d radians -
--- return p + (a - p) * complex(math.cos(d), math.sin(d)) -----
```

3.2. Distances.

```
 ----------------------------------------------------------------
# Distance: Point to 2D Line (ax + by + c = 0) ------------------
def dist_pt_line_eq(p, a, b, c): ---------------------------------
--- return abs(a*p.real + b*p.imag + c) / math.hypot(a, b) -------
 ----------------------------------------------------------------
# Distance: Point to 2D Line through points a and b -------------
def dist_pt_line(p, a, b): ---------------------------------------
--- cp = (p - a).conjugate() * (b - a) -------------------------
--- return abs(cp.imag) / abs(b - a) ---------------------------
 ----------------------------------------------------------------
# Distance: Point to 3D Plane (ax + by + cz + d = 0) ------------
def dist_pt_plane(p, a, b, c, d): --------------------------------
--- # math.hypot supports 3+ arguments in Python 3.8+ ----------
--- return abs(a*p.x + b*p.y + c*p.z + d) / math.hypot(a,b,c) ----
 ----------------------------------------------------------------
# Distance: Shortest distance between 3D lines AB and CD --------
def dist_line_3d(A, B, C, D): ------------------------------------
--- u, v, w = B - A, D - C, A - C ------------------------------
--- a, b = u.dot(u), u.dot(v) ----------------------------------
--- c, d, e = v.dot(v), u.dot(w), v.dot(w) ---------------------
--- det = a * c - b * b ----------------------------------------
--- if det < 1e-9: # Parallel lines ----------------------------
------- s, t = 0.0, d / b if b > c else e / c ------------------
--- else: # Skew lines -----------------------------------------
------- s = (b * e - c * d) / det ------------------------------
------- t = (a * e - b * d) / det ------------------------------
--- p1 = P3(A.x + u.x*s, A.y + u.y*s, A.z + u.z*s) -------------
--- p2 = P3(C.x + v.x*t, C.y + v.y*t, C.z + v.z*t) -------------
--- vec = p1 - p2 ----------------------------------------------
--- return math.sqrt(vec.dot(vec)) -----------------------------
```

3.3. Intersections.

3.3.1. *Circle Line Intersection.*

```
EPS = 1e-9 -------------------------------------------------------
def projLine(p, a, b): # Project point p onto line segment ab --------
--- v = b - a --------------------------------------------------
--- scalar = ((p - a) * v.conjugate()).real / abs(v)**2 -------
--- return a + v * scalar --------------------------------------
 ----------------------------------------------------------------
def rotate(c, p, t): # Rotate point p around center c by t radians ---
--- return c + (p - c) * cmath.rect(1, t) ----------------------
 ----------------------------------------------------------------
def CL_inter(c, r, a, b): ----------------------------------------
--- p = projLine(c, a, b) --------------------------------------
--- d = abs(c - p) ---------------------------------------------
--- ans = [] ---------------------------------------------------
--- ----------------------------------------------------------
--- if d > r + EPS: pass # None --------------------------------
--- elif d > r - EPS: ans.append(p) # Tangent ------------------
--- elif d < EPS: # Diameter -----------------------------------
------- v = r * (b - a) / abs(b - a) ---------------------------
------- ans.append(c + v) --------------------------------------
------- ans.append(c - v) --------------------------------------
--- else: # Secant ---------------------------------------------
------- t = math.acos(d / r) -----------------------------------
------- p = c + (p - c) * r / d --------------------------------
------- ans.append(rotate(c, p, t)) ----------------------------
------- ans.append(rotate(c, p, -t)) ---------------------------
--- return ans -------------------------------------------------
```

3.3.2. *Circle Circle Intersection.*

```
EPS = 1e-9 -------------------------------------------------------
def rotate(c, p, t): ---------------------------------------------
--- # Rotate point p around center c by t radians ----------------
--- return c + (p - c) * cmath.rect(1, t) ----------------------
 ----------------------------------------------------------------
def CC_inter(c1, r1, c2, r2): ------------------------------------
--- d = abs(c1 - c2) -------------------------------------------
--- ans = [] ---------------------------------------------------
--- if d < EPS: # Concentric circles ---------------------------
------- if abs(r1 - r2) < EPS: ---------------------------------
---------- pass # Infinite intersections (same circle) ----------
--- elif r1 < EPS: # Circle 1 is a point -----------------------
------- if abs(d - r2) < EPS: ----------------------------------
---------- ans.append(c1) --------------------------------------
--- else: # General case using Law of Cosines -------------------
------- s = (r1*r1 + d*d - r2*r2) / (2*r1*d) -------------------
------- s = max(-1.0, min(1.0, s)) # Prevent float domain errors -----
------- t = math.acos(s) ---------------------------------------
------- # Point on C1's radius pointing towards C2 --------------
------- mid = c1 + (c2 - c1) * r1 / d --------------------------
------- ans.append(rotate(c1, mid, t)) -------------------------
------- if abs(math.sin(t)) >= EPS: ----------------------------
---------- # FIXED: Rotate around c1, not c2! -------------------
---------- ans.append(rotate(c1, mid, -t)) ---------------------
--- return ans -------------------------------------------------
```

3.3.3. *Line Intersect.*

```
def line_inter_fast(a, b, c, d): ---------------------------------
--- A = cross(d - a, b - a) ------------------------------------
--- B = cross(c - a, b - a) ------------------------------------
--- return (B * d - A * c) / (B - A) if B - A else None ---------
```

3.4. Closest Pair.

```
def closest_pair(pts): -------------------------------------------
--- if len(pts) <= 1: return float('inf') ----------------------
--- px = sorted(pts) # Automatically sorts by x, then y ---------
--- def solve(l, r): # Base case: Brute force for small partitions ---
------- if r - l <= 3: -----------------------------------------
---------- d = float('inf') ------------------------------------
---------- for i in range(l, r): -------------------------------
--------------- for j in range(i + 1, r): ----------------------
------------------ d = min(d, math.dist(px[i], px[j])) ---------
---------- return d --------------------------------------------
------- mid = (l + r) // 2 -------------------------------------
------- mid_x = px[mid][0] -------------------------------------
------- # Recursively find the minimum in both halves ----------
------- d = min(solve(l, mid), solve(mid, r)) ------------------
------- # Gather points in the middle strip ---------------------
------- strip = [p for p in px[l:r] if abs(p[0] - mid_x) < d] --------
------- strip.sort(key=lambda p: p[1]) # Sort strip by y -------
------- # Check at most 7 geometric neighbors in the strip -----
------- for i, p1 in enumerate(strip): -------------------------
---------- for p2 in strip[i+1 : i+8]: -------------------------
--------------- d = min(d, math.dist(p1, p2)) ------------------
------- return d -----------------------------------------------
--- return solve(0, len(px)) -----------------------------------
```

3.5. Polygon Centroid.

```
def cross(a, b): -------------------------------------------------
--- return a[0] * b[1] - a[1] * b[0] ---------------------------
 ----------------------------------------------------------------
def centroid(points): --------------------------------------------
--- n = len(points) --------------------------------------------
--- ans_x, ans_y = 0.0, 0.0 ------------------------------------
--- z = 0.0 ----------------------------------------------------
 ----------------------------------------------------------------
--- for i in range(n): -----------------------------------------
------- j = (i - 1) % n ----------------------------------------
------- cp = cross(points[j], points[i]) -----------------------
 ----------------------------------------------------------------
------- ans_x += (points[j][0] + points[i][0]) * cp ------------
------- ans_y += (points[j][1] + points[i][1]) * cp ------------
------- z += cp ------------------------------------------------
 ----------------------------------------------------------------
--- return (ans_x / (3 * z), ans_y / (3 * z)) ------------------
```

3.6. Convex Hull.

3.6.1. *Convex Hull.*

```
def cross(o, a, b): # 2D cross product of OA and OB vectors
    return (a[0]-o[0])*(b[1]-o[1]) - (a[1]-o[1])*(b[0]-o[0])

def convex_hull(pts): # Sorts by x, then by y automatically
    pts = sorted(set(pts))
    if len(pts) <= 1:
        return pts
    def build(iterable):
        h = []
        for p in iterable:
            while len(h) >= 2 and cross(h[-2], h[-1], p) <= 0:
                h.pop()
            h.append(p)
        return h
    lower = build(pts)
    upper = build(reversed(pts))
    return lower[:-1] + upper[:-1]
```

3.6.2. *Convex Hull 3D.*

```
class P3:
    __slots__ = ['x', 'y', 'z']
    def __init__(self, x=0, y=0, z=0):
        self.x, self.y, self.z = x, y, z
    def __sub__(self, o):
        return P3(self.x-o.x, self.y-o.y, self.z-o.z)
    def cross(self, o):
        return P3(self.y*o.z - self.z*o.y,
                  self.z*o.x - self.x*o.z,
                  self.x*o.y - self.y*o.x)
    def dot(self, o):
        return self.x*o.x + self.y*o.y + self.z*o.z
    def __eq__(self, o):
        return (self.x, self.y, self.z) == (o.x, o.y, o.z)
    def __lt__(self, o):
        return (self.x, self.y, self.z) < (o.x, o.y, o.z)

class Face:
    __slots__ = ['p', 'q']
    def __init__(self, p, q):
        self.p = p # Tuple of 3 point indices
        self.q = q # Normal vector (P3 object)

def hull_3D(pts):
    n = len(pts)
    faces = []
    dead = [[True] * n for _ in range(n)]
    def add_face(a, b, c):
        q = (pts[b] - pts[a]).cross(pts[c] - pts[a])
        faces.append(Face((a, b, c), q))
        dead[a][b] = dead[b][c] = dead[c][a] = False
    # Initialize with a degenerate tetrahedron
    add_face(0, 1, 2)
    add_face(0, 2, 1)
    for i in range(3, n):
        f_inv = []
        for f in faces:
            # If face is visible from the point
            if (pts[i] - pts[f.p[0]]).dot(f.q) > 0:
                for j in range(3):
                    dead[f.p[j]][f.p[(j+1)%3]] = True
            else:
                f_inv.append(f)
        faces = []
        for f in f_inv:
            for j in range(3):
                a, b = f.p[j], f.p[(j+1)%3]
                # If reverse edge is dead but forward is alive
                if dead[b][a]:
                    add_face(b, a, i)
        faces.extend(f_inv)
    return faces
```

3.7. Areas.

3.7.1. *Triangle Area.*

```
def area(a, b, c):
    s = (a + b + c) / 2
    return (s*(s-a)*(s-b)*(s-c)) ** 0.5
```

3.7.2. *Polygon Area.*

```
def area(p, n):
    a = 0
    for i in range(n):
        j = (i - 1) % n
        a += cross(p[i], p[j])
    return abs(a) / 2
```

3.8. Dot Cross.

```
def dot(a, b):
    return a.x * b.x + a.y * b.y # + a.z * b.z
def cross(a, b):
    return a.x * b.y - a.y * b.x
def cross(a, b, c):
    return cross(a, b) + cross(b, c) + cross(c, a)
def cross3D(a, b):
    return point3(a.x*b.y - a.y*b.x, a.y*b.z - a.z*b.y, a.z*b.x -
↪ a.x*b.z)
```

3.9. Line Sweep Closest Pair.

```
import math

def dist_sq(p1, p2):
    return (p1[0] - p2[0])**2 + (p1[1] - p2[1])**2

def closest_pair(points):
    points.sort()

    def solve(pts):
        n = len(pts)

        if n <= 3:
            return min(dist_sq(pts[i], pts[j])
                       for i in range(n)
                       for j in range(i + 1, n)) if n > 1 else
↪ float('inf')

        mid = n // 2
        mid_x = pts[mid][0]

        left = pts[:mid]
        right = pts[mid:]

        d = min(solve(left), solve(right))

        strip = [p for p in pts if (p[0] - mid_x) ** 2 < d]
        strip.sort(key=lambda p: p[1])

        for i in range(len(strip)):
            for j in range(i + 1, min(i + 7, len(strip))):
                d = min(d, dist_sq(strip[i], strip[j]))

        return d

    return solve(points)
```

3.10. Point Projection.

```
EPS = 1e-9

def dot(a, b):
    return sum(x * y for x, y in zip(a, b))

def scale(v, k):
    return [k * x for x in v]

def add(a, b):
    return [x + y for x, y in zip(a, b)]

def sub(a, b):
    return [x - y for x, y in zip(a, b)]

def norm(v):
    return dot(v, v)

def proj(p, v):
    v_norm = norm(v)
    if v_norm < EPS:
        return [0] * len(p)
    return scale(v, dot(p, v) / v_norm)

def proj_line(p, a, b):
    ab = sub(b, a)
    ab_norm = norm(ab)
    if ab_norm < EPS:
        return a[:]

    t = dot(sub(p, a), ab) / ab_norm
    return add(a, scale(ab, t))

def proj_seg(p, a, b):
    ab = sub(b, a)
    ab_norm = norm(ab)
    if ab_norm < EPS:
        return a[:]

    t = dot(sub(p, a), ab) / ab_norm
    t = max(0.0, min(1.0, t))

    return add(a, scale(ab, t))

def proj_plane(p, a, b, c, d):
    n = [a, b, c]
    n_norm = norm(n)
    if n_norm < EPS:
        return p[:]

    dist = (dot(p, n) + d) / n_norm
    return sub(p, scale(n, dist))
```

3.11. Great Circle Distance.

```
import math

PI = math.pi

def clamp(x, lo, hi):
    return max(lo, min(hi, x))

# ========================================================
# version 1: lat/long (spherical law of cosines)
# ========================================================
def great_circle_dist_latlong(lat1, lon1, lat2, lon2, R=6371.0):
    lat1 *= PI / 180
    lon1 *= PI / 180
```

```
    lat2 *= PI / 180
    lon2 *= PI / 180

    val = (
        math.sin(lat1) * math.sin(lat2)
        + math.cos(lat1) * math.cos(lat2) * math.cos(abs(lon1 - lon2))
    )

    val = clamp(val, -1.0, 1.0)  # IMPORTANT FIX

    return R * math.acos(val)

def dot(a, b):
    return sum(x * y for x, y in zip(a, b))

def cross(a, b):
    return [
        a[1] * b[2] - a[2] * b[1],
        a[2] * b[0] - a[0] * b[2],
        a[0] * b[1] - a[1] * b[0],
    ]

def norm(v):
    return math.sqrt(dot(v, v))

# ========================================================
# version 2: using 3D vectors (angle between vectors)
# ========================================================
def great_circle_dist_vec(a, b, R=1.0):
    # assumes a and b are unit vectors on sphere
    cross_prod = cross(a, b)
    return R * math.atan2(norm(cross_prod), dot(a, b))

def to_vec(lat, lon):
    lat *= PI / 180
    lon *= PI / 180

    return [
        math.cos(lat) * math.cos(lon),
        math.cos(lat) * math.sin(lon),
        math.sin(lat),
    ]
```

3.12. Point In Polygon.

```
import math

EPS = 1e-9

def dist(a, b):
    return math.hypot(a[0] - b[0], a[1] - b[1])

def in_polygon(q, p):
    n = len(p)
    inside = False

    j = n - 1
    for i in range(n):
        xi, yi = p[i]
        xj, yj = p[j]
        xq, yq = q

        intersect = ((yi > yq) != (yj > yq)) and (
            xq < (xj - xi) * (yq - yi) / (yj - yi + EPS) + xi
        )

        if intersect:
            inside = not inside

        j = i

    return inside

def on_polygon(q, p):
    n = len(p)

    for i in range(n):
        j = (i + 1) % n

        a = p[i]
        b = p[j]

        if abs(dist(a, q) + dist(q, b) - dist(a, b)) < EPS:
            return True

    return False
```

3.13. Cut Polygon By Line.

```
EPS = 1e-9

def cross(a, b, c):
    return (b[0] - a[0]) * (c[1] - a[1]) - (b[1] - a[1]) * (c[0] -
↪  a[0])

def line_inter(p1, p2, a, b):
    x1, y1 = p1
    x2, y2 = p2
    x3, y3 = a
    x4, y4 = b

    den = (x1 - x2) * (y3 - y4) - (y1 - y2) * (x3 - x4)
    if abs(den) < EPS:
        return p1

    px = (
        (x1 * y2 - y1 * x2) * (x3 - x4)
        - (x1 - x2) * (x3 * y4 - y3 * x4)
    ) / den

    py = (
        (x1 * y2 - y1 * x2) * (y3 - y4)
        - (y1 - y2) * (x3 * y4 - y3 * x4)
    ) / den

    return (px, py)

def cut(poly, a, b):
    n = len(poly)
    res = []

    for i in range(n):
        j = (i - 1 + n) % n

        c1 = cross(a, b, poly[j])
        c2 = cross(a, b, poly[i])

        if c1 >= -EPS:
            res.append(poly[j])

        if c1 * c2 < -EPS:
            inter = line_inter(poly[j], poly[i], a, b)
            res.append(inter)

    return res
```

3.14. Triangle Centers.

```
import math

EPS = 1e-9

def add(a, b):
    return (a[0] + b[0], a[1] + b[1])
def sub(a, b):
    return (a[0] - b[0], a[1] - b[1])
def scale(a, k):
    return (a[0] * k, a[1] * k)
def norm2(a, b):
    return (a[0] - b[0]) ** 2 + (a[1] - b[1]) ** 2
def bary(A, B, C, a, b, c):
    s = a + b + c
    if abs(s) < EPS:
        return (0.0, 0.0)

    return (
        (A[0] * a + B[0] * b + C[0] * c) / s,
        (A[1] * a + B[1] * b + C[1] * c) / s,
    )
def dist(a, b):
    return math.sqrt(norm2(a, b))
def trilinear(A, B, C, a, b, c):
    return bary(
        A,
        B,
        C,
        dist(B, C) * a,
        dist(C, A) * b,
        dist(A, B) * c,
    )
def centroid(A, B, C):
    return bary(A, B, C, 1, 1, 1)
def circumcenter(A, B, C):
    a = dist(B, C)
    b = dist(C, A)
    c = dist(A, B)

    return bary(
        A,
        B,
        C,
        a * (b + c - a),
        b * (c + a - b),
        c * (a + b - c),
    )
def orthocenter(A, B, C):
    def foot(P, Q, R):
        q = sub(Q, R)
        t = dot(sub(P, R), q) / (dot(q, q) + EPS)
        return add(R, scale(q, t))
    def dot(a, b):
        return a[0] * b[0] + a[1] * b[1]

    H1 = foot(A, B, C)
    H2 = foot(B, A, C)

    return bary(A, B, C, 1, 1, 1)
def incenter(A, B, C):
    return bary(
        A,
        B,
        C,
        dist(B, C),
        dist(C, A),
        dist(A, B),
    )
def inradius(a, b, c):
    s = (a + b + c) / 2
    area = math.sqrt(max(s * (s - a) * (s - b) * (s - c), 0))
    return area / s if s > EPS else 0
def excenter(A, B, C):
    a = dist(B, C)
    b = dist(C, A)
    c = dist(A, B)
    return bary(A, B, C, -a, b, c)
def symmedian(A, B, C):
```

```
--- return bary(
------- A,
------- B,
------- C,
------- norm2(B, C),
------- norm2(C, A),
------- norm2(A, B),
--- )
```

3.15. Convex Polygon Intersection.

```
EPS = 1e-9

def sub(a, b):
--- return (a[0] - b[0], a[1] - b[1])
def add(a, b):
--- return (a[0] + b[0], a[1] + b[1])
def cross(a, b):
--- return a[0] * b[1] - a[1] * b[0]
def dot(a, b):
--- return a[0] * b[0] + a[1] * b[1]
def orient(a, b, c):
--- return cross(sub(b, a), sub(c, a))
def seg_inter(a, b, c, d):
--- def on_seg(p, a, b):
------- return (
----------- abs(orient(a, b, p)) < EPS
----------- and min(a[0], b[0]) - EPS <= p[0] <= max(a[0], b[0]) + EPS
----------- and min(a[1], b[1]) - EPS <= p[1] <= max(a[1], b[1]) + EPS
------- )
--- def line_inter(a, b, c, d):
------- A1 = b[1] - a[1]
------- B1 = a[0] - b[0]
------- C1 = A1 * a[0] + B1 * a[1]
------- A2 = d[1] - c[1]
------- B2 = c[0] - d[0]
------- C2 = A2 * c[0] + B2 * c[1]
------- det = A1 * B2 - A2 * B1
------- if abs(det) < EPS:
----------- return None
------- x = (B2 * C1 - B1 * C2) / det
------- y = (A1 * C2 - A2 * C1) / det
------- return (x, y)
--- p = line_inter(a, b, c, d)
--- if p is None:
------- return None
--- if (
------- on_seg(p, a, b)
------- and on_seg(p, c, d)
--- ):
------- return p
--- return None
def in_poly(p, poly):
--- inside = False
--- n = len(poly)
--- for i in range(n):
------- j = (i - 1) % n
------- a, b = poly[i], poly[j]
------- if ((a[1] > p[1]) != (b[1] > p[1])):
----------- x = (b[0] - a[0]) * (p[1] - a[1]) / (b[1] - a[1] + EPS) +
↪  a[0]
----------- if p[0] < x:
--------------- inside = not inside
--- return inside
def on_poly(p, poly):
--- n = len(poly)
--- for i in range(n):
------- j = (i - 1) % n
------- if abs(orient(poly[j], poly[i], p)) < EPS:
----------- return True
--- return False
def convex_hull(points):
--- points = sorted(points)
--- def build(h):
------- for p in points:
----------- while len(h) >= 2 and orient(h[-2], h[-1], p) <= EPS:
--------------- h.pop()
----------- h.append(p)
------- return h
--- lower = build([])
--- upper = build([])
--- return lower[:-1] + upper[:-1]
def convex_polygon_inter(a, b):
--- ans = []
--- for p in a:
------- if in_poly(p, b) or on_poly(p, b):
----------- ans.append(p)
--- for p in b:
------- if in_poly(p, a) or on_poly(p, a):
----------- ans.append(p)
--- for i in range(len(a)):
------- I = (i - 1) % len(a)
------- for j in range(len(b)):
----------- J = (j - 1) % len(b)
----------- p = seg_inter(a[I], a[i], b[J], b[j])
----------- if p is not None:
--------------- ans.append(p)
--- if not ans:
------- return []
--- return convex_hull(ans)
```

3.16. Pick Theorem Lattice.

```
import math

def area(poly):
--- n = len(poly)
--- s = 0
--- for i in range(n):
------- j = (i - 1) % n
------- s += poly[j][0] * poly[i][1] - poly[i][0] * poly[j][1]
--- return abs(s) // 2
def boundary(poly):
--- n = len(poly)
--- ans = 0
--- for i in range(n):
------- j = (i - 1) % n
------- dx = poly[i][0] - poly[j][0]
------- dy = poly[i][1] - poly[j][1]
------- ans += math.gcd(abs(dx), abs(dy))
--- return ans
def interior(poly):
--- A = area(poly)
--- B = boundary(poly)
--- return A - B // 2 + 1
```

3.17. Minimum Enclosing Circle.

```
import math

EPS = 1e-9
def dist(a, b):
--- return math.hypot(a[0] - b[0], a[1] - b[1])
def mid(a, b):
--- return ((a[0] + b[0]) / 2, (a[1] + b[1]) / 2)
def cross(a, b, c):
--- return (b[0] - a[0]) * (c[1] - a[1]) - (b[1] - a[1]) * (c[0] -
↪  a[0])
def circumcenter(a, b, c):
--- ax, ay = a
--- bx, by = b
--- cx, cy = c
--- d = 2 * (ax * (by - cy) + bx * (cy - ay) + cx * (ay - by))
--- if abs(d) < EPS:
------- return mid(a, b)
--- ux = (
------- (ax * ax + ay * ay) * (by - cy)
------- + (bx * bx + by * by) * (cy - ay)
------- + (cx * cx + cy * cy) * (ay - by)
--- ) / d
--- uy = (
------- (ax * ax + ay * ay) * (cx - bx)
------- + (bx * bx + by * by) * (ax - cx)
------- + (cx * cx + cy * cy) * (bx - ax)
--- ) / d
--- return (ux, uy)
def bounding_ball(p):
--- random.shuffle(p)
--- center = p[0]
--- radius = 0.0
--- n = len(p)
--- for i in range(n):
------- if dist(center, p[i]) > radius + EPS:
----------- center = p[i]
----------- radius = 0.0
----------- for j in range(i):
--------------- if dist(center, p[j]) > radius + EPS:
------------------- center = mid(p[i], p[j])
------------------- radius = dist(center, p[i])
------------------- for k in range(j):
----------------------- if dist(center, p[k]) > radius + EPS:
--------------------------- center = circumcenter(p[i], p[j], p[k])
--------------------------- radius = dist(center, p[i])
--- return center, radius
def verify(p, center, r):
--- for x in p:
------- if dist(x, center) > r + 1e-6:
----------- return False
--- return True
```

3.18. Shamos Algorithm.

```
import math

EPS = 1e-9
def sub(a, b):
--- return (a[0] - b[0], a[1] - b[1])
def cross(a, b):
--- return a[0] * b[1] - a[1] * b[0]
def dist_pt_line(p, a, b):
--- ab = sub(b, a)
--- ap = sub(p, a)
--- return abs(cross(ab, ap)) / (math.hypot(ab[0], ab[1]) + EPS)
def convex_hull(points):
--- points = sorted(points)
--- def build():
------- hull = []
------- for p in points:
----------- while len(hull) >= 2 and cross(sub(hull[-1], hull[-2]),
↪  sub(p, hull[-1])) <= EPS:
--------------- hull.pop()
----------- hull.append(p)
------- return hull
--- lower = build()
--- upper = build()
--- return lower[:-1] + upper[:-1]
def shamos(p):
--- h = convex_hull(p)
--- k = len(h)

--- if k <= 2:
------- return 0.0

--- d = float("inf")
--- j = 1

--- for i in range(k):
```

```
------- ni = (i + 1) % k ----------------------------------------------
 -------------------------------------------------------------------
------- a = h[i] ------------------------------------------------------
------- b = h[ni] -----------------------------------------------------
 -------------------------------------------------------------------
------- while True: ---------------------------------------------------
----------- nj = (j + 1) % k ------------------------------------------
----------- if dist_pt_line(h[nj], a, b) > dist_pt_line(h[j], a, b): -
--------------- j = nj ------------------------------------------------
----------- else: -----------------------------------------------------
--------------- break -------------------------------------------------
------- d = min(d, dist_pt_line(h[j], a, b)) --------------------------
--- return d ------------------------------------------------------------
```

3.19. Kd Tree.

```
import heapq --------------------------------------------------------
 -------------------------------------------------------------------
EPS = 1e-9 ----------------------------------------------------------
def dist2(a, b): ----------------------------------------------------
--- return (a[0] - b[0]) ** 2 + (a[1] - b[1]) ** 2 ------------------
class KDTree: -------------------------------------------------------
--- def __init__(self, points): -------------------------------------
------- self.p = points[:] --------------------------------------------
------- self.n = len(points) ------------------------------------------
------- self.build(0, self.n, 0) --------------------------------------
--- def build(self, L, R, dvx): -------------------------------------
------- if R - L <= 1: ------------------------------------------------
----------- return ----------------------------------------------------
------- mid = (L + R) // 2 --------------------------------------------
------- if dvx: -------------------------------------------------------
----------- self.p[L:R] = sorted(self.p[L:R], key=lambda x: x[0]) ----
------- else: ---------------------------------------------------------
----------- self.p[L:R] = sorted(self.p[L:R], key=lambda x: x[1]) ----
------- self.build(L, mid, not dvx) -----------------------------------
------- self.build(mid + 1, R, not dvx) -------------------------------
--- def knn(self, x, y, k=1, r=-1): ---------------------------------
------- self.qx = x ---------------------------------------------------
------- self.qy = y ---------------------------------------------------
------- self.k = k ----------------------------------------------------
------- self.prune = float("inf") if r < 0 else r * r -----------------
------- self.heap = [] ------------------------------------------------
------- self._dfs(0, self.n, False) -----------------------------------
------- res = [p for _, p in sorted(self.heap, reverse=True)] --------
------- return res ----------------------------------------------------
--- def _dfs(self, L, R, dvx): --------------------------------------
------- if R - L <= 0: ------------------------------------------------
----------- return ----------------------------------------------------
------- mid = (L + R) // 2 --------------------------------------------
------- p = self.p[mid] -----------------------------------------------
------- dx = self.qx - p[0] -------------------------------------------
------- dy = self.qy - p[1] -------------------------------------------
------- D = dx * dx + dy * dy -----------------------------------------
------- if D <= self.prune: -------------------------------------------
----------- heapq.heappush(self.heap, (-D, p)) ------------------------
----------- if len(self.heap) > self.k: -------------------------------
--------------- heapq.heappop(self.heap) ------------------------------
------- delta = dx if dvx else dy -------------------------------------
------- nL, nR = L, mid -----------------------------------------------
------- fL, fR = mid + 1, R -------------------------------------------
------- if delta > 0: -------------------------------------------------
----------- nL, fL = fL, nL -------------------------------------------
----------- nR, fR = fR, nR -------------------------------------------
------- self._dfs(nL, nR, not dvx) ------------------------------------
------- if len(self.heap) < self.k or delta * delta <= self.prune: ---
----------- self._dfs(fL, fR, not dvx) --------------------------------
```

4. Graphs

4.1. Max Flow.

4.1.1. *Dinic.*

```
INF = float('inf') --------------------------------------------------
class Dinic: --------------------------------------------------------
--- def __init__(self, n, s, t): ------------------------------------
------- self.n, self.s, self.t = n, s, t ------------------------------
------- self.edges = []  ----------------------------------------------
------- self.adj = [[] for _ in range(n)] -----------------------------
 -------------------------------------------------------------------
--- def add_edge(self, u, v, c, bi=False): --------------------------
------- self.adj[u].append(len(self.edges)) ---------------------------
------- self.edges.append([v, c, 0]) ----------------------------------
------- self.adj[v].append(len(self.edges)) ---------------------------
------- self.edges.append([u, c if bi else 0, 0]) ---------------------
 -------------------------------------------------------------------
--- def bfs(self): --------------------------------------------------
------- self.dist = [-1] * self.n -------------------------------------
------- self.dist[self.s] = 0 -----------------------------------------
------- q = deque([self.s]) -------------------------------------------
------- while q: ------------------------------------------------------
----------- u = q.popleft() -------------------------------------------
----------- for i in self.adj[u]: -------------------------------------
--------------- v, c, f = self.edges[i] -------------------------------
--------------- if self.dist[v] < 0 and c > f: ------------------------
------------------- self.dist[v] = self.dist[u] + 1 -------------------
------------------- q.append(v) -----------------------------------------
------- return self.dist[self.t] != -1 --------------------------------
---  ------------------------------------------------------------------
--- def dfs(self, u, pushed): ---------------------------------------
------- if pushed == 0 or u == self.t: return pushed ------------------
------- while self.ptr[u] < len(self.adj[u]): -------------------------
----------- i = self.adj[u][self.ptr[u]] ------------------------------
----------- v, c, f = self.edges[i] -----------------------------------
----------- if self.dist[u]+1 == self.dist[v] and c > f: --------------
--------------- tr = self.dfs(v, min(pushed, c - f)) ------------------
--------------- if tr > 0: --------------------------------------------
------------------- self.edges[i][2] += tr ----------------------------
------------------- self.edges[i^1][2] -= tr --------------------------
------------------- return tr -------------------------------------------
----------- self.ptr[u] += 1 ------------------------------------------
------- return 0 ------------------------------------------------------
 -------------------------------------------------------------------
--- def calc_max_flow(self): ----------------------------------------
------- flow = 0 ------------------------------------------------------
------- while self.bfs(): ---------------------------------------------
----------- self.ptr = [0] * self.n -----------------------------------
----------- while True: -----------------------------------------------
--------------- pushed = self.dfs(self.s, INF) ------------------------
--------------- if not pushed: ----------------------------------------
------------------- break -----------------------------------------------
--------------- flow += pushed ----------------------------------------
------- return flow ---------------------------------------------------
```

4.1.2. *Edmonds Karp.*

```
INF = float('inf') --------------------------------------------------
class EdmondsKarp: --------------------------------------------------
--- def __init__(self, n, s, t): ------------------------------------
------- self.n, self.s, self.t = n, s, t ------------------------------
------- self.adj = [[] for _ in range(n)] -----------------------------
------- self.res = [[0] * n for _ in range(n)] ------------------------
 -------------------------------------------------------------------
--- def add_edge(self, u, v, w): ------------------------------------
------- self.adj[u].append(v) -----------------------------------------
------- self.adj[v].append(u) -----------------------------------------
------- self.res[u][v] += w -------------------------------------------
 -------------------------------------------------------------------
--- def bfs(self): --------------------------------------------------
------- self.par = [-1] * self.n --------------------------------------
------- self.par[self.s] = self.s -------------------------------------
------- q = deque([self.s]) -------------------------------------------
------- while q: ------------------------------------------------------
----------- u = q.popleft() -------------------------------------------
----------- for v in self.adj[u]: -------------------------------------
--------------- if self.res[u][v] > 0 and self.par[v] == -1: ---------
------------------- self.par[v] = u -------------------------------------
------------------- if v == self.t: -------------------------------------
----------------------- return True -----------------------------------
------------------- q.append(v) -----------------------------------------
------- return False --------------------------------------------------
 -------------------------------------------------------------------
--- def calc_max_flow(self): ----------------------------------------
------- ans = 0 -------------------------------------------------------
------- while self.bfs(): ---------------------------------------------
----------- flow = INF ------------------------------------------------
----------- u = self.t ------------------------------------------------
----------- while u != self.s: ----------------------------------------
--------------- p = self.par[u] ---------------------------------------
--------------- flow = min(flow, self.res[p][u]) ----------------------
--------------- u = p -------------------------------------------------
----------- u = self.t ------------------------------------------------
----------- while u != self.s: ----------------------------------------
--------------- p = self.par[u] ---------------------------------------
--------------- self.res[p][u] -= flow --------------------------------
--------------- self.res[u][p] += flow --------------------------------
--------------- u = p -------------------------------------------------
----------- ans += flow -----------------------------------------------
------- return ans ----------------------------------------------------
```

4.1.3. *Bipartite Matching.*

```
from collections import deque ---------------------------------------
 -------------------------------------------------------------------
INF = float('inf') --------------------------------------------------
class BipartiteGraph: -----------------------------------------------
--- def __init__(self, n, m): ---------------------------------------
------- self.n = n ----------------------------------------------------
------- self.m = m ----------------------------------------------------
------- self.adj = [[] for _ in range(n)] -----------------------------
------- self.L = [-1] * n ---------------------------------------------
------- self.R = [-1] * m ---------------------------------------------
------- self.dist = [INF] * (n + 1) -----------------------------------
 -------------------------------------------------------------------
--- def add_edge(self, u, v): ---------------------------------------
------- self.adj[u].append(v) -----------------------------------------
 -------------------------------------------------------------------
--- def bfs(self): --------------------------------------------------
------- queue = deque() -----------------------------------------------
------- for v in range(self.n): ---------------------------------------
----------- if self.L[v] == -1: ---------------------------------------
--------------- self.dist[v] = 0 --------------------------------------
--------------- queue.append(v) ---------------------------------------
----------- else: -----------------------------------------------------
--------------- self.dist[v] = INF ------------------------------------
 -------------------------------------------------------------------
------- self.dist[self.n] = INF ---------------------------------------
 -------------------------------------------------------------------
------- while queue: --------------------------------------------------
----------- v = queue.popleft() ---------------------------------------
----------- if self.dist[v] < self.dist[self.n]: ----------------------
--------------- for u in self.adj[v]: --------------------------------
------------------- next_v = self.R[u] ----------------------------------
------------------- dist_next = self.dist[next_v] if next_v != -1 else
↪  self.dist[self.n]
 -------------------------------------------------------------------
------------------- if (next_v == -1 and self.dist[self.n] == INF) or \
----------------------------- (next_v != -1 and self.dist[next_v] ==
↪  INF):
 -------------------------------------------------------------------
----------------------- target = next_v if next_v != -1 else self.n --
----------------------- self.dist[target] = self.dist[v] + 1 ---------
----------------------- if target != self.n: --------------------------
----------------------------- queue.append(target) ------------------
 -------------------------------------------------------------------
------- return self.dist[self.n] != INF -------------------------------
```

```
    def dfs(self, v):
        if v != -1:
            for u in self.adj[v]:
                next_v = self.R[u]
                dist_next = self.dist[next_v] if next_v != -1 else self.dist[self.n]

                if dist_next == self.dist[v] + 1:
                    if self.dfs(next_v):
                        self.R[u] = v
                        self.L[v] = u
                        return True
            self.dist[v] = INF
            return False
        return True

    def maximum_matching(self):
        matching = 0
        for u in range(self.n):
            for v in self.adj[u]:
                if self.R[v] == -1:
                    self.L[u] = v
                    self.R[v] = u
                    matching += 1
                    break

        while self.bfs():
            for i in range(self.n):
                if self.L[i] == -1 and self.dfs(i):
                    matching += 1
        return matching
# Input Format: g = BipartiteGraph(2, 2)
#               g.add_edge(0, 0)
#               g.add_edge(0, 1)
#               g.add_edge(1, 0)
#               print(f"Max Matching: {g.maximum_matching()}")
```

4.2. Shortest Path.

4.2.1. *Dijkstra.*

```
import heapq
INF = float('inf')
def dijkstra(n, adj, s):
    dist = [INF] * n
    dist[s] = 0
    pq = [(0, s)]

    while pq:
        d, u = heapq.heappop(pq)
        if dist[u] < d:
            continue
        for v, w in adj[u]:
            if dist[v] > d + w:
                dist[v] = d + w
                heapq.heappush(pq, (dist[v], v))
    return dist
```

4.2.2. *Bellman Ford.*

```
INF = float('inf')
def bellman_ford(n, adj, s):
    dist = [INF] * n
    dist[s] = 0
    for _ in range(n - 1):
        for u in range(n):
            if dist[u] == INF: continue
            for v, w in adj[u]:
                if dist[u] + w < dist[v]:
                    dist[v] = dist[u] + w
    for u in range(n):
        if dist[u] == INF: continue
        for v, w in adj[u]:
            if dist[u] + w < dist[v]:
                return dist, True
    return dist, False
```

4.3. Minimum Spanning Tree.

4.3.1. *Kruskal Min Spanning Tree.*

```
import heapq

class UnionFind:
    def __init__(self, n):
        self.parent = list(range(n))
        self.rank = [0] * n

    def find(self, x):
        while self.parent[x] != x:
            self.parent[x] = self.parent[self.parent[x]]
            x = self.parent[x]
        return x

    def unite(self, a, b):
        a = self.find(a)
        b = self.find(b)

        if a == b:
            return False

        if self.rank[a] < self.rank[b]:
            self.parent[a] = b
        else:
            self.parent[b] = a
            if self.rank[a] == self.rank[b]:
                self.rank[a] += 1

        return True


def kruskal(n, edges):
    edges = edges[:]
    heapq.heapify(edges)

    uf = UnionFind(n)
    total_weight = 0
    mst = []

    while edges:
        w, u, v = heapq.heappop(edges)
        if uf.unite(u, v):
            mst.append((u, v, w))
            total_weight += w

            if len(mst) == n - 1:
                break

    return mst, total_weight
```

4.3.2. *Prim Min Spanning Tree.*

```
import heapq

def prim(n, adj, start=0):
    visited = [False] * n
    pq = [(0, start, -1)]

    total_weight = 0
    mst = []

    while pq:
        w, u, parent = heapq.heappop(pq)

        if visited[u]:
            continue

        visited[u] = True

        if parent != -1:
            mst.append((parent, u, w))
            total_weight += w

        for v, weight in adj[u]:
            if not visited[v]:
                heapq.heappush(pq, (weight, v, u))

    return mst, total_weight
```

4.4. Least Common Ancestor.

4.4.1. *Binary Lifting Lca.*

```
import math

class BinaryLifting:
    def __init__(self, adj):
        self.n = len(adj)
        self.LOG = math.ceil(math.log2(self.n)) + 1
        self.adj = adj

        self.dep = [0] * self.n
        self.par = [[-1] * self.LOG for _ in range(self.n)]

        self.build(0)

    def dfs(self, u, p):
        self.par[u][0] = p
        for v in self.adj[u]:
            if v != p:
                self.dep[v] = self.dep[u] + 1
                self.dfs(v, u)

    def build(self, root):
        self.dfs(root, root)

        for k in range(1, self.LOG):
            for u in range(self.n):
                self.par[u][k] = self.par[self.par[u][k-1]][k-1]

    def lift(self, u, k):
        for i in range(self.LOG):
            if k & (1 << i):
                u = self.par[u][i]
        return u

    def lca(self, u, v):
        if self.dep[u] < self.dep[v]:
            u, v = v, u

        u = self.lift(u, self.dep[u] - self.dep[v])

        if u == v:
            return u

        for k in reversed(range(self.LOG)):
            if self.par[u][k] != self.par[v][k]:
                u = self.par[u][k]
                v = self.par[v][k]

        return self.par[u][0]
```

4.4.2. *Euler Lca.*

```
class EulerLCA:
    def __init__(self, adj):
        self.n = len(adj)
        self.adj = adj

        self.euler = []
        self.first = [-1] * self.n
        self.depth = [0] * self.n

        self.build(0)

    def dfs(self, u, p, d):
        self.first[u] = len(self.euler)
        self.depth[u] = d
        self.euler.append(u)

        for v in self.adj[u]:
            if v != p:
                self.dfs(v, u, d + 1)
                self.euler.append(u)

    def build(self, root):
        self.dfs(root, root, 0)

        m = len(self.euler)
        LOG = m.bit_length()

        self.st = [[0] * m for _ in range(LOG)]
        self.log = [0] * (m + 1)

        for i in range(2, m + 1):
            self.log[i] = self.log[i // 2] + 1

        for i in range(m):
            self.st[0][i] = self.euler[i]

        for k in range(1, LOG):
            for i in range(m - (1 << k) + 1):
                a = self.st[k-1][i]
                b = self.st[k-1][i + (1 << (k-1))]
                self.st[k][i] = a if self.depth[a] < self.depth[b] else
↪   b

    def lca(self, u, v):
        l, r = self.first[u], self.first[v]
        if l > r:
            l, r = r, l

        k = self.log[r - l + 1]
        a = self.st[k][l]
        b = self.st[k][r - (1 << k) + 1]

        return a if self.depth[a] < self.depth[b] else b
```

4.4.3. *Tarjan Lca.*

```
class DSU:
    def __init__(self, n):
        self.p = list(range(n))

    def find(self, x):
        if self.p[x] != x:
            self.p[x] = self.find(self.p[x])
        return self.p[x]

    def unite(self, a, b):
        self.p[self.find(b)] = self.find(a)


class Tarjan:
    def __init__(self, adj, queries):
        self.adj = adj
        self.queries = queries
        self.n = len(adj)

        self.dsu = DSU(self.n)
        self.vis = [False] * self.n
        self.anc = [0] * self.n
        self.res = {}

    def dfs(self, u, p):
        self.anc[u] = u

        for v in self.adj[u]:
            if v == p:
                continue
            self.dfs(v, u)
            self.dsu.unite(u, v)
            self.anc[self.dsu.find(u)] = u

        self.vis[u] = True

        for v, idx in self.queries[u]:
            if self.vis[v]:
                self.res[idx] = self.anc[self.dsu.find(v)]
```

4.5. Minimum Mean Weight Cycle.

```
def min_mean_cycle(adj):
    n = len(adj)
    INF = float('inf')

    arr = [[INF] * n for _ in range(n + 1)]

    for i in range(n):
        arr[0][i] = 0

    for k in range(1, n + 1):
        for u in range(n):
            if arr[k - 1][u] == INF:
                continue
            for v, w in adj[u]:
                arr[k][v] = min(arr[k][v], arr[k - 1][u] + w)

    result = INF

    for v in range(n):
        if arr[n][v] == INF:
            continue

        max_avg = -INF
        for k in range(n):
            if arr[k][v] == INF:
                continue
            avg = (arr[n][v] - arr[k][v]) / (n - k)
            max_avg = max(max_avg, avg)

        result = min(result, max_avg)

    return result
```

4.6. Strongly Connected Components.

```
class KosarajuGraph:
    def __init__(self, n):
        self.n = n
        self.graph = [[] for _ in range(n)]
        self.rev_graph = [[] for _ in range(n)]
        self.vis = [0] * n
        self.sccs = []

    def add_edge(self, u, v):
        self.graph[u].append(v)
        self.rev_graph[v].append(u)

    def dfs(self, u, adj, container):
        self.vis[u] = 1
        for v in adj[u]:
            if not self.vis[v]:
                self.dfs(v, adj, container)
        container.append(u)

    def kosaraju(self):
        topo = []

        # First pass
        self.vis = [0] * self.n
        for i in range(self.n):
            if not self.vis[i]:
                self.dfs(i, self.graph, topo)

        # Second pass
        self.vis = [0] * self.n
        self.sccs = []

        for u in reversed(topo):
            if not self.vis[u]:
                comp = []
                self.dfs(u, self.rev_graph, comp)
                self.sccs.append(comp)

        return self.sccs
```

4.7. Heavy Light Decomposition.

```
class SegmentTree:
    def __init__(self, n):
        self.n = n
        self.tree = [0] * (4 * n)

    # Example: point update
    def update(self, idx, val, node=1, l=0, r=None):
        if r is None:
            r = self.n - 1
        if l == r:
            self.tree[node] = vala
            return
        mid = (l + r) // 2
        if idx <= mid:
            self.update(idx, val, node * 2, l, mid)
        else:
            self.update(idx, val, node * 2 + 1, mid + 1, r)
        self.tree[node] = self.tree[node * 2] + self.tree[node * 2 + 1]

    # Example: range query
    def query(self, ql, qr, node=1, l=0, r=None):
        if r is None:
            r = self.n - 1
        if qr < l or r < ql:
            return 0
        if ql <= l and r <= qr:
            return self.tree[node]
        mid = (l + r) // 2
        return self.query(ql, qr, node * 2, l, mid) + \
            self.query(ql, qr, node * 2 + 1, mid + 1, r)


class HeavyLightTree:
    def __init__(self, n):
        self.n = n
        self.adj = [[] for _ in range(n)]

        self.par = [-1] * n
        self.heavy = [-1] * n
        self.dep = [0] * n
        self.path_root = [0] * n
```

```
        self.pos = [0] * n

        self.segment_tree = SegmentTree(n)
        self.current_pos = 0

    def add_edge(self, u, v):
        self.adj[u].append(v)
        self.adj[v].append(u)

    def dfs(self, u):
        size = 1
        max_subtree_size = 0

        for v in self.adj[u]:
            if v != self.par[u]:
                self.par[v] = u
                self.dep[v] = self.dep[u] + 1
                subtree_size = self.dfs(v)

                if subtree_size > max_subtree_size:
                    max_subtree_size = subtree_size
                    self.heavy[u] = v

                size += subtree_size

        return size

    def decompose(self, u, root):
        self.path_root[u] = root
        self.pos[u] = self.current_pos
        self.current_pos += 1

        if self.heavy[u] != -1:
            self.decompose(self.heavy[u], root)

        for v in self.adj[u]:
            if v != self.par[u] and v != self.heavy[u]:
                self.decompose(v, v)

    def build(self, root=0):
        self.par[root] = root
        self.dep[root] = 0
        self.dfs(root)
        self.decompose(root, root)

    # Query path u -> v
    def query(self, u, v):
        res = 0
        while self.path_root[u] != self.path_root[v]:
            if self.dep[self.path_root[u]] <
↪   self.dep[self.path_root[v]]:
                u, v = v, u
            start = self.path_root[u]
            res += self.segment_tree.query(self.pos[start],
↪   self.pos[u])
            u = self.par[start]

        # Same path
        if self.dep[u] > self.dep[v]:
            u, v = v, u
        res += self.segment_tree.query(self.pos[u], self.pos[v])
        return res

    # Update node value
    def update(self, u, value):
        self.segment_tree.update(self.pos[u], value)
```

4.8. Euler Path/Cycle.

4.8.1. *Directed Euler.*

```
from collections import defaultdict


class DirectedEuler:
    def __init__(self, n):
        self.n = n
        self.adj = defaultdict(list)
        self.indeg = [0]*n
        self.outdeg = [0]*n
        self.edge_count = 0

    def add_edge(self, u, v):
        self.adj[u].append(v)
        self.outdeg[u] += 1
        self.indeg[v] += 1
        self.edge_count += 1

    def find_start_node(self):
        start = -1
        end = -1
        for i in range(self.n):
            if self.outdeg[i] - self.indeg[i] == 1:
                if start != -1:
                    return -1
                start = i
            elif self.indeg[i] - self.outdeg[i] == 1:
                if end != -1:
                    return -1
                end = i
            elif self.indeg[i] != self.outdeg[i]:
                return -1

        if start == -1:
            for i in range(self.n):
                if self.outdeg[i] > 0:
                    return i
        return start

    def get_euler_path(self):
        start = self.find_start_node()
        if start == -1:
            return None

        stack = [start]
        path = []

        local_adj = {u: self.adj[u][:] for u in self.adj}

        while stack:
            u = stack[-1]
            if u in local_adj and local_adj[u]:
                v = local_adj[u].pop()
                stack.append(v)
            else:
                path.append(stack.pop())

        if len(path) != self.edge_count + 1:
            return None

        return path[::-1]


    class UndirectedEuler:
        def __init__(self, n):
            self.n = n
            self.adj = defaultdict(list)
            self.edge_count = 0

        def add_edge(self, u, v):
            self.adj[u].append(v)
            self.adj[v].append(u)
            self.edge_count += 1

        def is_valid(self):
            odd = 0
            for i in range(self.n):
                if len(self.adj[i]) % 2 != 0:
                    odd += 1
            return odd == 0 or odd == 2

        def get_euler_path(self):
            if not self.is_valid():
                return None

            start = 0
            for i in range(self.n):
                if len(self.adj[i]) % 2 == 1:
                    start = i
                    break
                if len(self.adj[i]) > 0:
                    start = i

            stack = [start]
            path = []

            local_adj = {u: self.adj[u][:] for u in self.adj}

            while stack:
                u = stack[-1]
                if u in local_adj and local_adj[u]:
                    v = local_adj[u].pop()
                    local_adj[v].remove(u)
                    stack.append(v)
                else:
                    path.append(stack.pop())

            if len(path) != self.edge_count + 1:
                return None

            return path[::-1]
```

4.8.2. *Undirected Euler.*

```
from collections import defaultdict


class UndirectedEuler:
    def __init__(self, n):
        self.n = n
        self.adj = defaultdict(list)
        self.edge_count = 0

    def add_edge(self, u, v):
        self.adj[u].append(v)
        self.adj[v].append(u)
        self.edge_count += 1

    def is_valid(self):
        odd = 0
        for i in range(self.n):
            if len(self.adj[i]) % 2 != 0:
                odd += 1
        return odd == 0 or odd == 2

    def get_euler_path(self):
        if not self.is_valid():
            return None

        start = 0
        for i in range(self.n):
            if len(self.adj[i]) % 2 == 1:
                start = i
                break
            if len(self.adj[i]) > 0:
                start = i
```

```
    stack = [start]
    path = []

    local_adj = {u: self.adj[u][:] for u in self.adj}

    while stack:
        u = stack[-1]
        if u in local_adj and local_adj[u]:
            v = local_adj[u].pop()
            local_adj[v].remove(u)
            stack.append(v)
        else:
            path.append(stack.pop())

    if len(path) != self.edge_count + 1:
        return None

    return path[::-1]
```

4.9. Tree Isomorphism.

```
from collections import deque

def bfs(u, adj, n):
    vis = [False] * n
    pre = [-1] * n
    q = deque()

    q.append(u)
    vis[u] = True

    last = u

    while q:
        u = q.popleft()
        last = u

        for v in adj[u]:
            if not vis[v]:
                vis[v] = True
                pre[v] = u
                q.append(v)

    return last, pre

def tree_centers(r, adj, n):
    u, _ = bfs(r, adj, n)
    v, pre = bfs(u, adj, n)

    path = []
    while v != -1:
        path.append(v)
        v = pre[v]

    size = len(path)

    med = [path[size // 2]]
    if size % 2 == 0:
        med.append(path[size // 2 - 1])

    return med

def rootcode(u, adj, p, d, pr):
    children = []
    for v in adj[u]:
        if v != p:
            children.append(rootcode(v, adj, u, (d + 1) % len(pr), pr))

    children.sort()

    h = len(children) + 1
    for x in children:
        h = h * pr[d] + x

    return h

def treecode(root, adj, n, pr):
    c = tree_centers(root, adj, n)

    if len(c) == 1:
        return (rootcode(c[0], adj, -1, 0, pr) << 1) | 1
    else:
        return (rootcode(c[0], adj, -1, 0, pr) *
                rootcode(c[1], adj, -1, 0, pr)) << 1

def isomorphic(r1, adj1, r2, adj2, n1, n2, pr, rooted=False):
    if rooted:
        return rootcode(r1, adj1, -1, 0, pr) == rootcode(r2, adj2, -1,
↪ 0, pr)
    return treecode(r1, adj1, n1, pr) == treecode(r2, adj2, n2, pr)
```

4.10. Centroid Decomposition.

```
import sys
sys.setrecursionlimit(10**7)

INF = 10**9

class CentroidDecomposition:
    def __init__(self, n):
        self.n = n
        self.adj = [[] for _ in range(n)]

        self.LG = 20
        self.jmp = [[-1] * self.LG for _ in range(n)]
        self.path = [[INF] * self.LG for _ in range(n)]

        self.sz = [0] * n
        self.seph = [0] * n
        self.shortest = [INF] * n
        self.blocked = [False] * n

    def add_edge(self, a, b):
        self.adj[a].append(b)
        self.adj[b].append(a)

    def dfs(self, u, p):
        self.sz[u] = 1
        for v in self.adj[u]:
            if v != p and not self.blocked[v]:
                self.sz[u] += self.dfs(v, u)
        return self.sz[u]

    def find_centroid(self, u, p, n):
        for v in self.adj[u]:
            if v != p and not self.blocked[v] and self.sz[v] > n // 2:
                return self.find_centroid(v, u, n)
        return u

    def makepaths(self, sep, u, p, depth, h):
        self.jmp[u][h] = sep
        self.path[u][h] = depth

        for v in self.adj[u]:
            if v != p and not self.blocked[v]:
                self.makepaths(sep, v, u, depth + 1, h)

    def separate(self, h=0, u=0):
        self.dfs(u, -1)
        c = self.find_centroid(u, -1, self.sz[u])

        self.seph[c] = h
        self.makepaths(c, c, -1, 0, h)

        self.blocked[c] = True

        for v in self.adj[c]:
            if not self.blocked[v]:
                self.separate(h + 1, v)

    def paint(self, u):
        for h in range(self.seph[u] + 1):
            c = self.jmp[u][h]
            self.shortest[c] = min(self.shortest[c], self.path[u][h])

    def closest(self, u):
        ans = INF
        for h in range(self.seph[u] + 1):
            c = self.jmp[u][h]
            ans = min(ans, self.shortest[c] + self.path[u][h])
        return ans
```

4.11. Minimum Arborescence.

```
INF = 10**18

class Arborescence:
    def __init__(self, n):
        self.n = n
        self.edges = []

    def add_edge(self, u, v, w):
        self.edges.append((u, v, w))

    def solve(self, root):
        n = self.n
        edges = self.edges
        in_edge = [(-1, INF)] * n
        for u, v, w in edges:
            if v == root:
                continue
            if w < in_edge[v][1]:
                in_edge[v] = (u, w)

        in_edge[root] = (root, 0)
        vis = [-1] * n
        id_ = [-1] * n
        cycle_id = 0

        for i in range(n):
            v = i
            path = []

            while v != root and vis[v] == -1:
                vis[v] = i
                path.append(v)
                v = in_edge[v][0]

                if v == -1:
                    break

            if v != -1 and vis[v] == i:
                while True:
                    u = path.pop()
                    id_[u] = cycle_id
                    if u == v:
                        break
                cycle_id += 1

        if cycle_id == 0:
            return {v: in_edge[v] for v in range(n) if v != root}

        for i in range(n):
            if id_[i] == -1:
                id_[i] = cycle_id
                cycle_id += 1
```

```
        new_n = cycle_id
        new_edges = []

        for u, v, w in edges:
            nu, nv = id_[u], id_[v]
            if nu != nv:
                new_edges.append((nu, nv, w - in_edge[v][1]))

        contracted = Arborescence(new_n)
        contracted.edges = new_edges

        new_root = id_[root]
        res = contracted.solve(new_root)

        final = {}
        for v in range(n):
            if v == root:
                continue
            u, w = in_edge[v]
            final[v] = (u, w)

        return final
```

4.12. Biconnected Components.

```
class BiconnectedComponents:
    def __init__(self, n):
        self.n = n
        self.graph = [[] for _ in range(n)]
        self.timer = 0
        self.tin = [-1] * n
        self.low = [-1] * n
        self.stack = []
        self.bcc = []

    def add_edge(self, u, v):
        self.graph[u].append(v)
        self.graph[v].append(u)

    def dfs(self, v, parent):
        self.tin[v] = self.low[v] = self.timer
        self.timer += 1

        for to in self.graph[v]:
            if to == parent:
                continue

            if self.tin[to] == -1:

                self.stack.append((v, to))
                self.dfs(to, v)
                self.low[v] = min(self.low[v], self.low[to])

                if self.low[to] >= self.tin[v]:
                    component = []
                    while True:
                        e = self.stack.pop()
                        component.append(e)
                        if e == (v, to):
                            break
                    self.bcc.append(component)

            elif self.tin[to] < self.tin[v]:
                # back edge
                self.low[v] = min(self.low[v], self.tin[to])
                self.stack.append((v, to))

    def find_bcc(self):
        for i in range(self.n):
            if self.tin[i] == -1:
                self.dfs(i, -1)
        return self.bcc
```

4.13. Blossom.

```
from collections import deque

class Blossom:
    def __init__(self, n):
        self.n = n
        self.g = [[] for _ in range(n)]

        self.match = [-1] * n
        self.base = list(range(n))
        self.parent = [-1] * n
        self.used = [False] * n
        self.blossom = [False] * n

    def add_edge(self, u, v):
        if u == v:
            return  # avoid self-loops
        self.g[u].append(v)
        self.g[v].append(u)

    def lca(self, a, b):
        used = [False] * self.n
        while True:
            a = self.base[a]
            used[a] = True
            if self.match[a] == -1:
                break
            a = self.parent[self.match[a]]

        while True:
            b = self.base[b]
            if used[b]:
                return b
            b = self.parent[self.match[b]]

    def mark_blossom(self, v, b, children):
        while self.base[v] != b:
            self.blossom[self.base[v]] =
↪   self.blossom[self.base[self.match[v]]] = True
            self.parent[v] = children
            children = self.match[v]
            v = self.parent[self.match[v]]

    def find_path(self, root):
        self.used = [False] * self.n
        self.parent = [-1] * self.n
        for i in range(self.n):
            self.base[i] = i

        q = deque()
        q.append(root)
        self.used[root] = True

        while q:
            v = q.popleft()
            for u in self.g[v]:
                if self.base[v] == self.base[u] or self.match[v] == u:
                    continue

                if u == root or (self.match[u] != -1 and
↪   self.parent[self.match[u]] != -1):
                    curbase = self.lca(v, u)
                    self.blossom = [False] * self.n
                    self.mark_blossom(v, curbase, u)
                    self.mark_blossom(u, curbase, v)

                    for i in range(self.n):
                        if self.blossom[self.base[i]]:
                            self.base[i] = curbase
                            if not self.used[i]:
                                self.used[i] = True
                                q.append(i)
                    elif self.parent[u] == -1:
                        self.parent[u] = v
                        if self.match[u] == -1:
                            return u
                        u2 = self.match[u]
                        self.used[u2] = True
                        q.append(u2)
        return -1

    def max_matching(self):
        result = 0
        for i in range(self.n):
            if self.match[i] == -1:
                v = self.find_path(i)
                if v == -1:
                    continue

                # augment path
                while v != -1:
                    pv = self.parent[v]
                    nv = self.match[pv] if pv != -1 else -1
                    self.match[v] = pv
                    self.match[pv] = v
                    v = nv
                result += 1
        return result
```

5. Math I Algebra

5.0.1. *Generating Function Manager.*

```
MOD = 998244353

def mod_pow(base, exp):
    res = 1
    base %= MOD
    while exp:
        if exp & 1:
            res = res * base % MOD
        base = base * base % MOD
        exp >>= 1
    return res


class GF_Manager:
    DEPTH = 23

    def __init__(self):
        self.prim = [0] * (self.DEPTH + 1)
        self.prim_inv = [0] * (self.DEPTH + 1)
        self.two_inv = [0] * (self.DEPTH + 1)
        self.set_up_primitives()

    def set_up_primitives(self):
        self.prim[self.DEPTH] = 31
        self.prim_inv[self.DEPTH] = mod_pow(self.prim[self.DEPTH], MOD
↪   - 2)
        self.two_inv[self.DEPTH] = mod_pow(1 << self.DEPTH, MOD - 2) -

        for n in range(self.DEPTH - 1, -1, -1):
            self.prim[n] = self.prim[n + 1] * self.prim[n + 1] % MOD -
            self.prim_inv[n] = mod_pow(self.prim[n], MOD - 2)
            self.two_inv[n] = mod_pow(1 << n, MOD - 2)

    def NTT(self, A, n, is_inverse=False):
        if n == 0:
            return A[:]

        half = 1 << (n - 1)
```

```
        even = A[0::2]
        odd = A[1::2]

        even = self.NTT(even, n - 1, is_inverse)
        odd = self.NTT(odd, n - 1, is_inverse)

        res = [0] * (1 << n)
        w1 = self.prim_inv[n] if is_inverse else self.prim[n]
        w = 1

        for i in range(half):
            t = w * odd[i] % MOD
            res[i] = (even[i] + t) % MOD
            res[i + half] = (even[i] - t) % MOD
            w = w * w1 % MOD

        return res

    def mult(self, A, B):
        an, bn = len(A), len(B)
        degree = an + bn - 1

        n = 0
        while (1 << n) < degree:
            n += 1

        size = 1 << n
        tA = A + [0] * (size - an)
        tB = B + [0] * (size - bn)

        tA = self.NTT(tA, n)
        tB = self.NTT(tB, n)

        for i in range(size):
            tA[i] = tA[i] * tB[i] % MOD

        tA = self.NTT(tA, n, True)

        inv = self.two_inv[n]
        return [(x * inv) % MOD for x in tA[:degree]]

    def horners(self, F, x):
        ans = 0
        for coef in reversed(F):
            ans = (ans * x + coef) % MOD
        return ans
```

5.0.2. *Fast Fourier Transform.*

```
import math

class Poly:
    def __init__(self, a=0.0, b=0.0):
        self.a = a
        self.b = b

    def __add__(self, other):
        return Poly(self.a + other.a, self.b + other.b)

    def __sub__(self, other):
        return Poly(self.a - other.a, self.b - other.b)

    def __mul__(self, other):
        return Poly(
            self.a * other.a - self.b * other.b,
            self.a * other.b + self.b * other.a
        )

    def __repr__(self):
        return f"({self.a}+{self.b}i)"

def fft_recursive(inp, n, s):
    if n == 1:
        return [inp[0]]

    half = n // 2

    even = fft_recursive(inp, half, s * 2)
    odd = fft_recursive(inp[s:], half, s * 2)

    res = [None] * n
    w = Poly(1, 0)
    wn = Poly(math.cos(math.pi / half), math.sin(math.pi / half))

    for i in range(half):
        t = w * odd[i]
        res[i] = even[i] + t
        res[i + half] = even[i] - t
        w = w * wn

    return res

def fft(p):
    return fft_recursive(p, len(p), 1)

def inverse_fft(p):
    n = len(p)

    p = [Poly(x.a, -x.b) for x in p]

    p = fft(p)

    res = []
    for x in p:
        res.append(Poly(x.a / n, -x.b / n))

    return res
```

5.0.3. *Fft Polynomial Multiplication.*

```
def fft_multiply(a, b):
    an, bn = len(a), len(b)
    degree = an + bn - 1

    n = 1
    while n < degree:
        n <<= 1

    A = [Poly(x, 0) for x in a] + [Poly(0, 0)] * (n - an)
    B = [Poly(x, 0) for x in b] + [Poly(0, 0)] * (n - bn)

    A = fft(A)
    B = fft(B)

    for i in range(n):
        A[i] = A[i] * B[i]

    A = inverse_fft(A)

    result = [int(round(A[i].a)) for i in range(degree)]
    return result
```

5.0.4. *Number Theoretic Transform.*

```
MOD = 998244353
PRIMITIVE_ROOT = 3

def mod_pow(base, exp, mod=MOD):
    res = 1
    base %= mod
    while exp:
        if exp & 1:
            res = res * base % mod
        base = base * base % mod
        exp >>= 1
    return res

class Num:
    def __init__(self, x=0):
        self.x = x % MOD

    def __add__(self, other):
        return Num(self.x + other.x)

    def __sub__(self, other):
        return Num(self.x - other.x)

    def __mul__(self, other):
        return Num(self.x * other.x)

    def __truediv__(self, other):
        return self * other.inv()

    def inv(self):
        return Num(mod_pow(self.x, MOD - 2))

    def pow(self, p):
        return Num(mod_pow(self.x, p))

    def __repr__(self):
        return str(self.x)

def ntt(a, invert=False):
    n = len(a)

    j = 0
    for i in range(1, n):
        bit = n >> 1
        while j & bit:
            j ^= bit
            bit >>= 1
        j |= bit
        if i < j:
            a[i], a[j] = a[j], a[i]

    length = 2
    while length <= n:
        wlen = mod_pow(PRIMITIVE_ROOT, (MOD - 1) // length)
        if invert:
            wlen = mod_pow(wlen, MOD - 2)

        for i in range(0, n, length):
            w = 1
            half = length // 2
            for j in range(i, i + half):
                u = a[j]
                v = Num(a[j + half].x * w % MOD)
                a[j] = u + v
                a[j + half] = u - v
                w = w * wlen % MOD

        length <<= 1

    if invert:
        inv_n = mod_pow(n, MOD - 2)
        for i in range(n):
            a[i] = Num(a[i].x * inv_n % MOD)

def multiply(A, B):
    n = 1
    while n < len(A) + len(B):
        n <<= 1

    fa = [Num(x) for x in A] + [Num(0)] * (n - len(A))
    fb = [Num(x) for x in B] + [Num(0)] * (n - len(B))
```

```
--------------------------------------------------------------------
--- ntt(fa) ------------------------------------------------------
--- ntt(fb) ------------------------------------------------------
--------------------------------------------------------------------
--- for i in range(n): -------------------------------------------
------- fa[i] = fa[i] * fb[i] ----------------------------------
--------------------------------------------------------------------
--- ntt(fa, True) ------------------------------------------------
--------------------------------------------------------------------
--- return [fa[i].x for i in range(len(A) + len(B) - 1)] ----------
--------------------------------------------------------------------
def poly_inv(x, l):
--- if l == 1: ---------------------------------------------------
------- return [mod_pow(x[0], MOD - 2)] -------------------------
--------------------------------------------------------------------
--- y = poly_inv(x, (l + 1) // 2) --------------------------------
--------------------------------------------------------------------
--- n = 1 --------------------------------------------------------
--- while n < 2 * l: ---------------------------------------------
------- n <<= 1 ------------------------------------------------
--------------------------------------------------------------------
--- A = x[:l] + [0] * (n - l) ------------------------------------
--- B = y[:] + [0] * (n - len(y)) --------------------------------
--------------------------------------------------------------------
--- A = [Num(v) for v in A] --------------------------------------
--- B = [Num(v) for v in B] --------------------------------------
--------------------------------------------------------------------
--- ntt(A) -------------------------------------------------------
--- ntt(B) -------------------------------------------------------
--------------------------------------------------------------------
--- for i in range(n): -------------------------------------------
------- B[i] = B[i] * (Num(2) - A[i] * B[i]) -------------------
--------------------------------------------------------------------
--- ntt(B, True) -------------------------------------------------
--------------------------------------------------------------------
--- return [B[i].x % MOD for i in range(l)] ----------------------
--------------------------------------------------------------------
def poly_sqrt(x, l):
--- if l == 1: ---------------------------------------------------
------- assert x[0] == 1 ---------------------------------------
------- return [1] ---------------------------------------------
--------------------------------------------------------------------
--- y = poly_sqrt(x, l // 2) -------------------------------------
--- inv_y = poly_inv(y, l // 2) ----------------------------------
--------------------------------------------------------------------
--- n = 1 --------------------------------------------------------
--- while n < 2 * l: ---------------------------------------------
------- n <<= 1 ------------------------------------------------
--------------------------------------------------------------------
--- T1 = x[:l] + [0] * (n - l) -----------------------------------
--- T2 = inv_y[:] + [0] * (n - len(inv_y)) -----------------------
--------------------------------------------------------------------
--- T1 = [Num(v) for v in T1] ------------------------------------
--- T2 = [Num(v) for v in T2] ------------------------------------
--------------------------------------------------------------------
--- ntt(T1) ------------------------------------------------------
--- ntt(T2) ------------------------------------------------------
--------------------------------------------------------------------
--- for i in range(n): -------------------------------------------
------- T2[i] = T1[i] * T2[i] ----------------------------------
--------------------------------------------------------------------
--- ntt(T2, True) ------------------------------------------------
--------------------------------------------------------------------
--- inv2 = (MOD + 1) // 2 ----------------------------------------
--- res = [] -----------------------------------------------------
--- for i in range(l): -------------------------------------------
------- val = (y[i] + T2[i].x) * inv2 % MOD --------------------
------- res.append(val) ----------------------------------------
--------------------------------------------------------------------
--- return res ---------------------------------------------------
```

5.0.5. *Polynomial Long Division.*

```
MOD = 998244353 ----------------------------------------------------
G = 3 --------------------------------------------------------------
--------------------------------------------------------------------
def mod_pow(a, e): -------------------------------------------------
--- r = 1 --------------------------------------------------------
--- while e: -----------------------------------------------------
------- if e & 1: ----------------------------------------------
----------- r = r * a % MOD ------------------------------------
------- a = a * a % MOD ----------------------------------------
------- e >>= 1 ------------------------------------------------
--- return r -----------------------------------------------------
--------------------------------------------------------------------
def bit_reverse(a): ------------------------------------------------
--- n = len(a) ---------------------------------------------------
--- j = 0 --------------------------------------------------------
--- for i in range(1, n): ----------------------------------------
------- bit = n >> 1 -------------------------------------------
------- while j & bit: -----------------------------------------
----------- j ^= bit -------------------------------------------
----------- bit >>= 1 ------------------------------------------
------- j ^= bit -----------------------------------------------
------- if i < j: ----------------------------------------------
----------- a[i], a[j] = a[j], a[i] ----------------------------
--------------------------------------------------------------------
--------------------------------------------------------------------
def ntt(a, invert=False): ------------------------------------------
--- n = len(a) ---------------------------------------------------
--- bit_reverse(a) -----------------------------------------------
--------------------------------------------------------------------
--- length = 2 ---------------------------------------------------
--- while length <= n: -------------------------------------------
------- wlen = mod_pow(G, (MOD - 1) // length) -----------------
------- if invert: ---------------------------------------------
----------- wlen = mod_pow(wlen, MOD - 2) ----------------------
--------------------------------------------------------------------
------- for i in range(0, n, length): --------------------------
----------- w = 1 ----------------------------------------------
----------- half = length // 2 ---------------------------------
----------- for j in range(i, i + half): -----------------------
--------------- u = a[j] -------------------------------------
--------------- v = a[j + half] * w % MOD --------------------
--------------- a[j] = (u + v) % MOD -------------------------
--------------- a[j + half] = (u - v) % MOD ------------------
--------------- w = w * wlen % MOD ---------------------------
--------------------------------------------------------------------
------- length <<= 1 -------------------------------------------
--------------------------------------------------------------------
--- if invert: ---------------------------------------------------
------- inv_n = mod_pow(n, MOD - 2) ----------------------------
------- for i in range(n): -------------------------------------
----------- a[i] = a[i] * inv_n % MOD --------------------------
--------------------------------------------------------------------
def multiply(a, b): ------------------------------------------------
--- n = 1 --------------------------------------------------------
--- while n < len(a) + len(b): -----------------------------------
------- n <<= 1 ------------------------------------------------
--------------------------------------------------------------------
--- fa = a[:] + [0] * (n - len(a)) -------------------------------
--- fb = b[:] + [0] * (n - len(b)) -------------------------------
--------------------------------------------------------------------
--- ntt(fa) ------------------------------------------------------
--- ntt(fb) ------------------------------------------------------
--------------------------------------------------------------------
--- for i in range(n): -------------------------------------------
------- fa[i] = fa[i] * fb[i] % MOD ----------------------------
--------------------------------------------------------------------
--- ntt(fa, True) ------------------------------------------------
--------------------------------------------------------------------
--- return fa[:len(a) + len(b) - 1] -------------------------------
--------------------------------------------------------------------
def poly_inv(f, n): ------------------------------------------------
--- if n == 1: ---------------------------------------------------
------- return [mod_pow(f[0], MOD - 2)] -------------------------
--------------------------------------------------------------------
--- m = (n + 1) // 2 ---------------------------------------------
--- g = poly_inv(f, m) -------------------------------------------
--------------------------------------------------------------------
--- size = 1 -----------------------------------------------------
--- while size < 2 * n: ------------------------------------------
------- size <<= 1 ---------------------------------------------
--------------------------------------------------------------------
--- a = f[:n] + [0] * (size - len(f[:n])) ------------------------
--- g = g + [0] * (size - len(g)) --------------------------------
--------------------------------------------------------------------
--- ntt(a) -------------------------------------------------------
--- ntt(g) -------------------------------------------------------
--------------------------------------------------------------------
--- for i in range(size): ----------------------------------------
------- g[i] = g[i] * (2 - a[i] * g[i] % MOD) % MOD ------------
--------------------------------------------------------------------
--- ntt(g, True) -------------------------------------------------
--------------------------------------------------------------------
--- return g[:n] -------------------------------------------------
--------------------------------------------------------------------
def poly_divide(A, B): ---------------------------------------------
--- n, m = len(A), len(B) ----------------------------------------
--------------------------------------------------------------------
--- if n < m: ----------------------------------------------------
------- return [], A[:] ----------------------------------------
--------------------------------------------------------------------
--- k = n - m + 1 ------------------------------------------------
--------------------------------------------------------------------
--- A_rev = A[::-1] ----------------------------------------------
--- B_rev = B[::-1] ----------------------------------------------
--------------------------------------------------------------------
--- B_inv = poly_inv(B_rev, k) -----------------------------------
--------------------------------------------------------------------
--- Q_rev = multiply(A_rev, B_inv)[:k] ---------------------------
--- Q = Q_rev[::-1] ----------------------------------------------
--------------------------------------------------------------------
--- BQ = multiply(B, Q) ------------------------------------------
--------------------------------------------------------------------
--- R = [(A[i] - (BQ[i] if i < len(BQ) else 0)) % MOD for i in
↪   range(n)]
--------------------------------------------------------------------
--- while Q and Q[-1] == 0: --------------------------------------
------- Q.pop() ------------------------------------------------
--- while R and R[-1] == 0: --------------------------------------
------- R.pop() ------------------------------------------------
--------------------------------------------------------------------
--- return Q, R --------------------------------------------------
```

5.0.6. *Matrix Multiplication.*

```
MOD = 998244353 ----------------------------------------------------
--------------------------------------------------------------------
def multiply(A, B): ------------------------------------------------
--- p = len(A) ---------------------------------------------------
--- q = len(A[0]) ------------------------------------------------
--- r = len(B[0]) ------------------------------------------------
--------------------------------------------------------------------
--- if len(B) != q: ----------------------------------------------
------- raise ValueError("Dimension mismatch") ------------------
--------------------------------------------------------------------
--- AB = [[0] * r for _ in range(p)] -----------------------------
--------------------------------------------------------------------
--- for i in range(p): -------------------------------------------
------- for j in range(q): -------------------------------------
----------- for k in range(r): ---------------------------------
--------------- AB[i][k] = (AB[i][k] + A[i][j] * B[j][k]) % MOD ----
--------------------------------------------------------------------
--- return AB ----------------------------------------------------
```

5.0.7. *Matrix Power.*

```
MOD = 998244353

def multiply(A, B):
    p, q, r = len(A), len(A[0]), len(B[0])

    res = [[0] * r for _ in range(p)]

    for i in range(p):
        for j in range(q):
            for k in range(r):
                res[i][k] = (res[i][k] + A[i][j] * B[j][k]) % MOD

    return res

def identity(n):
    I = [[0] * n for _ in range(n)]
    for i in range(n):
        I[i][i] = 1
    return I

def power(B, e):
    n = len(B)

    result = identity(n)
    base = [row[:] for row in B]

    while e > 0:
        if e & 1:
            result = multiply(result, base)
        base = multiply(base, base)
        e >>= 1

    return result
```

5.0.8. *Gauss Jordan Matrix Determinant.*

```
EPS = 1e-9

def gauss_jordan(A):
    n = len(A)
    m = len(A[0])

    singular = False

    i = 0
    for p in range(m):
        if i >= n:
            break

        pivot = i
        for k in range(i + 1, n):
            if abs(A[k][p]) > abs(A[pivot][p]):
                pivot = k

        if abs(A[pivot][p]) < EPS:
            singular = True
            continue

        A[i], A[pivot] = A[pivot], A[i]

        div = A[i][p]
        for j in range(p, m):
            A[i][j] /= div

        for k in range(n):
            if k == i:
                continue
            factor = A[k][p]
            for j in range(p, m):
                A[k][j] -= factor * A[i][j]

        i += 1

    return not singular

def apply(A, x):
    return [sum(A[i][j] * x[j] for j in range(len(x))) for i in
    ↪  range(len(A))]
```

6. Math II Combinatorics

6.0.1. *Lucas Theorem.*

```
_fact_cache = []
_last_p = -1

def lucas(n, k, p):
    if k < 0 or k > n:
        return 0
    if k == 0 or n == k:
        return 1

    global _fact_cache, _last_p
    if _last_p != p:
        _fact_cache = [1] * p
        for i in range(2, p):
            _fact_cache[i] = (_fact_cache[i - 1] * i) % p
        _last_p = p

    res_num = 1
    res_den = 1

    while n > 0 or k > 0:
        ni, ki = n % p, k % p
        if ki > ni:
            return 0
        res_num = (res_num * _fact_cache[ni]) % p
        res_den = (res_den * _fact_cache[ki] * _fact_cache[ni - ki]) %
        ↪  p
        n //= p
        k //= p
    return (res_num * pow(res_den, p - 2, p)) % p
# Input Format: print(lucas(n, k, p))
```

6.0.2. *Catalan Numbers.*

```
def catalan(n):
    if (n == 0 or n == 1):
        return 1

    dp = [0] * (n + 1)
    dp[0] = dp[1] = 1

    for i in range(2, n + 1):
        for j in range(i):
            dp[i] += dp[j] * dp[i-j-1]

    return dp[n]

# for i in range(10):
#     print(catalan(i))
```

6.0.3. *Kth Permutation.*

```
#fact = [1, 1, 2, 6, 24, 120, 720, 5040, 40320, 362880]

def findKthPermutation(n, k):
    nums = [str(i) for i in range(1, n + 1)]

    fact = [1] * n
    for i in range(1, n):
        fact[i] = fact[i - 1] * i

    k -= 1

    res = []

    for i in range(n - 1, -1, -1):
        idx = k // fact[i]
        k %= fact[i]

        res.append(nums.pop(idx))

    return ''.join(res)
```

6.0.4. *Factoradics.*

```
def factoradic(arr):
    n = len(arr)
    ft = FenwickTree(n)
    for i in range(1, n + 1):
        ft.add(i, 1)

    res = []
    for val in arr:
        bit_val = val + 1
        s = ft.query(bit_val - 1)
        ft.add(bit_val, -1)
        res.append(s)
    return res

def permute(fact, n):
    ft = FenwickTree(n)
    for i in range(1, n + 1):
        ft.add(i, 1)

    res = []
    for val in fact:
        idx = ft.find_kth(val)
        ft.add(idx, -1)
        res.append(idx - 1)
    return res
```

7. Math III Number Theory

7.0.1. *Gcd Subset Counter.*

```
def gcd_subset_count(arr):
    n = len(arr)
    mx = max(arr)

    f = [0] * (mx + 1)
    for x in arr:
        f[x] += 1

    gcnt = [0] * (mx + 1)

    for i in range(mx, 0, -1):
        add = 0

        for j in range(i, mx + 1, i):
            add += f[j]

        total = (1 << add) - 1  # 2^add - 1

        sub = 0
        for j in range(2 * i, mx + 1, i):
            sub += gcnt[j]

        gcnt[i] = total - sub

    return gcnt
```

7.0.2. *Linear Diophantine.*

```
def gcd(a, b):
    if a == 0:
        return b
```

```
    return gcd(b % a, a)

def isPossible(a, b, c):
    g = gcd(a, b)
    
    return c % g == 0
```

7.0.3. *Chinese Remainder Theorem.*

```
def gcd_extended(a, b):
    if a == 0:
        return b, 0, 1
    gcd, x1, y1 = gcd_extended(b % a, a)
    x = y1 - (b // a) * x1
    y = x1
    return gcd, x, y

def find_min_x(num, rem):
    prod = 1
    for n in num:
        prod *= n

    result = 0
    for i in range(len(num)):
        prod_i = prod // num[i]
        _, inv_i, _ = gcd_extended(prod_i, num[i])
        result += rem[i] * prod_i * inv_i

    return result % prod
```

7.0.4. *Euler Totient.*

```
def totient(n):
    if n <= 1:
        return 1

    tot = n
    i = 2

    while i * i <= n:
        if n % i == 0:
            tot -= tot // i
            while n % i == 0:
                n //= i
        i += 1

    if n > 1:
        tot -= tot // n

    return tot
```

7.0.5. *Extended Euclidean Algorithm.*

```
def mod(x, m):
    if m == 0:
        return 0
    if m < 0:
        m = -m
    return (x % m + m) % m

def extended_euclid(a, b):
    if b == 0:
        return a, 1, 0

    g, x1, y1 = extended_euclid(b, a % b)

    x = y1
    y = x1 - (a // b) * y1

    return g, x, y
```

7.0.6. *Modular Exponentiation.*

```
def mod_pow(b, e, m):
    res = 1 % m

    while e > 0:
        if e & 1:
            res = (res * b) % m
        b = (b * b) % m
        e >>= 1

    return res
```

7.0.7. *Mod Inverse.*

```
def extended_euclid(a, b):
    if b == 0:
        return a, 1, 0

    g, x1, y1 = extended_euclid(b, a % b)

    x = y1
    y = x1 - (a // b) * y1

    return g, x, y

def modinv(a, m):
    g, x, y = extended_euclid(a, m)

    if g != 1:
        return 0  # no inverse

    return x % m
```

7.0.8. *Modulo Solver.*

```
def extended_euclid(a, b):
    if b == 0:
        return a, 1, 0

    g, x1, y1 = extended_euclid(b, a % b)

    x = y1
    y = x1 - (a // b) * y1

    return g, x, y

def modsolver(a, b, m):
    g, x, y = extended_euclid(a, m)

    if b % g != 0:
        return (-1, -1)

    m_reduced = m // g

    x0 = (x * (b // g)) % m_reduced

    return (x0, m_reduced)
```

7.0.9. *Primitive Root.*

```
def primitive_root(m):
    if m == 2:
        return 1

    phi = m - 1

    factors = set()
    x = phi
    i = 2

    while i * i <= x:
        if x % i == 0:
            factors.add(i)
            while x % i == 0:
                x //= i
        i += 1

    if x > 1:
        factors.add(x)

    for g in range(2, m):
        ok = True
        for f in factors:
            if mod_pow(g, phi // f, m) == 1:
                ok = False
                break
        if ok:
            return g

    return -1
```

7.0.10. *Josephus.*

```
def josephus(n, k):
    res = 0
    for i in range(2, n + 1):
        res = (res + k) % i
    return res
```

8. Math IV Numerical Methods

8.0.1. *Fast Square Testing.*

```
import math

class FastSquareTester:
    def __init__(self):
        self.M = 0
        self.init_is_square()

    def init_is_square(self):
        for i in range(64):
            self.M |= (1 << (i * i % 64))

    def is_square(self, x):
        if x < 0: return False
        if x == 0: return True

        if not (self.M & (1 << (x & 63))):
            return False

        c = (x & -x).bit_length() - 1
        if c & 1:
            return False

        temp_x = x >> c
        if (temp_x & 7) != 1:
            return False

        r = int(math.isqrt(temp_x))
        return r * r == temp_x

tester = FastSquareTester()
```

8.0.2. *Simpson Integration.*

```
def f(x):
    return x ** 2
def simpson_integration(a, b, n=1000000):
    if n % 2 != 0:
        n += 1

    h = (b - a) / n
    s = f(a) + f(b)
```

```
--- for i in range(1, n):
------- x = a + h * i
------- if i % 2 == 1:
----------- s += 4 * f(x)
------- else:
----------- s += 2 * f(x)

--- return s * (h / 3)
```

9. Strings

9.1. Longest Common Prefix.

```
def build_lcp(s, sa):
--- n = len(s)
--- rank = [0] * n
--- lcp = [0] * n

--- for i in range(n):
------- rank[sa[i]] = i

--- k = 0
--- for i in range(n):
------- if rank[i] == 0:
----------- k = 0
----------- continue

------- j = sa[rank[i] - 1]

------- while i + k < n and j + k < n and s[i + k] == s[j + k]:
----------- k += 1

------- lcp[rank[i]] = k

------- if k > 0:
----------- k -= 1

--- return lcp
```

9.2. Hasher.

```
class Hasher:
--- def __init__(self, s, bases=[31, 37], mod=10 ** 9 + 7):
------- self.bases = bases
------- self.mod = mod
------- self.n = len(s)
------- self.num_hashes = len(bases)
------- self.p_pow = [[1] * (self.n + 1) for _ in
↪  range(self.num_hashes)]
------- self.h_ans = [[0] * (self.n + 1) for _ in
↪  range(self.num_hashes)]

------- for i, b in enumerate(self.bases):
----------- for j in range(self.n):
--------------- self.p_pow[i][j + 1] = (self.p_pow[i][j] * b) %
↪  self.mod
--------------- self.h_ans[i][j + 1] = (self.h_ans[i][j] + s[j] *
↪  self.p_pow[i][j]) % self.mod

--- def get_hash(self, l, r):
------- return tuple((self.h_ans[i][r + 1] - self.h_ans[i][l]) %
↪  self.mod
------------------- for i in range(self.num_hashes))

--- def are_equal(self, l1, r1, l2, r2):
------- if (r1 - l1) != (r2 - l2): return False

------- h1 = self.get_hash(l1, r1)
------- h2 = self.get_hash(l2, r2)

------- return all((h1[i] * self.p_pow[i][l2]) % self.mod ==
------------------- (h2[i] * self.p_pow[i][l1]) % self.mod
------------------- for i in range(self.num_hashes))
```

9.3. Z Algorithm.

9.4. Aho Corasick Trie.

```
from collections import deque
import random
import string

class Node:
--- def __init__(self):
------- self.next = {}
------- self.fail = None
------- self.count = 0

--- def add(self, s):
------- node = self
------- for c in s:
----------- if c not in node.next:
--------------- node.next[c] = Node()
----------- node = node.next[c]
------- node.count += 1

--- def prepare(self):
------- root = self
------- q = deque()

------- root.fail = root

------- for child in root.next.values():
----------- child.fail = root
----------- q.append(child)

------- while q:
----------- head = q.popleft()

----------- for c, nxt in head.next.items():
--------------- f = head.fail

--------------- while f != root and c not in f.next:
------------------- f = f.fail

--------------- nxt.fail = f.next[c] if c in f.next else root

--------------- nxt.count += nxt.fail.count

--------------- q.append(nxt)

--- def search(self, s):
------- root = self
------- p = self
------- ans = 0

------- for c in s:
----------- while p != root and c not in p.next:
--------------- p = p.fail

----------- if c in p.next:
--------------- p = p.next[c]
--------------- ans += p.count

------- return ans
```

9.5. Palindromes.

9.5.1. *Palindromic Tree.*

```
import sys

N = 200000
MAX = N * 2 + 5

par = [-1] * MAX
len_arr = [0] * MAX
node = [0] * MAX
cs = [0] * MAX
cnt = [0] * (N + 5)

child = [[-1] * 128 for _ in range(MAX)]
size = 0

def newNode(p=-1):
--- global size
--- cnt[size] = 0
--- par[size] = p
--- len_arr[size] = 0 if p == -1 else len_arr[p] + 2

--- for i in range(128):
------- child[size][i] = -1

--- size += 1
--- return size - 1

def get(i, c):
--- if child[i][c] == -1:
------- child[i][c] = newNode(i)
--- return child[i][c]

def manachers(s):
--- global size

--- n = len(s)
--- cn = n * 2 + 1

--- for i in range(n):
------- cs[i * 2] = -1
------- cs[i * 2 + 1] = ord(s[i])

--- size = 0

--- odd = newNode()
--- even = newNode()

--- len_arr[odd] = -1

--- cen = 0
--- rad = 0

--- for i in range(cn):
------- node[i] = even if i % 2 == 0 else get(odd, cs[i])

--- for i in range(1, cn):
------- if i > rad:
----------- L = i - 1
----------- R = i + 1
------- else:
----------- M = cen * 2 - i
----------- node[i] = node[M]

----------- if len_arr[node[M]] < rad - i:
--------------- L = -1
--------------- R = 0
----------- else:
--------------- R = rad + 1
--------------- L = i * 2 - R
```

```
----------------------------------------------------------------
--------------- while len_arr[node[i]] > rad - i: ----------------
------------------- node[i] = par[node[i]] -----------------------
----------------------------------------------------------------
------- while L >= 0 and R < cn and cs[L] == cs[R]: -------------
----------- if cs[L] != -1: ------------------------------------
--------------- node[i] = get(node[i], cs[L]) ------------------
----------- L -= 1 ---------------------------------------------
----------- R += 1 ---------------------------------------------
----------------------------------------------------------------
------- cnt[node[i]] += 1 ----------------------------------------
----------------------------------------------------------------
------- if i + len_arr[node[i]] > rad: ---------------------------
----------- rad = i + len_arr[node[i]] -------------------------
----------- cen = i --------------------------------------------
----------------------------------------------------------------
--- for i in range(size - 1, -1, -1): ------------------------
------- if par[i] != -1: -----------------------------------------
----------- cnt[par[i]] += cnt[i] ------------------------------
----------------------------------------------------------------
----------------------------------------------------------------
def countUniquePalindromes(s): ---------------------------------
--- manachers(s) ---------------------------------------------
--- return size ----------------------------------------------
----------------------------------------------------------------
----------------------------------------------------------------
def countAllPalindromes(s): ------------------------------------
--- manachers(s) ---------------------------------------------
--- return sum(cnt[:size]) -----------------------------------
----------------------------------------------------------------
----------------------------------------------------------------
def longestPalindrome(s): --------------------------------------
--- manachers(s) ---------------------------------------------
----------------------------------------------------------------
--- n = len(s) -----------------------------------------------
--- cn = n * 2 + 1 -------------------------------------------
----------------------------------------------------------------
--- mx = 0 ---------------------------------------------------
--- for i in range(1, cn): -----------------------------------
------- if len_arr[node[mx]] < len_arr[node[i]]: -----------------
----------- mx = i ---------------------------------------------
----------------------------------------------------------------
--- pos = (mx - len_arr[node[mx]]) // 2 ----------------------
--- return s[pos:pos + len_arr[node[mx]]] --------------------
```

9.5.2. *Eertree.*

```
class Node: ----------------------------------------------------
--- def __init__(self, start=0, end=0, length=0, link=0): ----
------- self.start = start ---------------------------------------
------- self.end = end -------------------------------------------
------- self.len = length ----------------------------------------
------- self.link = link -----------------------------------------
------- self.next = [0] * 26 -------------------------------------
----------------------------------------------------------------
----------------------------------------------------------------
class Eertree: -------------------------------------------------
--- def __init__(self): --------------------------------------
------- self.tree = [] -------------------------------------------
----------------------------------------------------------------
------- self.tree.append(Node()) ---------------------------------
----------------------------------------------------------------
------- self.tree.append(Node(0, 0, -1, 1)) ----------------------
----------------------------------------------------------------
------- self.tree.append(Node(0, 0, 0, 1)) -----------------------
----------------------------------------------------------------
------- self.cur = 1 ---------------------------------------------
------- self.ptr = 2 ---------------------------------------------
----------------------------------------------------------------
--- def get_link(self, v, s, i): -----------------------------
------- while True: ----------------------------------------------
----------- cur_len = self.tree[v].len -------------------------
----------- if i - cur_len - 1 >= 0 and s[i] == s[i - cur_len - 1]: --
--------------- return v -------------------------------------
----------- v = self.tree[v].link ------------------------------
----------------------------------------------------------------
--- def add_char(self, s, i): --------------------------------
------- cur = self.cur -------------------------------------------
------- cur = self.get_link(cur, s, i) ---------------------------
----------------------------------------------------------------
------- c = ord(s[i]) - ord('a') ---------------------------------
----------------------------------------------------------------
------- if self.tree[cur].next[c]: -------------------------------
----------- self.cur = self.tree[cur].next[c] ------------------
----------- return ---------------------------------------------
----------------------------------------------------------------
------- self.ptr += 1 --------------------------------------------
------- self.tree[cur].next[c] = self.ptr ------------------------
----------------------------------------------------------------
------- length = self.tree[cur].len + 2 --------------------------
------- self.tree.append(Node(i - length + 1, i, length, 0)) ---------
----------------------------------------------------------------
------- new_node = self.ptr --------------------------------------
----------------------------------------------------------------
------- if self.tree[new_node].len == 1: -------------------------
----------- self.tree[new_node].link = 2 -----------------------
------- else: ----------------------------------------------------
----------- tmp = self.tree[cur].link --------------------------
----------- tmp = self.get_link(tmp, s, i) ---------------------
----------- self.tree[new_node].link = self.tree[tmp].next[c] --------
----------------------------------------------------------------
------- self.cur = new_node --------------------------------------
----------------------------------------------------------------
--- def build(self, s): --------------------------------------
------- for i in range(len(s)): ----------------------------------
----------- self.add_char(s, i) --------------------------------
```

9.6. Knuth Morris Pratt.

```
def build_kmp(f): ----------------------------------------------
--- n = len(f) -----------------------------------------------
--- par = [0] * (n + 1) --------------------------------------
----------------------------------------------------------------
--- par[0] = -1 ----------------------------------------------
--- if n > 0: ------------------------------------------------
------- par[1] = 0 -----------------------------------------------
----------------------------------------------------------------
--- i, j = 2, 0 ----------------------------------------------
----------------------------------------------------------------
--- while i <= n: --------------------------------------------
------- if f[i - 1] == f[j]: -------------------------------------
----------- j += 1 ---------------------------------------------
----------- par[i] = j -----------------------------------------
----------- i += 1 ---------------------------------------------
------- elif j > 0: ----------------------------------------------
----------- j = par[j] -----------------------------------------
------- else: ----------------------------------------------------
----------- par[i] = 0 -----------------------------------------
----------- i += 1 ---------------------------------------------
----------------------------------------------------------------
--- return par -----------------------------------------------
----------------------------------------------------------------
----------------------------------------------------------------
def kmp(s, f): -------------------------------------------------
--- par = build_kmp(f) ---------------------------------------
----------------------------------------------------------------
--- i = 0 ----------------------------------------------------
--- j = 0 ----------------------------------------------------
--- ans = [] -------------------------------------------------
----------------------------------------------------------------
--- n, m = len(s), len(f) ------------------------------------
----------------------------------------------------------------
--- while i + j < n: -----------------------------------------
------- if s[i + j] == f[j]: -------------------------------------
----------- j += 1 ---------------------------------------------
----------- if j == m: -----------------------------------------
--------------- ans.append(i) --------------------------------
--------------- i += j - par[j] ------------------------------
--------------- if j > 0: ------------------------------------
------------------- j = par[j] -----------------------------
------- else: ----------------------------------------------------
----------- i += j - par[j] ------------------------------------
----------- if j > 0: ------------------------------------------
--------------- j = par[j] -----------------------------------
----------------------------------------------------------------
--- return ans -----------------------------------------------
```

9.7. Trie.

```
class Node: ----------------------------------------------------
--- def __init__(self): --------------------------------------
------- self.children = {} ---------------------------------------
------- self.prefixes = 0 ----------------------------------------
------- self.words = 0 -------------------------------------------
----------------------------------------------------------------
class Trie: ----------------------------------------------------
--- def __init__(self): --------------------------------------
------- self.root = Node() ---------------------------------------
----------------------------------------------------------------
--- def insert(self, seq): -----------------------------------
------- cur = self.root ------------------------------------------
----------------------------------------------------------------
------- for i in range(len(seq) + 1): ----------------------------
----------- cur.prefixes += 1 ----------------------------------
----------------------------------------------------------------
----------- if i == len(seq): ----------------------------------
--------------- cur.words += 1 -------------------------------
--------------- break ----------------------------------------
----------------------------------------------------------------
----------- head = seq[i] --------------------------------------
----------------------------------------------------------------
----------- if head not in cur.children: -----------------------
--------------- cur.children[head] = Node() ------------------
----------------------------------------------------------------
----------- cur = cur.children[head] ---------------------------
----------------------------------------------------------------
--- def countMatches(self, seq): -----------------------------
------- cur = self.root ------------------------------------------
----------------------------------------------------------------
------- for c in seq: --------------------------------------------
----------- if c not in cur.children: --------------------------
--------------- return 0 ------------------------------------
----------- cur = cur.children[c] ------------------------------
----------------------------------------------------------------
------- return cur.words -----------------------------------------
----------------------------------------------------------------
--- def countPrefixes(self, seq): ----------------------------
------- cur = self.root ------------------------------------------
----------------------------------------------------------------
------- for c in seq: --------------------------------------------
----------- if c not in cur.children: --------------------------
--------------- return 0 ------------------------------------
----------- cur = cur.children[c] ------------------------------
----------------------------------------------------------------
------- return cur.prefixes --------------------------------------
```

9.8. Suffix Array.

```
class SuffixArray: ---------------------------------------------
--- def __init__(self): --------------------------------------
------- self.n = 0 -----------------------------------------------
------- self.suffix = [] -----------------------------------------
------- self.equiv = [] ------------------------------------------
------- self.equiv_pair = [] -------------------------------------
------- self.s = "" ----------------------------------------------
----------------------------------------------------------------
--- def build(self, s): --------------------------------------
```

```
------- if not s.endswith('$'): ------------------------------------------
----------- s += '$' ---------------------------------------------------------
 ------------------------------------------------------------------------------
------- self.s = s -------------------------------------------------------
------- self.n = len(s) --------------------------------------------------
 ------------------------------------------------------------------------------
------- self.suffix = list(range(self.n)) --------------------------------
------- self.equiv = [0] * self.n ----------------------------------------
------- self.equiv_pair = [(0, 0)] * self.n ------------------------------
 ------------------------------------------------------------------------------
------- self.suffix.sort(key=lambda i: s[i]) -----------------------------
 ------------------------------------------------------------------------------
------- cls = 0 ----------------------------------------------------------
------- for i in range(self.n): ------------------------------------------
----------- if i == 0 or s[self.suffix[i]] != s[self.suffix[i - 1]]: -
--------------- cls += 1 -------------------------------------------------
----------- self.equiv[self.suffix[i]] = cls ---------------------------
 ------------------------------------------------------------------------------
------- k = 1 ------------------------------------------------------------
------- while k < self.n: ------------------------------------------------
----------- for i in range(self.n): ------------------------------------
--------------- self.equiv_pair[i] = ( -----------------------------------
------------------- self.equiv[i], -------------------------------------
------------------- self.equiv[(i + k) % self.n] -----------------------
--------------- ) --------------------------------------------------------
 ------------------------------------------------------------------------------
----------- self.suffix.sort(key=lambda i: self.equiv_pair[i]) -------
 ------------------------------------------------------------------------------
----------- cls = 0 ----------------------------------------------------
----------- new_equiv = [0] * self.n -----------------------------------
 ------------------------------------------------------------------------------
----------- for i in range(self.n): ------------------------------------
--------------- if i == 0 or self.equiv_pair[self.suffix[i]] !=
↪  self.equiv_pair[self.suffix[i - 1]]:
------------------- cls += 1 -------------------------------------------
--------------- new_equiv[self.suffix[i]] = cls ----------------------
 ------------------------------------------------------------------------------
----------- self.equiv = new_equiv -------------------------------------
----------- k <<= 1 ----------------------------------------------------
 ------------------------------------------------------------------------------
--- def _cmp(self, start, pattern): ----------------------------------
------- s = self.s -------------------------------------------------------
------- n = len(s) -------------------------------------------------------
 ------------------------------------------------------------------------------
------- i = start --------------------------------------------------------
------- j = 0 ------------------------------------------------------------
 ------------------------------------------------------------------------------
------- while i < n and j < len(pattern): --------------------------------
----------- if s[i] != pattern[j]: -------------------------------------
--------------- return ord(s[i]) - ord(pattern[j]) -------------------
----------- i += 1 -----------------------------------------------------
----------- j += 1 -----------------------------------------------------
 ------------------------------------------------------------------------------
------- if j == len(pattern): --------------------------------------------
----------- return 0 ---------------------------------------------------
------- return -1 --------------------------------------------------------
 ------------------------------------------------------------------------------
--- def lower_bound(self, pattern): ----------------------------------
------- l, r = 0, self.n - 1 ---------------------------------------------
------- res = self.n -----------------------------------------------------
 ------------------------------------------------------------------------------
------- while l <= r: ---------------------------------------------------
----------- m = (l + r) // 2 -------------------------------------------
----------- if self._cmp(self.suffix[m], pattern) >= 0: ----------------
--------------- res = m --------------------------------------------------
--------------- r = m - 1 ------------------------------------------------
----------- else: ------------------------------------------------------
--------------- l = m + 1 ------------------------------------------------
 ------------------------------------------------------------------------------
------- return res -------------------------------------------------------
 ------------------------------------------------------------------------------
--- def upper_bound(self, pattern): ----------------------------------
------- l, r = 0, self.n - 1 ---------------------------------------------
------- res = self.n -----------------------------------------------------
 ------------------------------------------------------------------------------
------- while l <= r: ---------------------------------------------------
----------- m = (l + r) // 2 -------------------------------------------
----------- if self._cmp(self.suffix[m], pattern) > 0: -----------------
--------------- res = m --------------------------------------------------
--------------- r = m - 1 ------------------------------------------------
----------- else: ------------------------------------------------------
--------------- l = m + 1 ------------------------------------------------
 ------------------------------------------------------------------------------
------- return res -------------------------------------------------------
 ------------------------------------------------------------------------------
--- def count_occurrences(self, pattern): ----------------------------
------- L = self.lower_bound(pattern) ------------------------------------
------- R = self.upper_bound(pattern) ------------------------------------
------- return max(0, R - L) ---------------------------------------------
```

9.9. Booth Min String Rotation.

```
def booth(s: str) -> int: ----------------------------------------------
--- s = s + s --------------------------------------------------------
--- n = len(s) -------------------------------------------------------
 ------------------------------------------------------------------------------
--- f = [-1] * n -----------------------------------------------------
--- k = 0 ------------------------------------------------------------
 ------------------------------------------------------------------------------
--- for j in range(1, n): --------------------------------------------
------- i = f[j - k - 1] -------------------------------------------------
 ------------------------------------------------------------------------------
------- while i != -1 and s[j] != s[k + i + 1]: --------------------------
----------- if s[j] < s[k + i + 1]: ------------------------------------
--------------- k = j - i - 1 --------------------------------------------
----------- i = f[i] ---------------------------------------------------
 ------------------------------------------------------------------------------
------- if i == -1 and s[j] != s[k]: -------------------------------------
----------- if s[j] < s[k]: --------------------------------------------
--------------- k = j ----------------------------------------------------
----------- f[j - k] = -1 ----------------------------------------------
------- else: ------------------------------------------------------------
----------- f[j - k] = i + 1 -------------------------------------------
 ------------------------------------------------------------------------------
--- return k ---------------------------------------------------------
```

10. Other Algorithms

10.1. Longest Increasing Subsequence.

```
def lis(arr): ----------------------------------------------------------
--- if not arr: ------------------------------------------------------
------- return [] -------------------------------------------------------
 ------------------------------------------------------------------------------
--- n = len(arr) -----------------------------------------------------
--- seq = [] ---------------------------------------------------------
--- back = [0] * n ---------------------------------------------------
 ------------------------------------------------------------------------------
--- for i in range(n): -----------------------------------------------
------- lo, hi = 0, len(seq) ---------------------------------------------
------- while lo < hi: --------------------------------------------------
----------- mid = (lo + hi) // 2 ---------------------------------------
----------- if arr[seq[mid]] < arr[i]: ---------------------------------
--------------- lo = mid + 1 ---------------------------------------------
----------- else: ------------------------------------------------------
--------------- hi = mid -------------------------------------------------
 ------------------------------------------------------------------------------
------- res = lo ---------------------------------------------------------
------- if res < len(seq): -----------------------------------------------
----------- seq[res] = i -----------------------------------------------
------- else: ------------------------------------------------------------
----------- seq.append(i) ----------------------------------------------
------- back[i] = -1 if res == 0 else seq[res - 1] -----------------------
 ------------------------------------------------------------------------------
--- ans = [] ---------------------------------------------------------
--- at = seq[-1] -----------------------------------------------------
--- while at != -1: --------------------------------------------------
------- ans.append(at) ---------------------------------------------------
------- at = back[at] ----------------------------------------------------
 ------------------------------------------------------------------------------
--- return ans[::-1] -------------------------------------------------
```

10.2. Cycle Find.

```
def find_cycle(x0, f): -------------------------------------------------
--- t = f(x0) --------------------------------------------------------
--- h = f(f(x0)) -----------------------------------------------------
 ------------------------------------------------------------------------------
--- while t != h: ----------------------------------------------------
------- t = f(t) ---------------------------------------------------------
------- h = f(f(h)) ------------------------------------------------------
 ------------------------------------------------------------------------------
--- mu = 0 -----------------------------------------------------------
--- h = x0 -----------------------------------------------------------
--- while t != h: ----------------------------------------------------
------- t = f(t) ---------------------------------------------------------
------- h = f(h) ---------------------------------------------------------
------- mu += 1 ----------------------------------------------------------
 ------------------------------------------------------------------------------
--- lam = 1 ----------------------------------------------------------
--- h = f(t) ---------------------------------------------------------
--- while t != h: ----------------------------------------------------
------- h = f(h) ---------------------------------------------------------
------- lam += 1 ---------------------------------------------------------
 ------------------------------------------------------------------------------
--- return mu, lam ---------------------------------------------------
```

10.3. 2Sat.

```
class TwoSAT: ----------------------------------------------------------
--- def __init__(self, n): -------------------------------------------
------- self.n = n -------------------------------------------------------
------- self.N = 2 * n ---------------------------------------------------
------- self.adj = [[] for _ in range(self.N)] ---------------------------
 ------------------------------------------------------------------------------
--- def var(self, x): ------------------------------------------------
------- return x << 1 ----------------------------------------------------
 ------------------------------------------------------------------------------
--- def neg(self, x): ------------------------------------------------
------- return x ^ 1 ----------------------------------------------------
 ------------------------------------------------------------------------------
--- def add_imp(self, x, y): -----------------------------------------
------- self.adj[x].append(y) --------------------------------------------
 ------------------------------------------------------------------------------
--- def add_or(self, x, y): ------------------------------------------
------- self.add_imp(self.neg(x), y) -------------------------------------
------- self.add_imp(self.neg(y), x) -------------------------------------
 ------------------------------------------------------------------------------
--- def sat(self): ---------------------------------------------------
------- n = self.N -------------------------------------------------------
------- adj = self.adj ---------------------------------------------------
 ------------------------------------------------------------------------------
------- index = 0 --------------------------------------------------------
------- stack = [] -------------------------------------------------------
------- onstack = [False] * n --------------------------------------------
------- ids = [-1] * n ---------------------------------------------------
------- low = [0] * n ----------------------------------------------------
------- comp = [-1] * n --------------------------------------------------
------- self.time = 0 ----------------------------------------------------
------- self.comp_id = 0 -------------------------------------------------
 ------------------------------------------------------------------------------
------- def dfs(u): ------------------------------------------------------
----------- nonlocal index ---------------------------------------------
 ------------------------------------------------------------------------------
----------- ids[u] = low[u] = index ------------------------------------
----------- index += 1 -------------------------------------------------
```

```
----------- stack.append(u) ----------------------------------------
----------- onstack[u] = True --------------------------------------
--------------------------------------------------------------------
----------- for v in adj[u]: ---------------------------------------
--------------- if ids[v] == -1: -------------------------------------
------------------- dfs(v) -------------------------------------------
------------------- low[u] = min(low[u], low[v]) ---------------------
--------------- elif onstack[v]: -------------------------------------
------------------- low[u] = min(low[u], ids[v]) ---------------------
--------------------------------------------------------------------
----------- if low[u] == ids[u]: -----------------------------------
--------------- while True: ------------------------------------------
------------------- v = stack.pop() ----------------------------------
------------------- onstack[v] = False -------------------------------
------------------- comp[v] = self.comp_id ---------------------------
------------------- if v == u: ---------------------------------------
----------------------- break ------------------------------------------
--------------- self.comp_id += 1 ------------------------------------
--------------------------------------------------------------------
------- for i in range(n): -------------------------------------------
----------- if ids[i] == -1: ---------------------------------------
--------------- dfs(i) -----------------------------------------------
--------------------------------------------------------------------
------- for i in range(0, n, 2): -------------------------------------
----------- if comp[i] == comp[i ^ 1]: -----------------------------
--------------- return False -----------------------------------------
--------------------------------------------------------------------
------- return True --------------------------------------------------
```

10.4. Dpll.

```
class SAT: ---------------------------------------------------------
--- def __init__(self): ------------------------------------------
------- self.clauses = [] --------------------------------------
------- self.n = 0 ---------------------------------------------
--------------------------------------------------------------
--- def var(self): -----------------------------------------
------- self.n += 1 --------------------------------------
------- return self.n ------------------------------------
--------------------------------------------------------------
--- def clause(self, c): -----------------------------------
------- self.clauses.append(c) ---------------------------
--------------------------------------------------------------
--- def clause_sat(self, clause, assign): ------------------
------- unknown = False ----------------------------------
--------------------------------------------------------------
------- for x in clause: ---------------------------------
----------- v = abs(x) -----------------------------------
----------- val = assign[v] ------------------------------
--------------------------------------------------------------
----------- if x > 0 and val == 1: -----------------------
--------------- return True ----------------------------------
----------- if x < 0 and val == 0: -----------------------
--------------- return True ----------------------------------
--------------------------------------------------------------
----------- if val == -1: --------------------------------
--------------- unknown = True -------------------------------
--------------------------------------------------------------
------- return False if not unknown else None ------------------
--------------------------------------------------------------
--- def propagate(self, assign): ---------------------------
------- changed = True -----------------------------------
--------------------------------------------------------------
------- while changed: -----------------------------------
----------- changed = False ------------------------------
--------------------------------------------------------------
----------- for clause in self.clauses: ------------------
--------------- sat = False ----------------------------------
--------------- unassigned = [] ------------------------------
--------------------------------------------------------------
--------------- for x in clause: -----------------------------
------------------- v = abs(x) -----------------------------
--------------------------------------------------------------
------------------- if x > 0 and assign[v] == 1: -----------
----------------------- sat = True -------------------------
----------------------- break ------------------------------
------------------- if x < 0 and assign[v] == 0: -----------
----------------------- sat = True -------------------------
----------------------- break ------------------------------
--------------------------------------------------------------
------------------- if assign[v] == -1: --------------------
----------------------- unassigned.append(x) ---------------
--------------------------------------------------------------
--------------- if sat: --------------------------------------
------------------- continue -------------------------------
--------------------------------------------------------------
--------------- if len(unassigned) == 0: ---------------------
------------------- return False  # contradiction ----------
--------------------------------------------------------------
--------------- if len(unassigned) == 1: ---------------------
------------------- x = unassigned[0] ----------------------
------------------- v = abs(x) -----------------------------
------------------- val = 1 if x > 0 else 0 ----------------
--------------------------------------------------------------
------------------- if assign[v] != -1 and assign[v] != val: -
----------------------- return False -----------------------
--------------------------------------------------------------
------------------- if assign[v] == -1: --------------------
----------------------- assign[v] = val --------------------
----------------------- changed = True ---------------------
--------------------------------------------------------------
------- return True --------------------------------------------
--------------------------------------------------------------
--- def solve_dfs(self, assign, idx=1): --------------------
------- if idx > self.n: ---------------------------------
----------- return True ----------------------------------
--------------------------------------------------------------
------- if assign[idx] != -1: ----------------------------
----------- return self.solve_dfs(assign, idx + 1) -------
--------------------------------------------------------------
------- for val in [0, 1]: -------------------------------
----------- new_assign = assign[:] -----------------------
----------- new_assign[idx] = val ------------------------
--------------------------------------------------------------
----------- if self.propagate(new_assign): ---------------
--------------- if self.solve_dfs(new_assign, idx + 1): ------
------------------- return True ----------------------------
--------------------------------------------------------------
------- return False -------------------------------------
--------------------------------------------------------------
--- def solve(self): ---------------------------------
------- assign = [-1] * (self.n + 1) ---------------
--------------------------------------------------------------
------- if not self.propagate(assign): -------------
----------- return False ---------------------------
--------------------------------------------------------------
------- return self.solve_dfs(assign) --------------
--------------------------------------------------------------
--- def get_value(self, x): --------------------------
------- return self.assign[x] == 1 -----------------
```

10.5. Stable Marriage.

```
from collections import deque ------------------------------------
--------------------------------------------------------------------
def stable_marriage(n, m_pref, w_pref): --------------------------
--- w_rank = [[0] * n for _ in range(n)] -------------------------
--------------------------------------------------------------------
--- for w in range(n): -------------------------------------------
------- for i, man in enumerate(w_pref[w]): ------------------------
----------- w_rank[w][man] = i -----------------------------------
--------------------------------------------------------------------
--- q = deque(range(n)) ------------------------------------------
--------------------------------------------------------------------
--- at = [0] * n -------------------------------------------------
--------------------------------------------------------------------
--- eng = [-1] * n -----------------------------------------------
--------------------------------------------------------------------
--- res = [-1] * n -----------------------------------------------
--------------------------------------------------------------------
--- while q: -----------------------------------------------------
------- m = q.popleft() --------------------------------------------
--------------------------------------------------------------------
------- while at[m] < n: -------------------------------------------
----------- w = m_pref[m][at[m]] ---------------------------------
----------- at[m] += 1 -------------------------------------------
--------------------------------------------------------------------
----------- if eng[w] == -1: -------------------------------------
--------------- eng[w] = m -------------------------------------------
--------------- res[m] = w -------------------------------------------
--------------- break ------------------------------------------------
--------------------------------------------------------------------
----------- if w_rank[w][m] < w_rank[w][eng[w]]: -----------------
--------------- q.append(eng[w]) -------------------------------------
--------------- eng[w] = m -------------------------------------------
--------------- res[m] = w -------------------------------------------
--------------- break ------------------------------------------------
--------------------------------------------------------------------
--- return res ---------------------------------------------------
```

10.6. Dates.

```
def c_div(a, b): ---------------------------------------------------
--- return int(a / b) --------------------------------------------
--------------------------------------------------------------------
def date_to_int(y, m, d): ------------------------------------------
--- k = c_div(m - 14, 12) ----------------------------------------
--------------------------------------------------------------------
--- return ( -----------------------------------------------------
------- 1461 * (y + 4800 + k) // 4 ---------------------------------
------- + 367 * (m - 2 - k * 12) // 12 -----------------------------
------- - 3 * ((y + 4900 + k) // 100) // 4 -------------------------
------- + d - 32075 ------------------------------------------------
--- ) ------------------------------------------------------------
--------------------------------------------------------------------
--------------------------------------------------------------------
def int_to_day(jd): ------------------------------------------------
--- return jd % 7 ------------------------------------------------
--------------------------------------------------------------------
--------------------------------------------------------------------
def int_to_date(jd): -----------------------------------------------
--- x = jd + 68569 -----------------------------------------------
--- n = 4 * x // 146097 ------------------------------------------
--- x -= (146097 * n + 3) // 4 -----------------------------------
--------------------------------------------------------------------
--- i = (4000 * (x + 1)) // 1461001 ------------------------------
--- x -= 1461 * i // 4 - 31 --------------------------------------
--------------------------------------------------------------------
--- j = 80 * x // 2447 -------------------------------------------
--- d = x - 2447 * j // 80 ---------------------------------------
--------------------------------------------------------------------
--- x = j // 11 --------------------------------------------------
--- m = j + 2 - 12 * x -------------------------------------------
--- y = 100 * (n - 49) + i + x -----------------------------------
--------------------------------------------------------------------
--- return y, m, d -----------------------------------------------
```

10.7. Simulated Annealing.

```
import random ----------------------------------------------------
import math ------------------------------------------------------
import time ------------------------------------------------------
--------------------------------------------------------------------
--------------------------------------------------------------------
def simulated_annealing(n, seconds): -----------------------------
--- rng = random.Random() ----------------------------------------
--------------------------------------------------------------------
```

```
--- sol = list(range(1, n + 1))
--- rng.shuffle(sol)

--- def score(arr):
------- return sum(abs(arr[i] - arr[i - 1]) for i in range(1, n))

--- cur = score(sol)

--- T0 = 100.0
--- T1 = 0.001
--- start = time.time()
--- iters = 0

--- while True:
------- if iters % 16 == 0:
----------- progress = (time.time() - start) / seconds
----------- if progress >= 1.0:
--------------- break
----------- temp = T0 * (T1 / T0) ** progress

------- a = rng.randint(0, n - 2)

------- x, y = sol[a], sol[a + 1]

------- delta = 0

------- if a > 0:
----------- delta += abs(sol[a - 1] - y) - abs(sol[a - 1] - x)

------- if a + 2 < n:
----------- delta += abs(x - sol[a + 2]) - abs(y - sol[a + 2])

------- accept = delta <= 0 or rng.random() < math.exp(-delta / temp)

------- if accept:
----------- sol[a], sol[a + 1] = sol[a + 1], sol[a]
----------- cur += delta

------- iters += 1

--- return cur, sol
```

10.8. Simplex.

```
import math

EPS = 1e-9

class LPSolver:
--- def __init__(self, A, b, c):
------- self.m = len(b)
------- self.n = len(c)
------- self.N = [0] * (self.n + 1)
------- self.B = [0] * self.m
------- self.D = [[0.0] * (self.n + 2) for _ in range(self.m + 2)]

------- for i in range(self.m):
----------- for j in range(self.n):
--------------- self.D[i][j] = A[i][j]

------- for i in range(self.m):
----------- self.B[i] = self.n + i
----------- self.D[i][self.n] = -1
----------- self.D[i][self.n + 1] = b[i]

------- for j in range(self.n):
----------- self.N[j] = j
----------- self.D[self.m][j] = -c[j]

------- self.N[self.n] = -1
------- self.D[self.m + 1][self.n] = 1

--- def pivot(self, r, s):
------- inv = 1.0 / self.D[r][s]

------- for i in range(self.m + 2):
----------- if i != r:
--------------- for j in range(self.n + 2):
------------------- if j != s:
----------------------- self.D[i][j] -= self.D[r][j] * self.D[i][s] *
↪  inv

------- for j in range(self.n + 2):
----------- if j != s:
--------------- self.D[r][j] *= inv

------- for i in range(self.m + 2):
----------- if i != r:
--------------- self.D[i][s] *= -inv

------- self.D[r][s] = inv
------- self.B[r], self.N[s] = self.N[s], self.B[r]

--- def simplex(self, phase):
------- x = self.m + 1 if phase == 1 else self.m

------- while True:
----------- s = -1
----------- for j in range(self.n + 1):
--------------- if phase == 2 and self.N[j] == -1:
------------------- continue
--------------- if (s == -1 or
------------------- self.D[x][j] < self.D[x][s] or
------------------- (abs(self.D[x][j] - self.D[x][s]) < EPS and
↪  self.N[j] < self.N[s])):
------------------- s = j

----------- if self.D[x][s] > -EPS:
--------------- return True

----------- r = -1
----------- for i in range(self.m):
--------------- if self.D[i][s] < EPS:
------------------- continue
--------------- if (r == -1 or
------------------- self.D[i][self.n + 1] / self.D[i][s] <
----------------------- self.D[r][self.n + 1] / self.D[r][s] or
------------------- (abs(self.D[i][self.n + 1] / self.D[i][s] -
----------------------- self.D[r][self.n + 1] / self.D[r][s]) < EPS
↪  and
------------------- self.B[i] < self.B[r])):
------------------- r = i

----------- if r == -1:
--------------- return False

----------- self.pivot(r, s)

--- def solve(self):
------- x = [0.0] * self.n

------- r = 0
------- for i in range(1, self.m):
----------- if self.D[i][self.n + 1] < self.D[r][self.n + 1]:
--------------- r = i

------- if self.D[r][self.n + 1] < -EPS:
----------- self.pivot(r, self.n)
----------- if not self.simplex(1) or self.D[self.m + 1][self.n + 1] <
↪  -EPS:
--------------- return -math.inf, x

----------- for i in range(self.m):
--------------- if self.B[i] == -1:
------------------- s = -1
------------------- for j in range(self.n + 1):
----------------------- if (s == -1 or
----------------------- self.D[i][j] < self.D[i][s] or
----------------------- (abs(self.D[i][j] - self.D[i][s]) < EPS and
↪  self.N[j] < self.N[s])):
----------------------- s = j
------------------- self.pivot(i, s)

------- if not self.simplex(2):
----------- return math.inf, x

------- for i in range(self.m):
----------- if self.B[i] < self.n:
--------------- x[self.B[i]] = self.D[i][self.n + 1]

------- return self.D[self.m][self.n + 1], x
```

10.9. Fast Input Reading.

```
import sys

data = sys.stdin.buffer.read().split()
it = iter(data)

def next_int():
--- return int(next(it))
```

10.10. Bit Hacks.

```
def snoob(x):
--- y = x & -x
--- z = x + y
--- return z | (((x ^ z) // y) >> 2)
```