

Quantum Neural Network-enhanced Residual Multi- Layer Perceptron Mixture-of-Experts (QNN-enhanced ResMLP_MoE)

Presenter: Seon-Geun Jeong

Team PNU: Pusan National University, Republic of Korea

Seon-Geun Jeong, Ph.D Candidate

Doan Hieu Nguyen, Ph.D Candidate

Le Tung Giang, Ph.D Candidate

Mai Dinh Cong, M.S. Candidate

Sanghun Sel, Ph.D Candidate

Juseong Kim, Ph.D Candidate

Min-Gyeol Kim, M.S. Candidate

Prof. Won-Joo Hwang

Prof. Giltae Song

Prof. In-Soo Yoon



부산대학교
PUSAN NATIONAL UNIVERSITY

1. Dataset & Task

- Task: 1) PK/PD modelling, 2) Dose optimization

Patient Data









Figure 1: Dataset.

2. Quantum-enhanced ML Framework for Dose Optimization

QNN-enhanced ResMLP_MoE Framework



3. Model Search

- Cascade + ResMLP+MoE achieves the best performance in terms of PK/PD RMSE.







Figure 3: QNN-enhanced ResMLP_MoE.




(A) Independent modeling



(B) Cascade mode



(C) Multi-task mode



(D) Encoder Backbones




Figure 4: Overview of modeling frameworks.




Figure 5: Empirical evaluation results.

3. Quantum Model (Qubits, Layers, Advantage)

- Technical Feasibility: Based on IBM quantum systems, the quantum volume reflects the maximum circuit size with width \approx depth. State-of-the-arts $QV = 512 \Rightarrow T \leq 9$. That is, (9 qubits and 9 depth)

Table 1: The up-to-date IBM Quantum's quantum computers

No.	System	Qubits	QV	EPLG ^a	CLOPS ^b	T1 (μ s) ^c	T2 (μ s) ^c	QPU ^d	Processor
1	ibm_fez	156	512	0.8%	3.8K	136.52	78.58	us-east	Heron r1
2	ibm_toronto	133	512	1.0%	3.8K	158.27	122.18	us-east	Heron r1







Figure 6: Results of QNN-enhanced ResMLP_MoE

4. Conclusion

- Quantum advantages [1]:
- 1) Model complexity reduction



- 2) approximation performance (Neural Network $F(x)$, Quantum Neural Network $Q(x)$, continuous function $f(x)$)
 $|f(x) - F(x)|dx < \varepsilon$, $|f(x) - Q(x)|dx < \delta$. ($\varepsilon > \delta$) in the same number of parameters.
- 3) model convergence speed (Training time)
- 4) inference time (Faster than NN)
- 5) higher expressivity (Small dataset).



Model	# Qubit	# C params.	# Q params.	# Operation time
Classical NN	-	$(N_{in} + M_{out})M_{in} + M_{in}^2(L_{nn} + 2)$	-	$O((N_{in} + M_{out})M_{in} + M_{in}^2(L_{nn} + 2))CPU_{time}$
HQNN	M_{in}	$(N_{in} + M_{out})M_{in}$	$3M_{in}L_{qnn}$	$O((N_{in} + M_{out})M_{in})CPU_{time} + O(4L_{qnn})QPU_{single} + O(M_{in}L_{qnn})QPU_{two}$

[1] Jeong, Seon-Geun, Kyeong-Hwan Moon, and Won-Joo Hwang. "Hybrid quantum neural networks for efficient protein-ligand binding affinity prediction." *EPJ Quantum Technology* 12.1 (2025): 1-36.

Thank you!

