

Advertisement

Home / Browse / Environment Modules / Mailing Lists



Environment Modules

Manage your shell environment variables and aliases Brought to you by: leomania, rkowen, sirdude, xdelaruelle

> Get latest updates about Open Source Projects, Conferences and News.

> > Sign Up

No, Thank you

Re: [Modules] modulefiles loops Re: [Modules] modulefiles loops From: Mark Lakata <mark@la...> - 2011-04-04 16:25:34 Attachments: Message as HTML As a side note, you should not put conditional logic in your module file unless you are doing something very strange. The module command will automatically do all the conditional logic of loading. For example, if you have 'module load foo' in your module file 'bar', then when you type 'module unload bar', it will automatically do 'module unload foo'. I would change your module file to look like this: module load 4.5.2/basic module load 4.5.2/openmpi/1.4.3 set fftw_path /usr/local/gcc/4.5.2/fftw/3.2.2 prepend-pathPATH\$fftw_path/bin prepend-pathLD LIBRARY PATH \$fftw path/lib prepend-path--delim " "CFLAGS"-I\$fftw_path/include" prepend-path--delim " "CXXFLAGS"-I\$fftw_path/include" prepend-path--delim " "LDFLAGS"-I\$fftw_path/lib" prepend-pathMANPATH \$fftw path/share/man -Mark On 4/4/2011 3:45 AM, Giuseppe Aprea wrote: > if [module-info mode load] { > set this_module [module-info name] > if [is-loaded \$this_module] {exit} > if ![is-loaded 4.5.2/basic] { module load 4.5.2/basic } > if ![is-loaded 4.5.2/openmpi/1.4.3] { module load 4.5.2/openmpi/1.4.3 } > } > prepend-pathPATH/usr/local/gcc/4.5.2//fftw/3.2.2/bin > prepend-pathLD_LIBRARY_PATH/usr/local/gcc/4.5.2//fftw/3.2.2/lib > prepend-path--delim " "CFLAGS"-I/usr/local/gcc/4.5.2//fftw/3.2.2/include" > prepend-path--delim " > "CXXFLAGS"-I/usr/local/gcc/4.5.2//fftw/3.2.2/include" > prepend-path--delim " "LDFLAGS"-I/usr/local/gcc/4.5.2//fftw/3.2.2/lib" > prepend-pathMANPATH/usr/local/gcc/4.5.2//fftw/3.2.2/share/man

Thread view

[Modules] modulefiles loops

From: Giuseppe Aprea <giuseppe.aprea@gm...> - 2011-04-04 10:46:09 Attachments: Message as HTML

```
Hi all,

I am quiite new to modules software so I hope my question is not too silly:
```

Get latest updates about Open Source Projects, Conferences and News.

Sign Up

No, Thank you

© 2020 Slashdot Media. All Rights Reserved.

Terms Privacy Opt Out Advertise

Get latest updates about Open Source Projects, Conferences and News.

Sign Up

No, Thank you