Virtual Memory: Systems

These slides adapted from materials provided by the textbook authors.

Virtual Memory: Systems

- Simple memory system example
- **Case study: Core i7/Linux memory system**
- Memory mapping

Intel Core i7 Memory System



Review of Symbols

- **Basic Parameters**
  - **N = 2^n** : Number of addresses in virtual address space
  - **M = 2^m** : Number of addresses in physical address space
  - **P = 2^p** : Page size (bytes)
- **Components of the virtual address (VA)**
  - **TLBI**: TLB index
  - **TLBT**: TLB tag
  - **VPO**: Virtual page offset
  - **VPN**: Virtual page number
- **Components of the physical address (PA)**
  - **PPO**: Physical page offset (same as VPO)
  - **PPN:** Physical page number
  - **CO**: Byte offset within cache line
  - **CI:** Cache index
  - **CT**: Cache tag

End-to-end Core i7 Address Translation



Core i7 Level 1-3 Page Table Entries



Each entry references a 4K child page table. Significant fields:

P: Child page table present in physical memory (1) or not (0).

R/W: Read-only or read-write access access permission for all reachable pages.

U/S: user or supervisor (kernel) mode access permission for all reachable pages.

WT: Write-through or write-back cache policy for the child page table.

A: Reference bit (set by MMU on reads and writes, cleared by software).

PS: Page size either 4 KB or 4 MB (defined for Level 1 PTEs only).

Page table physical base address: 40 most significant bits of physical page table address (forces page tables to be 4KB aligned)

XD: Disable or enable instruction fetches from all pages reachable from this PTE.

Core i7 Level 4 Page Table Entries



Each entry references a 4K child page. Significant fields:

P: Child page is present in memory (1) or not (0)

R/W: Read-only or read-write access permission for child page

U/S: User or supervisor mode access

WT: Write-through or write-back cache policy for this page

A: Reference bit (set by MMU on reads and writes, cleared by software)

D: Dirty bit (set by MMU on writes, cleared by software)

Page physical base address: 40 most significant bits of physical page address (forces pages to be 4KB aligned)

XD: Disable or enable instruction fetches from this page.

Core i7 Page Table Translation



Cute Trick for Speeding Up L1 Access



- **Observation**
  - Bits that determine CI identical in virtual and physical address
  - Can index into cache while address translation taking place
  - Generally we hit in TLB, so PPN bits (CT bits) available next
  - “Virtually indexed, physically tagged”
  - Cache carefully sized to make this possible

Virtual Address Space of a Linux Process



Linux Organizes VM as Collection of "Areas"



- **pgd:**
  - Page global directory address
  - Points to L1 page table
- **vm_prot:**
  - Read/write permissions for this area
- **vm_flags**
  - Pages **shared** with other processes or **private** to this process

Linux Page Fault Handling



Segmentation fault:
accessing a non-existing page

Normal page fault

Protection exception:
e.g., violating permission by writing to a read-only page (Linux reports as Segmentation fault)