



Floating Point - Examples


These slides adapted from materials provided by the textbook

Floating Point


- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

Distribution of Values

- 6-bit IEEE-like format
 - e = 3 exponent bits
 - f = 2 fraction bits
 - Bias is $2^{3-1}-1=3$




Notice how the distribution gets denser toward zero.




Distribution of Values (close-up view)


6-bit IEEE-like format

- e = 3 exponent bits
- f = 2 fraction bits
- Bias is 3





Tiny Floating Point Example



8-bit Floating Point Representation

- the sign bit is in the most significant bit
- the next four bits are the exponent, with a bias of 7
- the last three bits are the frac

Same general form as IEEE Format

- normalized, denormalized
- representation of 0, NaN, infinity

Dynamic Range (Positive Only) $v = (-1)^s M 2^E$

-	s	exp	frac	E	Value		n: E = Exp — Bias
	0	0000	000	-6	0		d: E = 1 - Bias
	0	0000	001	-6	1/8*1/64	= 1/512	closest to zero
Denormalized	0	0000	010	-6	2/8*1/64	= 2/512	0.0000110 2010
numbers	•••						
	0	0000	110	-6	6/8*1/64	= 6/512	
	0	0000	111	-6	7/8*1/64	= 7/512	largest denorm
	0	0001	000	-6	8/8*1/64	= 8/512	smallest norm
	0	0001	001	-6	9/8*1/64	= 9/512	Smallest norm
	•••						
	0	0110	110	-1	14/8*1/2	= 14/16	
	0	0110	111	-1	15/8*1/2	= 15/16	closest to 1 below
Normalized	0	0111	000	0	8/8*1	= 1	
numbers	0	0111	001	0	9/8*1	= 9/8	closest to 1 above
	0	0111	010	0	10/8*1	= 10/8	
	•••						
	0	1110	110	7	14/8*128	= 224	
	0	1110	111	7	15/8*128	= 240	largest norm
	0	1111	000	n/a	inf		

Creating Floating Point Number

Steps

- Normalize to have leading 1
- Round to fit within fraction

s exp frac

1 4-bits 3-bits

Postnormalize to deal with effects of rounding

Case Study

Convert 8-bit unsigned numbers to tiny floating point format

Example Numbers

128

10000000

Creating Floating Point Number

Steps

- Normalize to have leading 1
- Round to fit within fraction

- s exp frac

 1 4-bits 3-bits
- Postnormalize to deal with effects of rounding

Case Study

Convert 8-bit unsigned numbers to tiny floating point format

Example Numbers

35

00010011

Creating Floating Point Number

Steps

- Normalize to have leading 1
- Round to fit within fraction

s exp frac

1 4-bits 3-bits

Postnormalize to deal with effects of rounding

Case Study

Convert 8-bit unsigned numbers to tiny floating point format

Example Numbers

15

00001101

Special Properties of the IEEE Encoding

- FP Zero Same as Integer Zero
 - All bits = 0
- Can (Almost) Use Unsigned Integer Comparison
 - Must first compare sign bits
 - Must consider -0 = 0
 - NaNs problematic
 - Will be greater than any other values
 - What should comparison yield?
 - Otherwise OK
 - Denorm vs. normalized
 - Normalized vs. infinity