



Scan the QR code and  
visit the product page



|                          |   |                             |             |
|--------------------------|---|-----------------------------|-------------|
| Code                     | TK.LB.D0120.AEC   | Safety level                | Danger      |
| Dimensions (H x L)       | 69 mm x 140 mm (2,7" x 5,5")  | Version                     | Standard    |
| Material                 | PVC base with adhesive liner and protective layer   | Temperatures <sup>(1)</sup> | -40°C/+95°C |
| Applications             | Machinery and control panels. Indoor and outdoor locations  |                             |             |
| Languages <sup>(2)</sup> | Inglese   |                             |             |
| Message <sup>(3)</sup>   | <p>EN: Risk of electric shock. Orange wires inside the panel remain energized when the main switch is in the off positions. To service these circuits, shut off the equipment at the main service disconnect.</p> <p>IT: Rischio di shock elettrico. I conduttori arancioni all'interno del quadro rimangono sotto tensione quando l'interruttore principale è in posizione di spegnimento. Per operare su questi circuiti, spegnere l'apparecchiatura al sezionatore di servizio principale.</p> |                             |             |
| Certifications           | c(UL)us Recognized - File#MH60136 (PDGQ2, PGDQ8)  |                             |             |
| Standards of use         | ANSI Z535, OSHA Art. 1910.145, NFPA 70 (NEC), NFPA 79, UL 508A, CSA C22.1 (CECode), CSA C22.2 No.286  |                             |             |
| Standards Construction   | ANSI Z535, UL 969, CSA C22.2 No.0.15, ISO 3864, RoHS  |                             |             |
| Standard packaging       | 12 pz/pcs   |                             |             |

(1) For indoor and outdoor exposure with high humidity or with occasional exposure to water. The minimum application temperature is +0°C. UL certification is for maximum working temperatures of +60°C.

(2) Other languages may have different sizes and available upon request.

(3) The message and the image are shown in English language only.