Java Datatypes



Problem Statement

Java has 8 primitive data types; *char, boolean, byte, short, int, long, float, and double*. For this exercise, we'll work with the primitives used to hold integer values (*byte, short, int,* and *long*):

- A byte is an 8-bit signed integer.
- A short is a 16-bit signed integer.
- An *int* is a 32-bit signed integer.
- A long is a 64-bit signed integer.

Given an input integer, you must determine which primitive data types are capable of properly storing that input.

To get you started, a portion of the solution is provided for you in the editor.

Reference: https://docs.oracle.com/javase/tutorial/java/nutsandbolts/datatypes.html

Input Format

The first line contains an integer, T, denoting the number of test cases. Each test case, T, is comprised of a single line with an integer, n, which can be arbitrarily large or small.

Output Format

For each input variable n and appropriate primitive dataType, you must determine if the given primitives are capable of storing it. If yes, then print:

n can be fitted in:
* dataType

If there is more than one appropriate data type, print each one on its own line and order them by size (i.e.: byte < short < int < long).

If the number cannot be stored in one of the four aforementioned primitives, print the line:

n can't be fitted anywhere.

Sample Input

5 -150

-150 150000

150000

213333333333333333333333333333333333

-1000000000000000

Sample Output

- -150 can be fitted in:
- * short
- * int
- * long

150000 can be fitted in:	
* int	
* long	
150000000 can be fitted in:	

- * int

- * long
- -1000000000000000 can be fitted in:
- * long

Explanation

 $-150\ \mathrm{can}\ \mathrm{be}\ \mathrm{stored}\ \mathrm{in}\ \mathrm{a}\ \mathit{short}$, an int , or a long .

values for the primitive data types discussed in this problem.