


1. Reference to this part of EN ISO 12312-1: 2022

EN ISO 12311:2013

2. This Attestation of Compliance is issued on a voluntary basis for electrical equipment below the voltage limits of Personal Protective Equipment (PPE) Directive 2016/425.

3. NOTE: Not suitable for driving in twilight or at night Not suitable for driving at night or under condition of dull light .



ISO 7000-2952A



ISO 7000-2952B

4. Not for direct observation of the sun. Not for protection against artificial light sources, e.g. solaria.

5. Storage & Maintenance instructions:

Molsion sunglasses must be kept in their case at a temperature between -10°C and +35°C, Avoid long exposure to the sun in closed environments at high or low temperatures, e.g. on the car dashboard in summer, where the temperatures reach 60°C. Avoid leaving the sunglasses in a car for long periods. If the sun filters become worn (e.g. scratched, opaque), it is recommended to replace them with authentic spare parts.

Cleaning instructions:

Lens Cleaning:

For light dust, gently wipe the lenses with a clean microfiber cloth.

For stubborn stains or oil residues, apply a neutral detergent (e.g., mild alcohol-free dish soap) to the lenses, rub gently with fingertips, rinse thoroughly under lukewarm water, and dry with a microfiber cloth.

Frame and Contact Cleaning:

Temples and charging contacts (for smart glasses): Wipe surfaces and contacts lightly with a microfiber cloth. Avoid harsh chemicals or excessive pressure.

Nose pads and frame crevices: Rinse with warm water, then use a soft-bristled brush to remove oils and skin debris from gaps.

6. **Filter lens type:** photochromic Category 3.

7. **Manufacturer:** Dongguan baolifeng Electronic Technology Co., Ltd

Address: 4 / F, Mingxin Science Park, 138 Qiqiao Road, Qishi Town, Dongguan City

8. This product is intended to protect against the risk to the damage to the eyes due to exposure to sunlight (other than during observation of the sun).

9. **Protection Level and Category:** UV Protection

Luminous Transmittance (8%-75%)