

Brief summary of basic Python syntax

Joakim Sundnes^{1,2} Hans Petter Langtangen^{1,2} Ola Skavhaug³

Center for Biomedical Computing, Simula Research Laboratory¹

Dept. of Informatics, University of Oslo²

mCASH (formerly Dept. of Informatics, University of Oslo)³

Aug 25, 2014

Contents

- Python variables; numbers, strings, lists++
- Simple control structures
- Functions
- Reading and writing files
- Using and writing modules
- Doc strings

Sources for more information and documentation

- H.P. Langtangen and G. K. Sandve: Illustrating Python via Bioinformatics Examples: [PDF](#) or [HTML](#)
- `pydoc anymodule`, `pydoc anymodule.anyfunc`
- Python Library Reference (go to *index* in the upper right corner)
- Python 2.7 Quick Reference
- Python Global Module Index
- Think Python (textbook)
- Dive Into Python (textbook)
- Think Like a Computer Scientist (textbook)
- Unix Need-to-know
- Emacs Need-to-know

Video material

- A Gentle Introduction to Programming Using Python
- Introduction to Computer Science and Programming
- Learning Python Programming Language Through Video Lectures
- Python Programming Tutorials Video Lecture Course
- Python Videos, Tutorials and Screencasts

First Python encounter: a scientific hello world program

```
#!/usr/bin/env python
from math import sin
import sys
x = float(sys.argv[1])
print "Hello world, sin({}) = {}".format(x, sin(x))
```

Running the script from the command line

Code in file `hw.py`.

Run with command:

```
> python hw.py 0.5
Hello world, sin(0.5) = 0.479426.
```

Linux alternative if file is executable (`chmod a+x hw.py`):

```
> ./hw.py 0.5
Hello world, sin(0.5) = 0.479426.
```

Interactive Python & IPython

- Typing python gives you an interactive Python shell
- IPython is better, can also run scripts:
In [1]: run hw.py 3.14159
- IPython is integrated with Python's pdb debugger
- pdb can be automatically invoked when an exception occurs
- IPython supports tab completion, additional help commands, and much more, ...

Dissection of hw.py (1)

On Unix: find out what kind of script language (interpreter) to use:

```
#!/usr/bin/env python
```

Access library functionality like the function sin and the list sys.argv (of command-line arguments):

```
from math import sin
import sys
```

Read 1st command line argument and convert it to a floating point object:

```
x = float(sys.argv[1])
```

Dissection of hw.py (2)

Print out the result using a format string:

```
print "Hello world, sin({0}) = {1}".format(x, sin(x)) # v2.x
print("Hello world, sin({0}) = {1}".format(x, sin(x))) # v3.x
```

or with complete control of the formatting of floats (printf syntax):

```
print "Hello world, sin({x:g}) = {s:.3f}".format(x=x, s=sin(x))
print("Hello world, sin({x:g}) = {s:.3f}".format(x=x, s=sin(x)))
```

Python variables

Variables are not declared

Variables hold references to objects

```
a = 3          # ref to an int object containing 3
a = 3.0        # ref to a float object containing 3.0
a = '3.'       # ref to a string object containing '3.'
a = ['1', 2]   # ref to a list object containing
               # a string '1' and an integer 2
```

Test for a variable's type:

```
if isinstance(a, int): # int?
if isinstance(a, (list, tuple)): # list or tuple?
```

Common types

- Numbers: int, float, complex
- Sequences: str, list, tuple, ndarray
- Mappings: dict (dictionary/hash)
- User-defined type (via user-defined class)

Simple Assignments

```
a = 10          # a is a variable referencing an
                 # integer object of value 10

b = True        # b is a boolean variable

a = b           # a is now a boolean as well
                 # (referencing the same object as b)

b = increment(4) # b is the value returned by a function

is_equal = a == b # is_equal is True if a == b
```

Lists and tuples

```
mylist = ['a string', 2.5, 6, 'another string']
mytuple = ('a string', 2.5, 6, 'another string')
mylist[1] = -10
mylist.append('a third string')
mytuple[1] = -10 # illegal: cannot change a tuple
```

A tuple is a constant list (known as an *immutable* object, contrary to *mutable* objects which can change their content)

List functionality

Construction	Meaning
<code>a = []</code>	initialize an empty list
<code>a = [1, 4.4, 'run.py']</code>	initialize a list
<code>a.append(elem)</code>	add elem object to the end
<code>a + [1,3]</code>	add two lists
<code>a.insert(i, e)</code>	insert element e before index i
<code>a[3]</code>	index a list element
<code>a[-1]</code>	get last list element
<code>a[1:3]</code>	slice: copy data to sublist (here: index 1, 2)
<code>del a[3]</code>	delete an element (index 3)
<code>a.remove(e)</code>	remove an element with value e
<code>a.index('run.py')</code>	find index corresponding to an element's value
<code>'run.py' in a</code>	test if a value is contained in the list
<code>a.count(v)</code>	count how many elements that have the value v
<code>len(a)</code>	number of elements in list a
<code>min(a)</code>	the smallest element in a
<code>max(a)</code>	the largest element in a
<code>sum(a)</code>	add all elements in a
<code>sorted(a)</code>	return sorted version of list a
<code>reversed(a)</code>	return reversed sorted version of list a
<code>b[3][0][2]</code>	nested list indexing
<code>isinstance(a, list)</code>	is True if a is a list
<code>type(a) is list</code>	is True if a is a list

Dictionary functionality

Construction	Meaning
<code>a = {}</code>	initialize an empty dictionary
<code>a = {'point': [0,0.1], 'value': 7}</code>	initialize a dictionary
<code>a = dict(point=[2,7], value=3)</code>	initialize a dictionary w/string keys
<code>a.update(b)</code>	add key-value pairs from b in a
<code>a.update(key1=value1, key2=value2)</code>	add key-value pairs in a
<code>a['hide'] = True</code>	add new key-value pair to a
<code>a['point']</code>	get value corresponding to key point
<code>for key in a:</code>	loop over keys in unknown order
<code>for key in sorted(a):</code>	loop over keys in alphabetic order
<code>'value' in a</code>	True if string value is a key in a
<code>del a['point']</code>	delete a key-value pair from a
<code>list(a.keys())</code>	list of keys
<code>list(a.values())</code>	list of values
<code>len(a)</code>	number of key-value pairs in a
<code>isinstance(a, dict)</code>	is True if a is a dictionary

String operations

```
s = 'Berlin: 18.4 C at 4 pm'
s[8:17] # extract substring
':' in s # is ':' contained in s?
s.find(':') # index where first ':' is found
s.split(':') # split into substrings
s.split() # split wmt whitespace
'Berlin' in s # test if substring is in s
s.replace('18.4', '20')
s.lower() # lower case letters only
s.upper() # upper case letters only
s.split()[4].isdigit()
s.strip() # remove leading/trailing blanks
', '.join(list_of_words)
```

Strings in Python use single or double quotes, or triple single/double quotes

Single- and double-quoted strings work in the same way:
'some string' is equivalent to "some string"

Triple-quoted strings can be multi line with embedded newlines:

```
text = """large portions of a text
can be conveniently placed inside
triple-quoted strings (newlines
are preserved)"""
```

Raw strings, where backslash is backslash:

```
s3 = r'\\(\\s+\\.\\d+\\)'
# in an ordinary string one must quote backslash:
s3 = '\\(\\s+\\.\\d+\\)'
```

Simple control structures

Loops:

```
while condition:
    <block of statements>
```

Here, condition must be a boolean expression (or have a boolean interpretation), for example: `i < 10` or `!found`

```
for element in somelist:
    <block of statements>
```

Conditionals/branching:

```
if condition:
    <block of statements>
elif condition:
    <block of statements>
else:
    <block of statements>
```

Looping over integer indices is done with range

```
for i in range(10):  
    print(i)
```

Remark:

range in Python 3.x is equal to xrange in Python 2.x and generates an *iterator* over integers, while range in Python 2.x returns a list of integers.

Examples on loops and branching

```
x = 0  
dx = 1.0  
while x < 6:  
    if x < 2:  
        x += dx  
    elif 2 <= x < 4:  
        x += 2*dx  
    else:  
        x += 3*dx  
    print 'new x:', x  
print 'loop is over'
```

(Visualize execution)

```
mylist = [0, 0.5, 1, 2, 4, 10]  
for i, x in enumerate(mylist):  
    print i, x  
print 'loop is over'
```

(Visualize execution)

Functions and arguments

User-defined functions:

```
def split(string, char):  
    position = string.find(char)  
    if position > 0:  
        return string[:position+1], string[position+1:]  
    else:  
        return string, ''
```

```
# function call:  
message = 'Heisann'  
print(split(message, 'i'))  
# prints ('Hei', 'sann')
```

Positional arguments must appear before keyword arguments:

```
def split(message, char='i'):  
    ...
```

eval and exec turn strings into live code

Evaluating string expressions with eval:

```
>>> x = 20  
>>> r = eval('x + 1.1')  
>>> r  
21.1  
>>> type(r)  
<type 'float'>
```

Executing strings with Python code, using exec:

```
import sys  
user_expression = sys.argv[1]  
  
# Wrap user_expression in a Python function  
# (assuming the expression involves x)  
  
exec("""  
def f(x):  
    return %s  
""" % user_expression)  
  
# or  
  
f = eval('lambda x: %s' % user_expression)
```

File reading

Reading a file:

```
infile = open(filename, 'r')  
for line in infile:  
    # process line  
  
lines = infile.readlines()  
for line in lines:  
    # process line  
  
for i in xrange(len(lines)):  
    # process lines[i] and perhaps next line lines[i+1]  
  
fstr = infile.read() # fstr contains the entire file  
fstr = fstr.replace('some string', 'another string')  
for piece in fstr.split(';'):  
    # process piece (separated by ;)  
  
infile.close()
```

File writing

```
outfile = open(filename, 'w') # new file or overwrite  
outfile = open(filename, 'a') # append to existing file  
  
outfile.write("""Some string  
...  
""")  
outfile.writelines(list_of_lines)  
  
outfile.close()
```

Using modules

Import module:

```
import sys
x = float(sys.argv[1])
```

Import module member `argv` into current namespace:

```
from sys import argv
x = float(argv[1])
```

Import everything from `sys` (not recommended)

```
from sys import *
x = float(argv[1])

flags = ''
# Oops, flags was also imported from sys, this new flags
# name overwrites sys.flags!
```

Import `argv` under an alias:

```
from sys import argv as a
x = float(a[1])
```

Making your own Python modules

- Reuse scripts by wrapping them in classes or functions
- Collect classes and functions in library modules
- How? just put classes and functions in a file `MyMod.py`
- Put `MyMod.py` in one of the directories where Python can find it (see next slide)

Examples:

```
import MyMod
# or
import MyMod as M # M is a short form
# or
from MyMod import *
# or
from MyMod import myspecialfunction, myotherspecialfunction
```

How Python can find your modules?

Python has some “official” module directories, typically

```
/usr/lib/python2.7
/usr/lib/python2.7/site-packages
/usr/lib/python3.4
/usr/lib/python3.4/site-packages
```

+ current working directory

The environment variable `PYTHONPATH` may contain additional directories with modules

```
> echo $PYTHONPATH
/home/me/python/mymodules:/usr/lib/python3.4:/home/you/yourlibs
```

Python’s `sys.path` list contains the directories where Python searches for modules, and `sys.path` contains “official” directories, plus those in `PYTHONPATH`

Packages

- A class of modules can be collected in a *package*
- Normally, a package is organized as module files in a directory tree
- Each subdirectory has a file `__init__.__` (can be empty)

Can import modules in the tree like this:

```
from MyMod.numerics.pde.grids import fdm_grids

grid = fdm_grids()
grid.domain(xmin=0, xmax=1, ymin=0, ymax=1)
...
```

Here, class `fdm_grids` is in module `grids` (file `grids.py` in the directory `MyMod/numerics/pde`)

Test block in a module

Module files can have a test/demo section at the end:

```
if __name__ == '__main__':
    infile = sys.argv[1]; outfile = sys.argv[2]
    for i in sys.argv[3:]:
        create(infile, outfile, i)
```

- The block is executed *only if* the module file is run as a program
- The tests at the end of a module often serve as good examples on the usage of the module

Installing modules

- Python has its own tool, `Distutils`, for distributing and installing modules
- Installation is based on the script `setup.py`

Standard command:

```
> sudo python setup.py install
```

Writing your own setup.py script

Suppose you have a module in `mymod.py` that you want to distribute to others such that they can easily install it by `setup.py install`.

```
from distutils.core import setup
name='mymod'

setup(name=name,
      version='0.1',
      py_modules=[name],      # modules to be installed
      scripts=[name + '.py'], # programs to be installed
      )
```

Now, `setup.py` will be installed both as a module and as an executable script (if it has a test block for sensible code).

Can easily be extended to install a package of modules, see the [introduction to Distutils](#)

Use doc strings in functions, classes, and modules!

Doc strings = first string in a function, class, or file (module)

```
def ignorecase_sort(a, b):
    """Compare strings a and b, ignoring case."""
    return cmp(a.lower(), b.lower())
```

Doc strings in modules are a (often long multi-line) string starting in the top of the file

```
"""
This module is a fake module
for exemplifying multi-line
doc strings.
"""
import sys
import collections

def somefunc():
    ...
```

Doc strings serve many purposes

- Documentation in the source code
- Online documentation
(Sphinx can automatically produce manuals with doc strings)
- Balloon help in sophisticated GUIs (e.g., IDLE)
- Automatic testing with the `doctest` module