

KPI Quotidien

Interval From 11.05.2026 00:00

To 12.05.2026 00:00

Period Daily values

|                           |             |                     |      | Q1     | 05.05  | 06.05    | 07.05 | 08.05    | 09.05  | 10.05    | 11.05  | FULL YEAR               |
|---------------------------|-------------|---------------------|------|--------|--------|----------|-------|----------|--------|----------|--------|-------------------------|
| PLANT RESULTS LAGGING KPI |             |                     |      | Target | MARDI  | MERCREDI | JEUDI | VENDREDI | SAMEDI | DIMANCHE | LUNDI  | BUDGET 2026             |
| FOUR B                    | CO2         | Débit Bois          | T/h  | 2      |        | 0.24     | 0.57  | 0.47     | 0.83   | 0.72     | 0.01   | 2                       |
|                           | PERFORMANCE | Débit Four          | T/j  | 950    | 879    | 833      | 904   | 898      | 878    | 847      | 812    | 920                     |
|                           |             | Nb Arrêt Four       | #    | 0      | 1      | 0        | 0     | 0        | 0      | 0        | 2      |                         |
|                           |             | NAI Four            | %    |        | 100.0  | 100.0    | 100.0 | 100.0    | 100.0  | 100.0    | 71.4   |                         |
|                           |             | %KM HLC Utilisation | %    | 80     |        |          | 59.45 | 72.60    | 71.02  |          | 55.37  | 80                      |
|                           | ENERGY      | STEC                | MJ/t | 5300   | 22813  | 5802     | 5392  | 5402     | 5458   | 5511     | 6014   | 5300                    |
| FOUR C                    | CO2         | TSR                 | %    | 34     | 34.13  | 62.54    | 43.46 | 62.97    | 39.11  | 22.17    | 141.42 | 35,7%                   |
|                           |             | Débit DSB           | T/h  | 2      | 1.77   | 1.70     | 1.92  | 2.03     | 1.53   | 1.46     | 1.04   | 1,9                     |
|                           |             | GAI                 | %    | 95     | 96.96  | 87.42    | 93.20 | 100.00   | 91.32  | 73.66    | 61.10  | 95,0%                   |
|                           |             | Débit FAN           | T/h  | 2      | 2.14   | 1.93     | 1.93  | 1.82     | 1.77   | 0.88     | 1.18   | 1,9                     |
|                           |             | GAI                 | %    | 80     | 100.16 | 96.36    | 98.48 | 97.08    | 100.00 | 100.23   | 65.72  | 80,0%                   |
|                           |             | Débit Bois Amont    | T/h  | 1,3    | 1.35   | 1.30     | 1.00  | 1.00     | 1.00   | 1.06     | 0.70   | 1,6                     |
|                           |             | GAI                 | %    | 90     | 100.00 | 96.69    | 98.55 | 100.00   | 100.00 | 100.00   | 36.77  | 90,0%                   |
|                           |             | Débit G2000         | T/h  | 1,3    | 0.44   | 0.40     | 0.90  | 1.00     | 1.00   | 0.30     |        | 1,3                     |
|                           |             | Débit STEPI         | T/h  | 0,5    |        |          |       |          |        |          |        | 0,5                     |
|                           | PERFORMANCE | Débit Four          | T/j  | 1530   | 669    | 532      | 1267  | 1359     | 1366   | 405      | 497    | 1570 NORMAL<br>1470 HTS |
|                           |             | Nb Arrêt Four       | #    | 0      | 1      | 1        | 0     | 0        | 0      | 1        | 1      |                         |
|                           |             | NAI Four            | %    |        | 43.5   | 41.9     | 96.0  | 100.0    | 100.0  | 29.8     | 39.1   |                         |
|                           |             | %KM HLC Utilisation | %    | 60     | 26.75  | 21.51    | 25.38 | 21.75    | 18.14  | 15.09    | 5.18   | 80                      |
|                           | ENERGY      | STEC                | MJ/t | 4074   | 4563   | 6152     | 4496  | 4320     | 4315   | 4312     | 6555   | 4050                    |

|          |             |                                  |      |      |      |      |     |      |      |      |      |       |
|----------|-------------|----------------------------------|------|------|------|------|-----|------|------|------|------|-------|
| BK BLANC | CO2         | %CALCAIRE<br>(CEM II 52,5)       | %    | 7.2  |      | 8.1  | 7.5 | 7.7  | 7.8  | 7.7  | 7.5  | 7,2%  |
|          | PERFORMANCE | Nombre d'arrêts BK15             | nbre | 1    | 0    | 2    | 2   | 1    | 0    | 2    | 1    | 0     |
|          | MONITORING  | %DOUTEUX BK15                    | %    | 5    |      | 9.8  | 4.1 | 0.0  | 0.0  | 0.0  | 0.0  | 5%    |
| BK GRIS  | CO2         | %AJOUTS<br>à la cible du produit | %    | 29,9 |      |      |     |      |      |      |      | 29,9% |
|          | PERFORMANCE | Nombre d'arrêts BK0              | nbre | 1    | 2    | 1    | 0   | 1    | 1    | 2    | 2    |       |
|          |             | Nombre d'arrêts BK1              | nbre | 1    | 4    | 0    | 0   | 4    | 0    | 0    | 0    |       |
|          | MONITORING  | %DOUTEUX BK0                     | %    | 30   | 12.5 | 10.1 | 5.7 | 21.6 | 21.9 | 14.9 | 13.1 | 20    |
|          |             | %DOUTEUX au BK1                  | %    | 30   | 0.0  | 0.0  | 0.0 | 0.0  |      |      |      | 20    |
|          |             | %DOUTEUX Dilution                | %    | 8    | 0.1  | 0.1  | 0.0 | 0.0  | 0.1  | 0.0  | 0.0  | 8%    |