

KPI Quotidien

Interval From 03.10.2026 00:00

To 04.10.2026 00:00

Period Daily values

|                           |             |                     |      | Q1     | 27.09    | 28.09  | 29.09  | 30.09    | 01.10  | 02.10    | 03.10  | FULL YEAR               |
|---------------------------|-------------|---------------------|------|--------|----------|--------|--------|----------|--------|----------|--------|-------------------------|
|                           |             |                     |      | Target | DIMANCHE | LUNDI  | MARDI  | MERCREDI | JEUDI  | VENDREDI | SAMEDI | BUDGET 2026             |
| PLANT RESULTS LAGGING KPI | KPI         | Unit                |      |        |          |        |        |          |        |          |        |                         |
| FOUR B                    | CO2         | Débit Bois          | T/h  | 2      | 1.22     | 1.48   | 1.86   | 1.79     | 1.02   | 1.40     | 0.30   | 2                       |
|                           | PERFORMANCE | Débit Four          | T/j  | 950    | 769      | 779    | 829    | 821      | 836    | 830      | 855    | 920                     |
|                           |             | Nb Arrêt Four       | #    | 0      | 0        | 0      | 0      | 0        | 0      | 0        | 0      |                         |
|                           |             | NAI Four            | %    |        | 100.0    | 100.0  | 100.0  | 100.0    | 100.0  | 100.0    | 100.0  |                         |
|                           |             | %KM HLC Utilisation | %    | 80     |          |        |        |          |        | 68.87    |        | 80                      |
|                           | ENERGY      | STEC                | MJ/t | 5300   | 6140     | 6071   | 5883   | 6035     | 5361   | 5428     | 5361   | 5300                    |
| FOUR C                    | CO2         | TSR                 | %    | 34     | 32.76    | 26.38  | 28.92  | 16.57    | 16.70  | 24.28    | 28.14  | 35,7%                   |
|                           |             | Débit DSB           | T/h  | 2      | 1.37     | 1.64   | 1.59   | 1.35     | 1.48   | 1.49     | 1.49   | 1,9                     |
|                           |             | GAI                 | %    | 95     | 100.00   | 100.00 | 88.82  | 100.00   | 100.00 | 100.00   | 99.65  | 95,0%                   |
|                           |             | Débit FAN           | T/h  | 2      | 1.54     | 1.27   | 1.43   |          |        | 1.77     | 1.79   | 1,9                     |
|                           |             | GAI                 | %    | 80     | 91.67    | 94.51  | 38.19  | 0.00     | 0.00   | 59.38    | 98.13  | 80,0%                   |
|                           |             | Débit Bois Amont    | T/h  | 1,3    | 1.43     | 1.28   | 1.36   | 1.36     | 1.21   | 1.26     | 1.20   | 1,6                     |
|                           |             | GAI                 | %    | 90     | 100.00   | 100.00 | 100.00 | 100.00   | 100.00 | 99.72    | 100.00 | 90,0%                   |
|                           |             | Débit G2000         | T/h  | 1,3    | 1.38     | 0.87   | 1.12   | 0.99     | 0.84   | 1.40     | 1.40   | 1,3                     |
|                           |             | Débit STEPI         | T/h  | 0,5    |          |        |        |          |        |          |        | 0,5                     |
|                           | PERFORMANCE | Débit Four          | T/j  | 1530   | 1569     | 1583   | 1592   | 1547     | 1680   | 1668     | 1693   | 1570 NORMAL<br>1470 HTS |
|                           |             | Nb Arrêt Four       | #    | 0      | 0        | 0      | 0      | 0        | 0      | 0        | 0      |                         |
|                           |             | NAI Four            | %    |        | 100.0    | 100.0  | 100.0  | 100.0    | 100.0  | 100.0    | 100.0  |                         |
|                           |             | %KM HLC Utilisation | %    | 60     | 25.98    | 37.73  | 25.43  | 44.08    | 48.43  | 32.78    | 28.20  | 80                      |
|                           | ENERGY      | STEC                | MJ/t | 4074   | 3960     | 3914   | 3952   | 3896     | 3823   | 3930     | 3960   | 4050                    |

|          |             |                                  |      |      |      |      |      |      |      |      |      |       |
|----------|-------------|----------------------------------|------|------|------|------|------|------|------|------|------|-------|
| BK BLANC | CO2         | %CALCAIRE<br>(CEM II 52,5)       | %    | 7,2  | 8.4  | 8.5  | 8.4  | 8.6  | 8.1  | 8.4  | 8.2  | 7,2%  |
|          | PERFORMANCE | Nombre d'arrêts BK15             | nbre | 1    | 0    | 1    | 2    | 0    | 1    | 0    | 1    | 0     |
|          | MONITORING  | %DOUTEUX BK15                    | %    | 5    | 0.0  | 0.0  | 6.5  | 3.8  | 0.0  | 0.0  | 0.0  | 5%    |
| BK GRIS  | CO2         | %AJOUTS<br>à la cible du produit | %    | 29,9 |      |      |      |      |      |      |      | 29,9% |
|          | PERFORMANCE | Nombre d'arrêts BK0              | nbre | 1    | 1    | 0    | 1    | 4    | 0    | 0    | 1    |       |
|          |             | Nombre d'arrêts BK1              | nbre | 1    | 1    | 1    | 5    | 1    | 0    | 0    | 0    |       |
|          | MONITORING  | %DOUTEUX BK0                     | %    | 30   | 20.6 | 12.0 | 16.2 | 10.7 | 13.6 | 18.1 | 16.6 | 20    |
|          |             | %DOUTEUX au BK1                  | %    | 30   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.3  | 20    |
|          |             | %DOUTEUX Dilution                | %    | 8    | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 8%    |