

KPI Quotidien

Interval From 01.06.2026 00:00

To 02.06.2026 00:00

Period Daily values

|        |                           |                     |      | Q1     | 26.05 | 27.05    | 28.05  | 29.05    | 30.05  | 31.05    | 01.06  | FULL YEAR               |
|--------|---------------------------|---------------------|------|--------|-------|----------|--------|----------|--------|----------|--------|-------------------------|
|        |                           |                     |      | Target | MARDI | MERCREDI | JEUDI  | VENDREDI | SAMEDI | DIMANCHE | LUNDI  | BUDGET 2026             |
| FOUR B | PLANT RESULTS LAGGING KPI | KPI                 | Unit |        |       |          |        |          |        |          |        |                         |
|        | CO2                       | Débit Bois          | T/h  | 2      | 0.41  | 0.20     | 1.65   | 0.58     | 1.39   | 1.54     | 1.28   | 2                       |
|        | PERFORMANCE               | Débit Four          | T/j  | 950    | 892   | 840      | 865    | 860      | 822    | 865      | 850    | 920                     |
|        |                           | Nb Arrêt Four       | #    | 0      | 0     | 0        | 0      | 1        | 0      | 0        | 0      |                         |
|        |                           | NAI Four            | %    |        | 100.0 | 100.0    | 100.0  | 28.3     | 94.1   | 100.0    | 100.0  |                         |
|        |                           | %KM HLC Utilisation | %    | 80     | 71.66 |          | 56.67  | 40.25    |        | 43.46    | 79.29  | 80                      |
|        | ENERGY                    | STEC                | MJ/t | 5300   | 4247  | 4332     | 4362   | 18656    | 5835   | 4385     | 5303   | 5300                    |
| FOUR C | CO2                       | TSR                 | %    | 34     |       |          | 100.00 | 36.95    | 80.57  | 37.48    | 39.11  | 35,7%                   |
|        |                           | Débit DSB           | T/h  | 2      |       |          |        | 1.18     | 1.42   | 1.65     | 1.48   | 1,9                     |
|        |                           | GAI                 | %    | 95     |       |          |        | 68.76    | 45.69  | 98.89    | 69.58  | 95,0%                   |
|        |                           | Débit FAN           | T/h  | 2      |       |          |        | 1.65     | 1.42   | 1.88     | 1.60   | 1,9                     |
|        |                           | GAI                 | %    | 80     |       |          |        | 77.72    | 74.14  | 100.00   | 100.00 | 80,0%                   |
|        |                           | Débit Bois Amont    | T/h  | 1,3    |       |          |        | 1.01     | 0.99   | 1.33     | 1.20   | 1,6                     |
|        |                           | GAI                 | %    | 90     |       |          |        | 16.74    | 94.83  | 100.00   | 100.00 | 90,0%                   |
|        |                           | Débit G2000         | T/h  | 1,3    |       |          |        | 0.48     | 0.12   | 1.24     | 1.40   | 1,3                     |
|        |                           | Débit STEPI         | T/h  | 0,5    |       |          |        |          |        |          |        | 0,5                     |
|        | PERFORMANCE               | Débit Four          | T/j  | 1530   | 0     | 0        | 0      | 738      | 180    | 1281     | 1549   | 1570 NORMAL<br>1470 HTS |
|        |                           | Nb Arrêt Four       | #    | 0      | 0     | 0        | 0      | 1        | 0      | 0        | 0      |                         |
|        |                           | NAI Four            | %    |        | 0.0   | 0.0      | 0.0    | 65.1     | 16.1   | 100.0    | 100.0  |                         |
|        |                           | %KM HLC Utilisation | %    | 60     | 0.00  | 0.00     | 0.00   | 10.85    | 0.00   | 24.02    | 29.87  | 80                      |
|        | ENERGY                    | STEC                | MJ/t | 4074   |       |          |        | 4884     | 11024  | 4522     | 4173   | 4050                    |

|          |             |                                  |      |      |      |      |     |      |      |      |      |       |
|----------|-------------|----------------------------------|------|------|------|------|-----|------|------|------|------|-------|
| BK BLANC | CO2         | %CALCAIRE<br>(CEM II 52,5)       | %    | 7.2  | 8.6  | 8.2  | 8.0 | 7.6  | 7.8  |      | 7.8  | 7,2%  |
|          | PERFORMANCE | Nombre d'arrêts BK15             | nbre | 1    | 0    | 1    | 5   | 1    | 3    | 3    | 1    | 0     |
|          | MONITORING  | %DOUTEUX BK15                    | %    | 5    |      | 0.2  | 0.0 | 0.0  | 0.0  | 0.0  | 0.0  | 5%    |
| BK GRIS  | CO2         | %AJOUTS<br>à la cible du produit | %    | 29,9 |      |      |     |      |      |      |      | 29,9% |
|          | PERFORMANCE | Nombre d'arrêts BK0              | nbre | 1    | 1    | 1    | 2   | 1    | 0    | 0    | 0    |       |
|          |             | Nombre d'arrêts BK1              | nbre | 1    | 3    | 1    | 6   | 4    | 0    | 3    | 4    |       |
|          | MONITORING  | %DOUTEUX BK0                     | %    | 30   | 25.1 | 10.6 | 8.1 | 13.7 | 17.4 | 21.1 | 19.6 | 20    |
|          |             | %DOUTEUX au BK1                  | %    | 30   | 13.9 | 23.2 | 0.8 | 0.0  | 0.0  | 0.0  | 21.4 | 20    |
|          |             | %DOUTEUX Dilution                | %    | 8    | 0.0  | 0.0  | 0.0 | 0.0  | 0.0  | 0.0  | 0.0  | 8%    |