

KPI Quotidien

Interval From 26.08.2026 00:00

To 27.08.2026 00:00

Period Daily values

|        |                              |                     |      | Q1     | 20.08 | 21.08    | 22.08  | 23.08    | 24.08  | 25.08 | 26.08    | FULL YEAR               |
|--------|------------------------------|---------------------|------|--------|-------|----------|--------|----------|--------|-------|----------|-------------------------|
|        | PLANT RESULTS<br>LAGGING KPI | KPI                 | Unit | Target | JEUDI | VENDREDI | SAMEDI | DIMANCHE | LUNDI  | MARDI | MERCREDI | BUDGET 2026             |
| FOUR B | CO2                          | Débit Bois          | T/h  | 2      |       |          |        |          |        |       |          | 2                       |
|        | PERFORMANCE                  | Débit Four          | T/j  | 950    |       |          |        |          |        |       |          | 920                     |
|        |                              | Nb Arrêt Four       | #    | 0      | 0     | 0        | 0      | 0        | 0      | 0     | 0        |                         |
|        |                              | NAI Four            | %    |        | 100.0 | 100.0    | 100.0  | 100.0    | 100.0  | 100.0 | 100.0    |                         |
|        |                              | %KM HLC Utilisation | %    | 80     |       |          |        |          |        |       |          | 80                      |
|        | ENERGY                       | STEC                | MJ/t | 5300   |       |          |        |          |        |       |          | 5300                    |
| FOUR C | CO2                          | TSR                 | %    | 34     |       |          |        |          | 100.00 | 63.91 | 27.35    | 35,7%                   |
|        |                              | Débit DSB           | T/h  | 2      |       |          |        |          |        | 1.16  | 1.45     | 1,9                     |
|        |                              | GAI                 | %    | 95     |       |          |        |          |        | 22.36 | 89.31    | 95,0%                   |
|        |                              | Débit FAN           | T/h  | 2      |       |          |        |          |        | 1.07  | 1.41     | 1,9                     |
|        |                              | GAI                 | %    | 80     |       |          |        |          |        | 65.11 | 99.17    | 80,0%                   |
|        |                              | Débit Bois Amont    | T/h  | 1,3    |       |          |        |          |        | 0.69  | 0.98     | 1,6                     |
|        |                              | GAI                 | %    | 90     |       |          |        |          |        | 30.22 | 100.00   | 90,0%                   |
|        |                              | Débit G2000         | T/h  | 1,3    |       |          |        |          |        | 0.04  | 0.78     | 1,3                     |
|        |                              | Débit STEPI         | T/h  | 0,5    |       |          |        |          |        |       |          | 0,5                     |
|        | PERFORMANCE                  | Débit Four          | T/j  | 1530   | 0     | 0        | 0      | 0        | 0      | 350   | 1366     | 1570 NORMAL<br>1470 HTS |
|        |                              | Nb Arrêt Four       | #    | 0      | 0     | 0        | 0      | 0        | 0      | 1     | 0        |                         |
|        |                              | NAI Four            | %    |        | 0.0   | 0.0      | 0.0    | 0.0      | 0.0    | 28.3  | 100.0    |                         |
|        |                              | %KM HLC Utilisation | %    | 60     | 0.00  | 0.00     | 0.00   | 0.00     | 0.00   | 13.80 | 20.59    | 80                      |
|        |                              | ENERGY              | STEC | MJ/t   | 4074  |          |        |          |        |       | 8342     | 4352                    |

|          |             |                                  |      |      |     |      |      |      |     |     |     |       |
|----------|-------------|----------------------------------|------|------|-----|------|------|------|-----|-----|-----|-------|
| BK BLANC | CO2         | %CALCAIRE<br>(CEM II 52,5)       | %    | 7,2  |     | 8.4  | 8.0  |      | 8.8 | 8.4 | 8.1 | 7,2%  |
|          | PERFORMANCE | Nombre d'arrêts BK15             | nbre | 1    | 0   | 0    | 2    | 1    | 0   | 1   | 0   | 0     |
|          | MONITORING  | %DOUTEUX BK15                    | %    | 5    |     |      | 0.0  | 0.0  |     | 0.0 |     | 5%    |
| BK GRIS  | CO2         | %AJOUTS<br>à la cible du produit | %    | 29,9 |     |      |      |      |     |     |     | 29,9% |
|          | PERFORMANCE | Nombre d'arrêts BK0              | nbre | 1    | 0   | 1    | 0    | 1    | 1   | 0   | 0   |       |
|          |             | Nombre d'arrêts BK1              | nbre | 1    | 0   | 0    | 2    | 2    | 0   | 0   | 0   |       |
|          | MONITORING  | %DOUTEUX BK0                     | %    | 30   |     | 19.8 | 19.1 | 12.0 | 2.1 |     |     | 20    |
|          |             | %DOUTEUX au BK1                  | %    | 30   |     |      | 0.0  | 0.0  |     |     |     | 20    |
|          |             | %DOUTEUX Dilution                | %    | 8    | 0.0 | 0.0  | 0.0  | 0.0  | 0.0 | 0.0 | 0.0 | 8%    |