

# KPI Quotidien

Interval From 20.05.2026 00:00

To 21.05.2026 00:00

Period Daily values

|                           |             |                     |      | Q1     | 14.05 | 15.05    | 16.05  | 17.05    | 18.05 | 19.05  | 20.05    | FULL YEAR               |
|---------------------------|-------------|---------------------|------|--------|-------|----------|--------|----------|-------|--------|----------|-------------------------|
| PLANT RESULTS LAGGING KPI |             |                     |      | Target | JEUDI | VENDREDI | SAMEDI | DIMANCHE | LUNDI | MARDI  | MERCREDI | BUDGET 2026             |
| FOUR B                    | CO2         | Débit Bois          | T/h  | 2      | 1.04  | 0.90     | 1.10   |          |       |        | 0.12     | 2                       |
|                           | PERFORMANCE | Débit Four          | T/j  | 950    | 823   | 838      | 843    | 841      | 833   | 841    | 830      | 920                     |
|                           |             | Nb Arrêt Four       | #    | 0      | 0     | 0        | 0      | 0        | 0     | 1      | 0        |                         |
|                           |             | NAI Four            | %    |        | 100.0 | 100.0    | 100.0  | 100.0    | 100.0 | 93.6   | 100.0    |                         |
|                           |             | %KM HLC Utilisation | %    | 80     |       |          |        |          |       |        | 38.64    | 80                      |
|                           | ENERGY      | STEC                | MJ/t | 5300   | 5722  | 5633     | 5778   | 5712     | 5697  | 5711   | 5729     | 5300                    |
| FOUR C                    | CO2         | TSR                 | %    | 34     | 53.04 | 47.59    | 33.06  | 43.31    | 38.81 | 100.00 | 58.34    | 35,7%                   |
|                           |             | Débit DSB           | T/h  | 2      | 1.86  | 1.95     | 1.78   | 1.57     | 1.78  |        | 1.42     | 1,9                     |
|                           |             | GAI                 | %    | 95     | 99.79 | 74.03    | 97.22  | 96.46    | 94.03 |        | 83.18    | 95,0%                   |
|                           |             | Débit FAN           | T/h  | 2      | 1.50  | 1.40     | 1.40   | 1.72     | 1.82  |        | 1.40     | 1,9                     |
|                           |             | GAI                 | %    | 80     | 93.26 | 100.00   | 100.00 | 100.00   | 66.69 |        | 82.65    | 80,0%                   |
|                           |             | Débit Bois Amont    | T/h  | 1,3    | 0.98  | 1.21     | 1.31   | 1.00     | 1.06  |        | 1.09     | 1,6                     |
|                           |             | GAI                 | %    | 90     | 65.83 | 100.00   | 54.65  | 54.72    | 76.56 |        | 68.07    | 90,0%                   |
|                           |             | Débit G2000         | T/h  | 1,3    | 1.40  | 1.40     | 1.40   | 1.40     | 1.37  |        | 0.53     | 1,3                     |
|                           |             | Débit STEPI         | T/h  | 0,5    |       |          |        |          |       |        |          | 0,5                     |
|                           | PERFORMANCE | Débit Four          | T/j  | 1530   | 1509  | 1592     | 1595   | 1575     | 1571  | 0      | 753      | 1570 NORMAL<br>1470 HTS |
|                           |             | Nb Arrêt Four       | #    | 0      | 0     | 0        | 0      | 0        | 1     | 0      | 0        |                         |
|                           |             | NAI Four            | %    |        | 100.0 | 100.0    | 100.0  | 100.0    | 97.8  | 0.0    | 52.8     |                         |
|                           |             | %KM HLC Utilisation | %    | 60     | 46.22 | 39.74    | 44.29  | 44.67    | 46.40 | 0.00   | 31.48    | 80                      |
|                           | ENERGY      | STEC                | MJ/t | 4074   | 3965  | 3955     | 3868   | 3921     | 3902  |        | 5584     | 4050                    |

|          |             |                                  |      |      |      |      |      |      |      |      |      |       |
|----------|-------------|----------------------------------|------|------|------|------|------|------|------|------|------|-------|
| BK BLANC | CO2         | %CALCAIRE<br>(CEM II 52,5)       | %    | 7.2  | 7.8  | 7.9  | 8.1  | 8.4  | 8.4  | 7.8  | 7.8  | 7,2%  |
|          | PERFORMANCE | Nombre d'arrêts BK15             | nbre | 1    | 1    | 0    | 1    | 0    | 0    | 0    | 1    | 0     |
|          | MONITORING  | %DOUTEUX BK15                    | %    | 5    | 0.0  | 0.0  | 0.0  |      |      | 0.0  | 0.0  | 5%    |
| BK GRIS  | CO2         | %AJOUTS<br>à la cible du produit | %    | 29,9 |      |      |      |      |      |      |      | 29,9% |
|          | PERFORMANCE | Nombre d'arrêts BK0              | nbre | 1    | 0    | 1    | 1    | 1    | 0    | 0    | 2    |       |
|          |             | Nombre d'arrêts BK1              | nbre | 1    | 1    | 0    | 1    | 0    | 0    | 1    | 2    |       |
|          | MONITORING  | %DOUTEUX BK0                     | %    | 30   | 19.3 | 20.7 | 10.4 | 20.0 | 22.0 | 13.6 | 21.4 | 20    |
|          |             | %DOUTEUX au BK1                  | %    | 30   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 19.5 | 20    |
|          |             | %DOUTEUX Dilution                | %    | 8    | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.1  | 8%    |