

KPI Quotidien

Interval From 04.08.2026 00:00

To 05.08.2026 00:00

Period Daily values

|                           |             |                     |      | Q1     | 29.07    | 30.07  | 31.07    | 01.08  | 02.08    | 03.08 | 04.08 | FULL YEAR               |
|---------------------------|-------------|---------------------|------|--------|----------|--------|----------|--------|----------|-------|-------|-------------------------|
|                           |             |                     |      | Target | MERCREDI | JEUDI  | VENDREDI | SAMEDI | DIMANCHE | LUNDI | MARDI | BUDGET 2026             |
| PLANT RESULTS LAGGING KPI | KPI         | Unit                |      |        |          |        |          |        |          |       |       |                         |
| FOUR B                    | CO2         | Débit Bois          | T/h  | 2      | 0.53     | 0.38   | 0.69     | 0.76   | 0.20     | 0.38  | 0.71  | 2                       |
|                           | PERFORMANCE | Débit Four          | T/j  | 950    | 856      | 822    | 819      | 829    | 807      | 792   | 756   | 920                     |
|                           |             | Nb Arrêt Four       | #    | 0      | 1        | 1      | 0        | 1      | 3        | 0     | 0     |                         |
|                           |             | NAI Four            | %    |        | 99.0     | 99.0   | 100.0    | 98.5   | 72.6     | 69.9  | 100.0 |                         |
|                           |             | %KM HLC Utilisation | %    | 80     |          |        |          |        |          |       |       | 80                      |
|                           | ENERGY      | STEC                | MJ/t | 5300   | 5713     | 5530   | 5607     | 5606   | 5787     | 6324  | 5681  | 5300                    |
| FOUR C                    | CO2         | TSR                 | %    | 34     | 29.12    | 37.06  | 64.08    | 47.01  | 41.34    |       |       | 35,7%                   |
|                           |             | Débit DSB           | T/h  | 2      | 1.74     | 1.65   | 1.69     | 1.73   | 1.80     |       |       | 1,9                     |
|                           |             | GAI                 | %    | 95     | 100.00   | 97.71  | 94.18    | 81.53  | 100.09   |       |       | 95,0%                   |
|                           |             | Débit FAN           | T/h  | 2      | 1.55     | 1.83   | 1.83     | 1.74   | 1.74     |       |       | 1,9                     |
|                           |             | GAI                 | %    | 80     | 96.39    | 100.00 | 96.70    | 100.00 | 98.55    |       |       | 80,0%                   |
|                           |             | Débit Bois Amont    | T/h  | 1,3    | 1.19     | 1.19   | 1.17     | 1.20   | 1.20     |       |       | 1,6                     |
|                           |             | GAI                 | %    | 90     | 100.00   | 100.00 | 98.74    | 100.00 | 100.00   |       |       | 90,0%                   |
|                           |             | Débit G2000         | T/h  | 1,3    | 1.15     | 1.18   | 0.51     | 1.20   | 0.98     |       |       | 1,3                     |
|                           |             | Débit STEPI         | T/h  | 0,5    |          |        |          |        |          |       |       | 0,5                     |
|                           | PERFORMANCE | Débit Four          | T/j  | 1530   | 1349     | 1390   | 517      | 1569   | 1378     | 0     | 0     | 1570 NORMAL<br>1470 HTS |
|                           |             | Nb Arrêt Four       | #    | 0      | 0        | 0      | 1        | 0      | 1        | 0     | 0     |                         |
|                           |             | NAI Four            | %    |        | 100.0    | 100.0  | 44.2     | 100.0  | 81.4     | 0.0   | 0.0   |                         |
|                           |             | %KM HLC Utilisation | %    | 60     | 52.97    | 66.19  | 43.67    | 36.59  | 27.84    | 0.00  | 0.00  | 80                      |
|                           | ENERGY      | STEC                | MJ/t | 4074   | 4887     | 4843   | 6239     | 3985   | 4055     |       |       | 4050                    |

|          |             |                                  |      |      |      |      |     |     |      |      |     |       |
|----------|-------------|----------------------------------|------|------|------|------|-----|-----|------|------|-----|-------|
| BK BLANC | CO2         | %CALCAIRE<br>(CEM II 52,5)       | %    | 7,2  | 8.1  | 8.3  | 8.2 | 8.1 |      | 8.8  | 8.2 | 7,2%  |
|          | PERFORMANCE | Nombre d'arrêts BK15             | nbre | 1    | 2    | 0    | 0   | 1   | 1    | 1    | 1   | 0     |
|          | MONITORING  | %DOUTEUX BK15                    | %    | 5    | 0.0  | 0.0  | 0.0 | 0.0 | 0.0  | 0.0  | 0.0 | 5%    |
| BK GRIS  | CO2         | %AJOUTS<br>à la cible du produit | %    | 29,9 |      |      |     |     |      |      |     | 29,9% |
|          | PERFORMANCE | Nombre d'arrêts BK0              | nbre | 1    | 2    | 0    | 2   | 2   | 1    | 2    | 2   |       |
|          |             | Nombre d'arrêts BK1              | nbre | 1    | 1    | 2    | 0   | 3   | 0    | 1    | 0   |       |
|          | MONITORING  | %DOUTEUX BK0                     | %    | 30   | 16.7 | 19.1 | 7.8 | 7.9 | 12.4 | 13.3 | 5.0 | 20    |
|          |             | %DOUTEUX au BK1                  | %    | 30   | 0.0  | 0.0  | 0.0 | 0.0 | 0.0  | 0.0  | 0.0 | 20    |
|          |             | %DOUTEUX Dilution                | %    | 8    | 0.0  | 0.0  | 0.0 | 0.0 | 0.0  | 0.0  | 0.0 | 8%    |