

KPI Quotidien

Interval From 08.05.2026 00:00

To 09.05.2026 00:00

Period Daily values

|                           |             |                     |      | Q1     | 02.05  | 03.05    | 04.05  | 05.05  | 06.05    | 07.05 | 08.05    | FULL YEAR               |
|---------------------------|-------------|---------------------|------|--------|--------|----------|--------|--------|----------|-------|----------|-------------------------|
| PLANT RESULTS LAGGING KPI |             |                     |      | Target | SAMEDI | DIMANCHE | LUNDI  | MARDI  | MERCREDI | JEUDI | VENDREDI | BUDGET 2026             |
| FOUR B                    | CO2         | Débit Bois          | T/h  | 2      |        |          |        |        | 0.24     | 0.57  | 0.47     | 2                       |
|                           | PERFORMANCE | Débit Four          | T/j  | 950    |        |          |        | 879    | 833      | 904   | 898      | 920                     |
|                           |             | Nb Arrêt Four       | #    | 0      | 0      | 0        | 0      | 1      | 0        | 0     | 0        |                         |
|                           |             | NAI Four            | %    |        | 100.0  | 100.0    | 100.0  | 69.9   | 100.0    | 100.0 | 100.0    |                         |
|                           |             | %KM HLC Utilisation | %    | 80     |        |          |        |        |          | 59.45 | 72.60    | 80                      |
|                           | ENERGY      | STEC                | MJ/t | 5300   |        |          |        | 22813  | 5802     | 5392  | 5402     | 5300                    |
| FOUR C                    | CO2         | TSR                 | %    | 34     | 28.70  | 68.68    | 30.35  | 34.13  | 62.54    | 43.46 | 62.97    | 35,7%                   |
|                           |             | Débit DSB           | T/h  | 2      | 1.62   | 1.60     | 1.63   | 1.77   | 1.70     | 1.92  | 2.03     | 1,9                     |
|                           |             | GAI                 | %    | 95     | 95.40  | 89.10    | 64.31  | 96.96  | 87.42    | 93.20 | 100.00   | 95,0%                   |
|                           |             | Débit FAN           | T/h  | 2      | 1.81   | 1.72     | 1.88   | 2.14   | 1.93     | 1.93  | 1.82     | 1,9                     |
|                           |             | GAI                 | %    | 80     | 99.72  | 100.00   | 99.31  | 100.16 | 96.36    | 98.48 | 97.08    | 80,0%                   |
|                           |             | Débit Bois Amont    | T/h  | 1,3    | 1.12   | 1.00     | 1.18   | 1.35   | 1.30     | 1.00  | 1.00     | 1,6                     |
|                           |             | GAI                 | %    | 90     | 99.79  | 100.00   | 100.00 | 100.00 | 96.69    | 98.55 | 100.00   | 90,0%                   |
|                           |             | Débit G2000         | T/h  | 1,3    | 1.39   | 1.19     | 0.70   | 0.44   | 0.40     | 0.90  | 1.00     | 1,3                     |
|                           |             | Débit STEPI         | T/h  | 0,5    |        |          |        |        |          |       |          | 0,5                     |
|                           | PERFORMANCE | Débit Four          | T/j  | 1530   | 1641   | 1626     | 1655   | 669    | 532      | 1267  | 1359     | 1570 NORMAL<br>1470 HTS |
|                           |             | Nb Arrêt Four       | #    | 0      | 1      | 0        | 0      | 1      | 1        | 0     | 0        |                         |
|                           |             | NAI Four            | %    |        | 99.6   | 100.0    | 100.0  | 43.5   | 41.9     | 96.0  | 100.0    |                         |
|                           |             | %KM HLC Utilisation | %    | 60     | 30.34  | 30.81    | 38.96  | 26.75  | 21.51    | 25.38 | 21.75    | 80                      |
|                           | ENERGY      | STEC                | MJ/t | 4074   | 3961   | 4067     | 3883   | 4563   | 6152     | 4496  | 4320     | 4050                    |

|          |             |                                  |      |      |      |      |      |      |      |     |      |       |
|----------|-------------|----------------------------------|------|------|------|------|------|------|------|-----|------|-------|
| BK BLANC | CO2         | %CALCAIRE<br>(CEM II 52,5)       | %    | 7.2  | 8.0  | 8.2  | 8.6  |      | 8.1  | 7.5 | 7.7  | 7,2%  |
|          | PERFORMANCE | Nombre d'arrêts BK15             | nbre | 1    | 1    | 0    | 0    | 0    | 2    | 2   | 1    | 0     |
|          | MONITORING  | %DOUTEUX BK15                    | %    | 5    | 11.7 |      | 0.0  |      | 9.8  | 4.1 | 0.0  | 5%    |
| BK GRIS  | CO2         | %AJOUTS<br>à la cible du produit | %    | 29,9 |      |      |      |      |      |     |      | 29,9% |
|          | PERFORMANCE | Nombre d'arrêts BK0              | nbre | 1    | 2    | 2    | 0    | 2    | 1    | 0   | 1    |       |
|          |             | Nombre d'arrêts BK1              | nbre | 1    | 3    | 1    | 3    | 4    | 0    | 0   | 4    |       |
|          | MONITORING  | %DOUTEUX BK0                     | %    | 30   | 21.0 | 21.0 | 13.1 | 12.5 | 10.1 | 5.7 | 21.6 | 20    |
|          |             | %DOUTEUX au BK1                  | %    | 30   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0 | 0.0  | 20    |
|          |             | %DOUTEUX Dilution                | %    | 8    | 0.0  | 0.1  | 0.0  | 0.1  | 0.1  | 0.0 | 0.0  | 8%    |