

KPI Quotidien

Interval From 24.09.2026 00:00

To 25.09.2026 00:00

Period Daily values

|                           |             |                     |      | Q1     | 18.09    | 19.09  | 20.09    | 21.09  | 22.09  | 23.09    | 24.09  | FULL YEAR               |
|---------------------------|-------------|---------------------|------|--------|----------|--------|----------|--------|--------|----------|--------|-------------------------|
|                           |             |                     |      | Target | VENDREDI | SAMEDI | DIMANCHE | LUNDI  | MARDI  | MERCREDI | JEUDI  | BUDGET 2026             |
| PLANT RESULTS LAGGING KPI | KPI         | Unit                |      |        |          |        |          |        |        |          |        |                         |
| FOUR B                    | CO2         | Débit Bois          | T/h  | 2      | 0.38     | 0.70   | 0.47     | 1.42   | 0.40   | 1.30     | 1.47   | 2                       |
|                           | PERFORMANCE | Débit Four          | T/j  | 950    | 835      | 800    | 765      | 789    | 785    | 815      | 820    | 920                     |
|                           |             | Nb Arrêt Four       | #    | 0      | 1        | 1      | 1        | 0      | 0      | 0        | 0      |                         |
|                           |             | NAI Four            | %    |        | 91.6     | 91.6   | 77.0     | 100.0  | 100.0  | 100.0    | 100.0  |                         |
|                           |             | %KM HLC Utilisation | %    | 80     |          |        |          |        |        |          |        | 80                      |
|                           | ENERGY      | STEC                | MJ/t | 5300   | 6982     | 5762   | 6073     | 5466   | 5753   | 5265     | 5260   | 5300                    |
| FOUR C                    | CO2         | TSR                 | %    | 34     | 33.67    | 42.61  | 40.89    | 20.38  | 26.79  | 34.44    | 44.80  | 35,7%                   |
|                           |             | Débit DSB           | T/h  | 2      | 1.06     | 1.42   | 1.65     | 1.11   | 1.50   | 1.48     | 1.66   | 1,9                     |
|                           |             | GAI                 | %    | 95     | 98.75    | 71.39  | 99.03    | 68.96  | 62.92  | 95.00    | 100.00 | 95,0%                   |
|                           |             | Débit FAN           | T/h  | 2      | 2.00     | 1.41   | 1.92     | 1.86   | 1.72   | 1.61     | 1.89   | 1,9                     |
|                           |             | GAI                 | %    | 80     | 100.00   | 64.90  | 97.64    | 95.83  | 97.50  | 92.99    | 100.00 | 80,0%                   |
|                           |             | Débit Bois Amont    | T/h  | 1,3    | 1.20     | 1.27   | 1.30     | 1.30   | 1.38   | 1.40     | 1.40   | 1,6                     |
|                           |             | GAI                 | %    | 90     | 100.00   | 69.01  | 100.00   | 100.00 | 100.00 | 100.00   | 100.00 | 90,0%                   |
|                           |             | Débit G2000         | T/h  | 1,3    | 0.39     | 0.32   | 0.77     | 0.39   | 1.07   | 1.40     | 1.40   | 1,3                     |
|                           |             | Débit STEPI         | T/h  | 0,5    |          |        |          |        |        |          |        | 0,5                     |
|                           | PERFORMANCE | Débit Four          | T/j  | 1530   | 1592     | 702    | 1405     | 1551   | 1574   | 1644     | 1580   | 1570 NORMAL<br>1470 HTS |
|                           |             | Nb Arrêt Four       | #    | 0      | 0        | 2      | 0        | 0      | 0      | 0        | 0      |                         |
|                           |             | NAI Four            | %    |        | 100.0    | 52.4   | 100.0    | 100.0  | 100.0  | 100.0    | 100.0  |                         |
|                           |             | %KM HLC Utilisation | %    | 60     | 27.10    | 15.53  | 22.40    | 34.48  | 20.69  | 21.23    | 25.35  | 80                      |
|                           | ENERGY      | STEC                | MJ/t | 4074   | 4200     | 5055   | 4611     | 4295   | 4270   | 4204     | 4255   | 4050                    |

|          |             |                                  |      |      |      |      |      |      |      |      |      |       |
|----------|-------------|----------------------------------|------|------|------|------|------|------|------|------|------|-------|
| BK BLANC | CO2         | %CALCAIRE<br>(CEM II 52,5)       | %    | 7,2  |      |      |      | 7.9  |      | 8.1  | 8.2  | 7,2%  |
|          | PERFORMANCE | Nombre d'arrêts BK15             | nbre | 1    | 2    | 1    | 1    | 0    | 1    | 3    | 2    | 0     |
|          | MONITORING  | %DOUTEUX BK15                    | %    | 5    | 0.1  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 5%    |
| BK GRIS  | CO2         | %AJOUTS<br>à la cible du produit | %    | 29,9 |      |      |      |      |      |      |      | 29,9% |
|          | PERFORMANCE | Nombre d'arrêts BK0              | nbre | 1    | 3    | 2    | 0    | 2    | 0    | 0    | 0    |       |
|          |             | Nombre d'arrêts BK1              | nbre | 1    | 1    | 2    | 2    | 5    | 0    | 0    | 1    |       |
|          | MONITORING  | %DOUTEUX BK0                     | %    | 30   | 22.7 | 23.1 | 21.5 | 18.9 | 24.5 | 21.6 | 20.3 | 20    |
|          |             | %DOUTEUX au BK1                  | %    | 30   | 0.0  | 0.0  | 0.6  | 0.0  | 0.0  | 0.0  | 0.0  | 20    |
|          |             | %DOUTEUX Dilution                | %    | 8    | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 8%    |