

KPI Quotidien

Interval From 19.05.2026 00:00

To 20.05.2026 00:00

Period Daily values

|        |                           |                     |      | Q1     | 13.05    | 14.05 | 15.05    | 16.05  | 17.05    | 18.05 | 19.05  | FULL YEAR               |
|--------|---------------------------|---------------------|------|--------|----------|-------|----------|--------|----------|-------|--------|-------------------------|
|        |                           |                     |      | Target | MERCREDI | JEUDI | VENDREDI | SAMEDI | DIMANCHE | LUNDI | MARDI  | BUDGET 2026             |
| FOUR B | PLANT RESULTS LAGGING KPI | KPI                 | Unit |        |          |       |          |        |          |       |        |                         |
|        | CO2                       | Débit Bois          | T/h  | 2      | 1.06     | 1.04  | 0.90     | 1.10   |          |       |        | 2                       |
|        | PERFORMANCE               | Débit Four          | T/j  | 950    | 835      | 823   | 838      | 843    | 841      | 833   | 841    | 920                     |
|        |                           | Nb Arrêt Four       | #    | 0      | 0        | 0     | 0        | 0      | 0        | 0     | 1      |                         |
|        |                           | NAI Four            | %    |        | 100.0    | 100.0 | 100.0    | 100.0  | 100.0    | 100.0 | 93.6   |                         |
|        |                           | %KM HLC Utilisation | %    | 80     |          |       |          |        |          |       |        | 80                      |
| FOUR C | ENERGY                    | STEC                | MJ/t | 5300   | 5575     | 5722  | 5633     | 5778   | 5712     | 5697  | 5711   | 5300                    |
|        | CO2                       | TSR                 | %    | 34     | 34.96    | 53.04 | 47.59    | 33.06  | 43.31    | 38.81 | 100.00 | 35,7%                   |
|        |                           | Débit DSB           | T/h  | 2      | 1.67     | 1.86  | 1.95     | 1.78   | 1.57     | 1.78  |        | 1,9                     |
|        |                           | GAI                 | %    | 95     | 98.68    | 99.79 | 74.03    | 97.22  | 96.46    | 94.03 |        | 95,0%                   |
|        |                           | Débit FAN           | T/h  | 2      | 1.67     | 1.50  | 1.40     | 1.40   | 1.72     | 1.82  |        | 1,9                     |
|        |                           | GAI                 | %    | 80     | 89.72    | 93.26 | 100.00   | 100.00 | 100.00   | 66.69 |        | 80,0%                   |
|        |                           | Débit Bois Amont    | T/h  | 1,3    | 1.10     | 0.98  | 1.21     | 1.31   | 1.00     | 1.06  |        | 1,6                     |
|        |                           | GAI                 | %    | 90     | 99.38    | 65.83 | 100.00   | 54.65  | 54.72    | 76.56 |        | 90,0%                   |
|        |                           | Débit G2000         | T/h  | 1,3    | 1.40     | 1.40  | 1.40     | 1.40   | 1.40     | 1.37  |        | 1,3                     |
|        |                           | Débit STEPI         | T/h  | 0,5    |          |       |          |        |          |       |        | 0,5                     |
|        | PERFORMANCE               | Débit Four          | T/j  | 1530   | 1503     | 1509  | 1592     | 1595   | 1575     | 1571  | 0      | 1570 NORMAL<br>1470 HTS |
|        |                           | Nb Arrêt Four       | #    | 0      | 0        | 0     | 0        | 0      | 0        | 1     | 0      |                         |
|        |                           | NAI Four            | %    |        | 100.0    | 100.0 | 100.0    | 100.0  | 100.0    | 97.8  | 0.0    |                         |
|        |                           | %KM HLC Utilisation | %    | 60     | 34.92    | 46.22 | 39.74    | 44.29  | 44.67    | 46.40 | 0.00   | 80                      |
|        | ENERGY                    | STEC                | MJ/t | 4074   | 4151     | 3965  | 3955     | 3868   | 3921     | 3902  |        | 4050                    |

|          |             |                                  |      |      |      |      |      |      |      |      |      |       |
|----------|-------------|----------------------------------|------|------|------|------|------|------|------|------|------|-------|
| BK BLANC | CO2         | %CALCAIRE<br>(CEM II 52,5)       | %    | 7.2  | 7.7  | 7.8  | 7.9  | 8.1  | 8.4  | 8.4  | 7.8  | 7,2%  |
|          | PERFORMANCE | Nombre d'arrêts BK15             | nbre | 1    | 1    | 1    | 0    | 1    | 0    | 0    | 0    | 0     |
|          | MONITORING  | %DOUTEUX BK15                    | %    | 5    | 0.1  | 0.0  | 0.0  | 0.0  |      |      | 0.0  | 5%    |
| BK GRIS  | CO2         | %AJOUTS<br>à la cible du produit | %    | 29,9 |      |      |      |      |      |      |      | 29,9% |
|          | PERFORMANCE | Nombre d'arrêts BK0              | nbre | 1    | 2    | 0    | 1    | 1    | 1    | 0    | 0    |       |
|          |             | Nombre d'arrêts BK1              | nbre | 1    | 2    | 1    | 0    | 1    | 0    | 0    | 1    |       |
|          | MONITORING  | %DOUTEUX BK0                     | %    | 30   | 21.7 | 19.3 | 20.7 | 10.4 | 20.0 | 22.0 | 13.6 | 20    |
|          |             | %DOUTEUX au BK1                  | %    | 30   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 20    |
|          |             | %DOUTEUX Dilution                | %    | 8    | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 8%    |