

# Maximum Demand Indicators /Maximum Demand Controller

## EMS-15 / EMS-15c

### Features

- High brightness red LED display.
- Measurement of basic, power, energy and demand parameters.
- High brightness alpha numeric LED display for parameters and numeric values.
- Automatic CT reverse correction for energy and demand.
- Programmable demand techniques block / sliding window
- Programmable demand parameters Apparent / Active power.
- Programmable demand range Kilo / Mega.
- Programmable Alarm / hysteresis settings.
- Programmable RTC setting to match EB meter's clock.




### Ordering Information


Models	Function	Source Voltage	Display Parameters	
EMS-15	Maximum Demand Indicator	170V to 270V AC/DC	Basic	V(R, Y, B), V(RY, YB, BR), A(R, Y, B), Hz, RTC Time
			Power	PF(R, Y, B, T), W(R, Y, B, T), VAr(R, Y, B, T), VA(R, Y, B, T)
			Integral	KWh, KVAh-C, KVAh-I, KVAh, LH
EMS-15c	Maximum Demand Controller		Demand	Md (Fixed/Sliding), Md Time (Fixed/Sliding), Wd (Fixed/Sliding), Rd (Fixed), Elapsed Time (Fixed/Sliding)

### Front View

#### EMS-15




#### EMS-15c




### Rear View

#### EMS-15



#### EMS-15c





### Over-all Dimension

Models	Dimension Details in mm			Cutout Dimension in mm	
	W	H	D	W	H
EMS-15/EMS-15c	96	96	95.5	92	92

## ■ Specifications

Parameters	Models	EMS-15	EMS-15c
Function		Maximum Demand Indicator	Maximum Demand Controller
Rated supply Voltage		85V – 270V AC/DC	
Rated Frequency		50 / 60Hz $\pm$ 5% for AC only	
Power consumption		AC Approx. 6 VA DC Approx. 4W	
Burden		< 0.2 VA per Volts/Amps input	
Input Voltage		3 Phase 4 wire (R,Y,B,N) 415 VAC (-40% to +20%) 110 VAC (-40% to +20%)	
Input Frequency		50 Hz, $\square$ 2%	
Input Current		Current inputs (AR, AY, AB) 1A to 5A (to 200%)	
Recovery Time		2 sec minimum	
Accuracy		Class 1.0 For Active Energy Class 2.0 For Reactive Energy	
RTC Accuracy		Up to 20Sec per month	
Communication		RS-485 MODBUS RTU Protocol	
Meter Constant		3200 Pulses/KWh 3200 Pulses/KVArh	
Battery life		Approx 2yrs	
CT Ratio Selectable		Primary 1 to 5KA max Secondary 1 to 5A	
PT Ratio Selectable		Primary 110 to 11KV Secondary 110 to 500V	
Device Id		1-247	
Baud Rate		2400,4800,9600,19200bps	
Pulse Output		Active Energy/ Reactive	
Synchronization technique		Sliding Window/ Fixed(bloc) Window	
Demand Parameter		Active/ Apparent	
Demand Range		Kilo/ Mega	
Demand Period		05 / 10 / 15 / 30 Mins	
Ambient Temperature		Operation: -10°C to +55°C(14°F to 131°F) Storage : -25°C to +80°C(-13°F to 176°F)	
Humidity		Up to 95% RH @ 40°C	
Dielectric Strength		a)2.5 KV AC,50Hz for 1minute(Between current carrying & non-current carrying parts)	
Insulation resistance		>100M Ohms @500V DC	
Dimension (W x H x D)		96 X 96 X 95.5 mm	
Cut-out Dimension(W x H)		92 x 92mm	

## Connection and Terminal Details

	EMS-15	EMS-15c
Connection Details		

	EMS-15	EMS-15c
Terminal Details	<b>1, 2, 3, 4 :</b> R, Y, B, N <b>7,8 :</b> A,B (RS 485Communication port) <b>9, 10 :</b> S1, S2 (R Phase) <b>11,12 :</b> S1, S2 (Y Phase) <b>13,14 :</b> S1, S2 (B Phase) <b>15,16 :</b> Auxiliary Supply(85-270 V AC/DC)	<b>1, 2, 3, 4 :</b> R, Y, B, N <b>5,6 :</b> Digital Output to Relay Module <b>7,8 :</b> A,B (RS 485Communication port) <b>9, 10 :</b> S1, S2 (R Phase) <b>11,12 :</b> S1, S2 (Y Phase) <b>13,14 :</b> S1, S2 (B Phase) <b>15,16 :</b> Auxiliary Supply(240 V AC/DC, -20 to +10%)

## ■ Coils Ratings for High-sensitivity Models

Rated voltage	5VDC	12VDC	24VDC
Rated current	50.0mA	20.8mA	10.42 mA
Coil resistance	100Ω	576Ω	2,304Ω
Must operate voltage	75% max. of the rated voltage		
Must release voltage	10% min. of the rated voltage		
Max. voltage	180% of rated voltage (at 23°C)		
Power consumption	Approx. 250mW		

**Note:** The rated current and coil resistance are measured at a coil temperature of 23°C with a tolerance of  $\pm 10\%$ .

## ■ Contact Ratings

Item	General-purpose Models		High-capacity Models	High-sensitivity Models
Number of poles	1 pole	2 poles	1 pole	1 pole
Contact material	Ag Alloy (Cd free)			
Load	Resistive load ( $\cos\phi=1$ )			
Rated load	12A at 250VAC 12A at 24 VDC (See note.)	8A at 250 VAC 8A at 30VDC (See note.)	16A at 250VAC 16A at 30VDC (See note.)	10A at 250VAC 10A at 24VDC (See note.)
Rated carry current	12A (See note.)	8A (70°C)/5A (85°C) (See note.)	16A (See note.)	10A (See note.)
Max. switching voltage	440VAC, 300VDC			
Max. switching current	12A	8A	16A	10A
Max. switching power	3,000VA (4,000VA)	2,000VA	4,000 VA	2,500VA

**Note:** Contact your OMRON representative for the ratings on fully sealed models.

## ■ Characteristics

Item	General-purpose (High-capacity) Models	General-purpose Models	High-sensitivity Models
Number of poles	1 pole	2 pole	1 pole
Contact resistance	100mΩ max.		
Operate (set) time	15ms max.		
Release (reset) time	5ms max.		
Max. operating frequency	Mechanical: 18,000 operation/hr Electrical: 1,800 operation/hr at rated load		
Insulation resistance	1,000MΩ min. (at 500VDC)		
Dielectric strength	5,000VAC, 1min between coil and contacts 1,000VAC, 1min between contacts of same polarity	5,000VAC, 1min between coil and contacts 2,500VAC, 1min between contacts of different polarity 1,000VAC, 1min between contacts of same polarity	5,000VAC, 1min between coil and contacts 1,000VAC, 1min between contacts of same polarity
Impulse withstand voltage	10kV (1.2×50μs) between coil and contact		
Vibration resistance	Destruction: 10 to 55 to 10Hz, 0.75mm single amplitude (1.5mm double amplitude) Malfunction: 10 to 55 to 10Hz, 0.75mm single amplitude (1.5mm double amplitude)		
Shock resistance	Destruction: 1,000m/s <sup>2</sup> (approx. 100G) Malfunction: 100 m/s <sup>2</sup> (approx. 10 G)		
Endurance (Mechanical)	20,000,000 operations (at 18,000 operations/hr)		
Ambient temperature	Operating: -40°C to 85°C (with no icing) Storage: -40°C to 85°C (with no icing)		
Ambient humidity	5% to 85%		
Weight	Approx. 12g		

**Note:** Values in the above table are the initial values.

## ■ Approved Standards

UL Recognized (File No. E41643) / CSA Certified (File No. LR31928) -- Ambient Temp. = 40°C

Model	Contact form	Coil ratings	Contact ratings	Number of test operations
G2RL-1A	SPST-NO	3 to 48 VDC	12 A at 250 VAC (General use)	100,000
G2RL-1	SPDT		12 A at 24 VDC (Resistive)	50,000
G2RL-1A-E	SPST-NO	3 to 48 VDC	16 A at 250 VAC (General use)	100,000
G2RL-1-E	SPDT		16 A at 24 VDC (Resistive)	50,000
G2RL-1A-H	SPST-NO	5 to 24 VDC	10 A at 250 VAC (General use) 10 A at 24 VDC (Resistive)	50,000
G2RL-1-H	SPDT			
G2RL-2A	DPST-NO	3 to 48 VDC	8 A at 277 VAC (General use) 8 A at 30 VDC (Resistive)	100,000
G2RL-2	DPDT			

**Note:** Consult Omron for additional UL/CSA ratings

VDE (EN 61810-1) (License No. 119650)

Model	Contact form	Coil ratings	Contact ratings
G2RL-1(A)	1 pole	5, 12, 18, 22, 24, 48 VDC	12 A at 250 VAC ( $\cos\phi=1$ ) 12 A at 24 VDC (L/R=0 ms) AC15: 3 A at 240 VAC DC13: 2.5 A at 24 VDC, 50 ms
G2RL-1(A)-E	1 pole	5, 12, 18, 22, 24, 48 VDC	16 A at 250 VAC ( $\cos\phi=1$ ) 16 A at 24 VDC (L/R=0 ms) AC15: 3 A at 240 VAC (NO) 1.5 A at 240 VAC (NC) DC13: 2.5 A at 24 VDC (NO), 50 ms
G2RL-1(A)-H	1 pole	5, 9, 12, 24 VDC	10 A at 250 VAC ( $\cos\phi=1$ ) 10 A at 24 VDC (L/R=0 ms)
G2RL-2(A)	2 poles	5, 12, 18, 22, 24, 48 VDC	8 A at 250 VAC ( $\cos\phi=1$ ) 8 A at 24 VDC (L/R=0 ms) AC15: 1.5 A at 240 VAC DC13: 2 A at 30 VDC, 50 ms

**Note:** To achieve approved life cycles on sealed models, the relay should be vented by removing the “knock off vent nib” on top of relay case after the soldering/washing process.

## Electrical Life Data

<b>G2RL-1-E</b>	16 A at 250 VAC ( $\cos\phi=1$ ) 16 A at 24 VDC 8 A at 250 VAC ( $\cos\phi=0.4$ ) 8 A at 30 VDC (L/R=7 ms)	30,000 operations min. 30,000 operations min. 200,000 operation min. (normally open side operation) 10,000 operation min. (normally open side operation)
<b>G2RL-1</b>	12 A at 250 VAC ( $\cos\phi=1$ ) 12 A at 24 VDC 5 A at 250 VAC ( $\cos\phi=0.4$ ) 5 A at 30 VDC (L/R=7 ms)	50,000 operations min. 30,000 operations min. 150,000 operation min. (normally open side operation) 20,000 operation min. (normally open side operation)
<b>G2RL-1-H</b>	10 A at 250 VAC ( $\cos\phi=1$ ) 10 A at 24 VDC	100,000 operations min. 50,000 operations min.
<b>G2RL-2</b>	8 A at 250 VAC ( $\cos\phi=1$ ) 8 A at 30 VDC	30,000 operations min. 30,000 operations min.


**Note:** 1. The results shown reflect values measured using very severe test conditions i.e., Duty: 1s ON/1s OFF.

- In order to obtain the full rated life cycles on the fully sealed models, the relay should be properly vented by removing the “knock off vent nib” on top of the relay case after the soldering/washing process.
- Electrical endurance will vary depending on the test conditions. Contact your OMRON representative if you require more detailed information for the electrical endurance under your test conditions.


# EngineeringData

## ■ MaximumSwitchingCapacity


G2RL-1A,G2RL-1




G2RL-1A-E,G2RL-1-E




G2RL-1A-H,G2RL-1-H




G2RL-2A,G2RL-2



## ■ AmbientTemperature vs Rated Carry Current



## ■ AmbientTemperature vs Maximum Coil Voltage




**Note:** The maximum coil voltage refers to the maximum value in a varying range of operating power voltage, not a continuous voltage.

**Note:** Contact your OMRON representative for the data on fully sealed models.


# Dimensions

**Note:** All units are in millimeters unless otherwise indicated.


## G2RL-1A(-H), G2RL-1A4




## G2RL-1(-H), G2RL-14




## G2RL-1A-E, G2RL-1A4-E




## G2RL-1-E, G2RL-14-E



## G2RL-2A, G2RL-2A4



## G2RL-2, G2RL-24





# MEMO



# Omron Electronic Components, LLC

## Terms and Conditions of Sales

### I. GENERAL

- Definitions:** The words used herein are defined as follows.
  - Terms:** These terms and conditions
  - Seller:** Omron Electronic Components LLC and its subsidiaries
  - Buyer:** The buyer of Products, including any end user in section III through VI
  - Products:** Products and/or services of Seller
  - Including:** Including without limitation
- Offer; Acceptance:** These Terms are deemed part of all quotations, acknowledgments, invoices, purchase orders and other documents, whether electronic or in writing, relating to the sale of Products by Seller. Seller hereby objects to any Terms proposed in Buyer's purchase order or other documents which are inconsistent with, or in addition to, these Terms.
- Distributor:** Any distributor shall inform its customer of the contents after and including section II of these Terms.

### II. SALES

- Prices; Payment:** All prices stated are current, subject to change without notice by Seller. Buyer agrees to pay the price in effect at the time the purchase order is accepted by Seller. Payments for Products received are due net 30 days unless otherwise stated in the invoice. Buyer shall have no right to set off any amounts against the amount owing in respect of this invoice.
- Discounts:** Cash discounts, if any, will apply only on the net amount of invoices sent to Buyer after deducting transportation charges, taxes and duties, and will be allowed only if (a) the invoice is paid according to Seller's payment terms and (b) Buyer has no past due amounts owing to Seller.
- Interest:** Seller, at its option, may charge Buyer 1.5% interest per month or the maximum legal rate, whichever is less, on any balance not paid within the stated terms.
- Orders:** Seller will accept no order less than 200 U.S. dollars net billing.
- Currencies:** If the prices quoted herein are in a currency other than U.S. dollars, Buyer shall make remittance to Seller at the then current exchange rate most favorable to Seller; provided that if remittance is not made when due, Buyer will convert the amount to U.S. dollars at the then current exchange rate most favorable to Seller available during the period between the due date and the date remittance is actually made.
- Governmental Approvals:** Buyer shall be responsible for all costs involved in obtaining any governmental approvals regarding the importation or sale of the Products.
- Taxes:** All taxes, duties and other governmental charges (other than general real property and income taxes), including any interest or penalties thereon, imposed directly or indirectly on Seller or required to be collected directly or indirectly by Seller for the manufacture, production, sale, delivery, importation, consumption or use of the Products sold hereunder (including customs duties and sales, excise, use, turnover and license taxes) shall be charged to and remitted by Buyer to Seller.
- Financial:** If the financial position of Buyer at any time becomes unsatisfactory to Seller, Seller reserves the right to stop shipments or require satisfactory security or payment in advance. If Buyer fails to make payment or otherwise comply with these Terms or any related agreement, Seller may (without liability and in addition to other remedies) cancel any unshipped portion of Products sold hereunder and stop any Products in transit until Buyer pays all amounts, including amounts payable hereunder, whether or not then due, which are owing to it by Buyer. Buyer shall in any event remain liable for all unpaid accounts.
- Cancellation; Etc:** Orders are not subject to rescheduling or cancellation unless Buyer indemnifies Seller fully against all costs or expenses arising in connection therewith.
- Force Majeure:** Seller shall not be liable for any delay or failure in delivery resulting from causes beyond its control, including earthquakes, fires, floods, strikes or other labor disputes, shortage of labor or materials, accidents to machinery, acts of sabotage, riots, delay in or lack of transportation or other requirements of any governmental authority.
- Shipping; Delivery:** Unless otherwise expressly agreed in writing by Seller:
  - All sales and shipments of Products shall be FOB shipping point (unless otherwise stated in writing by Seller), at which point title to and all risk of loss of the Products shall pass from Seller to Buyer, provided that Seller shall retain a security interest in the Products until the full purchase price is paid by Buyer;
  - Delivery and shipping dates are estimates only; and
  - Seller will package Products as it deems proper for protection against normal handling and extra charges apply to special conditions.
- Claims:** Any claim by Buyer against Seller for shortage or damage to the Products occurring before delivery to the carrier or any claim related to pricing or other charges must be presented in detail in writing to Seller within 30 days of receipt of shipment.

### III. PRECAUTIONS

- Suitability:** IT IS THE BUYER'S SOLE RESPONSIBILITY TO ENSURE THAT ANY OMRON PRODUCT IS FIT AND SUFFICIENT FOR USE IN A MOTORIZED VEHICLE APPLICATION. BUYER SHALL BE SOLELY RESPONSIBLE FOR DETERMINING APPROPRIATENESS OF THE PARTICULAR PRODUCT WITH RESPECT TO THE BUYER'S APPLICATION INCLUDING (A) ELECTRICAL OR ELECTRONIC COMPONENTS, (B) CIRCUITS, (C) SYSTEM ASSEMBLIES, (D) END PRODUCT, (E) SYSTEM, (F) MATERIALS OR SUBSTANCES OR (G) OPERATING ENVIRONMENT. Buyer acknowledges that it alone has determined that the Products will meet the requirements of the intended use in all cases. Buyer must know and observe all prohibitions of use applicable to the Product/s.
- Use with Attention:** The following are some examples of applications for which particular attention must be given. This is not intended to be an exhaustive list of all possible use of any Product, nor to imply that any use listed may be suitable for any Product:
  - Outdoor use, use involving potential chemical contamination or electrical interference.

- Use in consumer Products or any use in significant quantities.
  - Energy control systems, combustion systems, railroad systems, aviation systems, medical equipment, amusement machines, vehicles, safety equipment, and installation on subject to separate industry or government regulations.
  - Systems, machines, and equipment that could present a risk to life or property.
- Prohibited Use:** NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE PRODUCT IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.
  - MotORIZED Vehicle Application:** USE OF ANY PRODUCT FOR A MOTORIZED VEHICLE APPLICATION MUST BE EXPRESSLY STATED IN THE SPECIFICATION BY SELLER.
  - Programmable Products:** Seller shall not be responsible for the Buyer's programming of a programmable Product.

### IV. WARRANTY AND LIMITATION

- Warranty:** Seller's exclusive warranty is that the Products will be free from defects in materials and workmanship for a period of twelve months from the date of sale by Seller (or such other period expressed in writing by Seller). SELLER MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT ALL OTHER WARRANTIES, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCTS.
- Buyer Remedy:** Seller's sole obligation hereunder shall be to replace (in the form originally shipped with Buyer responsible for labor charges for removal or replacement thereof) the non-complying Product or, at Seller's election, to repay or credit Buyer an amount equal to the purchase price of the Product; provided that there shall be no liability for Seller or its affiliates unless Seller's analysis confirms that the Products were correctly handled, stored, installed and maintained and not subject to contamination, abuse, misuse or inappropriate modification. Return of any Products by Buyer must be approved in writing by Seller before shipment.
- Limitation on Liability:** SELLER AND ITS AFFILIATES SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE OR STRICT LIABILITY. FURTHER, IN NO EVENT SHALL THE LIABILITY OF SELLER OR ITS AFFILIATES EXCEED THE INDIVIDUAL PRICE OF THE PRODUCT ON WHICH LIABILITY IS ASSERTED.
- Indemnities:** Buyer shall indemnify and hold harmless Seller, its affiliates and its employees from and against all liabilities, losses, claims, costs and expenses (including attorney's fees and expenses) related to any claim, investigation, litigation or proceeding (whether or not Seller is a party) which arises or is alleged to arise from Buyer's acts or omissions under these Terms or in any way with respect to the Products.

### V. INFORMATION; ETC.

- Intellectual Property:** The intellectual property embodied in the Products is the exclusive property of Seller and its affiliates and Buyer shall not attempt to duplicate it in any way without the written permission of Seller. Buyer (at its own expense) shall indemnify and hold harmless Seller and defend or settle any action brought against Seller to the extent that it is based on a claim that any Product made to Buyer's specifications infringes intellectual property rights of another party.
- Property; Confidentiality:** Notwithstanding any charges to Buyer for engineering or tooling, all engineering and tooling shall remain the exclusive property of Seller. All information and materials supplied by Seller to Buyer relating to the Products are confidential and proprietary, and Buyer shall limit distribution thereof to its trusted employees and strictly prevent disclosure to any third party.
- Performance Data:** Performance data is provided as guidance in determining suitability and does not constitute a warranty. It may represent the result of Seller's test conditions, and the users must correlate it to actual application requirements.
- Change In Specifications:** Product specifications and descriptions may be changed at any time based on improvements or other reasons. It is Seller's practice to change part numbers when published ratings or features are changed, or when significant engineering changes are made. However, some specifications of the Product may be changed without any notice.
- Errors And Omissions:** The information on Seller's website or in other documentation has been carefully checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical or proofreading errors or omissions.
- Export Controls:** Buyer shall comply with all applicable laws, regulations and licenses regarding (a) export of the Products or information provided by Seller; (b) sale of Products to forbidden or other proscribed persons or organizations; (c) disclosure to non-citizens of regulated technology or information.

### VI. MISCELLANEOUS

- Waiver:** No failure or delay by Seller in exercising any right and no course of dealing between Buyer and Seller shall operate as a waiver of rights by Seller.
- Assignment:** Buyer may not assign its rights hereunder without Seller's written consent.
- Law:** These Terms are governed by Illinois law (without regard to conflict of laws). Federal and state courts in Cook County, Illinois have exclusive jurisdiction for any dispute hereunder.
- Amendment:** These Terms constitute the entire agreement between Buyer and Seller relating to the Products, and no provision may be changed or waived unless in writing signed by the parties.
- Severability:** If any provision hereof is rendered ineffective or invalid, such provision shall not invalidate any other provision.

# Certain Precautions on Specifications and Use

1. **Suitability for Use.** Seller shall not be responsible for conformity with any standards, codes or regulations which apply to the combination of the Product in Buyer's application or use of the Product. At Buyer's request, Seller will provide applicable third party certification documents identifying ratings and limitations of use which apply to the Product. This information by itself is not sufficient for a completed determination of the suitability of the Product in combination with the end product, machine, system, or other application or use. Buyer shall be solely responsible for determining appropriateness of the particular Product with respect to Buyer's application, product or system. Buyer shall take application responsibility in all cases but the following is a non-exhaustive list of applications for which particular attention must be given:
  - (i) Outdoor use, uses involving potential chemical contamination or electrical interference, or conditions or uses not described in this document.
  - (ii) Energy control systems, combustion systems, railroad systems, aviation systems, medical equipment, amusement machines, vehicles, safety equipment, and installations subject to separate industry or government regulations.
  - (iii) Use in consumer products or any use in significant quantities.
  - (iv) Systems, machines and equipment that could present a risk to life or property. Please know and observe all prohibitions of use applicable to this product.

NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCT IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.
2. **Programmable Products.** Seller shall not be responsible for the user's programming of a programmable product, or any consequence thereof.
3. **Performance Data.** Performance data given in this publication is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of Seller's test conditions, and the users must correlate it to actual application requirements. Actual performance is subject to Seller's Warranty and Limitations of Liability.
4. **Change in Specifications.** Product specifications and accessories may be changed at any time based on improvements and other reasons. It is our practice to change part numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the Product may be changed without any notice. When in doubt, special part numbers may be assigned to fix or establish key specifications for your application. Please consult with your Seller representative at any time to confirm actual specifications of purchased Product.
5. **Errors and Omissions.** The information in this publication has been carefully checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical or proofreading errors, or omissions.
6. **RoHS Compliance.** Where indicated, our products currently comply, to the best of our knowledge as of the date of this publication, with the requirements of the European Union's Directive on the Restriction of certain Hazardous Substances ("RoHS"), although the requirements of RoHS do not take effect until July 2006. These requirements may be subject to change. Please consult our website for current information.

Complete "Terms and Conditions of Sale" for product purchase and use are on Omron's website at <http://www.components.omron.com> – under the "About Us" tab, in the Legal Matters section.

**ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.**

To convert millimeters to inches, multiply by 0.03937. To convert grams to ounces, multiply by 0.03527.

**OMRON**  
**OMRON ELECTRONIC**  
**COMPONENTS LLC**  
 55 E. Commerce Drive, Suite B  
 Schaumburg, IL 60173  
**847-882-2288**

**OMRON-ON-LINE**

Global-<http://www.omron.com>  
 USA-<http://www.components.omron.com>

Cat. No. X301-E-1

06/09

Specifications subject to change without notice

Printed in USA